

URLs and E-Mail Addresses	Amazon S3 Hosted Products
<ul style="list-style-type: none"> • Product registration page: http://aws.amazon.com/devpay • DevPay activity page: http://aws.amazon.com/devpayactivity • Customer Application Billing page: http://www.amazon.com/dp-applications • Customer activation page: http://www.amazon.com/dp-activate • License Service WSDL/schema: https://ls.amazonaws.com/doc/2008-04-28/AmazonLS.wsdl • Your questions about DevPay: devpay@amazon.com • Customers' technical questions: Your company's support address or phone number • Customers' billing questions: application-payments@amazon.com 	<div> <div> Product ID Used: <ul style="list-style-type: none"> • Product token • Product code </div> <div> Customer Identifiers Used: <ul style="list-style-type: none"> • Customer's activation key • Customer's persistent identifier (PID) • Customer's user token </div> </div> <div> Your Identifiers Used: <ul style="list-style-type: none"> • Your AWS Access Key ID • Your Secret Access Key </div>
Paid and Supported AMIs	
<ul style="list-style-type: none"> • Associate your product code with your AMI: ec2-modify-image-attribute <AMI ID> --product-code <product code> • Confirm an instance is running your product code: ec2-confirm-product-instance <product code> -i <instance ID> • Verify the product code from within an instance: GET http://169.254.169.254/2007-03-01/meta-data/product-codes 	<div> ActivateHostedProduct Authentication required; use your AWS Secret Access Key or X.509 certificate (for SOAP). HTTPS required. </div> <div> <div> Request includes: <ul style="list-style-type: none"> • ActivationKey • ProductToken • TokenExpiration (optional) • Authentication parameters </div> <div> Response includes: <ul style="list-style-type: none"> • Customer's PID • Customer's UserToken </div> </div>
Amazon S3 Desktop Products	
<div> <div> Product ID Used: <ul style="list-style-type: none"> • Product token </div> <div> Your Identifiers Used: <ul style="list-style-type: none"> • None </div> </div> <div> Customer Identifiers Used: <ul style="list-style-type: none"> • Customer's activation key • Customer's user token • Customer's AWS Access Key ID • Customer's Secret Access Key </div>	<div> RefreshUserToken Authentication required; use your AWS Secret Access Key or X.509 certificate (for SOAP). HTTPS required. </div> <div> <div> Request includes: <ul style="list-style-type: none"> • UserToken • Authentication parameters </div> <div> Response includes: <ul style="list-style-type: none"> • Refreshed UserToken </div> </div>
ActivateDesktopProduct No authentication required. HTTPS required.	<div> VerifyProductSubscriptionByPid Authentication required; use your AWS Secret Access Key or X.509 certificate (for SOAP). HTTPS required. </div> <div> <div> Request includes: <ul style="list-style-type: none"> • ActivationKey • ProductToken • TokenExpiration (optional) </div> <div> Response includes: <ul style="list-style-type: none"> • Customer's AWSAccessKeyId • Customer's SecretAccessKey • Customer's UserToken </div> </div>
VerifyProductSubscriptionByTokens Authentication required; use customer's AWS Secret Access Key. HTTPS required.	<div> Amazon S3 Requests Authentication required; use customer's AWS Secret Access Key. </div> <div> Request includes: <ul style="list-style-type: none"> • UserToken • ProductToken • Authentication parameters </div>
Amazon S3 Requests Authentication required; use customer's AWS Secret Access Key.	<div> Request includes: <ul style="list-style-type: none"> • UserToken • ProductCode (required only if using a user token created on or before May 15, 2008) • Authentication parameters </div>