
Amazon Elastic Compute Cloud

API Reference

API Version 2012-06-15



Amazon Elastic Compute Cloud: API Reference

Copyright © 2012 Amazon Web Services LLC or its affiliates. All rights reserved.

The following are trademarks or registered trademarks of Amazon: Amazon, Amazon.com, Amazon.com Design, Amazon DevPay, Amazon EC2, Amazon Web Services Design, AWS, CloudFront, EC2, Elastic Compute Cloud, Kindle, and Mechanical Turk. In addition, Amazon.com graphics, logos, page headers, button icons, scripts, and service names are trademarks, or trade dress of Amazon in the U.S. and/or other countries. Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon.

All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

| | |
|--------------------------------------|-----|
| Welcome | 1 |
| List of Actions by Function | 3 |
| Actions | 9 |
| AllocateAddress | 13 |
| AssignPrivateIpAddresses | 15 |
| AssociateAddress | 18 |
| AssociateDhcpOptions | 21 |
| AssociateRouteTable | 23 |
| AttachInternetGateway | 25 |
| AttachNetworkInterface | 27 |
| AttachVolume | 29 |
| AttachVpnGateway | 31 |
| AuthorizeSecurityGroupEgress | 33 |
| AuthorizeSecurityGroupIngress | 36 |
| BundleInstance | 40 |
| CancelBundleTask | 43 |
| CancelConversionTask | 45 |
| CancelExportTask | 47 |
| CancelSpotInstanceRequests | 49 |
| ConfirmProductInstance | 51 |
| CreateCustomerGateway | 53 |
| CreateDhcpOptions | 55 |
| CreateImage | 58 |
| CreateInstanceExportTask | 60 |
| CreateInternetGateway | 63 |
| CreateKeyPair | 65 |
| CreateNetworkAcl | 67 |
| CreateNetworkAclEntry | 69 |
| CreateNetworkInterface | 72 |
| CreatePlacementGroup | 77 |
| CreateRoute | 79 |
| CreateRouteTable | 82 |
| CreateSecurityGroup | 84 |
| CreateSnapshot | 86 |
| CreateSpotDatafeedSubscription | 89 |
| CreateSubnet | 91 |
| CreateTags | 93 |
| CreateVolume | 95 |
| CreateVpc | 97 |
| CreateVpnConnection | 99 |
| CreateVpnGateway | 103 |
| DeleteCustomerGateway | 105 |
| DeleteDhcpOptions | 107 |
| DeleteInternetGateway | 109 |
| DeleteKeyPair | 111 |
| DeleteNetworkAcl | 113 |
| DeleteNetworkAclEntry | 115 |
| DeleteNetworkInterface | 117 |
| DeletePlacementGroup | 119 |
| DeleteRoute | 121 |
| DeleteRouteTable | 123 |
| DeleteSecurityGroup | 125 |
| DeleteSnapshot | 127 |
| DeleteSpotDatafeedSubscription | 129 |
| DeleteSubnet | 130 |
| DeleteTags | 132 |
| DeleteVolume | 135 |
| DeleteVpc | 137 |

| | |
|--|-----|
| DeleteVpnConnection | 139 |
| DeleteVpnGateway | 141 |
| DeregisterImage | 143 |
| DescribeAddresses | 145 |
| DescribeAvailabilityZones | 150 |
| DescribeBundleTasks | 153 |
| DescribeConversionTasks | 156 |
| DescribeCustomerGateways | 158 |
| DescribeDhcpOptions | 161 |
| DescribeExportTasks | 165 |
| DescribeImageAttribute | 167 |
| DescribeImages | 170 |
| DescribeInstanceAttribute | 178 |
| DescribeInstances | 181 |
| DescribeInstanceStatus | 197 |
| DescribeInternetGateways | 203 |
| DescribeKeyPairs | 206 |
| DescribeNetworkAcls | 209 |
| DescribeNetworkInterfaceAttribute | 214 |
| DescribeNetworkInterfaces | 216 |
| DescribePlacementGroups | 222 |
| DescribeRegions | 225 |
| DescribeReservedInstances | 228 |
| DescribeReservedInstancesOfferings | 232 |
| DescribeRouteTables | 236 |
| DescribeSecurityGroups | 240 |
| DescribeSnapshotAttribute | 244 |
| DescribeSnapshots | 246 |
| DescribeSpotDatafeedSubscription | 251 |
| DescribeSpotInstanceRequests | 253 |
| DescribeSpotPriceHistory | 259 |
| DescribeSubnets | 263 |
| DescribeTags | 267 |
| DescribeVolumes | 272 |
| DescribeVolumeAttribute | 276 |
| DescribeVolumeStatus | 278 |
| DescribeVpcs | 283 |
| DescribeVpnConnections | 286 |
| DescribeVpnGateways | 290 |
| DetachInternetGateway | 294 |
| DetachNetworkInterface | 296 |
| DetachVolume | 298 |
| DetachVpnGateway | 300 |
| DisassociateAddress | 302 |
| DisassociateRouteTable | 304 |
| EnableVolumeIO | 306 |
| GetConsoleOutput | 308 |
| GetPasswordData | 310 |
| ImportInstance | 312 |
| ImportKeyPair | 316 |
| ImportVolume | 318 |
| ModifyImageAttribute | 321 |
| ModifyInstanceAttribute | 324 |
| ModifyNetworkInterfaceAttribute | 327 |
| ModifySnapshotAttribute | 329 |
| ModifyVolumeAttribute | 331 |
| MonitorInstances | 333 |
| PurchaseReservedInstancesOffering | 335 |

| | |
|---|-----|
| RebootInstances | 337 |
| RegisterImage | 339 |
| ReleaseAddress | 343 |
| ReplaceNetworkAclAssociation | 345 |
| ReplaceNetworkAclEntry | 347 |
| ReplaceRoute | 350 |
| ReplaceRouteTableAssociation | 352 |
| ReportInstanceStatus | 354 |
| RequestSpotInstances | 357 |
| ResetImageAttribute | 365 |
| ResetInstanceAttribute | 367 |
| ResetNetworkInterfaceAttribute | 369 |
| ResetSnapshotAttribute | 371 |
| RevokeSecurityGroupEgress | 373 |
| RevokeSecurityGroupIngress | 376 |
| RunInstances | 379 |
| StartInstances | 390 |
| StopInstances | 392 |
| TerminateInstances | 394 |
| UnassignPrivateIpAddresses | 396 |
| UnmonitorInstances | 398 |
| Data Types | 400 |
| AssignPrivateIpAddressesSetItemRequestType | 402 |
| AssignPrivateIpAddressesType | 403 |
| AttachmentSetItemResponseType | 403 |
| AttachmentType | 404 |
| AvailabilityZoneItemType | 405 |
| AvailabilityZoneMessageType | 406 |
| BlockDeviceMappingItemType | 406 |
| BundleInstanceS3StorageType | 407 |
| BundleInstanceTaskErrorType | 408 |
| BundleInstanceTaskStorageType | 408 |
| BundleInstanceTaskType | 409 |
| CancelSpotInstanceRequestsResponseSetItemType | 410 |
| ConversionTaskType | 411 |
| CreateVolumePermissionItemType | 411 |
| CustomerGatewayType | 412 |
| DescribeAddressesResponseItemType | 413 |
| DescribeImagesResponseItemType | 414 |
| DescribeKeyPairsResponseItemType | 416 |
| DescribeReservedInstancesOfferingsResponseSetItemType | 417 |
| DescribeReservedInstancesResponseSetItemType | 418 |
| DescribeSnapshotsSetItemResponseType | 419 |
| DescribeVolumesSetItemResponseType | 420 |
| DhcpConfigurationItemType | 421 |
| DhcpOptionsType | 422 |
| DhcpValueType | 423 |
| DiskImageDescriptionType | 423 |
| DiskImageVolumeDescriptionType | 424 |
| EbsBlockDeviceType | 425 |
| EbsInstanceBlockDeviceMappingResponseType | 425 |
| ExportTaskResponseType | 426 |
| ExportToS3TaskResponseType | 427 |
| GroupItemType | 428 |
| IamInstanceProfileRequestType | 429 |
| IamInstanceProfileResponseType | 429 |
| IcmpTypeCodeType | 430 |
| ImportInstanceTaskDetailsType | 430 |

| | |
|---|-----|
| ImportInstanceVolumeDetailItemType | 431 |
| ImportVolumeTaskDetailsType | 432 |
| InstanceBlockDeviceMappingItemType | 433 |
| InstanceBlockDeviceMappingResponseItemType | 434 |
| InstanceEbsBlockDeviceType | 434 |
| InstanceExportTaskResponseType | 435 |
| InstanceStateEventsSetType | 435 |
| InstanceStateEventType | 436 |
| InstanceStateItemType | 436 |
| InstanceStateSetType | 437 |
| InstanceStateDetailsSetType | 438 |
| InstanceStateType | 438 |
| InstanceMonitoringStateType | 439 |
| InstanceNetworkInterfaceSetItemRequestType | 440 |
| InstanceNetworkInterfaceSetType | 441 |
| InstanceStateChangeType | 442 |
| InstanceStateType | 442 |
| InternetGatewayAttachmentType | 443 |
| InternetGatewayType | 444 |
| IpPermissionType | 445 |
| IpRangeItemType | 446 |
| LaunchPermissionItemType | 446 |
| LaunchSpecificationRequestType | 447 |
| LaunchSpecificationResponseType | 448 |
| MonitoringInstanceType | 449 |
| MonitorInstancesResponseSetItemType | 450 |
| NetworkAclEntryType | 451 |
| NetworkAclType | 452 |
| NetworkAclAssociationType | 452 |
| NetworkInterfaceAssociationType | 453 |
| NetworkInterfaceSet | 454 |
| NetworkInterfaceAttachmentType | 455 |
| NetworkInterfacePrivateIpAddressesSetItemType | 456 |
| NetworkInterfaceType | 456 |
| PlacementGroupInfoType | 457 |
| PlacementRequestType | 458 |
| PlacementResponseType | 459 |
| PortRangeType | 459 |
| PrivateIpAddressesSetItemRequestType | 460 |
| ProductCodeItemType | 460 |
| ProductCodesSetItemType | 461 |
| ProductDescriptionSetItemType | 462 |
| RecurringChargesSetItemType | 462 |
| RegionItemType | 463 |
| ReservationInfoType | 463 |
| ResourceTagSetItemType | 464 |
| RouteTableAssociationType | 464 |
| RouteTableType | 465 |
| RouteType | 466 |
| RunningInstancesItemType | 467 |
| SecurityGroupIdSetItemType | 470 |
| SecurityGroupItemType | 470 |
| SpotDatafeedSubscriptionType | 471 |
| SpotInstanceRequestSetItemType | 472 |
| SpotInstanceStateFaultType | 474 |
| SpotPriceHistorySetItemType | 474 |
| StateReasonType | 475 |
| SubnetType | 476 |

| | |
|-----------------------------------|-----|
| TagSetItemType | 477 |
| UserData Type | 478 |
| UserIdGroupPairType | 478 |
| ValueType | 479 |
| VolumeStatusItemType | 480 |
| VolumeStatusInfoType | 481 |
| VolumeStatusDetailsItemType | 481 |
| VolumeStatusEventItemType | 482 |
| VolumeStatusActionItemType | 482 |
| VpcType | 483 |
| VpnConnectionType | 484 |
| VpnGatewayType | 485 |
| VpnTunnelTelemetryType | 486 |
| Common Query Parameters | 488 |
| Error Codes | 490 |
| Amazon EC2 Resources | 499 |
| Document History | 501 |

Welcome

This is the *Amazon Elastic Compute Cloud API Reference*. This guide provides detailed information about Amazon Elastic Compute Cloud (Amazon EC2) actions, data types, parameters, and errors. For detailed information about Amazon EC2 features and their associated API calls, go to the [Amazon Elastic Compute Cloud User Guide](#).

Amazon EC2 is a web service that provides resizable computing capacity—literally, server instances in Amazon's data centers—that you use to build and host your software systems. With Amazon EC2, you can get access to infrastructure resources using APIs or web tools and utilities.

Note

This guide also includes the actions for Amazon Virtual Private Cloud (Amazon VPC). For more information about the service, go to the [Amazon Virtual Private Cloud User Guide](#).

This reference has a single set of topics for both the Query and SOAP APIs (the actions are the same for both APIs). The topic for a given action shows the Query API request parameters. The XML request elements for the SOAP API have names that are very similar to the Query API parameter names. You can view the XML request elements in the WSDL, or look at the proxy classes that a SOAP toolkit generates from the WSDL. Therefore you can look at the topic for a given action and see what you need to provide for either the Query API or the SOAP API. You can also see what the XML response looks like (it's the same for both APIs).

| | |
|--|--|
| Current WSDL (2012-06-15) | Location of the current WSDL |
| Making API Requests | Information about using the API |
| List of Actions by Function (p. 3) | List of the Amazon EC2 actions by function |
| Actions (p. 9) | Alphabetical list of all Amazon EC2 actions |
| Data Types (p. 400) | Alphabetical list of all Amazon EC2 data types |
| Common Query Parameters (p. 488) | Parameters that all Query actions can use |
| Error Codes (p. 490) | Client and server errors the API returns |

[Amazon EC2 product page](#)

Information about this product

List of Actions by Function

Amazon DevPay

- [ConfirmProductInstance](#) (p. 51)

AMIs

- [CreateImage](#) (p. 58)
- [DeregisterImage](#) (p. 143)
- [DescribeImageAttribute](#) (p. 167)
- [DescribeImages](#) (p. 170)
- [ModifyImageAttribute](#) (p. 321)
- [RegisterImage](#) (p. 339)
- [ResetImageAttribute](#) (p. 365)

Availability Zones and Regions

- [DescribeAvailabilityZones](#) (p. 150)
- [DescribeRegions](#) (p. 225)

Customer Gateways (Amazon VPC)

- [CreateCustomerGateway](#) (p. 53)
- [DeleteCustomerGateway](#) (p. 105)
- [DescribeCustomerGateways](#) (p. 158)

DHCP Options (Amazon VPC)

- [AssociateDhcpOptions](#) (p. 21)
- [CreateDhcpOptions](#) (p. 55)
- [DeleteDhcpOptions](#) (p. 107)

- [DescribeDhcpOptions](#) (p. 161)

Elastic Block Store

- [AttachVolume](#) (p. 29)
- [CreateSnapshot](#) (p. 86)
- [CreateVolume](#) (p. 95)
- [DeleteSnapshot](#) (p. 127)
- [DeleteVolume](#) (p. 135)
- [DescribeSnapshotAttribute](#) (p. 244)
- [DescribeSnapshots](#) (p. 246)
- [DescribeVolumes](#) (p. 272)
- [DescribeVolumeAttribute](#) (p. 276)
- [DescribeVolumeStatus](#) (p. 278)
- [DetachVolume](#) (p. 298)
- [EnableVolumeIO](#) (p. 306)
- [ImportVolume](#) (p. 318)
- [ModifySnapshotAttribute](#) (p. 329)
- [ModifyVolumeAttribute](#) (p. 331)
- [ResetSnapshotAttribute](#) (p. 371)

Elastic IP Addresses

- [AllocateAddress](#) (p. 13)
- [AssociateAddress](#) (p. 18)
- [DescribeAddresses](#) (p. 145)
- [DisassociateAddress](#) (p. 302)
- [ReleaseAddress](#) (p. 343)

Elastic Network Interfaces

- [AttachNetworkInterface](#) (p. 27)
- [DetachNetworkInterface](#) (p. 296)
- [CreateNetworkInterface](#) (p. 72)
- [DeleteNetworkInterface](#) (p. 117)
- [DescribeNetworkInterfaces](#) (p. 216)
- [DescribeNetworkInterfaceAttribute](#) (p. 214)
- [ModifyNetworkInterfaceAttribute](#) (p. 327)
- [ResetNetworkInterfaceAttribute](#) (p. 369)

General

- [GetConsoleOutput](#) (p. 308)

Instances

- [DescribeInstanceAttribute](#) (p. 178)
- [DescribeInstances](#) (p. 181)
- [DescribeInstanceStatus](#) (p. 197)
- [ImportInstance](#) (p. 312)
- [ModifyInstanceAttribute](#) (p. 324)
- [RebootInstances](#) (p. 337)
- [ReportInstanceStatus](#) (p. 354)
- [ResetInstanceAttribute](#) (p. 367)
- [RunInstances](#) (p. 379)
- [StartInstances](#) (p. 390)
- [StopInstances](#) (p. 392)
- [TerminateInstances](#) (p. 394)

Internet Gateways (Amazon VPC)

- [AttachInternetGateway](#) (p. 25)
- [CreateInternetGateway](#) (p. 63)
- [DeleteInternetGateway](#) (p. 109)
- [DescribeInternetGateways](#) (p. 203)
- [DetachInternetGateway](#) (p. 294)

Key Pairs

- [CreateKeyPair](#) (p. 65)
- [DeleteKeyPair](#) (p. 111)
- [DescribeKeyPairs](#) (p. 206)
- [ImportKeyPair](#) (p. 316)

Monitoring

- [MonitorInstances](#) (p. 333)
- [UnmonitorInstances](#) (p. 398)

Network ACLs (Amazon VPC)

- [CreateNetworkAcl](#) (p. 67)
- [CreateNetworkAclEntry](#) (p. 69)
- [DeleteNetworkAcl](#) (p. 113)
- [DeleteNetworkAclEntry](#) (p. 115)
- [DescribeNetworkAcls](#) (p. 209)
- [ReplaceNetworkAclAssociation](#) (p. 345)

- [ReplaceNetworkAclEntry](#) (p. 347)

Placement Groups

- [CreatePlacementGroup](#) (p. 77)
- [DeletePlacementGroup](#) (p. 119)
- [DescribePlacementGroups](#) (p. 222)

Reserved Instances

- [DescribeReservedInstances](#) (p. 228)
- [DescribeReservedInstancesOfferings](#) (p. 232)
- [PurchaseReservedInstancesOffering](#) (p. 335)

Route Tables (Amazon VPC)

- [AssociateRouteTable](#) (p. 23)
- [CreateRoute](#) (p. 79)
- [CreateRouteTable](#) (p. 82)
- [DeleteRoute](#) (p. 121)
- [DeleteRouteTable](#) (p. 123)
- [DescribeRouteTables](#) (p. 236)
- [DisassociateRouteTable](#) (p. 304)
- [ReplaceRoute](#) (p. 350)
- [ReplaceRouteTableAssociation](#) (p. 352)

Security Groups

- [AuthorizeSecurityGroupEgress](#) (p. 33) (Amazon VPC security groups only)
- [AuthorizeSecurityGroupIngress](#) (p. 36)
- [CreateSecurityGroup](#) (p. 84)
- [DeleteSecurityGroup](#) (p. 125)
- [DescribeSecurityGroups](#) (p. 240)
- [RevokeSecurityGroupEgress](#) (p. 373) (Amazon VPC security groups only)
- [RevokeSecurityGroupIngress](#) (p. 376)

Spot Instances

- [CancelSpotInstanceRequests](#) (p. 49)
- [CreateSpotDatafeedSubscription](#) (p. 89)
- [DeleteSpotDatafeedSubscription](#) (p. 129)
- [DescribeSpotDatafeedSubscription](#) (p. 251)
- [DescribeSpotInstanceRequests](#) (p. 253)

- [DescribeSpotPriceHistory](#) (p. 259)
- [RequestSpotInstances](#) (p. 357)

Subnets (Amazon VPC)

- [CreateSubnet](#) (p. 91)
- [DeleteSubnet](#) (p. 130)
- [DescribeSubnets](#) (p. 263)

Tags

- [CreateTags](#) (p. 93)
- [DeleteTags](#) (p. 132)
- [DescribeTags](#) (p. 267)

VM Import

- [CancelConversionTask](#) (p. 45)
- [DescribeConversionTasks](#) (p. 156)
- [ImportInstance](#) (p. 312)
- [ImportVolume](#) (p. 318)

VM Export

- [CancelExportTask](#) (p. 47)
- [CreateInstanceExportTask](#) (p. 60)
- [DescribeExportTasks](#) (p. 165)

VPCs (Amazon VPC)

- [CreateVpc](#) (p. 97)
- [DeleteVpc](#) (p. 137)
- [DescribeVpcs](#) (p. 283)

VPN Connections (Amazon VPC)

- [CreateVpnConnection](#) (p. 99)
- [DeleteVpnConnection](#) (p. 139)
- [DescribeVpnConnections](#) (p. 286)

Virtual Private Gateways (Amazon VPC)

- [AttachVpnGateway](#) (p. 31)
- [CreateVpnGateway](#) (p. 103)
- [DeleteVpnGateway](#) (p. 141)

- [DescribeVpnGateways](#) (p. 290)
- [DetachVpnGateway](#) (p. 300)

Windows

- [BundleInstance](#) (p. 40)
- [CancelBundleTask](#) (p. 43)
- [DescribeBundleTasks](#) (p. 153)
- [GetPasswordData](#) (p. 310)

Actions

Topics

- [AllocateAddress](#) (p. 13)
- [AssignPrivateIpAddresses](#) (p. 15)
- [AssociateAddress](#) (p. 18)
- [AssociateDhcpOptions](#) (p. 21)
- [AssociateRouteTable](#) (p. 23)
- [AttachInternetGateway](#) (p. 25)
- [AttachNetworkInterface](#) (p. 27)
- [AttachVolume](#) (p. 29)
- [AttachVpnGateway](#) (p. 31)
- [AuthorizeSecurityGroupEgress](#) (p. 33)
- [AuthorizeSecurityGroupIngress](#) (p. 36)
- [BundleInstance](#) (p. 40)
- [CancelBundleTask](#) (p. 43)
- [CancelConversionTask](#) (p. 45)
- [CancelExportTask](#) (p. 47)
- [CancelSpotInstanceRequests](#) (p. 49)
- [ConfirmProductInstance](#) (p. 51)
- [CreateCustomerGateway](#) (p. 53)
- [CreateDhcpOptions](#) (p. 55)
- [CreateImage](#) (p. 58)
- [CreateInstanceExportTask](#) (p. 60)
- [CreateInternetGateway](#) (p. 63)
- [CreateKeyPair](#) (p. 65)
- [CreateNetworkAcl](#) (p. 67)
- [CreateNetworkAclEntry](#) (p. 69)
- [CreateNetworkInterface](#) (p. 72)
- [CreatePlacementGroup](#) (p. 77)
- [CreateRoute](#) (p. 79)
- [CreateRouteTable](#) (p. 82)
- [CreateSecurityGroup](#) (p. 84)

- [CreateSnapshot](#) (p. 86)
- [CreateSpotDatafeedSubscription](#) (p. 89)
- [CreateSubnet](#) (p. 91)
- [CreateTags](#) (p. 93)
- [CreateVolume](#) (p. 95)
- [CreateVpc](#) (p. 97)
- [CreateVpnConnection](#) (p. 99)
- [CreateVpnGateway](#) (p. 103)
- [DeleteCustomerGateway](#) (p. 105)
- [DeleteDhcpOptions](#) (p. 107)
- [DeleteInternetGateway](#) (p. 109)
- [DeleteKeyPair](#) (p. 111)
- [DeleteNetworkAcl](#) (p. 113)
- [DeleteNetworkAclEntry](#) (p. 115)
- [DeleteNetworkInterface](#) (p. 117)
- [DeletePlacementGroup](#) (p. 119)
- [DeleteRoute](#) (p. 121)
- [DeleteRouteTable](#) (p. 123)
- [DeleteSecurityGroup](#) (p. 125)
- [DeleteSnapshot](#) (p. 127)
- [DeleteSpotDatafeedSubscription](#) (p. 129)
- [DeleteSubnet](#) (p. 130)
- [DeleteTags](#) (p. 132)
- [DeleteVolume](#) (p. 135)
- [DeleteVpc](#) (p. 137)
- [DeleteVpnConnection](#) (p. 139)
- [DeleteVpnGateway](#) (p. 141)
- [DeregisterImage](#) (p. 143)
- [DescribeAddresses](#) (p. 145)
- [DescribeAvailabilityZones](#) (p. 150)
- [DescribeBundleTasks](#) (p. 153)
- [DescribeConversionTasks](#) (p. 156)
- [DescribeCustomerGateways](#) (p. 158)
- [DescribeDhcpOptions](#) (p. 161)
- [DescribeExportTasks](#) (p. 165)
- [DescribeImageAttribute](#) (p. 167)
- [DescribeImages](#) (p. 170)
- [DescribeInstanceAttribute](#) (p. 178)
- [DescribeInstances](#) (p. 181)
- [DescribeInstanceState](#) (p. 197)
- [DescribeInternetGateways](#) (p. 203)
- [DescribeKeyPairs](#) (p. 206)
- [DescribeNetworkAcls](#) (p. 209)
- [DescribeNetworkInterfaceAttribute](#) (p. 214)
- [DescribeNetworkInterfaces](#) (p. 216)
- [DescribePlacementGroups](#) (p. 222)

- [DescribeRegions](#) (p. 225)
- [DescribeReservedInstances](#) (p. 228)
- [DescribeReservedInstancesOfferings](#) (p. 232)
- [DescribeRouteTables](#) (p. 236)
- [DescribeSecurityGroups](#) (p. 240)
- [DescribeSnapshotAttribute](#) (p. 244)
- [DescribeSnapshots](#) (p. 246)
- [DescribeSpotDatafeedSubscription](#) (p. 251)
- [DescribeSpotInstanceRequests](#) (p. 253)
- [DescribeSpotPriceHistory](#) (p. 259)
- [DescribeSubnets](#) (p. 263)
- [DescribeTags](#) (p. 267)
- [DescribeVolumes](#) (p. 272)
- [DescribeVolumeAttribute](#) (p. 276)
- [DescribeVolumeStatus](#) (p. 278)
- [DescribeVpcs](#) (p. 283)
- [DescribeVpnConnections](#) (p. 286)
- [DescribeVpnGateways](#) (p. 290)
- [DetachInternetGateway](#) (p. 294)
- [DetachNetworkInterface](#) (p. 296)
- [DetachVolume](#) (p. 298)
- [DetachVpnGateway](#) (p. 300)
- [DisassociateAddress](#) (p. 302)
- [DisassociateRouteTable](#) (p. 304)
- [EnableVolumeIO](#) (p. 306)
- [GetConsoleOutput](#) (p. 308)
- [GetPasswordData](#) (p. 310)
- [ImportInstance](#) (p. 312)
- [ImportKeyPair](#) (p. 316)
- [ImportVolume](#) (p. 318)
- [ModifyImageAttribute](#) (p. 321)
- [ModifyInstanceAttribute](#) (p. 324)
- [ModifyNetworkInterfaceAttribute](#) (p. 327)
- [ModifySnapshotAttribute](#) (p. 329)
- [ModifyVolumeAttribute](#) (p. 331)
- [MonitorInstances](#) (p. 333)
- [PurchaseReservedInstancesOffering](#) (p. 335)
- [RebootInstances](#) (p. 337)
- [RegisterImage](#) (p. 339)
- [ReleaseAddress](#) (p. 343)
- [ReplaceNetworkAclAssociation](#) (p. 345)
- [ReplaceNetworkAclEntry](#) (p. 347)
- [ReplaceRoute](#) (p. 350)
- [ReplaceRouteTableAssociation](#) (p. 352)
- [ReportInstanceStatus](#) (p. 354)
- [RequestSpotInstances](#) (p. 357)

- [ResetImageAttribute](#) (p. 365)
- [ResetInstanceAttribute](#) (p. 367)
- [ResetNetworkInterfaceAttribute](#) (p. 369)
- [ResetSnapshotAttribute](#) (p. 371)
- [RevokeSecurityGroupEgress](#) (p. 373)
- [RevokeSecurityGroupIngress](#) (p. 376)
- [RunInstances](#) (p. 379)
- [StartInstances](#) (p. 390)
- [StopInstances](#) (p. 392)
- [TerminateInstances](#) (p. 394)
- [UnassignPrivateIpAddresses](#) (p. 396)
- [UnmonitorInstances](#) (p. 398)

AllocateAddress

Description

This action applies to both EC2 Elastic IP addresses and VPC Elastic IP addresses.

For EC2 addresses: Acquires an Elastic IP address for use with your Amazon Web Services (AWS) account. For more information about EC2 Elastic IP addresses, see [Instance Addressing](#) in the *Amazon Elastic Compute Cloud User Guide*.

For VPC addresses: Acquires an Elastic IP address for use with your VPC. For information about VPC addresses and how they differ from EC2 addresses, see the [Elastic IP Addresses](#) in the *Amazon Virtual Private Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|---------------|--|-------------|
| <i>Domain</i> | Set to <code>vpc</code> to allocate the address to your VPC. Type: String Default: Address is standard (allocated to EC2) Valid values: <code>vpc</code> Condition: Required when allocating an address to a VPC | Conditional |

Response Elements

The elements in the following table are wrapped in an `AllocateAddressResponse` structure.

| Name | Description |
|---------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>publicIp</code> | The Elastic IP address. Type: <code>xsd:string</code> |
| <code>domain</code> | Specifies whether this Elastic IP address is for instances in EC2 (<code>standard</code>) or instances in a VPC. Type: <code>xsd:string</code> Valid values: <code>standard</code> <code>vpc</code> |
| <code>allocationId</code> | The ID that AWS assigns to represent the allocation of the address for use with Amazon VPC. Returned only for VPC elastic IP addresses. Type: <code>xsd:string</code> |

Examples

Example Request

This example returns an Elastic IP address for use with the account.

```
https://ec2.amazonaws.com/?Action=AllocateAddress
&AUTHPARAMS
```

Example Response

```
<AllocateAddressResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <publicIp>192.0.2.1</publicIp>
</AllocateAddressResponse>
```

Example Request

This example returns a VPC Elastic IP address for use with Amazon VPC.

```
https://ec2.amazonaws.com/?Action=AllocateAddress
Domain=vpc
&AUTHPARAMS
```

Example Response

```
<AllocateAddressResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <publicIp>198.51.100.1</publicIp>
  <domain>vpc</domain>
  <allocationId>eipalloc-5723d13e</allocationId>
</AllocateAddressResponse>
```

Related Operations

- [DescribeAddresses](#) (p. 145)
- [ReleaseAddress](#) (p. 343)
- [AssociateAddress](#) (p. 18)
- [DisassociateAddress](#) (p. 302)

AssignPrivateIpAddresses

Description

Assigns one or more secondary private IP addresses to a network interface in Amazon VPC. You can specify one or more specific secondary IP addresses that you want to assign or you can specify a number of secondary IP addresses to be automatically assigned within the subnet's CIDR block range. The number of secondary IP addresses that you can assign to an instance varies by instance type. For information on Amazon EC2 instance types, see [Available Instance Types](#) in the *Amazon Elastic Compute Cloud User Guide*. For more information about Elastic IP addresses for Amazon VPC, see [Elastic IP Addresses](#) in the *Amazon Virtual Private Cloud User Guide*.

This command is only available in Amazon VPC.

Request Parameters

| Name | Description | Required |
|---------------------------------------|---|-------------|
| <i>NetworkInterfaceId</i> | The network interface to which the IP address will be assigned. Type: String Default: None | Yes |
| <i>PrivateIpAddress.n</i> | Assigns the specified IP address as secondary IP address to the network interface. This option can be used multiple times to assign multiple secondary private IP addresses to network interface. Type: <code>AssignPrivateIpAddressesSetItemRequestType</code> Default: None Condition: You cannot specify this parameter when also specifying <code>SecondaryPrivateIpAddressCount</code> . | Conditional |
| <i>SecondaryPrivateIpAddressCount</i> | The number of secondary IP addresses to assign to the network interface. Type: Integer Default: None Condition: You cannot specify this parameter when also specifying <code>PrivateIPAddresses.n</code> . | Conditional |
| <i>AllowReassignment</i> | Specifies whether to allow an IP address that is already assigned to another network interface or instance to be reassigned to the specified network interface. Type: Boolean Default: False | No |

Response Elements

The elements in the following table are wrapped in an `AssignPrivateIpAddressesResponse` structure.

| Name | Description |
|-----------|---|
| requestId | The ID of the request. Type: xsd:string |
| return | Returns true if the request succeeds. Otherwise, returns an error. Type: xsd:boolean |

Examples

Example Request

This example assigns two secondary private IP addresses (10.0.2.1 and 10.0.2.11) to the specified network interface.

```
https://ec2.amazonaws.com/?Action=AssignPrivateIpAddresses
&NetworkInterfaceId=eni-d83388b1
&PrivateIpAddress.0=10.0.2.1
&PrivateIpAddress.1=10.0.2.11
&AUTHPARAMS
```

Example Response

```
<AssignPrivateIpAddresses xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <return>true</return>
</AssignPrivateIpAddresses>
```

Example Request

This example assigns two secondary private IP addresses to the network interface. The IP addresses are automatically assigned from the available IP addresses within the subnet's CIDR block range.

```
https://ec2.amazonaws.com/?Action=AssignPrivateIpAddresses
&NetworkInterfaceId=eni-d83388b1
&SecondaryPrivateIpAddressCount=2
&AUTHPARAMS
```

Example Response

```
<AssignPrivateIpAddresses xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <return>true</return>
</AssignPrivateIpAddresses>
```

Related Operations

- [DescribeAddresses](#) (p. 145)
- [ReleaseAddress](#) (p. 343)

- [AssociateAddress](#) (p. 18)
- [DisassociateAddress](#) (p. 302)

AssociateAddress

Description

This action applies to both EC2 Elastic IP addresses and VPC Elastic IP addresses.

For EC2 addresses: Associates an Elastic IP address with an instance (not running in a VPC). If the IP address is currently assigned to another instance, the IP address is assigned to the new instance. For more information about EC2 Elastic IP addresses, see [Instance Addressing](#) in the *Amazon Elastic Compute Cloud User Guide*.

For VPC addresses: Associates a VPC Elastic IP address with an instance in your VPC. If the IP address is currently assigned to another instance, Amazon EC2 returns an error. For information about VPC addresses and how they differ from EC2 addresses, see [Elastic IP Addresses](#) in the *Amazon Virtual Private Cloud User Guide*.

This is an idempotent operation. If you enter it more than once, Amazon EC2 does not return an error.

Request Parameters

| Name | Description | Required |
|---------------------------|--|-------------|
| <i>PublicIp</i> | The Elastic IP address to assign to the instance. Type: String Default: None Condition: Required for EC2 Elastic IP addresses | Conditional |
| <i>InstanceId</i> | The instance to associate with the IP address. Type: String Default: None | Conditional |
| <i>AllocationId</i> | The allocation ID that AWS returned when you allocated the Elastic IP address for use with Amazon VPC. Type: String Default: None Condition: Required for VPC Elastic IP addresses. | No |
| <i>NetworkInterfaceId</i> | The network interface ID to associate with an instance. Association will fail when specifying an instance ID unless exactly one interface is attached. Type: String Default: None Condition: If the instance has more than one network interface, you must specify a network interface ID. Available for VPC Elastic IP addresses only. | No |

| Name | Description | Required |
|---------------------------|--|----------|
| <i>PrivateIpAddress</i> | The primary or secondary private IP address to associate with the Elastic IP address. If no private IP address is specified, the Elastic IP address is associated with the primary private IP address. This is only available in Amazon VPC. Type: String Default: None | No |
| <i>AllowReassociation</i> | Allows an Elastic IP address that is already associated with another network interface or instance to be re-associated with the specified instance or interface. If the Elastic IP address is associated, and this option is not specified, the operation will fail. This is only available in Amazon VPC. Type: Boolean Default: False if not specified | No |

Response Elements

The elements in the following table are wrapped in an `AssociateAddressResponse` structure.

| Name | Description |
|----------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |
| <code>associationId</code> | The ID that AWS provides to represent the association of the address with an instance. Returned only for VPC Elastic IP addresses. Type: <code>xsd:string</code> |

Examples

Example Request

This example associates an EC2 Elastic IP address with an instance.

```
https://ec2.amazonaws.com/?Action=AssociateAddress
&InstanceId=i-2ea64347
&PublicIp=192.0.2.1
&AUTHPARAMS
```

Example Response

```
<AssociateAddressResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <return>true</return>
</AssociateAddressResponse>
```

Example Request

This example associates a VPC Elastic IP address with an instance in your VPC and allows the Elastic IP address to be re-assigned to this instance if it is currently assigned to another instance or interface.

```
https://ec2.amazonaws.com/?Action=AssociateAddress
&InstanceId=i-4fd2431a
&AllocationId=eipalloc-5723d13e
&AllowReassignment=true
&AUTHPARAMS
```

Example Response

```
<AssociateAddressResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <return>true</return>
  <associationId>eipassoc-fc5ca095</associationId>
</AssociateAddressResponse>
```

Related Operations

- [AllocateAddress](#) (p. 13)
- [DescribeAddresses](#) (p. 145)
- [ReleaseAddress](#) (p. 343)
- [DisassociateAddress](#) (p. 302)

AssociateDhcpOptions

Description

Associates a set of DHCP options (that you've previously created) with the specified VPC. Or, associates no DHCP options with the VPC.

After you associate the options with the VPC, any existing instances and all new instances that you launch in that VPC use the options. You don't need to restart or relaunch the instances. They automatically pick up the changes within a few hours, depending on how frequently the instance renews its DHCP lease. If you want, you can explicitly renew the lease using the operating system on the instance.

For more information about the supported DHCP options and using them with Amazon VPC, see [Using DHCP Options in Your VPC](#) in the *Amazon Virtual Private Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|----------------------|---|----------|
| <i>DhcpOptionsId</i> | The ID of the DHCP options you want to associate with the VPC, or <code>default</code> if you want the VPC to use no DHCP options. Type: String Default: None | Yes |
| <i>VpcId</i> | The ID of the VPC you want to associate the DHCP options with. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in an `AssociateDhcpOptionsResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example associates the DHCP options with ID `dopt-7a8b9c2d` with the VPC with ID `vpc-1a2b3c4d`.

```
https://ec2.amazonaws.com/?Action=AssociateDhcpOptions
&DhcpOptionsId=dopt-7a8b9c2d
&VpcId=vpc-1a2b3c4d
&AUTHPARAMS
```

Example Response

```
<AssociateDhcpOptionsResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</requestId>
  <return>>true</return>
</AssociateDhcpOptionsResponse>
```

Example Request

This example changes the VPC with ID vpc-1a2b3c4d to use no DHCP options.

```
https://ec2.amazonaws.com/?Action=AssociateDhcpOptions
&DhcpOptionsId=default
&VpcId=vpc-1a2b3c4d
&AUTHPARAMS
```

Example Response

```
<AssociateDhcpOptionsResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</requestId>
  <return>>true</return>
</AssociateDhcpOptionsResponse>
```

Related Operations

- [CreateDhcpOptions](#) (p. 55)
- [DescribeDhcpOptions](#) (p. 161)
- [DeleteDhcpOptions](#) (p. 107)

AssociateRouteTable

Description

Associates a subnet with a route table. The subnet and route table must be in the same VPC. This association causes traffic originating from the subnet to be routed according to the routes in the route table. The action returns an association ID, which you need if you want to disassociate the route table from the subnet later. A route table can be associated with multiple subnets.

For more information about route tables, see [Route Tables](#) in the *Amazon Virtual Private Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|---------------------|---|----------|
| <i>RouteTableId</i> | The ID of the route table. Type: String Default: None | Yes |
| <i>SubnetId</i> | The ID of the subnet. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in an `AssociateRouteTableResponse` structure.

| Name | Description |
|----------------------------|---|
| <code>requestId</code> | The ID of the request. Type: xsd:string |
| <code>associationId</code> | The ID that AWS provides to represent the association of the route table and the subnet. Type: xsd:string Example: <code>rtbassoc-f8ad4891</code> |

Examples

Example Request

This example associates a route table with ID `rtb-e4ad488d` with a subnet with ID `subnet-15ad487c`.

```
https://ec2.amazonaws.com/?Action=AssociateRouteTable
&RouteTableId=rtb-e4ad488d
&SubnetId=subnet-15ad487c
```

Example Response

```
<AssociateRouteTableResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <associationId>rtbassoc-f8ad4891</associationId>
</AssociateRouteTableResponse>
```

Related Operations

- [CreateRouteTable](#) (p. 82)
- [DisassociateRouteTable](#) (p. 304)
- [DescribeRouteTables](#) (p. 236)
- [ReplaceRouteTableAssociation](#) (p. 352)

AttachInternetGateway

Description

Attaches an Internet gateway to a VPC, enabling connectivity between the Internet and the VPC. For more information about your VPC and Internet gateway, see the [Amazon Virtual Private Cloud User Guide](#).

Request Parameters

| Name | Description | Required |
|--------------------------|--|----------|
| <i>InternetGatewayId</i> | The ID of the Internet gateway. Type: String Default: None | Yes |
| <i>VpcId</i> | The ID of the VPC. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in an `AttachInternetGatewayResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

The example attaches the Internet gateway with ID `igw-eaad4883` to the VPC with ID `vpc-11ad4878`.

```
https://ec2.amazonaws.com/?Action=AttachInternetGateway
&InternetGatewayId=igw-eaad4883
&VpcId=vpc-11ad4878
&AUTHPARAMS
```

Example Response

```
<AttachInternetGatewayResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
```



```
<requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>  
<return>>true</return>  
</AttachInternetGatewayResponse>
```

Related Operations

- [CreateInternetGateway](#) (p. 63)
- [DeleteInternetGateway](#) (p. 109)
- [DetachInternetGateway](#) (p. 294)
- [DescribeInternetGateways](#) (p. 203)

AttachNetworkInterface

Description

Attaches a network interface to an instance.

Request Parameters

| Name | Description | Required |
|---------------------------|---|----------|
| <i>NetworkInterfaceId</i> | The ID of the network interface to attach. Type: String Default: None | Yes |
| <i>InstanceId</i> | The ID of the instance to attach to the network interface. Type: String Default: None | Yes |
| <i>DeviceIndex</i> | The index of the device for the network interface attachment on the instance. Type: Integer Default: None | Yes |

Response Elements

The elements in the following table are wrapped in an `AttachNetworkInterfaceResponse` structure.

| Name | Description |
|---------------------------|---|
| <code>requestId</code> | The ID of the attachment request. Type: xsd:string |
| <code>attachmentId</code> | The ID of the attachment. Type: xsd:string |

Examples

Example Request

This example attaches an elastic network interface (ENI) `eni-ffda3197` to the specified EC2 instance `i-9cc316fe`.

```
https://ec2.amazonaws.com/?Action=AttachNetworkInterface
&DeviceIndex=1
&InstanceId=i-9cc316fe
&NetworkInterfaceId=eni-ffda3197
&AUTHPARAMS
```

Example Response

```
<AttachNetworkInterfaceResponse xmlns='http://ec2.amazonaws.com/doc/2011-11-15/'>
  <requestId>ace8cd1e-e685-4e44-90fb-92014d907212</requestId>
  <attachmentId>eni-attach-d94b09b0</attachmentId>
</AttachNetworkInterfaceResponse>
```

Related Operations

- [DetachNetworkInterface](#) (p. 296)
- [CreateNetworkInterface](#) (p. 72)
- [DeleteNetworkInterface](#) (p. 117)
- [DescribeNetworkInterfaceAttribute](#) (p. 214)
- [DescribeNetworkInterfaces](#) (p. 216)
- [ModifyNetworkInterfaceAttribute](#) (p. 327)
- [ResetNetworkInterfaceAttribute](#) (p. 369)

AttachVolume

Description

Attaches an Amazon EBS volume to a running instance and exposes it as the specified device.

For a list of supported device names, see [Attaching the Volume to an Instance](#). Any devices that aren't reserved for instance store volumes can be attached to an Amazon EBS volume. For more information, see [Amazon EC2 Instance Store](#).

Note

If a volume has an AWS Marketplace product code:

- The volume can only be attached to the root device of a stopped instance.
- You must be subscribed to the AWS Marketplace code that is on the volume.
- The configuration (instance type, operating system) of the instance must support that specific AWS Marketplace code. For example, you cannot take a volume from a Windows instance and attach it to a Linux instance.
- AWS Marketplace product codes are copied from the volume to the instance.

For an overview of the AWS Marketplace, go to <https://aws.amazon.com/marketplace/help/200900000>. For details on how to use the AWS Marketplace, see [AWS Marketplace](#).

Request Parameters

| Name | Description | Required |
|-------------------|--|----------|
| <i>VolumeId</i> | The ID of the Amazon EBS volume. The volume and instance must be within the same Availability Zone. Type: String Default: None | Yes |
| <i>InstanceId</i> | The ID of the instance. The instance must be running. Type: String Default: None | Yes |
| <i>Device</i> | The device name as exposed to the instance (e.g., /dev/sdh, or xvdh). Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in an `AttachVolumeResponse` structure.

| Name | Description |
|------------------------|--|
| <code>requestId</code> | The ID of the request. Type: xsd:string |

| Name | Description |
|------------|--|
| volumeId | The ID of the volume. Type: xsd:string |
| instanceId | The ID of the instance. Type: xsd:string |
| device | The device name as exposed to the instance (e.g., /dev/sdh, or xvdh). Type: xsd:string |
| status | The volume state. Type: xsd:string Valid values: attaching attached detaching detached |
| attachTime | The time stamp when the attachment initiated. Type: xsd:dateTime |

Examples

Example Request

This example attaches volume `vol-4d826724` to instance `i-6058a509` and exposes it as `/dev/sdh`. For information on standard storage locations, see the [Amazon Elastic Compute Cloud User Guide](#).

```
https://ec2.amazonaws.com/?Action=AttachVolume
&VolumeId=vol-4d826724
&InstanceId=i-6058a509
&Device=/dev/sdh
&AUTHPARAMS
```

Example Response

```
<AttachVolumeResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <volumeId>vol-4d826724</volumeId>
  <instanceId>i-6058a509</instanceId>
  <device>/dev/sdh</device>
  <status>attaching</status>
  <attachTime>2008-05-07T11:51:50.000Z</attachTime>
</AttachVolumeResponse>
```

Related Operations

- [CreateVolume](#) (p. 95)
- [DeleteVolume](#) (p. 135)
- [DescribeVolumes](#) (p. 272)
- [DetachVolume](#) (p. 298)

AttachVpnGateway

Description

Attaches a virtual private gateway to a VPC. For more information, see [Adding an IPsec Hardware Virtual Private Gateway to Your VPC](#) in the *Amazon Virtual Private Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|---------------------|---|----------|
| <i>VpnGatewayId</i> | The ID of the virtual private gateway. Type: String Default: None | Yes |
| <i>VpcId</i> | The ID of the VPC. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in an `AttachVpnGatewayResponse` structure.

| Name | Description |
|-------------------------|--|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>attachment</code> | Information about the attachment. Type: AttachmentType (p. 404) |

Examples

Example Request

This example attaches the virtual private gateway with ID `vgw-8db04f81` to the VPC with ID `vpc-1a2b3c4d`.

```
https://ec2.amazonaws.com/?Action=AttachVpnGateway
&VpnGatewayId=vgw-8db04f81
&VpcId=vpc-1a2b3c4d
&AUTHPARAMS
```

Example Response

```
<AttachVpnGatewayResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</requestId>
  <attachment>
```

```
<vpcId>vpc-1a2b3c4d</vpcId>  
<state>attaching</state>  
</attachment>  
</AttachVpnGatewayResponse>
```

Related Operations

- [CreateVpnGateway](#) (p. 103)
- [DescribeVpnGateways](#) (p. 290)
- [DetachVpnGateway](#) (p. 300)
- [CreateVpc](#) (p. 97)
- [CreateVpnConnection](#) (p. 99)

AuthorizeSecurityGroupEgress

Description

Adds one or more egress rules to a VPC security group. Specifically, this action permits instances in a security group to send traffic to one or more destination CIDR IP address ranges, or to one or more destination security groups in the same VPC.

This action applies only to security groups in a VPC; it's not supported for EC2 security groups. For information about Amazon Virtual Private Cloud and VPC security groups, see [Security Groups](#) in the *Amazon Virtual Private Cloud User Guide*.

Each rule consists of the protocol (e.g., TCP), plus either a CIDR range or a source group. For the TCP and UDP protocols, you must also specify the destination port or port range. For the ICMP protocol, you must also specify the ICMP type and code. You can use -1 for the type or code to mean all types or all codes.

Rule changes are propagated to instances within the security group as quickly as possible. However, a small delay might occur.

Important

For VPC security groups: You can have up to 50 rules total per group (covering both ingress and egress).

Request Parameters

| Name | Description | Required |
|-----------------------------------|---|-------------|
| <i>GroupId</i> | The ID of the VPC security group to modify. Type: String Default: None | Yes |
| <i>IpPermissions.n.IpProtocol</i> | The IP protocol name or number (go to Protocol Numbers). When you call <code>DescribeSecurityGroups</code> , the protocol value returned is the number. Exception: For TCP, UDP, and ICMP, the value returned is the name (e.g., <code>tcp</code> , <code>udp</code> , or <code>icmp</code>). Type: String Valid values: <code>tcp</code> <code>udp</code> <code>icmp</code> or any protocol number (go to Protocol Numbers). Use <code>-1</code> to specify all. | Yes |
| <i>IpPermissions.n.FromPort</i> | The start of port range for the TCP and UDP protocols, or an ICMP type number. For the ICMP type number, you can use -1 to specify all ICMP types. Type: Integer Default: None Condition: Required for ICMP and any protocol that uses ports | Conditional |

| Name | Description | Required |
|--|---|-------------|
| <i>IpPermissions.n.ToPort</i> | The end of port range for the TCP and UDP protocols, or an ICMP code number. For the ICMP code number, you can use -1 to specify all ICMP codes for the given ICMP type. Type: Integer Default: None Condition: Required for ICMP and any protocol that uses ports | Conditional |
| <i>IpPermissions.n.Groups.m.GroupId</i> | The name of the destination security group. Cannot be used when specifying a CIDR IP address. Type: String Default: None Condition: Required if modifying access for one or more destination security groups. | Conditional |
| <i>IpPermissions.n.IpRanges.m.CidrIp</i> | The CIDR range. Cannot be used when specifying a destination security group. Type: String Default: None Constraints: Valid CIDR IP address range. Condition: Required if modifying access for one or more IP address ranges. | Conditional |

Response Elements

The elements in the following table are wrapped in an `AuthorizeSecurityGroupEgressResponse` structure.

| Name | Description |
|------------------------|--|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if request is successful. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example grants your VPC security group with ID `sg-1a2b3c4d` access to the `192.0.2.0/24` and `198.51.100.0/24` address ranges on TCP port 80.

```
https://ec2.amazonaws.com/?Action=AuthorizeSecurityGroupEgress
&GroupId=sg-1a2b3c4d
&IpPermissions.1.IpProtocol=tcp
&IpPermissions.1.FromPort=80
```

```
&IpPermissions.1.ToPort=80
&IpPermissions.1.IpRanges.1.CidrIp=192.0.2.0/24
&IpPermissions.1.IpRanges.2.CidrIp=198.51.100.0/24
&AUTHPARAMS
```

Example Request

This example grants your VPC security group with ID sg-1a2b3c4d access to your VPC security group with ID sg-9a8d7f5c on TCP port 1433.

```
https://ec2.amazonaws.com/?Action=AuthorizeSecurityGroupEgress
&GroupId=sg-1a2b3c4d
&IpPermissions.1.IpProtocol=tcp
&IpPermissions.1.FromPort=1433
&IpPermissions.1.ToPort=1433
&IpPermissions.1.Groups.1.GroupId=sg-9a8d7f5c
&AUTHPARAMS
```

Example Response

```
<AuthorizeSecurityGroupEgressResponse xmlns="http://ec2.amazonaws.com/doc/2012-
06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <return>true</return>
</AuthorizeSecurityGroupEgressResponse>
```

Related Operations

- [CreateSecurityGroup](#) (p. 84)
- [DescribeSecurityGroups](#) (p. 240)
- [RevokeSecurityGroupEgress](#) (p. 373)
- [AuthorizeSecurityGroupIngress](#) (p. 36)
- [RevokeSecurityGroupIngress](#) (p. 376)
- [DeleteSecurityGroup](#) (p. 125)

AuthorizeSecurityGroupIngress

Description

Adds one or more ingress rules to a security group. This action applies to both EC2 security groups and VPC security groups. For information about VPC security groups and how they differ from EC2 security groups, see [Security Groups](#) in the *Amazon Virtual Private Cloud User Guide*.

For EC2 security groups, this action gives one or more CIDR IP address ranges permission to access a security group in your account, or gives one or more security groups (called the *source groups*) permission to access a security group in your account. A source group can be in your own AWS account, or another.

For VPC security groups, this action gives one or more CIDR IP address ranges permission to access a security group in your VPC, or gives one or more other security groups (called the *source groups*) permission to access a security group in your VPC. The groups must all be in the same VPC.

Each rule consists of the protocol (e.g., TCP), plus either a CIDR range or a source group. For the TCP and UDP protocols, you must also specify the destination port or port range. For the ICMP protocol, you must also specify the ICMP type and code. You can use -1 for the type or code to mean all types or all codes.

Rule changes are propagated to instances within the security group as quickly as possible. However, a small delay might occur.

Important

For EC2 security groups: You can have up to 100 rules per group.

For VPC security groups: You can have up to 50 rules total per group (covering both ingress and egress).

Request Parameters

| Name | Description | Required |
|------------------|--|-------------|
| <i>UserId</i> | Deprecated | No |
| <i>GroupId</i> | The ID of the EC2 or VPC security group to modify. The group must belong to your account. Type: String Default: None Condition: Required for VPC security groups; can be used instead of <i>GroupName</i> for EC2 security groups | Conditional |
| <i>GroupName</i> | The name of the EC2 security group to modify. Type: String Default: None Condition: Can be used instead of <i>GroupId</i> for EC2 security groups | Conditional |

Amazon Elastic Compute Cloud API Reference
Request Parameters

| Name | Description | Required |
|---|---|-------------|
| <i>IpPermissions.n.IpProtocol</i> | <p>The IP protocol name or number (see Protocol Numbers). EC2 security groups can have rules only for TCP, UDP, and ICMP, whereas VPC security groups can have rules assigned to any protocol number.</p> <p>When you call <code>DescribeSecurityGroups</code>, the protocol value returned is the number. Exception: For TCP, UDP, and ICMP, the value returned is the name (e.g., <code>tcp</code>, <code>udp</code>, or <code>icmp</code>).</p> <p>Type: String</p> <p>Valid values for EC2 security groups: <code>tcp</code> <code>udp</code> <code>icmp</code> or the corresponding protocol number (6 17 1).</p> <p>Valid values for VPC groups: <code>tcp</code> <code>udp</code> <code>icmp</code> or any protocol number (see Protocol Numbers). Use <code>-1</code> to specify all.</p> | Required |
| <i>IpPermissions.n.FromPort</i> | <p>The start of port range for the TCP and UDP protocols, or an ICMP type number. For the ICMP type number, you can use <code>-1</code> to specify all ICMP types.</p> <p>Type: Integer</p> <p>Default: None</p> <p>Default: Required for ICMP and any protocol that uses ports</p> | Conditional |
| <i>IpPermissions.n.ToPort</i> | <p>The end of port range for the TCP and UDP protocols, or an ICMP code number. For the ICMP code number, you can use <code>-1</code> to specify all ICMP codes for the given ICMP type.</p> <p>Type: Integer</p> <p>Default: None</p> <p>Default: Required for ICMP and any protocol that uses ports</p> | Conditional |
| <i>IpPermissions.n.Groups.m.UserId</i> | <p>The AWS account ID that owns the source security group. Cannot be used when specifying a CIDR IP address.</p> <p>Type: String</p> <p>Default: None</p> <p>Condition: For EC2 security groups only. Required if modifying access for one or more source security groups.</p> | Conditional |
| <i>IpPermissions.n.Groups.m.GroupName</i> | <p>The name of the source security group. Cannot be used when specifying a CIDR IP address.</p> <p>Type: String</p> <p>Default: None</p> <p>Condition: Required if modifying access for one or more source security groups.</p> | Conditional |

| Name | Description | Required |
|--|--|-------------|
| <i>IpPermissions.n.Groups.m.GroupId</i> | The ID of the source security group. Cannot be used when specifying a CIDR IP address. Type: String Default: None Condition: For VPC security groups only. Required if modifying access for one or more source security groups. | Conditional |
| <i>IpPermissions.n.IpRanges.m.CidrIp</i> | The CIDR range. Cannot be used when specifying a source security group. Type: String Default: None Constraints: Valid CIDR IP address range. Condition: Required if modifying access for one or more IP address ranges. | Conditional |

Response Elements

The elements in the following table are wrapped in an `AuthorizeSecurityGroupIngressResponse` structure.

| Name | Description |
|------------------------|--|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if request is successful. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example is for an EC2 security group. The request grants the 192.0.2.0/24 and 198.51.100.0/24 address ranges access to your `webserv` security group on TCP port 80.

```
https://ec2.amazonaws.com/?Action=AuthorizeSecurityGroupIngress
&GroupName=webserv
&IpPermissions.1.IpProtocol=tcp
&IpPermissions.1.FromPort=80
&IpPermissions.1.ToPort=80
&IpPermissions.1.IpRanges.1.CidrIp=192.0.2.0/24
&IpPermissions.1.IpRanges.2.CidrIp=198.51.100.0/24
&AUTHPARAMS
```

Example Request

This example is for an EC2 security group. The request grants TCP port 80 access from the source group called `OtherAccountGroup` (in AWS account 11112223333) to your `webserv` security group.

```
https://ec2.amazonaws.com/?Action=AuthorizeSecurityGroupIngress
&GroupName=webserv
&IpPermissions.1.IpProtocol=tcp
&IpPermissions.1.FromPort=80
&IpPermissions.1.ToPort=80
&IpPermissions.1.Groups.1.GroupName=OtherAccountGroup
&IpPermissions.1.Groups.1.UserId=111122223333
&AUTHPARAMS
```

Example Request

This example is for a VPC security group. The request grants TCP port 80 access from the source group called *OtherGroupInMyVPC* (sg-0a5d8e02) to your *VpcWebServers* security group (sg-140ba4c8). The request requires the group IDs and not the group names. Your AWS account ID is 111122223333.

```
https://ec2.amazonaws.com/?Action=AuthorizeSecurityGroupIngress
&GroupId=sg-140ba4c8
&IpPermissions.1.IpProtocol=tcp
&IpPermissions.1.FromPort=80
&IpPermissions.1.ToPort=80
&IpPermissions.1.Groups.1.GroupId=sg-0a5d8e02
&IpPermissions.1.Groups.1.UserId=111122223333
&AUTHPARAMS
```

Example Response

```
<AuthorizeSecurityGroupIngressResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <return>>true</return>
</AuthorizeSecurityGroupIngressResponse>
```

Related Operations

- [CreateSecurityGroup](#) (p. 84)
- [DescribeSecurityGroups](#) (p. 240)
- [RevokeSecurityGroupIngress](#) (p. 376)
- [DeleteSecurityGroup](#) (p. 125)

BundleInstance

Description

Bundles an Amazon instance store-backed Windows instance.

Note

During bundling, only the root store (C:\) is bundled. Data on the instance store is not preserved. For step-by-step instructions to bundle an instance store-backed Windows instance, see [Bundling Amazon EC2 instance store-backed Windows AMIs](#).

This procedure is not applicable for Linux and UNIX instances or Windows instances that use Amazon EBS volumes as their root devices.

Request Parameters

| Name | Description | Required |
|---|---|----------|
| <i>InstanceId</i> | The ID of the instance to bundle. Type: String Default: None | Yes |
| <i>Storage.S3.Bucket</i> | The bucket in which to store the AMI. You can specify a bucket that you already own or a new bucket that Amazon EC2 creates on your behalf. If you specify a bucket that belongs to someone else, Amazon EC2 returns an error. Type: String Default: None | Yes |
| <i>Storage.S3.Prefix</i> | The beginning of the file name of the AMI. Type: String Default: None | Yes |
| <i>Storage.S3.AWSSAccessKeyId</i> | The Access Key ID of the owner of the Amazon S3 bucket. Type: String Default: None | Yes |
| <i>Storage.S3.UploadPolicy</i> | A Base64-encoded Amazon S3 upload policy that gives Amazon EC2 permission to upload items into Amazon S3 on your behalf. Type: String Default: None | Yes |
| <i>Storage.S3.UploadPolicySignature</i> | The signature of the Base64 encoded JSON document. Type: String Default: None | Yes |

JSON Parameters

The upload policy gives Amazon EC2 limited permission to upload items into your Amazon S3 bucket. The following table describes the required parameters for the upload policy JSON document. Parameter


```
<instanceId>i-12345678</instanceId>
<bundleId>bun-c1a540a8</bundleId>
<state>bundling</state>
<startTime>2008-10-07T11:41:50.000Z</startTime>
<updateTime>2008-10-07T11:51:50.000Z</updateTime>
<progress>70%</progress>
<storage>
  <S3>
    <bucket>myawsbucket</bucket>
    <prefix>winami</prefix>
  </S3>
</storage>
</bundleInstanceTask>
</BundleInstanceResponse>
```

Related Operations

- [CancelBundleTask](#) (p. 43)
- [DescribeBundleTasks](#) (p. 153)
- [CreateImage](#) (p. 58)

CancelBundleTask

Description

Cancels a bundling operation for an Amazon S3-backed Windows instance (see [BundleInstance](#) (p. 40)).

Request Parameters

| Name | Description | Required |
|-----------------|---|----------|
| <i>BundleId</i> | The ID of the bundle task. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in a `CancelBundleTaskResponse` structure.

| Name | Description |
|---------------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>bundleInstanceTask</code> | The bundle task. Type: BundleInstanceTaskType (p. 409) |

Examples

Example Request

This example cancels the `bun-cla322b9` bundle task.

```
https://ec2.amazonaws.com/?Action=CancelBundleTask
&BundleId=bun-cla322b9
&AUTHPARAMS
```

Example Response

```
<CancelBundleTaskResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <bundleInstanceTask>
    <instanceId>i-12345678</instanceId>
    <bundleId>bun-cla322b9</bundleId>
    <state>canceling</state>
    <startTime>2008-10-07T11:41:50.000Z</startTime>
    <updateTime>2008-10-07T11:51:50.000Z</updateTime>
    <progress>20%</progress>
```

```
<storage>
  <S3>
    <bucket>myawsbucket</bucket>
    <prefix>my-new-image</prefix>
  </S3>
</storage>
</bundleInstanceTask>
</CancelBundleTaskResponse>
```

Related Operations

- [BundleInstance](#) (p. 40)
- [DescribeBundleTasks](#) (p. 153)

CancelConversionTask

Description

Cancels an active conversion task. The task can be the import of an instance or volume. The command removes all artifacts of the conversion, including a partially uploaded volume or instance. If the conversion is complete or is in the process of transferring the final disk image, the command fails and returns an exception.

For more information, see [Using the Command Line Tools to Import Your Virtual Machine to Amazon EC2](#) in the *Amazon Elastic Compute Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|-------------------------|--|----------|
| <i>ConversionTaskId</i> | The ID of the task. Type: String Default: None | Yes |

Response Elements

| Name | Description |
|------------------|---|
| <i>requestId</i> | The ID of the request. Type: string |
| <i>return</i> | Indicates whether the cancellation was successful. Type: Boolean |

Examples

Example Request

This example cancels the conversion task with ID import-i-fh95npoc.

```
https://ec2.amazonaws.com/?Action=CancelConversionTask
&ConversionTaskId=import-i-fh95npoc
&AUTHPARAMS
```

Example Response

```
<CancelConversionTaskResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <return>true</return>
</CancelConversionTaskResponse>
```

Related Operations

- [ImportInstance](#) (p. 312)
- [ImportVolume](#) (p. 318)
- [DescribeConversionTasks](#) (p. 156)

CancelExportTask

Description

Cancels an active export task. The command removes all artifacts of the export, including any partially created Amazon S3 objects. If the export task is complete or is in the process of transferring the final disk image, the command fails and returns an error.

Request Parameters

| Name | Description | Required |
|---------------------|---|----------|
| <i>ExportTaskId</i> | The ID of the export task. Type: String Default: None | Yes |

Response Elements

| Name | Description |
|------------------|---|
| <i>requestId</i> | The ID of the request. Type: xsd:string |
| <i>return</i> | Indicates whether the cancellation was successful. Type: xsd:boolean |

Examples

Example Request

This example cancels the export task with ID export-i-1234wxyz.

```
https://ec2.amazonaws.com/?Action=CancelExportTask
&exportTaskId=export-i-1234wxyz
&AUTHPARAMS
```

Example Response

```
<CancelExportTask xmlns="http://ec2.amazonaws.com/doc/EC2UserGuide">
<requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
<return>true</return>
</CancelExportTask>
```

Related Operations

- [CreateInstanceExportTask](#) (p. 60)

- [DescribeExportTasks](#) (p. 165)

CancelSpotInstanceRequests

Description

CancelSpotInstanceRequests cancels one or more Spot Instance requests. Spot Instances are instances that Amazon EC2 starts on your behalf when the maximum price that you specify exceeds the current Spot Price. Amazon EC2 periodically sets the Spot Price based on available Spot Instance capacity and current Spot Instance requests. For more information about Spot Instances, see [Spot Instances](#) in the *Amazon Elastic Compute Cloud User Guide*.

Important

Canceling a Spot Instance request does not terminate running Spot Instances associated with the request.

Request Parameters

| Name | Description | Required |
|-------------------------------------|---|----------|
| <code>SpotInstanceRequestIds</code> | One or more Spot Instance request IDs. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in a `CancelSpotInstanceRequestsResponse` structure.

| Name | Description |
|-------------------------------------|--|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>spotInstanceRequestSet</code> | A list of Spot Instance requests. Each request is wrapped in an <code>item</code> element. Type: CancelSpotInstanceRequestsResponseSetItemType (p. 410) |

Examples

Example Request

This example cancels a Spot Instance request.

```
https://ec2.amazonaws.com/?Action=CancelSpotInstanceRequests
&SpotInstanceRequestId.1=sir-e95fae02
&AUTHPARAMS
```


Example Response

```
<CancelSpotInstanceRequestsResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <spotInstanceRequestSet>
    <item>
      <spotInstanceRequestId>sir-e95fae02</spotInstanceRequestId>
      <state>cancelled</state>
    </item>
  </spotInstanceRequestSet></CancelSpotInstanceRequestsResponse>
```

Related Operations

- [DescribeSpotInstanceRequests](#) (p. 253)
- [RequestSpotInstances](#) (p. 357)
- [DescribeSpotPriceHistory](#) (p. 259)

ConfirmProductInstance

Description

Verifies whether a product code is associated with an instance. This can only be executed by the owner of the product code and is useful when a product code owner wants to verify whether another EC2 user's instance is eligible for support.

Request Parameters

| Name | Description | Required |
|--------------------|--|----------|
| <i>ProductCode</i> | The product code. Type: String Default: None | Yes |
| <i>InstanceId</i> | The instance. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in a `ConfirmProductInstanceResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the product code is attached to the instance. Otherwise, returns an error. Type: <code>xsd:boolean</code> |
| <code>ownerId</code> | The instance owner's account ID. Only present if the product code is attached to the instance. Type: <code>xsd:string</code> |

Examples

Example Request

This example displays the product code that is associated with the instance.

```
https://ec2.amazonaws.com/?Action=ConfirmProductInstance
&ProductCode=774F4FF8
&InstanceId=i-10a64379
&AUTHPARAMS
```

Example Response

```
<ConfirmProductInstanceResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <return>true</return>
  <ownerId>111122223333</ownerId>
</ConfirmProductInstanceResponse>
```

Related Operations

- [DescribeInstances](#) (p. 181)
- [RunInstances](#) (p. 379)

CreateCustomerGateway

Description

Provides information to AWS about your VPN customer gateway device. The customer gateway is the appliance at your end of the VPN connection (compared to the virtual private gateway, which is the device at the AWS side of the VPN connection).

You must provide the Internet-routable IP address of the customer gateway's external interface. The IP address must be static and can't be behind a device performing network address translation (NAT).

You must also provide the device's Border Gateway Protocol (BGP) Autonomous System Number (ASN). You can use an existing ASN assigned to your network. If you don't have an ASN already, you can use a private ASN (in the 64512 - 65534 range).

Note

Amazon EC2 supports all 2-byte ASN numbers in the range of 1 - 65534, with the exception of 7224, which is reserved in US East, and 9059, which is reserved in EU West.

For more information about ASNs, see the [Wikipedia article](#).

For more information about Amazon Virtual Private Cloud and VPN customer gateways, see [Adding an IPsec Hardware Virtual Private Gateway to Your VPC](#) in the *Amazon Virtual Private Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|------------------|---|----------|
| <i>Type</i> | The type of VPN connection this customer gateway supports. Type: String Default: None Valid values: <code>ipsec.1</code> | Yes |
| <i>IpAddress</i> | The Internet-routable IP address for the customer gateway's outside interface. The address must be static. Type: String Default: None | Yes |
| <i>BgpAsn</i> | The customer gateway's Border Gateway Protocol (BGP) Autonomous System Number (ASN). Type: Integer Default: None | Yes |

Response Elements

The elements in the following table are wrapped in an `CreateCustomerGatewayResponse` structure.

| Name | Description |
|-----------------|---|
| requestId | The ID of the request. Type: xsd:string |
| customerGateway | Information about the customer gateway. Type: CustomerGatewayType (p. 412) |

Examples

Example Request

This example passes information to AWS about the VPN customer gateway with IP address 12.1.2.3 and ASN 65534.

```
https://ec2.amazonaws.com/?Action=CreateCustomerGateway
&Type=ipsec.1
&IpAddress=12.1.2.3
&BgpAsn=65534
&AUTHPARAMS
```

Example Response

```
<CreateCustomerGatewayResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</requestId>
  <customerGateway>
    <customerGatewayId>cgw-b4dc3961</customerGatewayId>
    <state>pending</state>
    <type>ipsec.1</type>
    <ipAddress>12.1.2.3</ipAddress>
    <bgpAsn>65534</bgpAsn>
    <tagSet/>
  </customerGateway>
</CreateCustomerGatewayResponse>
```

Related Operations

- [DescribeCustomerGateways](#) (p. 158)
- [DeleteCustomerGateway](#) (p. 105)

CreateDhcpOptions

Description

Creates a set of DHCP options for your VPC. After creating the new set, you must then associate it with the VPC, causing all existing and new instances that you launch in the VPC to use the new set of DHCP options. The following table lists the individual DHCP options you can specify. For more information about the options, see [RFC 2132](#).

| DHCP Option Name | Description |
|----------------------|--|
| domain-name | A domain name of your choice (e.g., example.com). |
| domain-name-servers | The IP address of a domain name server. You can specify up to four addresses. |
| ntp-servers | The IP address of a Network Time Protocol (NTP) server. You can specify up to four addresses. |
| netbios-name-servers | The IP address of a NetBIOS name server. You can specify up to four addresses. |
| netbios-node-type | The NetBIOS node type (1, 2, 4, or 8). For more information about the values, see RFC 2132 . We recommend you only use 2 at this time (broadcast and multicast are currently not supported). |

Important

Your VPC automatically starts out with a set of DHCP options that includes only a DNS server that we provide (AmazonProvidedDNS). If you create a new set of options, and if your VPC has an Internet gateway, make sure to set the `domain-name-servers` option either to AmazonProvidedDNS or to a domain name server of your choice.

For more information about Amazon Virtual Private Cloud and DHCP options, see [Using DHCP Options in Your VPC](#) in the *Amazon Virtual Private Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|------------------------------------|---|----------|
| <i>DhcpConfiguration.n.Key</i> | The name of a DHCP option. Type: String Default: None | Yes |
| <i>DhcpConfiguration.n.Value.m</i> | A value for the DHCP option. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in an `CreateDhcpOptionsResponse` structure.

| Name | Description |
|-------------|--|
| requestId | The ID of the request. Type: xsd:string |
| dhcpOptions | A set of DHCP options. Type: DhcpOptionsType (p. 422) |

Examples

Example Request

This example creates a new set of DHCP options with a domain name example.com and two DNS servers (10.2.5.1 and 10.2.5.2).

```
https://ec2.amazonaws.com/?Action=CreateDhcpOptions
&DhcpConfiguration.1.Key=domain-name
&DhcpConfiguration.1.Value.1=example.com
&DhcpConfiguration.2.Key=domain-name-servers
&DhcpConfiguration.2.Value.1=10.2.5.1
&DhcpConfiguration.2.Value.2=10.2.5.2
&AUTHPARAMS
```

Example Response

```
<CreateDhcpOptionsResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</requestId>
  <dhcpOptions>
    <dhcpOptionsId>dopt-7a8b9c2d</dhcpOptionsId>
    <dhcpConfigurationSet>
      <item>
        <key>domain-name</key>
        <valueSet>
          <item>
            <value>example.com</value>
          </item>
        </valueSet>
      </item>
      <item>
        <key>domain-name-servers</key>
        <valueSet>
          <item>
            <value>10.2.5.1</value>
          </item>
          <item>
            <value>10.2.5.2</value>
          </item>
        </valueSet>
      </item>
    </dhcpConfigurationSet>
    <tagSet/>
  </dhcpOptions>
</CreateDhcpOptionsResponse>
```

Related Operations

- [AssociateDhcpOptions](#) (p. 21)
- [DescribeDhcpOptions](#) (p. 161)
- [DeleteDhcpOptions](#) (p. 107)

CreateImage

Description

Creates an Amazon EBS-backed AMI from an Amazon EBS-backed instance that is in either the `running` or `stopped` state. For more information about Amazon EBS-backed AMIs, see [Using Amazon EBS-Backed AMIs and Instances](#).

Note

If you customized your instance with instance store volumes or EBS volumes in addition to the root device, the new AMI contains block device mapping information for those volumes. When you then launch an instance from your new AMI, the instance automatically launches with the additional volumes.

Request Parameters

| Name | Description | Required |
|--------------------|---|----------|
| <i>InstanceId</i> | The ID of the instance. Type: String Default: None | Yes |
| <i>Name</i> | A name for the new image. Type: String Default: None Constraints: 3-128 alphanumeric characters, parenthesis (()), commas (,), slashes (/), dashes (-), or underscores(_) | Yes |
| <i>Description</i> | A description of the new image. Type: String Default: None Constraints: Up to 255 characters | No |
| <i>NoReboot</i> | By default this parameter is set to <code>false</code> , which means Amazon EC2 attempts to cleanly shut down the instance before image creation and reboots the instance afterwards. When the parameter is set to <code>true</code> , Amazon EC2 does not shut down the instance before creating the image. When this option is used, file system integrity on the created image cannot be guaranteed. Type: Boolean Default: <code>false</code> | No |

Response Elements

The elements in the following table are wrapped in a `CreateImageResponse` structure.

| Name | Description |
|-----------|--|
| requestId | The ID of the request. Type: xsd:string |
| imageId | The ID of the AMI. Type: xsd:string |

Examples

Example Request

This example creates an AMI from the i-10a64379 instance.

```
https://ec2.amazonaws.com/?Action=CreateImage
&Description=Standard+Web+Server+v1.0
&InstanceId=i-10a64379
&Name=standard-web-server-v1.0
&AUTHPARAMS
```

Example Response

```
<CreateImageResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <imageId>ami-4fa54026</imageId>
</CreateImageResponse>
```

Related Operations

- [RunInstances](#) (p. 379)
- [DescribeInstances](#) (p. 181)
- [TerminateInstances](#) (p. 394)

CreateInstanceExportTask

Description

Creates a new export task, produces an image of an EC2 instance for use in another virtualization environment, and then writes the image to the specified Amazon S3 bucket. If the instance is running at the time of export, Amazon EC2 will attempt to shut down the instance, initiate the export process, and then reboot the instance. Only instances derived from your own ImportInstance tasks may be exported. When the task is complete, the image can be downloaded from your Amazon S3 bucket.

Request Parameters

| Name | Description | Required |
|-----------------------------------|---|----------|
| <i>Description</i> | A description of the conversion task or the resource being exported. Type: String Default: None | No |
| <i>InstanceId</i> | The ID of the instance being exported. Type: String Default: None | Yes |
| <i>TargetEnvironment</i> | The target virtualization environment. Type: String Default: None Valid values: vmware citrix microsoft | Yes |
| <i>ExportToS3.DiskImageFormat</i> | The format for the exported image. Type: String Default: vmdk if TargetEnvironment = vmware, otherwise vhd Valid values: vmdk vhd | No |
| <i>ExportToS3.ContainerFormat</i> | The container format used to combine disk images with metadata (such as OVF). If absent, only the disk image will be exported. Type: String Default: ova if TargetEnvironment = vmare, otherwise blank Valid values: ova | No |
| <i>ExportToS3.S3Bucket</i> | The Amazon S3 bucket for the destination image. The bucket must exist and grant write permissions to AWS account vm-import-export@amazon.com. Type: String Default: None | Yes |

| Name | Description | Required |
|----------------------------|---|----------|
| <i>ExportToS3.S3Prefix</i> | The image is written to a single object in the Amazon S3 bucket at the S3 key s3prefix + exportTaskId + '.' + diskImageFormat. Type: String Default: None | No |

Response Elements

The elements in the following table are wrapped in a `CreateInstanceExportTaskResponse` structure.

| Name | Description |
|------------|--|
| requestId | The ID of the request. Type: xsd:string |
| exportTask | The details of the created ExportVM task. Type: ExportTaskResponseType (p. 426) |

Examples

Example Request

This example creates an Export VM task that makes a Windows instance available as an OVA.

```
https://ec2.amazonaws.com/?Action=CreateInstanceExportTask
&Description=Example%20for%20docs
&InstanceId=i-12345678
&TargetEnvironment=VMWare
&ExportToS3.DiskImageFormat=VMDK
&ExportToS3.ContainerFormat=OVA
&ExportToS3.S3bucket=my-bucket-for-exported-vm
&ExportToS3.S3prefix=my-exports/
&AUTHPARAMS
```

Example Response

```
<CreateInstanceExportTaskResponse xmlns="http://ec2.amazonaws.com/doc/2020-02-02/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <exportTask>
    <exportTaskId>export-i-1234wxyz</exportTaskId>
    <description>Example for docs</description>
    <state>active</state>
    <statusMessage>Running</statusMessage>
    <instanceExport>
      <instanceId>i-12345678</instanceId >
      <targetEnvironment>VMWare</targetEnvironment >
    </instanceExport>
```

```
<exportToS3>
<diskImageFormat>VMDK</diskImageFormat >
<containerFormat>OVA</containerFormat>
<s3Bucket>my-bucket-for-exported-vm</s3Bucket>
<s3Key>my-exports/ export-i-1234wxyz .ova</s3Key>
</exportToS3>
</exportTask>
</CreateInstanceExportTaskResponse>
```

Related Operations

- [CancelExportTask](#) (p. 47)
- [DescribeExportTasks](#) (p. 165)

CreateInternetGateway

Description

Creates a new Internet gateway in your AWS account. After creating the Internet gateway, you then attach it to a VPC using `AttachInternetGateway`. For more information about your VPC and Internet gateway, see [Amazon Virtual Private Cloud User Guide](#).

Request Parameters

This action has no request parameters.

Response Elements

The elements in the following table are wrapped in a `CreateInternetGatewayResponse` structure.

| Name | Description |
|------------------------------|--|
| <code>requestId</code> | The ID of the request. Type: String |
| <code>internetGateway</code> | Information about the Internet gateway Type: InternetGatewayType (p. 444) |

Examples

Example Request

This example creates an Internet gateway.

```
https://ec2.amazonaws.com/?Action=CreateInternetGateway
&AUTHPARAMS
```

Example Response

```
CreateInternetGatewayResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <internetGateway>
    <internetGatewayId>igw-eaad4883</internetGatewayId>
    <attachmentSet/>
    <tagSet/>
  </internetGateway>
</CreateInternetGatewayResponse>
```

Related Operations

- [DeleteInternetGateway](#) (p. 109)

- [AttachInternetGateway](#) (p. 25)
- [DetachInternetGateway](#) (p. 294)
- [DescribeInternetGateways](#) (p. 203)

CreateKeyPair

Description

Creates a new 2048-bit RSA key pair with the specified name. The public key is stored by Amazon EC2 and the private key is returned to you. The private key is returned as an unencrypted PEM encoded PKCS#8 private key. If a key with the specified name already exists, Amazon EC2 returns an error.

Tip

The key pair returned to you works only in the Region you're using when you create the key pair. If you'd like to create a key pair that works in all Regions, see [ImportKeyPair](#) (p. 316).

Request Parameters

| Name | Description | Required |
|----------------|--|----------|
| <i>KeyName</i> | A unique name for the key pair. Type: String Default: None Constraints: Accepts alphanumeric characters, spaces, dashes, and underscores. | Yes |

Response Elements

The elements in the following table are wrapped in a `CreateKeyPairResponse` structure.

| Name | Description |
|-----------------------------|--|
| <code>requestId</code> | The ID of the request. Type: xsd:string |
| <code>keyName</code> | The key pair name you provided. Type: xsd:string |
| <code>keyFingerprint</code> | A SHA-1 digest of the DER encoded private key. Type: xsd:string |
| <code>keyMaterial</code> | An unencrypted PEM encoded RSA private key. Type: xsd:string |

Examples

Example Request

This example creates a key pair named `gsg-keypair`.

CreateNetworkAcl

Description

Creates a new network ACL in a VPC. Network ACLs provide an optional layer of security (on top of security groups) for the instances in your VPC. For more information about network ACLs, see [Network ACLs](#) in the *Amazon Virtual Private Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|--------------|---|----------|
| <i>VpcId</i> | The ID of the VPC. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in a `CreateNetworkAclResponse` structure.

| Name | Description |
|-------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>networkAcl</code> | Information about the new network ACL. Type: NetworkAclType (p. 452) |

Examples

Example Request

The example creates a new network ACL in the VPC with ID `vpc-11ad4878`. Notice that the response includes a default entry for egress, and another for ingress, each with a very high rule number. These are the last entries Amazon VPC processes to decide whether traffic is allowed in or out of an associated subnet. If the traffic doesn't match any rules with a lower rule number, then these default entries ultimately deny the traffic.

```
https://ec2.amazonaws.com/?Action=CreateNetworkAcl
&VpcId=vpc-11ad4878
&AUTHPARAMS
```

Example Response

```
<CreateNetworkAclResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <networkAcl>
```

```
<networkAclId>acl-5fb85d36</networkAclId>
<vpcId>vpc-11ad4878</vpcId>
<default>>false</default>
<entrySet>
  <item>
    <ruleNumber>32767</ruleNumber>
    <protocol>all</protocol>
    <ruleAction>deny</ruleAction>
    <egress>>true</egress>
    <cidrBlock>0.0.0.0/0</cidrBlock>
  </item>
  <item>
    <ruleNumber>32767</ruleNumber>
    <protocol>all</protocol>
    <ruleAction>deny</ruleAction>
    <egress>>false</egress>
    <cidrBlock>0.0.0.0/0</cidrBlock>
  </item>
</entrySet>
<associationSet/>
<tagSet/>
</networkAcl>
</CreateNetworkAclResponse>
```

Related Operations

- [DeleteNetworkAcl](#) (p. 113)
- [DescribeNetworkAcls](#) (p. 209)
- [ReplaceNetworkAclAssociation](#) (p. 345)

CreateNetworkAclEntry

Description

Creates an entry (i.e., rule) in a network ACL with a rule number you specify. Each network ACL has a set of numbered ingress rules and a separate set of numbered egress rules. When determining whether a packet should be allowed in or out of a subnet associated with the ACL, Amazon VPC processes the entries in the ACL according to the rule numbers, in ascending order.

Important

We recommend that you leave room between the rule numbers (e.g., 100, 110, 120, etc.), and not number them one right after the other (e.g., 101, 102, 103, etc.). This allows you to easily add a new rule between existing ones without having to renumber the rules.

After you add an entry, you can't modify it; you must either replace it, or create a new entry and delete the old one.

For more information about network ACLs, see [Network ACLs](#) in the *Amazon Virtual Private Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|--------------|--|----------|
| NetworkAclId | The ID of the ACL. Type: String Default: None | Yes |
| RuleNumber | The rule number to assign to the entry (for example, 100). ACL entries are processed in ascending order by rule number. Type: Integer Default: None Constraints: Positive integer from 1 to 32766 | Yes |
| Protocol | The IP protocol the rule applies to. You can use -1 to mean all protocols. Type: Integer Valid values: -1 or a protocol number (go to Protocol Numbers). | Yes |
| RuleAction | Indicates whether to allow or deny traffic that matches the rule. Type: String Default: None Valid values: allow deny | Yes |

| Name | Description | Required |
|-----------------------------|--|-------------|
| <code>Egress</code> | Indicates whether this rule applies to egress traffic from the subnet (<code>true</code>) or ingress traffic to the subnet (<code>false</code>). Type: Boolean Default: <code>false</code> Valid values: <code>true</code> <code>false</code> | No |
| <code>CidrBlock</code> | The CIDR range to allow or deny, in CIDR notation (e.g., <code>172.16.0.0/24</code>). Type: String Default: None | Yes |
| <code>Icmp.Code</code> | For the ICMP protocol, the ICMP code. You can use <code>-1</code> to specify all ICMP codes for the given ICMP type. Type: Integer Default: None Condition: Required if specifying <code>1</code> (ICMP) for the protocol. | Conditional |
| <code>Icmp.Type</code> | For the ICMP protocol, the ICMP type. You can use <code>-1</code> to specify all ICMP types. Type: Integer Default: None Condition: Required if specifying <code>1</code> (ICMP) for the protocol. | Conditional |
| <code>PortRange.From</code> | The first port in the range. Type: Integer Default: None Condition: Required if specifying <code>6</code> (TCP) or <code>17</code> (UDP) for the protocol. | Conditional |
| <code>PortRange.To</code> | The last port in the range. Type: Integer Default: None Condition: Required if specifying <code>6</code> (TCP) or <code>17</code> (UDP) for the protocol. | Conditional |

Response Elements

The elements in the following table are wrapped in a `CreateNetworkAclEntryResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example creates an entry with rule number 110 in the network ACL with ID `acl-2cb85d45`. The rule allows ingress traffic from anywhere (0.0.0.0/0) on UDP port 53 into any associated subnet.

```
https://ec2.amazonaws.com/?Action=CreateNetworkAclEntry
&NetworkAclId=acl-2cb85d45
&RuleNumber=110
&Protocol=udp
&RuleAction=allow
&Egress=false
&CidrBlock=0.0.0.0/0
&PortRange.From=53
&PortRange.To=53
&AUTHPARAMS
```

Example Response

```
<CreateNetworkAclEntryResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <return>>true</return>
</CreateNetworkAclEntryResponse>
```

Related Operations

- [DeleteNetworkAclEntry](#) (p. 115)
- [ReplaceNetworkAclEntry](#) (p. 347)
- [DescribeNetworkAcls](#) (p. 209)

CreateNetworkInterface

Description

Creates a network interface in the specified subnet of Amazon VPC.

Request Parameters

| Name | Description | Required |
|--|---|----------|
| <i>SubnetId</i> | The ID of the subnet to associate with the network interface. Type: String Default: None | Yes |
| <i>PrivateIpAddress</i> | The primary private IP address of the network interface. Type: String Default: None | No |
| <i>PrivateIpAddresses.n.PrivateIpAddress</i> | The private IP address of the specified network interface. This parameter can be used multiple times to specify explicit private IP addresses for a network interface, but only one private IP address can be designated as primary. You cannot specify this parameter with the <i>PrivateIpAddresses.n.Primary</i> value of <code>true</code> if you specify the <i>PrivateIpAddress</i> option. Type: String Default: None | No |
| <i>PrivateIpAddresses.n.Primary</i> | Specifies whether the private IP address is the primary private IP address. Only one IP address can be designated as primary. You cannot specify this parameter with the value of <code>true</code> and the <i>PrivateIpAddresses.n.PrivateIpAddress</i> option if you specify the <i>PrivateIpAddress</i> option. Type: Boolean Default: False | No |

| Name | Description | Required |
|---------------------------------------|--|----------|
| <i>SecondaryPrivateIpAddressCount</i> | <p>The number of secondary private IP addresses to assign to a network interface. When you specify a number of secondary IP addresses, AWS automatically assigns these IP addresses within the subnet's range.</p> <p>The number of IP addresses you can assign to a network interface varies by instance type. For more information, see Available Instance Types in the <i>Amazon Elastic Compute Cloud User Guide</i>.</p> <p>For a single network interface, you cannot specify this option and specify more than one private IP address using <code>PrivateIpAddress.n</code>.</p> <p>Type: Integer Default: None</p> | No |
| <i>Description</i> | <p>The description of the network interface.</p> <p>Type: String Default: None</p> | No |
| <i>SecurityGroupId.n</i> | <p>A list of group IDs for use by the network interface.</p> <p>Type: SecurityGroupIdSetItemType (p. 470) Default: None</p> | No |

Response Elements

The elements in the following table are wrapped in an `CreateNetworkInterface` structure.

| Name | Description |
|-------------------------------|---|
| <code>requestId</code> | <p>The ID of the request to create a network interface.</p> <p>Type: <code>xsd:string</code></p> |
| <code>networkInterface</code> | <p>The network interface that was created.</p> <p>Type: NetworkInterfaceType (p. 456)</p> |

Examples

Example Request

This example creates an elastic network interface (ENI) in the specified subnet with a primary IP address that is automatically assigned to the network interface.

```
https://ec2.amazonaws.com/?Action=CreateNetworkInterface
&SubnetId=subnet-b2a249da
&AUTHPARAMS
```


Example Response

```
<CreateNetworkInterfaceResponse xmlns='http://ec2.amazonaws.com/doc/2012-06-15/'>
  <requestId>8dbe591e-5a22-48cb-b948-dd0aadd55adf</requestId>
  <networkInterface>
    <networkInterfaceId>eni-cfca76a6</networkInterfaceId>
    <subnetId>subnet-b2a249da</subnetId>
    <vpcId>vpc-c31dafaa</vpcId>
    <availabilityZone>ap-southeast-1b</availabilityZone>
    <description/>
    <ownerId>251839141158</ownerId>
    <requesterManaged>false</requesterManaged>
    <status>pending</status>
    <macAddress>02:74:b0:72:79:61</macAddress>
    <privateIpAddress>10.0.2.157</privateIpAddress>
    <sourceDestCheck>true</sourceDestCheck>
    <groupSet>
      <item>
        <groupId>sg-188d9f74</groupId>
        <groupName>default</groupName>
      </item>
    </groupSet>
    <tagSet/>
    <privateIpAddressesSet>
      <item>
        <privateIpAddress>10.0.2.157</privateIpAddress>
        <primary>true</primary>
      </item>
    </privateIpAddressesSet>
  </networkInterface>
</CreateNetworkInterfaceResponse>
```

Example Request

This example creates an elastic network interface (ENI) in the specified subnet with a primary IP address of 10.0.2.140 and four secondary private IP addresses that are automatically assigned to the network interface.

```
https://ec2.amazonaws.com/?Action=CreateNetworkInterface
&PrivateIpAddresses.0.Primary=true
&PrivateIpAddresses.0.PrivateIpAddress=10.0.2.140
&SecondaryPrivateIpAddressCount=4
&SubnetId=subnet-a61dafcf
&AUTHPARAMS
```

Example Response

```
<CreateNetworkInterfaceResponse xmlns='http://ec2.amazonaws.com/doc/2012-06-15/'>
  <requestId>bd78c839-0895-4fac-a17f-98b559b6b630</requestId>
  <networkInterface>
    <networkInterfaceId>eni-1bcb7772</networkInterfaceId>
    <subnetId>subnet-a61dafcf</subnetId>
```

```
<vpcId>vpc-c31dafaa</vpcId>
<availabilityZone>ap-southeast-1b</availabilityZone>
<description/>
<ownerId>251839141158</ownerId>
<requesterManaged>false</requesterManaged>
<status>pending</status>
<macAddress>02:74:b0:70:7f:1a</macAddress>
<privateIpAddress>10.0.2.140</privateIpAddress>
<sourceDestCheck>true</sourceDestCheck>
<groupSet>
  <item>
    <groupId>sg-188d9f74</groupId>
    <groupName>default</groupName>
  </item>
</groupSet>
<tagSet/>
<privateIpAddressesSet>
  <item>
    <privateIpAddress>10.0.2.140</privateIpAddress>
    <primary>true</primary>
  </item>
  <item>
    <privateIpAddress>10.0.2.172</privateIpAddress>
    <primary>false</primary>
  </item>
  <item>
    <privateIpAddress>10.0.2.169</privateIpAddress>
    <primary>false</primary>
  </item>
  <item>
    <privateIpAddress>10.0.2.170</privateIpAddress>
    <primary>false</primary>
  </item>
  <item>
    <privateIpAddress>10.0.2.171</privateIpAddress>
    <primary>false</primary>
  </item>
</privateIpAddressesSet>
</networkInterface>
</CreateNetworkInterfaceResponse>
```

Example Request

The following request creates a network interface with a primary private IP address of 10.0.2.130 and two secondary IP addresses of 10.0.2.132 and 10.0.2.133.

```
https://ec2.amazonaws.com/?Action=CreateNetworkInterface
&PrivateIpAddresses.0.Primary=true
&PrivateIpAddresses.0.PrivateIpAddress=10.0.2.130
&PrivateIpAddresses.1.Primary=false
&PrivateIpAddresses.1.PrivateIpAddress=10.0.2.132
&PrivateIpAddresses.2.Primary=false
&PrivateIpAddresses.2.PrivateIpAddress=10.0.2.133
&SubnetId=subnet-a61dafcf
&AUTHPARAMS
```

Example Response

```
<CreateNetworkInterfaceResponse xmlns='http://ec2.amazonaws.com/doc/2012-06-15/'>
  <requestId>a9565f4c-f928-4113-859b-905886d11658</requestId>
  <networkInterface>
    <networkInterfaceId>eni-41c47828</networkInterfaceId>
    <subnetId>subnet-a61dafcf</subnetId>
    <vpcId>vpc-c31dafaa</vpcId>
    <availabilityZone>ap-southeast-1b</availabilityZone>
    <description/>
    <ownerId>251839141158</ownerId>
    <requesterManaged>false</requesterManaged>
    <status>pending</status>
    <macAddress>02:74:b0:78:bf:ab</macAddress>
    <privateIpAddress>10.0.2.130</privateIpAddress>
    <sourceDestCheck>true</sourceDestCheck>
    <groupSet>
      <item>
        <groupId>sg-188d9f74</groupId>
        <groupName>default</groupName>
      </item>
    </groupSet>
    <tagSet/>
    <privateIpAddressesSet>
      <item>
        <privateIpAddress>10.0.2.130</privateIpAddress>
        <primary>true</primary>
      </item>
      <item>
        <privateIpAddress>10.0.2.133</privateIpAddress>
        <primary>false</primary>
      </item>
      <item>
        <privateIpAddress>10.0.2.132</privateIpAddress>
        <primary>false</primary>
      </item>
    </privateIpAddressesSet>
  </networkInterface>
</CreateNetworkInterfaceResponse>
```

Related Operations

- [AttachNetworkInterface](#) (p. 27)
- [DetachNetworkInterface](#) (p. 296)
- [DeleteNetworkInterface](#) (p. 117)
- [DescribeNetworkInterfaceAttribute](#) (p. 214)
- [DescribeNetworkInterfaces](#) (p. 216)
- [ModifyNetworkInterfaceAttribute](#) (p. 327)
- [ResetNetworkInterfaceAttribute](#) (p. 369)

CreatePlacementGroup

Description

Creates a placement group that you launch cluster instances into. You must give the group a name unique within the scope of your account. For more information about placement groups and cluster instances, see [Using Cluster Instances](#) in the *Amazon Elastic Compute Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|-----------|---|----------|
| GroupName | A name for the placement group. Type: String Default: None | Yes |
| Strategy | The placement group strategy. Type: String Valid values: <code>cluster</code> | Yes |

Response Elements

The elements in the following table are wrapped in a `CreatePlacementGroupResponse` structure.

| Name | Description |
|-----------|---|
| requestId | The ID of the request. Type: <code>xsd:string</code> |
| return | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example creates a placement group named XYZ-cluster.

```
https://ec2.amazonaws.com/?Action=CreatePlacementGroup
&GroupName=XYZ-cluster
&Strategy=cluster
&AUTHPARAMS
```

Example Response

```
<CreatePlacementGroupResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
```

```
<requestId>d4904fd9-82c2-4ea5-adfe-a9cc3EXAMPLE</requestId>  
<return>>true</return>  
</CreatePlacementGroupResponse>
```

Related Operations

- [DeletePlacementGroup](#) (p. 119)
- [DescribePlacementGroups](#) (p. 222)

CreateRoute

Description

Creates a new route in a route table within a VPC. The route's target can be either a gateway attached to the VPC or a NAT instance in the VPC.

When determining how to route traffic, we use the route with the most specific match. For example, let's say the traffic is destined for 192.0.2.3, and the route table includes the following two routes:

- 192.0.2.0/24 (goes to some target A)
- 192.0.2.0/28 (goes to some target B)

Both routes apply to the traffic destined for 192.0.2.3. However, the second route in the list covers a smaller number of IP addresses and is therefore more specific, so we use that route to determine where to target the traffic.

For more information about route tables, see [Route Tables](#) in the *Amazon Virtual Private Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|-----------------------------|--|-------------|
| <i>RouteTableId</i> | The ID of the route table where the route will be added. Type: String Default: None | Yes |
| <i>DestinationCidrBlock</i> | The CIDR address block used for the destination match. For example: 0.0.0.0/0. Routing decisions are based on the most specific match. Type: String Default: None | Yes |
| <i>GatewayId</i> | The ID of a gateway attached to your VPC. Type: String Default: None Condition: You must provide only one of the following: a <i>GatewayID</i> , <i>InstanceID</i> , or <i>NetworkInterfaceId</i> . | Conditional |
| <i>InstanceId</i> | The ID of a NAT instance in your VPC. Type: String Default: None Condition: You must provide only one of the following: a <i>GatewayID</i> , <i>InstanceID</i> , or <i>NetworkInterfaceId</i> . | Conditional |

| Name | Description | Required |
|---------------------------|--|-------------|
| <i>NetworkInterfaceId</i> | Allows the routing of network interface IDs. Exactly one interface must be attached when specifying an instance ID or it fails. Type: String Default: None Condition: You must provide only one of the following: a <code>GatewayId</code> , <code>InstanceId</code> , or <code>NetworkInterfaceId</code> . | Conditional |

Response Elements

The elements in the following table are wrapped in a `CreateRouteResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example creates a route in the route table with ID `rtb-e4ad488d`. The route matches all traffic (`0.0.0.0/0`) and routes it to the Internet gateway with ID `igw-eaad4883`.

```
https://ec2.amazonaws.com/?Action=CreateRoute
&RouteTableId=rtb-e4ad488d
&DestinationCidrBlock=0.0.0.0/0
&GatewayId=igw-eaad4883
&AUTHPARAMS
```

Example Request

This example creates a route in the route table with ID `rtb-g8ff4ea2`. The route sends all traffic (`0.0.0.0/0`) to the NAT instance with ID `i-1a2b3c4d`.

```
https://ec2.amazonaws.com/?Action=CreateRoute
&RouteTableId=rtb-g8ff4ea2
&DestinationCidrBlock=0.0.0.0/0
&InstanceId=i-1a2b3c4d
&AUTHPARAMS
```

Example Response

```
<CreateRouteResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">  
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>  
  <return>true</return>  
</CreateRouteResponse>
```

Related Operations

- [DeleteRoute](#) (p. 121)
- [ReplaceRoute](#) (p. 350)
- [DescribeRouteTables](#) (p. 236)

CreateRouteTable

Description

Creates a new route table within a VPC. After you create a new route table, you can add routes and associate the table with a subnet. For more information about route tables, see [Route Tables](#) in the *Amazon Virtual Private Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|--------------|---|----------|
| <i>VpcId</i> | The ID of the VPC. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in a `CreateRouteTableResponse` structure.

| Name | Description |
|-------------------------|---|
| <code>requestId</code> | The ID of the request received. Type: <code>xsd:string</code> |
| <code>routeTable</code> | Information about the newly created route table. Type: RouteTableType (p. 465) |

Examples

Example Request

This example creates a route table within the VPC with ID of `vpc-11ad4878`.

```
https://ec2.amazonaws.com/?Action=CreateRouteTable
&VpcId=vpc-11ad4878
&AUTHPARAMS
```

Example Response

By default, every route table includes a local route that enables traffic to flow within the VPC. The following response shows that route.

```
CreateRouteTableResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <routeTable>
    <routeTableId>rtb-f9ad4890</routeTableId>
```

```
<vpcId>vpc-11ad4878</vpcId>
<routeSet>
  <item>
    <destinationCidrBlock>10.0.0.0/22</destinationCidrBlock>
    <gatewayId>local</gatewayId>
    <state>active</state>
  </item>
</routeSet>
<associationSet/>
<tagSet/>
</routeTable>
</CreateRouteTableResponse>
```

Related Operations

- [AssociateRouteTable](#) (p. 23)
- [DisassociateRouteTable](#) (p. 304)
- [DescribeRouteTables](#) (p. 236)
- [DeleteRouteTable](#) (p. 123)
- [ReplaceRouteTableAssociation](#) (p. 352)
- [CreateRoute](#) (p. 79)

CreateSecurityGroup

Description

Creates a new security group. You can create either an EC2 security group (which works only with EC2), or a VPC security group (which works only with Amazon Virtual Private Cloud). The two types of groups have different capabilities. For information about VPC security groups and how the two types of groups differ, see [Security Groups](#) in the *Amazon Virtual Private Cloud User Guide*. For information about EC2 security groups, see [Using Security Groups](#) in the *Amazon Elastic Compute Cloud User Guide*.

When you create a security group, you give it a friendly name of your choice. You can have an EC2 security group with the same name as a VPC security group (each group has a unique security group ID separate from the name). Two standard groups can't have the same name, and two VPC groups can't have the same name.

If you don't specify a security group when you launch an instance, the instance is launched into the default security group. This group (and only this group) includes a default rule that gives the instances in the group unrestricted network access to each other. You have a default EC2 security group for instances you launch with EC2 (i.e., outside a VPC), and a default VPC security group for instances you launch in your VPC.

You can add or remove rules from your security groups (i.e., authorize or revoke permissions) using the `AuthorizeSecurityGroupIngress`, `AuthorizeSecurityGroupEgress`, `RevokeSecurityGroupIngress`, and `RevokeSecurityGroupEgress` actions.

Important

For EC2 security groups: You can have up to 500 groups.

For VPC security groups: You can have up to 50 groups per VPC.

Request Parameters

| Name | Description | Required |
|-------------------------|--|-------------|
| <i>GroupName</i> | The name of the security group. Type: String Default: None Constraints: Accepts alphanumeric characters, spaces, dashes, and underscores. | Yes |
| <i>GroupDescription</i> | A description of the group. This is informational only. Type: String Default: None Constraints: Accepts alphanumeric characters, spaces, dashes, and underscores. | Yes |
| <i>VpcId</i> | The ID of the VPC. Type: String Default: None Condition: Required for VPC security groups | Conditional |

Response Elements

The elements in the following table are wrapped in a `CreateSecurityGroupResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |
| <code>groupId</code> | The ID that AWS assigns to the security group. Type: <code>xsd:string</code> |

Examples

Example Request

This example creates the `webserv` security group.

```
https://ec2.amazonaws.com/?Action=CreateSecurityGroup
&GroupName=webserv
&GroupDescription=Web Servers
&AUTHPARAMS
```

Example Response

```
<CreateSecurityGroupResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <return>true</return>
  <groupId>sg-1a2b3c4d</groupId>
</CreateSecurityGroupResponse>
```

Related Operations

- [RunInstances](#) (p. 379)
- [DescribeSecurityGroups](#) (p. 240)
- [AuthorizeSecurityGroupIngress](#) (p. 36)
- [RevokeSecurityGroupIngress](#) (p. 376)
- [DeleteSecurityGroup](#) (p. 125)

CreateSnapshot

Description

Creates a snapshot of an Amazon EBS volume and stores it in Amazon S3. You can use snapshots for backups, to make identical copies of instance devices, and to save data before shutting down an instance. For more information about Amazon EBS, see [Using Amazon Elastic Block Store](#).

When a snapshot is created, any AWS Marketplace product codes from the volume are propagated to the snapshot.

When taking a snapshot of a file system, we recommend unmounting it first. This ensures the file system metadata is in a consistent state, that the 'mounted indicator' is cleared, and that all applications using that file system are stopped and in a consistent state. Some file systems, such as xfs, can freeze and unfreeze activity so a snapshot can be made without unmounting.

For Linux/UNIX, enter the following command from the command line to unmount the volume.

```
umount -d device_name
```

For example:

```
umount -d /dev/sdh
```

For Windows, open Disk Management, right-click the volume to unmount, and select Change Drive Letter and Path. Then, select the mount point to remove and click Remove.

Request Parameters

| Name | Description | Required |
|--------------------|---|----------|
| <i>VolumeId</i> | The ID of the Amazon EBS volume. Type: String Default: None | Yes |
| <i>Description</i> | A description of the Amazon EBS snapshot. Type: String Default: None Constraints: Up to 255 characters | No |

Response Elements

The elements in the following table are wrapped in a `CreateSnapshotResponse` structure.

| Name | Description |
|------------------------|--|
| <code>requestId</code> | The ID of the request. Type: xsd:string |

| Name | Description |
|-------------|--|
| snapshotId | The ID of the snapshot. Type: xsd:string |
| volumeId | The ID of the volume. Type: xsd:string |
| status | The snapshot state. Type: xsd:string Valid values: pending completed error |
| startTime | The time stamp when the snapshot was initiated. Type: xsd:dateTime |
| progress | The progress of the snapshot, as a percentage. Type: xsd:string |
| ownerId | The AWS account ID of the Amazon EBS snapshot owner. Type: xsd:string |
| volumeSize | The size of the volume, in GiB. Type: xsd:string |
| description | A description of the snapshot. Type: xsd:string |

Examples

Example Request

This example creates a snapshot of volume `vol-4d826724`.

```
https://ec2.amazonaws.com/?Action=CreateSnapshot
&VolumeId=vol-4d826724
&Description=Daily+Backup
&AUTHPARAMS
```

Example Response

```
<CreateSnapshotResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <snapshotId>snap-78a54011</snapshotId>
  <volumeId>vol-4d826724</volumeId>
  <status>pending</status>
  <startTime>2008-05-07T12:51:50.000Z</startTime>
  <progress>60%</progress>
  <ownerId>111122223333</ownerId>
  <volumeSize>10</volumeSize>
  <description>Daily Backup</description>
</CreateSnapshotResponse>
```

Related Operations

- [DeleteSnapshot](#) (p. 127)
- [DescribeSnapshots](#) (p. 246)

CreateSpotDatafeedSubscription

Description

Creates the datafeed for Spot Instances, enabling you to view Spot Instance usage logs. You can create one data feed per account. For more information about Spot Instances, see [Spot Instances](#) in the *Amazon Elastic Compute Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|---------------|--|----------|
| <i>Bucket</i> | The Amazon S3 bucket in which to store the Spot Instance datafeed. Type: String Default: None Constraints: Must be a valid bucket associated with your account. | Yes |
| <i>Prefix</i> | A prefix that is prepended to datafeed files. Type: String Default: None | No |

Response Elements

The elements in the following table are wrapped in a `CreateSpotDatafeedSubscriptionResponse` structure.

| Name | Description |
|---------------------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>spotDatafeedSubscription</code> | The datafeed subscription. Type: SpotDatafeedSubscriptionType (p. 471) |

Examples

Example Request

This example creates the data feed for the account.

```
https://ec2.amazonaws.com/?Action=CreateSpotDatafeedSubscription
&Bucket=myawsbucket
&AUTHPARAMS
```


Example Response

```
<CreateSpotDatafeedSubscriptionResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <spotDatafeedSubscription>
    <ownerId>111122223333</ownerId>
    <bucket>myawsbucket</bucket>
    <prefix/>
    <state>Active</state>
  </spotDatafeedSubscription>
</CreateSpotDatafeedSubscriptionResponse>
```

Related Operations

- [DeleteSpotDatafeedSubscription](#) (p. 129)
- [DescribeSpotDatafeedSubscription](#) (p. 251)

CreateSubnet

Description

Creates a subnet in an existing VPC. You can create up to 20 subnets in a VPC. If you add more than one subnet to a VPC, they're set up in a star topology with a logical router in the middle. If you feel you need more than 20 subnets, you can request more by going to <http://aws.amazon.com/contact-us/vpc-request/>.

When you create each subnet, you provide the VPC ID and the CIDR block you want for the subnet. After you create a subnet, you can't change its CIDR block. The subnet's CIDR block can be the same as the VPC's CIDR block (assuming you want only a single subnet in the VPC), or a subset of the VPC's CIDR block. If you create more than one subnet in a VPC, the subnets' CIDR blocks must not overlap. The smallest subnet (and VPC) you can create uses a /28 netmask (16 IP addresses), and the largest uses a /16 netmask (65,536 IP addresses).

Important

AWS reserves both the first four and the last IP address in each subnet's CIDR block. They're not available for use.

Important

If you launch an instance in a VPC using an Amazon EBS-backed AMI, the IP address doesn't change if you stop and restart the instance (unlike a similar instance launched outside a VPC, which gets a new IP address when restarted). It's therefore possible to have a subnet with no running instances (they're all stopped), but no remaining IP addresses available. For more information about Amazon EBS-backed AMIs, see [AMI Basics](#) in the *Amazon Elastic Compute Cloud User Guide*.

For more information about Amazon Virtual Private Cloud and subnets, see the [Amazon Virtual Private Cloud User Guide](#).

Request Parameters

| Name | Description | Required |
|-------------------------|--|----------|
| <i>VpcId</i> | The ID of the VPC. Type: String Default: None | Yes |
| <i>CidrBlock</i> | The CIDR block for the subnet to cover (e.g., 10.0.0.0/24). Type: String Default: None | Yes |
| <i>AvailabilityZone</i> | The Availability Zone for the subnet. Type: String Default: AWS selects a zone for you (recommended) | No |

Response Elements

The elements in the following table are wrapped in an `CreateSubnetResponse` structure.

| Name | Description |
|------------------------|--|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>subnet</code> | Information about the subnet. Type: SubnetType (p. 476) |

Examples

Example Request

This example creates a subnet with CIDR block 10.0.1.0/24 in the VPC with ID `vpc-1a2b3c4d`.

```
https://ec2.amazonaws.com/?Action=CreateSubnet
&VpcId=vpc-1a2b3c4d
&CidrBlock=10.0.1.0/24
&AUTHPARAMS
```

Example Response

```
<CreateSubnetResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</requestId>
  <subnet>
    <subnetId>subnet-9d4a7b6c</subnetId>
    <state>pending</state>
    <vpcId>vpc-1a2b3c4d</vpcId>
    <cidrBlock>10.0.1.0/24</cidrBlock>
    <availableIpAddressCount>250</availableIpAddressCount>
    <availabilityZone>us-east-1a</availabilityZone>
    <tagSet/>
  </subnet>
</CreateSubnetResponse>
```

Related Operations

- [DescribeSubnets](#) (p. 263)
- [DeleteSubnet](#) (p. 130)

CreateTags

Description

Adds or overwrites one or more tags for the specified resource or resources. Each resource can have a maximum of 10 tags. Each tag consists of a key and optional value. Tag keys must be unique per resource.

For more information about tags, see [Using Tags](#) in the *Amazon Elastic Compute Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|---------------------|--|----------|
| <i>ResourceId.n</i> | The ID of a resource to tag. For example, <code>ami-1a2b3c4d</code> . You can specify multiple resources to assign the tags to. Type: String Default: None | Yes |
| <i>Tag.n.Key</i> | The key for a tag. Type: String Default: None Constraints: Tag keys are case sensitive and accept a maximum of 128 Unicode characters. | Yes |
| <i>Tag.n.Value</i> | The value for a tag. If you don't want the tag to have a value, specify the parameter with no value, and we set the value to an empty string. Type: String Default: None Constraints: Tag values are case sensitive and accept a maximum of 256 Unicode characters. | Yes |

Response Elements

The elements in the following table are wrapped in a `CreateTagsResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example adds (or overwrites) two tags for an AMI and an instance. One of the tags is just a key (webserver), with no value (we set the value to an empty string). The other consists of a key (stack) and value (Production).

```
https://ec2.amazonaws.com/?Action=CreateTags
&ResourceId.1=ami-1a2b3c4d
&ResourceId.2=i-7f4d3a2b
&Tag.1.Key=webserver
&Tag.1.Value=
&Tag.2.Key=stack
&Tag.2.Value=Production
&AUTHPARAMS
```

Example Response

```
<CreateTagsResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</requestId>
  <return>>true</return>
</CreateTagsResponse>
```

Related Operations

- [DescribeTags](#) (p. 267)
- [DeleteTags](#) (p. 132)

CreateVolume

Description

Creates a new Amazon EBS volume that any Amazon EC2 instance in the same Availability Zone can attach to. Any AWS Marketplace product codes from the snapshot are propagated to the volume. For more information about Amazon EBS, see [Amazon Elastic Block Store](#).

Note

You must specify an Availability Zone when creating a volume. The volume and the instance to which it attaches must be in the same Availability Zone.

Request Parameters

| Name | Description | Required |
|-------------------------|--|-------------|
| <i>Size</i> | The size of the volume, in GiBs. Type: String Valid values: 1-1024 Default: If you're creating a volume from a snapshot and don't specify a size, the default is the snapshot size. Condition: Required if you're not creating a volume from a snapshot. | Conditional |
| <i>SnapshotId</i> | The snapshot from which to create the new volume. Type: String Default: None Condition: Required if you are creating a volume from a snapshot. | Conditional |
| <i>AvailabilityZone</i> | The Availability Zone for the new volume. Use DescribeAvailabilityZones (p. 150) to display Availability Zones that are currently available to your account. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in a `CreateVolumeResponse` structure.

| Name | Description |
|------------------------|--|
| <code>requestId</code> | The ID of the request. Type: xsd:string |
| <code>volumeId</code> | The ID of the volume. Type: xsd:string |

| Name | Description |
|------------------|---|
| size | The size of the volume, in GiBs. Type: xsd:string |
| snapshotId | The snapshot from which the volume was created, if applicable. Type: xsd:string |
| availabilityZone | The Availability Zone for the volume. Type: xsd:string |
| status | The volume state. Type: xsd:string Valid values: creating available in-use deleting deleted error |
| createTime | The time stamp when volume creation was initiated. Type: xsd:dateTime |

Examples

Example Request

This example creates a new 80 GiB volume in Availability Zone `us-east-1a`.

```
https://ec2.amazonaws.com/?Action=CreateVolume
&Size=80
&AvailabilityZone=us-east-1a
&AUTHPARAMS
```

Example Response

```
<CreateVolumeResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <volumeId>vol-4d826724</volumeId>
  <size>80</size>
  <snapshotId/>
  <availabilityZone>us-east-1a</availabilityZone>
  <status>creating</status>
  <createTime>2008-05-07T11:51:50.000Z</createTime>
</CreateVolumeResponse>
```

Related Operations

- [DeleteVolume](#) (p. 135)
- [DescribeVolumes](#) (p. 272)
- [AttachVolume](#) (p. 29)
- [DetachVolume](#) (p. 298)
- [DescribeAvailabilityZones](#) (p. 150)

CreateVpc

Description

Creates a VPC with the CIDR block you specify. The smallest VPC you can create uses a /28 netmask (16 IP addresses), and the largest uses a /16 netmask (65,536 IP addresses). To help you decide how big to make your VPC, see [Your VPC and Subnets](#) in the *Amazon Virtual Private Cloud User Guide*.

By default, each instance you launch in the VPC has the default DHCP options, which includes only a default DNS server that we provide (AmazonProvidedDNS). For more information about Amazon Virtual Private Cloud and DHCP options, see [Using DHCP Options in Your VPC](#) in the *Amazon Virtual Private Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|------------------------|---|----------|
| <i>CidrBlock</i> | The CIDR block you want the VPC to cover (e.g., 10.0.0.0/16). Type: String Default: None | Yes |
| <i>instanceTenancy</i> | The supported tenancy of instances launched into the VPC. A value of <code>default</code> means instances can be launched with any tenancy; a value of <code>dedicated</code> means all instances launched into the VPC will be launched as dedicated tenancy instances regardless of the tenancy assigned to the instance at launch. Setting the instance's tenancy attribute to <code>dedicated</code> specifies that your instance will run on single-tenant hardware. Type: String Default: default | No |

Response Elements

The elements in the following table are wrapped in an `CreateVpcResponse` structure.

| Name | Description |
|------------------------|--|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>vpc</code> | Information about the VPC. Type: VpcType (p. 483) |

Examples

Example Request

This example creates a VPC with CIDR block 10.0.0.0/16.

```
https://ec2.amazonaws.com/?Action=CreateVpc
&CidrBlock=10.0.0.0/16
&AUTHPARAMS
```

Example Response

```
<CreateVpcResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</requestId>
  <vpc>
    <vpcId>vpc-1a2b3c4d</vpcId>
    <state>pending</state>
    <cidrBlock>10.0.0.0/16</cidrBlock>
    <dhcpOptionsId>default</dhcpOptionsId>
    <tagSet/>
  </vpc>
</CreateVpcResponse>
```

Related Operations

- [DescribeVpcs](#) (p. 283)
- [DeleteVpc](#) (p. 137)
- [CreateDhcpOptions](#) (p. 55)
- [AssociateDhcpOptions](#) (p. 21)

CreateVpnConnection

Description

Creates a new VPN connection between an existing virtual private gateway and a VPN customer gateway. The only supported connection type is `ipsec.1`.

The response includes information that you need to configure your customer gateway, in XML format. We recommend you use the command line version of this operation (**ec2-create-vpn-connection**), which lets you get the configuration information formatted in a friendlier way. For information about the command, see [ec2-create-vpn-connection](#) in the *Amazon Elastic Compute Cloud Command Line Reference*.

Important

We strongly recommend you use HTTPS when calling this operation because the response contains sensitive cryptographic information for configuring your customer gateway.

If you decide to shut down your VPN connection for any reason and then create a new one, you must reconfigure your customer gateway with the new information returned from this call.

For more information about Amazon Virtual Private Cloud and VPN connections, see [Adding an IPsec Hardware Virtual Private Gateway to Your VPC](#) in the *Amazon Virtual Private Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|--------------------------|---|----------|
| <i>Type</i> | The type of VPN connection. Type: String Default: None Valid values: <code>ipsec.1</code> | Yes |
| <i>CustomerGatewayId</i> | The ID of the customer gateway. Type: String Default: None | Yes |
| <i>VpnGatewayId</i> | The ID of the virtual private gateway. Type: String Default: None | Yes |
| <i>AvailabilityZone</i> | The Availability Zone option has been deprecated. The action ignores this parameter. Type: String Default: None | No |

Response Elements

The elements in the following table are wrapped in an `CreateVpnConnectionResponse` structure.

| Name | Description |
|---------------|---|
| requestId | The ID of the request. Type: xsd:string |
| vpnConnection | Information about the VPN connection. Type: VpnConnectionType (p. 484) |

Examples

Example Request

This example creates a VPN connection between the virtual private gateway with ID vgw-8db04f81 and the customer gateway with ID cgw-b4dc3961. The response includes configuration information for the VPN connection's customer gateway (in the native XML format, but escaped).

```
https://ec2.amazonaws.com/?Action=CreateVpnConnection
&Type=ipsec.1
&CustomerGatewayId=cgw-b4dc3961
&VpnGatewayId=vgw-8db04f81
&AUTHPARAMS
```

Example Response

```
<CreateVpnConnectionResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</requestId>
  <vpnConnection>
    <vpnConnectionId>vpn-44a8938f</vpnConnectionId>
    <state>pending</state>
    <customerGatewayConfiguration>
      <?xml version="1.0" encoding="UTF-8"?>
      <vpn_connection id="vpn-44a8938f">
        <customer_gateway_id>cgw-b4dc3961</customer_gateway_id>
        <vpn_gateway_id>vgw-8db04f81</vpn_gateway_id>
        <vpn_connection_type>ipsec.1</vpn_connection_type>
        <ipsec_tunnel>
          <customer_gateway>
            <tunnel_outside_address>
              <ip_address>YOUR_UPLINK_ADDRESS</ip_address>
            </tunnel_outside_address>
            <tunnel_inside_address>
              <ip_address>169.254.255.1</ip_address>
              <network_mask>255.255.255.252</network_mask>
              <network_cidr>30</network_cidr>
            </tunnel_inside_address>
            <bgp>
              <asn>YOUR_BGP_ASN</asn>
              <hold_time>30</hold_time>
            </bgp>
          </customer_gateway>
          <vpn_gateway>
            <tunnel_outside_address>
```

```
<ip_address>72.21.209.193</ip_address>
</tunnel_outside_address>
<tunnel_inside_address>
  <ip_address>169.254.255.2</ip_address>
  <network_mask>255.255.255.252</network_mask>
  <network_cidr>30</network_cidr>
</tunnel_inside_address>
<bgp>
  <asn>7224</asn>
  <hold_time>30</hold_time>
</bgp>
</vpn_gateway>
<ike>
  <authentication_protocol>sha1</authentication_protocol>
  <encryption_protocol>aes-128-cbc</encryption_protocol>
  <lifetime>28800</lifetime>
  <perfect_forward_secrecy>group2</perfect_forward_secrecy>
  <mode>main</mode>
  <pre_shared_key>plain-text-password1</pre_shared_key>
</ike>
<ipsec>
  <protocol>esp</protocol>
  <authentication_protocol>hmac-shal-96</authentication_protocol>
  <encryption_protocol>aes-128-cbc</encryption_protocol>
  <lifetime>3600</lifetime>
  <perfect_forward_secrecy>group2</perfect_forward_secrecy>
  <mode>tunnel</mode>
  <clear_df_bit>true</clear_df_bit>
  <fragmentation_before_encryption>true</fragmentation_before_encryption>
  <tcp_mss_adjustment>1396</tcp_mss_adjustment>
  <dead_peer_detection>
    <interval>10</interval>
    <retries>3</retries>
  </dead_peer_detection>
</ipsec>
</ipsec_tunnel>
<ipsec_tunnel>
  <customer_gateway>
    <tunnel_outside_address>
      <ip_address>YOUR_UPLINK_ADDRESS</ip_address>
    </tunnel_outside_address>
    <tunnel_inside_address>
      <ip_address>169.254.255.5</ip_address>
      <network_mask>255.255.255.252</network_mask>
      <network_cidr>30</network_cidr>
    </tunnel_inside_address>
    <bgp>
      <asn>YOUR_BGP_ASN</asn>
      <hold_time>30</hold_time>
    </bgp>
  </customer_gateway>
</vpn_gateway>
  <tunnel_outside_address>
    <ip_address>72.21.209.225</ip_address>
  </tunnel_outside_address>
  <tunnel_inside_address>
    <ip_address>169.254.255.6</ip_address>
```

```
        <network_mask>255.255.255.252</network_mask>
        <network_cidr>30</network_cidr>
    </tunnel_inside_address>
    <bgp>
        <asn>7224</asn>
        <hold_time>30</hold_time>
    </bgp>
</vpn_gateway>
<ike>
    <authentication_protocol>sha1</authentication_protocol>
    <encryption_protocol>aes-128-cbc</encryption_protocol>
    <lifetime>28800</lifetime>
    <perfect_forward_secrecy>group2</perfect_forward_secrecy>
    <pre_shared_key>plain-text-password2</pre_shared_key>
    <mode>main</mode>
</ike>
<ipsec>
    <protocol>esp</protocol>
    <authentication_protocol>hmac-sha1-96</authentication_protocol>
    <encryption_protocol>aes-128-cbc</encryption_protocol>
    <lifetime>3600</lifetime>
    <perfect_forward_secrecy>group2</perfect_forward_secrecy>
    <mode>tunnel</mode>
    <clear_df_bit>true</clear_df_bit>
    <fragmentation_before_encryption>true</fragmentation_before_en
cryptio>
    <tcp_mss_adjustment>1396</tcp_mss_adjustment>
    <dead_peer_detection>
        <interval>10</interval>
        <retries>3</retries>
    </dead_peer_detection>
</ipsec>
</ipsec_tunnel>
</vpn_connection>
</customerGatewayConfiguration>
<type>ipsec.1</type>
<customerGatewayId>cgw-b4dc3961</customerGatewayId>
<vpnGatewayId>vgw-8db04f81</vpnGatewayId>
<tagSet/>
</vpnConnection>
</CreateVpnConnectionResponse>
```

Related Operations

- [DescribeVpnConnections](#) (p. 286)
- [DeleteVpnConnection](#) (p. 139)
- [CreateVpc](#) (p. 97)
- [CreateSubnet](#) (p. 91)
- [AttachVpnGateway](#) (p. 31)

CreateVpnGateway

Description

Creates a new virtual private gateway. A virtual private gateway is the VPC-side endpoint for your VPN connection. You can create a virtual private gateway before creating the VPC itself.

For more information about Amazon Virtual Private Cloud and virtual private gateways, see [Adding an IPsec Hardware Virtual Private Gateway to Your VPC](#) in the *Amazon Virtual Private Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|-------------------------|--|----------|
| <i>Type</i> | The type of VPN connection this virtual private gateway supports. Type: String Default: None Valid values: <code>ipsec.1</code> | Yes |
| <i>AvailabilityZone</i> | The Availability Zone option has been deprecated. The API ignores this parameter. Type: String Default: None | No |

Response Elements

The elements in the following table are wrapped in an `CreateVpnGatewayResponse` structure.

| Name | Description |
|-------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>vpnGateway</code> | Information about the virtual private gateway. Type: VpnGatewayType (p. 485) |

Examples

Example Request

This example creates a virtual private gateway.

```
https://ec2.amazonaws.com/?Action=CreateVpnGateway
&Type=ipsec.1
&AUTHPARAMS
```

Example Response

```
<CreateVpnGatewayResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</requestId>
  <vpnGateway>
    <vpnGatewayId>vgw-8db04f81</vpnGatewayId>
    <state>pending</state>
    <type>ipsec.1</type>
    <availabilityZone>us-east-1a</availabilityZone>
    <attachments/>
    <tagSet/>
  </vpnGateway>
</CreateVpnGatewayResponse>
```

Related Operations

- [DescribeVpnGateways](#) (p. 290)
- [DeleteVpnGateway](#) (p. 141)
- [AttachVpnGateway](#) (p. 31)
- [DetachVpnGateway](#) (p. 300)

DeleteCustomerGateway

Description

Deletes a VPN customer gateway. You must delete the VPN connection before deleting the customer gateway.

For more information about Amazon Virtual Private Cloud and VPN customer gateways, see [Adding an IPsec Hardware Virtual Private Gateway to Your VPC](#) in the *Amazon Virtual Private Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|--------------------------|--|----------|
| <i>CustomerGatewayId</i> | The ID of the customer gateway. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in an `DeleteCustomerGatewayResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example deletes the customer gateway with ID `cgw-b4dc3961`.

```
https://ec2.amazonaws.com/?Action=DeleteCustomerGateway
&CustomerGatewayId=cgw-b4dc3961
&AUTHPARAMS
```

Example Response

```
<DeleteCustomerGatewayResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</requestId>
```



```
<return>true</return>  
</DeleteCustomerGatewayResponse>
```

Related Operations

- [CreateCustomerGateway](#) (p. 53)
- [DescribeCustomerGateways](#) (p. 158)

DeleteDhcpOptions

Description

Deletes a set of DHCP options that you specify. Amazon VPC returns an error if the set of options you specify is currently associated with a VPC. You can disassociate the set of options by associating either a new set of options or the default options with the VPC.

For more information about Amazon Virtual Private Cloud and DHCP options sets, see [Using DHCP Options in Your VPC](#) in the *Amazon Virtual Private Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|----------------------|--|----------|
| <i>DhcpOptionsId</i> | The ID of the DHCP options set. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in an `DeleteDhcpOptionsResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example deletes the set of DHCP options with ID `dopt-7a8b9c2d`.

```
https://ec2.amazonaws.com/?Action=DeleteDhcpOptions
&DhcpOptionsId=dopt-7a8b9c2d
&AUTHPARAMS
```

Example Response

```
<DeleteDhcpOptionsResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</requestId>
```

```
<return>true</return>  
</DeleteDhcpOptionsResponse>
```

Related Operations

- [AssociateDhcpOptions](#) (p. 21)
- [CreateDhcpOptions](#) (p. 55)
- [DescribeDhcpOptions](#) (p. 161)

DeleteInternetGateway

Description

Deletes an Internet gateway from your AWS account. The gateway must not be attached to a VPC. For more information about your VPC and Internet gateway, see the [Amazon Virtual Private Cloud User Guide](#).

Request Parameters

| Name | Description | Required |
|--------------------------|--|----------|
| <i>InternetGatewayId</i> | The ID of the Internet gateway. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in a `DeleteInternetGatewayResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: String |
| <code>return</code> | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example deletes the Internet gateway with ID `igw-eaad4883`.

```
https://ec2.amazonaws.com/?Action=DeleteInternetGateway
&InternetGatewayId=igw-eaad4883
&AUTHPARAMS
```

Example Response

```
<DeleteInternetGatewayResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <return>true</return>
</DeleteInternetGatewayResponse>
```

Related Operations

- [CreateInternetGateway](#) (p. 63)
- [AttachInternetGateway](#) (p. 25)
- [DetachInternetGateway](#) (p. 294)
- [DescribeInternetGateways](#) (p. 203)

DeleteKeyPair

Description

Deletes the specified key pair, by removing the public key from Amazon EC2. You must own the key pair.

Request Parameters

| Name | Description | Required |
|----------------|--|----------|
| <i>KeyName</i> | The name of the key pair. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in a `DeleteKeyPairResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example deletes the `gsg-keypair` key pair.

```
https://ec2.amazonaws.com/?Action=DeleteKeyPair
&KeyName=gsg-keypair
&AUTHPARAMS
```

Example Response

```
<DeleteKeyPairResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <return>true</return>
</DeleteKeyPairResponse>
```

Related Operations

- [CreateKeyPair](#) (p. 65)

- [DescribeKeyPairs](#) (p. 206)
- [ImportKeyPair](#) (p. 316)

DeleteNetworkAcl

Description

Deletes a network ACL from a VPC. The ACL must not have any subnets associated with it. You can't delete the default network ACL. For more information about network ACLs, see [Network ACLs](#) in the *Amazon Virtual Private Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|---------------------|---|----------|
| <i>NetworkAclId</i> | The ID of the network ACL. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in a `DeleteNetworkAclResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example deletes the network ACL with ID `acl-2cb85d45`.

```
https://ec2.amazonaws.com/?Action=DeleteNetworkAcl
&NetworkAclId=acl-2cb85d45
&AUTHPARAMS
```

Example Response

```
<DeleteNetworkAclResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <return>true</return>
</DeleteNetworkAclResponse>
```


Related Operations

- [DeleteNetworkAcl](#) (p. 113)
- [DescribeNetworkAcls](#) (p. 209)
- [ReplaceNetworkAclAssociation](#) (p. 345)

DeleteNetworkAclEntry

Description

Deletes an ingress or egress entry (i.e., rule) from a network ACL. For more information about network ACLs, see [Network ACLs](#) in the *Amazon Virtual Private Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|--------------|--|----------|
| NetworkAclId | The ID of the network ACL. Type: string Default: none | Yes |
| RuleNumber | The rule number for the entry to delete. Type: Number Default: none | Yes |
| Egress | Specifies whether the rule to delete is an egress rule (<code>true</code>) or ingress rule (<code>false</code>). Type: Boolean Default: <code>false</code> Valid values: <code>true</code> <code>false</code> | No |

Response Elements

The elements in the following table are wrapped in a `ReplaceNetworkAclEntryResponse` structure.

| Name | Description |
|-----------|---|
| requestId | The ID of the request. Type: <code>xsd:string</code> |
| return | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example deletes the ingress entry with rule number 100 from the network ACL with ID `acl-2cb85d45`.

```
https://ec2.amazonaws.com/?Action=DeleteNetworkAclEntry
&NetworkAclId=acl-2cb85d45
&RuleNumber=100
&AUTHPARAMS
```

Example Response

```
<DeleteNetworkAclEntryResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <return>true</return>
</DeleteNetworkAclEntryResponse>
```

Related Operations

- [CreateNetworkAclEntry](#) (p. 69)
- [ReplaceNetworkAclEntry](#) (p. 347)
- [DescribeNetworkAcls](#) (p. 209)

DeleteNetworkInterface

Description

Deletes the specified network interface.

Request Parameters

| Name | Description | Required |
|--------------------|---|----------|
| NetworkInterfaceId | The ID of the network interface. Type: String Default: None | Yes |

Response Elements

| Name | Description |
|-----------|--|
| requestId | The ID of the request to delete the network interface. Type: xsd:string |
| return | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: xsd:boolean |

Examples

Example Request

This example deletes an elastic network interface (ENI) `eni-ffda3197`.

```
https://ec2.amazonaws.com/?Action=DeleteNetworkInterface
&NetworkInterfaceId=eni-ffda3197
&AUTHPARAMS
```

Example Response

```
<DeleteNetworkInterfaceResponse xmlns='http://ec2.amazonaws.com/doc/2011-11-15/'>
  <requestId>e1c6d73b-edaa-4e62-9909-6611404e1739</requestId>
  <return>true</return>
</DeleteNetworkInterfaceResponse>
```

Related Operations

- [AttachNetworkInterface](#) (p. 27)
- [DetachNetworkInterface](#) (p. 296)

- [CreateNetworkInterface](#) (p. 72)
- [DescribeNetworkInterfaceAttribute](#) (p. 214)
- [DescribeNetworkInterfaces](#) (p. 216)
- [ModifyNetworkInterfaceAttribute](#) (p. 327)
- [ResetNetworkInterfaceAttribute](#) (p. 369)

DeletePlacementGroup

Description

Deletes a placement group from your account. You must terminate all instances in the placement group before deleting it. For more information about placement groups and cluster instances, see [Using Cluster Instances](#) in the *Amazon Elastic Compute Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|-----------|---|----------|
| GroupName | The name of the placement group. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in a `DeletePlacementGroupResponse` structure.

| Name | Description |
|-----------|--|
| requestId | The ID of the request. Type: xsd:string |
| return | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: xsd:boolean |

Examples

Example Request

This example deletes the placement group named XYZ-cluster.

```
https://ec2.amazonaws.com/?Action=DeletePlacementGroup
&GroupName=XYZ-cluster
&AUTHPARAMS
```

Example Response

```
<DeletePlacementGroupResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>d4904fd9-82c2-4ea5-adfe-a9cc3EXAMPLE</requestId>
  <return>true</return>
</DeletePlacementGroupResponse>
```

Related Operations

- [CreatePlacementGroup](#) (p. 77)
- [DescribePlacementGroups](#) (p. 222)

DeleteRoute

Description

Deletes a route from a route table in a VPC. For more information about route tables, see [Route Tables](#) in the *Amazon Virtual Private Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|-----------------------------|---|----------|
| <i>RouteTableId</i> | The ID of the route table. Type: String Default: None | Yes |
| <i>DestinationCidrBlock</i> | The CIDR range for the route to delete. The value you specify must exactly match the CIDR for the route. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in a `ReplaceRouteResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example removes the route with destination CIDR 172.16.1.0/24 from the route table with ID `rtb-e4ad488d`.

```
https://ec2.amazonaws.com/?Action=DeleteRoute
&RouteTableId=rtb-e4ad488d
&DestinationCidrBlock=172.16.1.0/24
&AUTHPARMS
```


Example Response

```
<DeleteRouteResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <return>true</return>
</DeleteRouteResponse>
```

Related Operations

- [CreateRoute](#) (p. 79)
- [ReplaceRoute](#) (p. 350)
- [DescribeRouteTables](#) (p. 236)

DeleteRouteTable

Description

Deletes a route table from a VPC. The route table must not be associated with a subnet. You can't delete the main route table. For more information about route tables, see [Route Tables](#) in the *Amazon Virtual Private Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|---------------------------|---|----------|
| <code>RouteTableId</code> | The ID of the route table. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in a `DeleteRouteTableResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example deletes the route table with ID `rtb-e4ad488d`.

```
https://ec2.amazonaws.com/?Action=DeleteRouteTable
&RouteTableId=rtb-e4ad488d
&AUTHPARAMS
```

Example Response

```
<DeleteRouteTableResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <return>true</return>
</DeleteRouteTableResponse>
```

Related Operations

- [AssociateRouteTable](#) (p. 23)
- [DisassociateRouteTable](#) (p. 304)
- [DescribeRouteTables](#) (p. 236)
- [CreateRouteTable](#) (p. 82)
- [ReplaceRouteTableAssociation](#) (p. 352)

DeleteSecurityGroup

Description

Deletes a security group. This action applies to both EC2 security groups and VPC security groups. For information about VPC security groups and how they differ from EC2 security groups, see [Security Groups](#) in the *Amazon Virtual Private Cloud User Guide*.

Note

If you attempt to delete a security group that contains instances, or attempt to delete a security group that is referenced by another security group, an error is returned. For example, if security group B has a rule that allows access from security group A, security group A cannot be deleted until the rule is removed.

The fault returned is `InvalidGroup.InUse` for EC2 security groups, or `DependencyViolation` for VPC security groups.

Request Parameters

| Name | Description | Required |
|------------------|--|-------------|
| <i>GroupName</i> | The name of the security group. Type: String Default: None Condition: Either <i>GroupName</i> or <i>GroupId</i> is required | Conditional |
| <i>GroupId</i> | The ID of the security group. Type: String Default: None Condition: Required for a VPC security group; for an EC2 security group, either <i>GroupName</i> or <i>GroupId</i> is required | Conditional |

Response Elements

The elements in the following table are wrapped in a `DeleteSecurityGroupResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example deletes the EC2 security group named `websrv`.

```
https://ec2.amazonaws.com/?Action=DeleteSecurityGroup
&GroupName=websrv
&AUTHPARAMS
```

Example Request

This example deletes the VPC security group with ID sg-77d0f5a2.

```
https://ec2.amazonaws.com/?Action=DeleteSecurityGroup
&GroupId=sg-77d0f5a2
&AUTHPARAMS
```

Example Response

```
<DeleteSecurityGroupResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <return>true</return>
</DeleteSecurityGroupResponse>
```

Related Operations

- [CreateSecurityGroup](#) (p. 84)
- [DescribeSecurityGroups](#) (p. 240)
- [AuthorizeSecurityGroupIngress](#) (p. 36)
- [RevokeSecurityGroupIngress](#) (p. 376)

DeleteSnapshot

Description

Deletes a snapshot of an Amazon EBS volume.

Note

If you make periodic snapshots of a volume, the snapshots are incremental so that only the blocks on the device that have changed since your last snapshot are incrementally saved in the new snapshot. Even though snapshots are saved incrementally, the snapshot deletion process is designed so that you need to retain only the most recent snapshot in order to restore the volume.

Request Parameters

| Name | Description | Required |
|-------------------|---|----------|
| <i>SnapshotId</i> | The ID of the Amazon EBS snapshot. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in a `DeleteSnapshotResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example deletes snapshot `snap-78a54011`.

```
https://ec2.amazonaws.com/?Action=DeleteSnapshot
&SnapshotId.1=snap-78a54011
&AUTHPARAMS
```

Example Response

```
<DeleteSnapshotResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">  
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>  
  <return>true</return>  
</DeleteSnapshotResponse>
```

Related Operations

- [CreateSnapshot](#) (p. 86)
- [DescribeSnapshots](#) (p. 246)

DeleteSpotDatafeedSubscription

Description

Deletes the datafeed for Spot Instances. For more information about Spot Instances, see [Spot Instances](#) in the *Amazon Elastic Compute Cloud User Guide*.

Request Parameters

The `DeleteSpotDatafeedSubscription` operation does not have any request parameters.

Response Elements

The elements in the following table are wrapped in a `DeleteSpotDatafeedSubscriptionResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example deletes the data feed for the account.

```
https://ec2.amazonaws.com/?Action=DeleteSpotDatafeedSubscription
&AUTHPARAMS
```

Example Response

```
<DeleteSpotDatafeedSubscriptionResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <return>true</return>
</DeleteSpotDatafeedSubscriptionResponse>
```

Related Operations

- [CreateSpotDatafeedSubscription](#) (p. 89)
- [DescribeSpotDatafeedSubscription](#) (p. 251)

DeleteSubnet

Description

Deletes a subnet from a VPC. You must terminate all running instances in the subnet before deleting it, otherwise Amazon VPC returns an error.

Request Parameters

| Name | Description | Required |
|-----------------|--|----------|
| <i>SubnetId</i> | The ID of the subnet. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in an `DeleteSubnetResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example deletes the subnet with ID `subnet-9d4a7b6c`.

```
https://ec2.amazonaws.com/?Action=DeleteSubnet
&SubnetId=subnet-9d4a7b6c
&AUTHPARAMS
```

Example Response

```
<DeleteSubnetResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</requestId>
  <return>true</return>
</DeleteSubnetResponse>
```

Related Operations

- [CreateSubnet](#) (p. 91)
- [DescribeSubnets](#) (p. 263)

DeleteTags

Description

Deletes a specific set of tags from a specific set of resources. This call is designed to follow a `DescribeTags` call. You first determine what tags a resource has, and then you call `DeleteTags` with the resource ID and the specific tags you want to delete.

For more information about tags, see [Using Tags](#) in the *Amazon Elastic Compute Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|---------------------------|--|----------|
| <code>ResourceId.n</code> | The ID of the resource. For example, <code>ami-1a2b3c4d</code> . You can specify more than one resource ID. Type: String Default: None | Yes |
| <code>Tag.n.Key</code> | The tag's key. You can specify more than one tag to delete. Type: String Default: None | Yes |
| <code>Tag.n.Value</code> | The tag's value. Type: String Default: If you omit this parameter, we delete the tag regardless of its value. If you specify this parameter with an empty string as the value, we delete the key only if its value is an empty string. | No |

Response Elements

The elements in the following table are wrapped in a `DeleteTagsResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example deletes the tags for the AMI with ID `ami-1a2b3c4d`. You first get a list of the tags.

```
https://ec2.amazonaws.com/?Action=DescribeTags
&ResourceId.1=ami-1a2b3c4d
&AUTHPARAMS
```

Sample response:

```
<DescribeTagsResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</requestId>
  <tagSet>
    <item>
      <resourceId>ami-1a2b3c4d</resourceId>
      <resourceType>image</resourceType>
      <key>webserver</key>
      <value/>
    </item>
    <item>
      <resourceId>ami-1a2b3c4d</resourceId>
      <resourceType>image</resourceType>
      <key>stack</key>
      <value>Production</value>
    </item>
  </tagSet>
</DescribeTagsResponse>
```

Then you delete the tags. Specifying the value for the *stack* tag is optional.

```
https://ec2.amazonaws.com/?Action=DeleteTags
&ResourceId.1=ami-1a2b3c4d
&Tag.1.Key=webserver
&Tag.2.Key=stack
&AUTHPARAMS
```

Sample response:

```
<DeleteTagsResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</requestId>
  <return>true</return>
</DeleteTagsResponse>
```

Example Request

This example deletes the stack tag from two particular instances.

```
https://ec2.amazonaws.com/?Action=DeleteTags
&ResourceId.1=i-5f4e3d2a
&Tag.1.Key=stack
&ResourceId.2=i-12345678
&Tag.2.Key=stack
&AUTHPARAMS
```

Example Request

This example deletes the stack and webserver tags for one particular instance.

```
https://ec2.amazonaws.com/?Action=DeleteTags
&ResourceId.1=i-5f4e3d2a
&Tag.1.Key=stack
&ResourceId.2=i-5f4e3d2a
&Tag.2.Key=webserver
&AUTHPARAMS
```

Example Request

You can specify a tag key without a corresponding tag value if you want to delete the tag regardless of its value. This example deletes all tags whose key=`Purpose`, regardless of the tag value.

```
https://ec2.amazonaws.com/?Action=DeleteTags
&ResourceId.1=i-5f4e3d2a
&Tag.1.Key=Purpose
&AUTHPARAMS
```

Example Request

When you create a tag, you can set the tag value to the empty string. Correspondingly, you can delete only tags that have a specific key and whose value is the empty string. This example deletes all tags for the specified instance where key=`Purpose` and the tag value is the empty string.

```
https://ec2.amazonaws.com/?Action=DeleteTags
&ResourceId.1=i-5f4e3d2a
&Tag.1.Key=Purpose
&Tag.2.Value=
&AUTHPARAMS
```

Related Operations

- [CreateTags](#) (p. 93)
- [DescribeTags](#) (p. 267)

DeleteVolume

Description

Deletes an Amazon EBS volume. The volume must be in the `available` state (not attached to an instance). For more information about Amazon EBS, see [Using Amazon Elastic Block Store](#) in the *Amazon Elastic Compute Cloud User Guide*.

Note

The volume remains in the deleting state for several minutes after you call this action.

Request Parameters

| Name | Description | Required |
|-----------------------|--|----------|
| <code>VolumeId</code> | The ID of the volume. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in a `DeleteVolumeResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example deletes volume `vol-4282672b`.

```
https://ec2.amazonaws.com/?Action=DeleteVolume
&VolumeId=vol-4282672b
&AUTHPARAMS
```

Example Response

```
<DeleteVolumeResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
```

```
<return>true</return>  
</DeleteVolumeResponse>
```

Related Operations

- [CreateVolume](#) (p. 95)
- [DescribeVolumes](#) (p. 272)
- [AttachVolume](#) (p. 29)
- [DetachVolume](#) (p. 298)

DeleteVpc

Description

Deletes a VPC. You must detach or delete all gateways or other objects that are dependent on the VPC first. For example, you must terminate all running instances, delete all VPC security groups (except the default), delete all the route tables (except the default), etc.

For more information about Amazon Virtual Private Cloud and VPCs, see the [Amazon Virtual Private Cloud User Guide](#).

Request Parameters

| Name | Description | Required |
|--------------|---|----------|
| <i>VpcId</i> | The ID of the VPC. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in an `DeleteVpcResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example deletes the VPC with ID `vpc-1a2b3c4d`.

```
https://ec2.amazonaws.com/?Action=DeleteVpc
&VpcId=vpc-1a2b3c4d
&AUTHPARAMS
```

Example Response

```
<DeleteVpcResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</requestId>
```



```
<return>true</return>  
</DeleteVpcResponse>
```

Related Operations

- [CreateVpc](#) (p. 97)
- [DescribeVpcs](#) (p. 283)

DeleteVpnConnection

Description

Deletes a VPN connection. Use this if you want to delete a VPC and all its associated components. Another reason to use this operation is if you believe the tunnel credentials for your VPN connection have been compromised. In that situation, you can delete the VPN connection and create a new one that has new keys, without needing to delete the VPC or virtual private gateway. If you create a new VPN connection, you must reconfigure the customer gateway using the new configuration information returned with the new VPN connection ID.

If you're deleting the VPC and all its associated parts, we recommend you detach the virtual private gateway from the VPC and delete the VPC before deleting the VPN connection.

For more information about Amazon Virtual Private Cloud and VPN connections, see [Adding an IPsec Hardware Virtual Private Gateway to Your VPC](#) in the *Amazon Virtual Private Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|------------------------|--|----------|
| <i>VpnConnectionId</i> | The ID of the VPN connection. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in an `DeleteVpnConnectionResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example deletes the VPN connection with ID `vpn-44a8938f`.

```
https://ec2.amazonaws.com/?Action=DeleteVpnConnection
&vpnConnectionId=vpn-44a8938f
&AUTHPARAMS
```

Example Response

```
<DeleteVpnConnectionResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</requestId>
  <return>>true</return>
</DeleteVpnConnectionResponse>
```

Related Operations

- [CreateVpnConnection](#) (p. 99)
- [DescribeVpnConnections](#) (p. 286)
- [DetachVpnGateway](#) (p. 300)
- [DeleteVpc](#) (p. 137)

DeleteVpnGateway

Description

Deletes a virtual private gateway. Use this when you want to delete a VPC and all its associated components because you no longer need them. We recommend that before you delete a virtual private gateway, you detach it from the VPC and delete the VPN connection. Note that you don't need to delete the virtual private gateway if you just want to delete and recreate the VPN connection between your VPC and data center.

For more information about Amazon Virtual Private Cloud and virtual private gateways, see [Adding an IPsec Hardware Virtual Private Gateway to Your VPC](#) in the *Amazon Virtual Private Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|---------------------|---|----------|
| <i>VpnGatewayId</i> | The ID of the virtual private gateway. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in an `DeleteVpnGatewayResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example deletes the virtual private gateway with ID `vgw-8db04f81`.

```
https://ec2.amazonaws.com/?Action=DeleteVpnGateway
&vpnGatewayId=vgw-8db04f81
&AUTHPARAMS
```

Example Response

```
<DeleteVpnGatewayResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">  
  <requestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</requestId>  
  <return>true</return>  
</DeleteVpnGatewayResponse>
```

Related Operations

- [CreateVpnGateway](#) (p. 103)
- [DescribeVpnGateways](#) (p. 290)
- [DeleteVpnConnection](#) (p. 139)

DeregisterImage

Description

Deregisters the specified AMI. Once deregistered, the AMI cannot be used to launch new instances.

Note

This command does not delete the AMI.

Request Parameters

| Name | Description | Required |
|----------------|---|----------|
| <i>ImageId</i> | The ID of the AMI to deregister. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in a `DeregisterImageResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example deregisters the `ami-4fa54026` AMI.

```
https://ec2.amazonaws.com/?Action=DeregisterImage
&ImageId=ami-4fa54026
&AUTHPARAMS
```

Example Response

```
<DeregisterImageResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <return>true</return>
</DeregisterImageResponse>
```

Related Operations

- [RegisterImage](#) (p. 339)
- [DescribeImages](#) (p. 170)

DescribeAddresses

Description

Gives information about Elastic IP addresses allocated to your account. This includes both EC2 and VPC Elastic IP addresses. For information about VPC addresses and how they differ from EC2 addresses, see [Elastic IP Addresses](#) in the *Amazon Virtual Private Cloud User Guide*.

You can filter the results to return information only about Elastic IP addresses that match criteria you specify. For example, you could get information only about addresses tagged with a certain value. You can specify multiple values for a filter. An address must match at least one of the specified values for it to be included in the results.

You can specify multiple filters (e.g., the address is a particular value, and is tagged with a certain value). The result includes information for an address only if it matches *all* your filters. If there's no match, no special message is returned; the response is simply empty.

You can use wildcards with the filter values: `*` matches zero or more characters, and `?` matches exactly one character. You can escape special characters using a backslash before the character. For example, a value of `*amazon\?\` searches for the literal string `*amazon?\`.

The following table shows the available filters.

| Filter Name | Description |
|----------------------------|---|
| domain | Indicates whether the address is a EC2 address, or a VPC address. Type: String Valid values: <code>standard</code> <code>vpc</code> |
| instance-id | The instance the address is associated with (if any). Type: String |
| public-ip | The Elastic IP address. Type: String |
| allocation-id | The allocation ID for the address (VPC addresses only). Type: String |
| association-id | The association ID for the address (VPC addresses only). Type: String |
| network-interface-id | The network interface (if any) that the address is associated with. (for VPC addresses only). Type: String |
| network-interface-owner-id | The owner IID. |
| private-ip-address | The private IP address associated with the Elastic IP address (for VPC addresses only). Type: String |

Request Parameters

| Name | Description | Required |
|-------------------------|---|----------|
| <i>PublicIp.n</i> | One or more Elastic IP addresses. Applies only to standard (EC2) addresses. Type: String Default: None | No |
| <i>AllocationId.n</i> | One or more allocation IDs corresponding to the address or addresses to describe. Applies only to VPC addresses. Type: String Default: None | No |
| <i>Filter.n.Name</i> | The name of a filter. See the preceding table for a list of allowed filter names. Type: String Default: None | No |
| <i>Filter.n.Value.m</i> | A value for the filter. See the preceding table for a list of allowed values for each filter. Type: String Default: None | No |

Response Elements

The elements in the following table are wrapped in a `DescribeAddressesResponse` structure.

| Name | Description |
|---------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>addressesSet</code> | A list of IP addresses, each one wrapped in an <code>item</code> element. Type: DescribeAddressesResponseItemType (p. 413) |

Examples

Example Request

EC2 addresses: This example describes two specific EC2 Elastic IP addresses assigned to the account. Amazon EC2 returns information about 192.0.2.1, which is assigned to instance i-f15ebb98, and for 198.51.100.2, which is not assigned to an instance.

```
https://ec2.amazonaws.com/?Action=DescribeAddresses
&PublicIp.1=192.0.2.1
&PublicIp.2=198.51.100.2
&AUTHPARAMS
```

Example Response

```
<DescribeAddressesResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <addressesSet>
    <item>
      <publicIp>192.0.2.1</publicIp>
      <domain>standard</domain>
      <instanceId>i-f15ebb98</instanceId>
    </item>
    <item>
      <publicIp>198.51.100.2</publicIp>
      <domain>standard</domain>
      <instanceId/>
    </item>
  </addressesSet>
</DescribeAddressesResponse>
```

Example Request

VPC Addresses: This example describes a specific VPC address allocated to your account. You must use the allocation ID to specify the address.

```
https://ec2.amazonaws.com/?Action=DescribeAddresses
&AllocationId.1= eipalloc-08229861
&AUTHPARAMS
```

Example Response

```
<soap:Body>
  <DescribeAddressesResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
    <requestId>f7de5e98-491a-4c19-a92d-908d6EXAMPLE</requestId>
    <addressesSet>
      <item>
        <publicIp>46.51.223.41</publicIp>
        <allocationId>eipalloc-08229861</allocationId>
        <domain>vpc</domain>
        <instanceId>i-64600030</instanceId>
        <associationId>eipassoc-f0229899</associationId>
        <networkInterfaceId>eni-ef229886</networkInterfaceId>
        <networkInterfaceOwnerId>053230519467</networkInterfaceOwnerId>
        <privateIpAddress>10.0.0.228</privateIpAddress>
      </item>
    </addressesSet>
  </DescribeAddressesResponse>
```

Example Request

VPC Addresses: This example lists only your VPC addresses (assuming you have both standard and VPC addresses).

```
https://ec2.amazonaws.com/?Action=DescribeAddresses
&Filter.1.Name=allocation-id
&Filter.1.Value.1=*
&AUTHPARAMS
```

Example Response

```
<DescribeAddressesResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>0782c68a-5f24-4dce-93c0-b5a066d6e0d0</requestId>
  <addressesSet>
    <item>
      <publicIp>203.0.113.12</publicIp>
      <allocationId>eipalloc-08229861</allocationId>
      <domain>vpc</domain>
      <instanceId>i-64600030</instanceId>
      <associationId>eipassoc-f0229899</associationId>
      <networkInterfaceId>eni-ef229886</networkInterfaceId>
      <networkInterfaceOwnerId>053230519467</networkInterfaceOwnerId>
      <privateIpAddress>10.0.0.228</privateIpAddress>
    </item>
    <item>
      <publicIp>46.51.221.164</publicIp>
      <allocationId>eipalloc-1b5fe072</allocationId>
      <domain>vpc</domain>
    </item>
    <item>
      <publicIp>203.0.113.14</publicIp>
      <allocationId>eipalloc-f38a359a</allocationId>
      <domain>vpc</domain>
      <instanceId>i-7a00642e</instanceId>
      <associationId>eipassoc-1f239876</associationId>
      <networkInterfaceId>eni-d83388b1</networkInterfaceId>
      <networkInterfaceOwnerId>053230519467</networkInterfaceOwnerId>
      <privateIpAddress>10.0.0.12</privateIpAddress>
    </item>
    <item>
      <publicIp>203.0.113.33</publicIp>
      <allocationId>eipalloc-282d9641</allocationId>
      <domain>vpc</domain>
      <instanceId>i-7a00642e</instanceId>
      <associationId>eipassoc-252d964c</associationId>
      <networkInterfaceId>eni-d83388b1</networkInterfaceId>
      <networkInterfaceOwnerId>053230519467</networkInterfaceOwnerId>
      <privateIpAddress>10.0.0.14</privateIpAddress>
    </item>
    <item>
      <publicIp>203.0.113.22</publicIp>
      <allocationId>eipalloc-1266dd7b</allocationId>
      <domain>vpc</domain>
      <instanceId>i-880f6fdc</instanceId>
      <associationId>eipassoc-832e94ea</associationId>
      <networkInterfaceId>eni-af2e94c6</networkInterfaceId>
      <networkInterfaceOwnerId>053230519467</networkInterfaceOwnerId>
      <privateIpAddress>10.0.0.47</privateIpAddress>
    </item>
  </addressesSet>
</DescribeAddressesResponse>
```

```
<publicIp>203.0.113.42 </publicIp>
<allocationId>eipalloc-ff229896</allocationId>
<domain>vpc</domain>
</item>
<item>
<publicIp>203.0.113.53</publicIp>
<allocationId>eipalloc-b463dcdd</allocationId>
<domain>vpc</domain>
<instanceId>i-c844219c</instanceId>
<associationId>eipassoc-d667ddbfc</associationId>
<networkInterfaceId>eni-ea67dc83</networkInterfaceId>
<networkInterfaceOwnerId>053230519467</networkInterfaceOwnerId>
<privateIpAddress>10.0.0.174</privateIpAddress>
</item>
<item>
<publicIp>203.0.113.61</publicIp>
<allocationId>eipalloc-bf66dcd6</allocationId>
<domain>vpc</domain>
<instanceId>i-ba6a0dee</instanceId>
<associationId>eipassoc-9c66dcf5</associationId>
<networkInterfaceId>eni-73e05a1a</networkInterfaceId>
<networkInterfaceOwnerId>053230519467</networkInterfaceOwnerId>
<privateIpAddress>10.0.0.85</privateIpAddress>
</item>
</addressesSet>
</DescribeAddressesResponse>
```

Related Operations

- [AllocateAddress](#) (p. 13)
- [ReleaseAddress](#) (p. 343)
- [AssociateAddress](#) (p. 18)
- [DisassociateAddress](#) (p. 302)

DescribeAvailabilityZones

Description

Displays Availability Zones that are currently available to the account. The results include zones only for the Region you're currently using.

Note

Availability Zones are not the same across accounts. The Availability Zone `us-east-1a` for account A is not necessarily the same as `us-east-1a` for account B. Zone assignments are mapped independently for each account.

You can filter the results to return information only about zones that match criteria you specify. For example, you could filter the results to return only the zones whose state is `available`. You can specify multiple filters (e.g., the zone is in a particular Region, and the state is `available`). The result includes information for a particular zone only if it matches *all* your filters. If there's no match, no special message is returned; the response is simply empty.

You can use wildcards with the filter values: `*` matches zero or more characters, and `?` matches exactly one character. You can escape special characters using a backslash before the character. For example, a value of `*amazon\?\` searches for the literal string `*amazon?\`.

The following table shows the available filters.

| Filter Name | Description |
|--------------------------|--|
| <code>message</code> | Information about the Availability Zone. Type: String |
| <code>region-name</code> | The Region the Availability Zone is in (e.g., <code>us-east-1</code>). Type: String |
| <code>state</code> | The state of the Availability Zone Type: String Valid values: <code>available</code> |
| <code>zone-name</code> | The name of the zone. Type: String |

Request Parameters

| Name | Description | Required |
|----------------------------|--|----------|
| <code>ZoneName.n</code> | One or more Availability Zones. Type: String Default: None | No |
| <code>Filter.n.Name</code> | The name of a filter. See the preceding table for a list of allowed filter names. Type: String Default: None | No |

| Name | Description | Required |
|-------------------------|--|----------|
| <i>Filter.n.Value.m</i> | A value for the filter. See the preceding table for a list of allowed values for each filter. Type: String Default: None | No |

Response Elements

The elements in the following table are wrapped in a `DescribeAvailabilityZonesResponse` structure.

| Name | Description |
|-----------------------------------|--|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>availabilityZoneInfo</code> | A list of Availability Zones, each one wrapped in an <code>item</code> element. Type: AvailabilityZoneItemType (p. 405) |

Examples

Example Request

This example displays information about Availability Zones that are available to the account. The results includes zones only in the Region (endpoint) you're currently using.

```
https://ec2.amazonaws.com/?Action=DescribeAvailabilityZones
&AUTHPARAMS
```

Example Response

```
<DescribeAvailabilityZonesResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <availabilityZoneInfo>
    <item>
      <zoneName>us-east-1a</zoneName>
      <zoneState>available</zoneState>
      <regionName>us-east-1</regionName>
      <messageSet/>
    </item>
    <item>
      <zoneName>us-east-1b</zoneName>
      <zoneState>available</zoneState>
      <regionName>us-east-1</regionName>
      <messageSet/>
    </item>
    <item>
      <zoneName>us-east-1c</zoneName>
      <zoneState>available</zoneState>
    </item>
  </availabilityZoneInfo>
</DescribeAvailabilityZonesResponse>
```

```
<regionName>us-east-1</regionName>
<messageSet/>
</item>
<item>
  <zoneName>us-east-1d</zoneName>
  <zoneState>available</zoneState>
  <regionName>us-east-1</regionName>
  <messageSet/>
</item>
</availabilityZoneInfo>
</DescribeAvailabilityZonesResponse>
```

Related Operations

- [RunInstances](#) (p. 379)
- [DescribeRegions](#) (p. 225)

DescribeBundleTasks

Description

Describes current bundling tasks for Amazon S3-backed Windows instances.

Note

Completed bundle tasks are listed for only a limited time. If your bundle task is no longer in the list, you can still register an AMI from it. Just use the `RegisterImage` action with the Amazon S3 bucket name and image manifest name you provided to the bundle task.

You can filter the results to return information only about tasks that match criteria you specify. For example, you could filter the results to return only the tasks whose state is `complete`. You can specify multiple values for a filter. A bundle task must match at least one of the specified values for it to be included in the results.

You can specify multiple filters (e.g., the bundle is stored in a particular Amazon S3 bucket and the state is `complete`). The result includes information for a particular bundle task only if it matches *all* your filters. If there's no match, no special message is returned; the response is simply empty.

You can use wildcards with the filter values: `*` matches zero or more characters, and `?` matches exactly one character. You can escape special characters using a backslash before the character. For example, a value of `*amazon\?\` searches for the literal string `*amazon?\`.

The following table shows the available filters.

| Filter Name | Description |
|----------------------------|--|
| <code>bundle-id</code> | The ID of the bundle task. Type: String |
| <code>error-code</code> | If the task failed, the error code returned. Type: String |
| <code>error-message</code> | If the task failed, the error message returned. Type: String |
| <code>instance-id</code> | The ID of the instance that was bundled. Type: String |
| <code>progress</code> | The level of task completion, as a percentage (e.g., 20%). Type: String |
| <code>s3-bucket</code> | The Amazon S3 bucket to store the AMI. Type: String |
| <code>s3-prefix</code> | The beginning of the AMI name. Type: String |
| <code>start-time</code> | The time the task started, e.g., 2008-09-15T17:15:20.000Z. Type: DateTime |

| Filter Name | Description |
|-------------|--|
| state | The state of the task. Type: String Valid values: pending waiting-for-shutdown bundling storing cancelling complete failed |
| update-time | The time of the most recent update for the task, e.g., 2008-09-15T17:15:20.000Z. Type: DateTime |

Request Parameters

| Name | Description | Required |
|-------------------------|--|----------|
| <i>BundleId.n</i> | One or more bundle task IDs. Type: String Default: If no ID is specified, all bundle tasks are described. | No |
| <i>Filter.n.Name</i> | The name of a filter. See the preceding table for a list of allowed filter names. Type: String Default: None | No |
| <i>Filter.n.Value.m</i> | A value for the filter. See the preceding table for a list of allowed values for each filter. Type: String Default: None | No |

Response Elements

The elements in the following table are wrapped in a `DescribeBundleTasksResponse` structure.

| Name | Description |
|------------------------|--|
| requestId | The ID of the request. Type: xsd:string |
| bundleInstanceTasksSet | A list of bundle tasks, each one wrapped in an <code>item</code> element. Type: BundleInstanceTaskType (p. 409) |

Examples

Example Request

This example describes the status of the `bun-57a5403e` bundle task.

```
https://ec2.amazonaws.com/?Action=DescribeBundleTasks
&bundleId.1=bun-cla540a8
&AUTHPARAMS
```

Example Response

```
<DescribeBundleTasksResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <bundleInstanceTasksSet>
    <item>
      <instanceId>i-12345678</instanceId>
      <bundleId>bun-cla540a8</bundleId>
      <state>cancelling</state>
      <startTime>2008-10-07T11:41:50.000Z</startTime>
      <updateTime>2008-10-07T11:51:50.000Z</updateTime>
      <storage>
        <S3>
          <bucket>myawsbucket</bucket>
          <prefix>winami</prefix>
        </S3>
      </storage>
      <progress>20%</progress>
    </item>
  </bundleInstanceTasksSet>
</DescribeBundleTasksResponse>
```

Example Request

This example filters the results to display only bundle tasks whose state is either `complete` or `failed`, and in addition are targeted for the Amazon S3 bucket called `myawsbucket`.

```
https://ec2.amazonaws.com/?Action=DescribeBundleTasks
&Filter.1.Name=s3-bucket
&Filter.1.Value.1=myawsbucket
&Filter.2.Name=state
&Filter.2.Name.1=complete
&Filter.2.Name.2=failed
&AUTHPARAMS
```

Related Operations

- [BundleInstance](#) (p. 40)
- [CancelBundleTask](#) (p. 43)

DescribeConversionTasks

Description

Describes your conversion tasks. For more information, see [Using the Command Line Tools to Import Your Virtual Machine to Amazon EC2](#) in the *Amazon Elastic Compute Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|---------------------------|--|----------|
| <i>ConversionTaskId.n</i> | One or more conversion task IDs. Type: String | No |

Response Elements

The elements in the following table are wrapped in a `DescribeConversionTasksResponse` structure.

| Name | Description |
|------------------------------|--|
| <code>conversionTasks</code> | A list of conversion tasks, each one wrapped in an <code>item</code> element. Type: ConversionTaskType (p. 411) |

Examples

Example Request

This example describes all your conversion tasks.

```
https://ec2.amazonaws.com/?Action=DescribeConversionTasks
&AUTHPARAMS
```

Example Response

```
<DescribeConversionTasksResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <conversionTasks>
    <item>
      <conversionTask>
        <conversionTaskId>import-i-fh95npoc</conversionTaskId>
        <expirationTime>2010-12-22T12:01Z</expirationTime>
        <importVolume>
          <bytesConverted>1000</bytesConverted>
          <availabilityZone>us-east-1a</availabilityZone>
          <description/>
          <image>
            <format>VDMK</format>
            <size>128696320</size>
          </image>
        </importVolume>
      </conversionTask>
    </item>
  </conversionTasks>
</DescribeConversionTasksResponse>
```

```
        <importManifestUrl>
          https://s3.amazonaws.com/myawsbucket/a3a5e1b6-590d-43cc-97c1-
15c7325d3f41/Win_2008_Server_Data_Center_SP2_32-bit.vmdkmanifest.xml?AWSAccess
KeyId=AKIAIOSFODNN7EXAMPLE&Expires=1294855591&Signature=5snej01T1TtL0uR7KEx
tEXAMPLE%3D
        </importManifestUrl>
      </image>
      <volume>
        <size>8</size>
        <id>vol-34d8a2ff</id>
      </volume>
    </importVolume>
    <state>active</state>
    <statusMessage/>
  </conversionTask>
</item>
</conversionTasks>
</DescribeConversionTasksResponse>
```

Related Operations

- [ImportInstance](#) (p. 312)
- [ImportVolume](#) (p. 318)
- [CancelConversionTask](#) (p. 45)

DescribeCustomerGateways

Description

Gives you information about your VPN customer gateways. You can filter the results to return information only about customer gateways that match criteria you specify. For example, you could get information only about gateways whose state is `pending` or `available`. The customer gateway must match at least one of the specified values for it to be included in the results.

You can specify multiple filters (e.g., the customer gateway has a particular IP address for the Internet-routable external interface, and the gateway's state is `pending` or `available`). The result includes information for a particular customer gateway only if the gateway matches *all* your filters. If there's no match, no special message is returned; the response is simply empty.

You can use wildcards with the filter values: `*` matches zero or more characters, and `?` matches exactly one character. You can escape special characters using a backslash before the character. For example, a value of `*amazon\?\` searches for the literal string `*amazon?`.

The following table shows the available filters.

| Filter Name | Description |
|----------------------------------|--|
| <code>bgp-asn</code> | The customer gateway's Border Gateway Protocol (BGP) Autonomous System Number (ASN). Type: String |
| <code>customer-gateway-id</code> | The ID of the customer gateway. Type: String |
| <code>ip-address</code> | The IP address of the customer gateway's Internet-routable external interface (for example, 12.1.2.3). Type: String |
| <code>state</code> | The state of the customer gateway. Type: String Valid values: <code>pending</code> <code>available</code> <code>deleting</code> <code>deleted</code> |
| <code>type</code> | The type of customer gateway. Currently the only supported type is <code>ipsec.1</code> . Type: String Valid values: <code>ipsec.1</code> |
| <code>tag-key</code> | The key of a tag assigned to the resource. This filter is independent of the <code>tag-value</code> filter. For example, if you use both the filter <code>tag-key=Purpose</code> and the filter <code>tag-value=X</code> , you get any resources assigned both the tag key <code>Purpose</code> (regardless of what the tag's value is), and the tag value <code>X</code> (regardless of what the tag's key is). If you want to list only resources where <code>Purpose=X</code> , see the <code>tag:key</code> filter later in this table. For more information about tags, see Using Tags in the <i>Amazon Elastic Compute Cloud User Guide</i> . Type: String |
| <code>tag-value</code> | The value of a tag assigned to the resource. This filter is independent of the <code>tag-key</code> filter. Type: String |

| Filter Name | Description |
|------------------------------|--|
| <code>tag: <i>key</i></code> | Filters the results based on a specific tag/value combination. Example: To list just the resources assigned tag Purpose=X, then specify: <code>Filter.1.Name=tag:Purpose</code> <code>Filter.1.Value.1=X</code> Example: To list just resources assigned tag Purpose=X OR Purpose=Y, then specify: <code>Filter.1.Name=tag:Purpose</code> <code>Filter.1.Value.1=X</code> <code>Filter.1.Value.2=Y</code> |

For more information about Amazon Virtual Private Cloud and VPN customer gateways, see [Adding an IPsec Hardware Virtual Private Gateway to Your VPC](#) in the *Amazon Virtual Private Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|----------------------------------|--|----------|
| <code>CustomerGatewayId.n</code> | A customer gateway ID. You can specify more than one in the request. Type: String Default: Returns information about all your customer gateways | No |
| <code>Filter.n.Name</code> | The name of a filter. See the preceding table for a list of allowed filter names. Type: String Default: Returns information about all your customer gateways or those you specify by ID. | No |
| <code>Filter.n.Value.m</code> | A value for the filter. See the preceding table for a list of allowed values for each filter. Type: String Default: None | No |

Response Elements

The elements in the following table are wrapped in an `DescribeCustomerGatewaysResponse` structure.

| Name | Description |
|---------------------------------|--|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>customerGatewaySet</code> | A list of customer gateways, each one wrapped in an <code>item</code> element. Type: CustomerGatewayType (p. 412) |

Examples

Example Request

This example gives a description of the customer gateway with ID cgw-b4dc3961.

```
https://ec2.amazonaws.com/?Action=DescribeCustomerGateways
&CustomerGatewayId.1=cgw-b4dc3961
&AUTHPARAMS
```

Example Response

```
<DescribeCustomerGatewaysResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</requestId>
  <customerGatewaySet>
    <item>
      <customerGatewayId>cgw-b4dc3961</customerGatewayId>
      <state>available</state>
      <type>ipsec.1</type>
      <ipAddress>12.1.2.3</ipAddress>
      <bgpAsn>65534</bgpasn>
      <tagSet/>
    </item>
  </customerGatewaySet>
</DescribeCustomerGatewaysResponse>
```

Example Request

This example uses filters to give a description of any customer gateway you own whose IP address is 12.1.2.3, and whose state is either pending or available.

```
https://ec2.amazonaws.com/?Action=DescribeCustomerGateways
&Filter.1.Name=ip-address
&Filter.1.Value.1=12.1.2.3
&Filter.2.Name=state
&Filter.2.Value.1=pending
&Filter.2.Value.2=available
&AUTHPARAMS
```

Related Operations

- [CreateCustomerGateway](#) (p. 53)
- [DeleteCustomerGateway](#) (p. 105)

DescribeDhcpOptions

Description

Gives you information about one or more sets of DHCP options. You can specify one or more DHCP options set IDs, or no IDs (to describe all your sets of DHCP options).

You can filter the results to return information only about sets of options that match criteria you specify. For example, you could get information for sets that have a certain value for the `domain-name` option. You can specify multiple values for the filter. The option must match at least one of the specified values for the options set to be included in the results.

You can specify multiple filters (e.g., a certain value for `domain-name`, and a tag with a certain value). The result includes information for a set of options only if the specified option matches *all* your filters. If there's no match, no special message is returned; the response is simply empty.

You can use wildcards with the filter values: `*` matches zero or more characters, and `?` matches exactly one character. You can escape special characters using a backslash before the character. For example, a value of `*amazon\?\` searches for the literal string `*amazon?\`.

The following table shows the available filters.

| Filter Name | Description |
|------------------------------|--|
| <code>dhcp-options-id</code> | The ID of a set of DHCP options. Type: String |
| <code>key</code> | The key for one of the options (e.g., <code>domain-name</code>). Type: String |
| <code>value</code> | The value for one of the options. Type: String |
| <code>tag-key</code> | The key of a tag assigned to the resource. This filter is independent of the <code>tag-value</code> filter. For example, if you use both the filter <code>tag-key=Purpose</code> and the filter <code>tag-value=X</code> , you get any resources assigned both the tag key <code>Purpose</code> (regardless of what the tag's value is), and the tag value <code>X</code> (regardless of what the tag's key is). If you want to list only resources where <code>Purpose=X</code> , see the <code>tag:key</code> filter later in this table. For more information about tags, see Using Tags in the <i>Amazon Elastic Compute Cloud User Guide</i> . Type: String |
| <code>tag-value</code> | The value of a tag assigned to the resource. This filter is independent of the <code>tag-key</code> filter. Type: String |

| Filter Name | Description |
|----------------------|---|
| <code>tag:key</code> | <p>Filters the results based on a specific tag/value combination.</p> <p>Example: To list just the resources assigned tag Purpose=X, then specify: <code>Filter.1.Name=tag:Purpose</code> <code>Filter.1.Value.1=X</code></p> <p>Example: To list just resources assigned tag Purpose=X OR Purpose=Y, then specify: <code>Filter.1.Name=tag:Purpose</code> <code>Filter.1.Value.1=X</code> <code>Filter.1.Value.2=Y</code></p> |

For more information about Amazon Virtual Private Cloud and DHCP options sets, see [Using DHCP Options in Your VPC](#) in the *Amazon Virtual Private Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|-------------------------------|--|----------|
| <code>DhcpOptionsId.n</code> | <p>A DHCP options set ID. You can specify more than one in the request.</p> <p>Type: String</p> <p>Default: Returns information about all your sets of DHCP options, or only those otherwise specified.</p> | No |
| <code>Filter.n.Name</code> | <p>The name of a filter. See the preceding table for a list of allowed filter names.</p> <p>Type: String</p> <p>Default: Returns information about all your sets of DHCP options, or only those you otherwise specify.</p> | No |
| <code>Filter.n.Value.m</code> | <p>A value for the filter. See the preceding table for a list of allowed values for each filter.</p> <p>Type: String</p> <p>Default: None</p> | No |

Response Elements

The elements in the following table are wrapped in a `DescribeDhcpOptionsResponse` structure.

| Name | Description |
|------------------------|--|
| <code>requestId</code> | <p>The ID of the request.</p> <p>Type: <code>xsd:string</code></p> |

| Name | Description |
|----------------|---|
| dhcpOptionsSet | A list of DHCP options sets, each one wrapped in an <code>item</code> element. Type: DhcpOptionsType (p. 422) Ancestor: <code>DescribeDhcpOptionsResponse</code> Children: <code>item</code> |

Examples

Example Request

This example gives a description of the DHCP options set with ID `dopt-7a8b9c2d`.

```
https://ec2.amazonaws.com/?Action=DescribeDhcpOptions
&DhcpOptionsId.1=dopt-7a8b9c2d
&AUTHPARAMS
```

Example Response

```
<DescribeDhcpOptionsResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</requestId>
  <dhcpOptionsSet>
    <item>
      <dhcpOptionsId>dopt-7a8b9c2d</dhcpOptionsId>
      <dhcpConfigurationSet>
        <item>
          <key>domain-name</key>
          <valueSet>
            <item>
              <value>example.com</value>
            </item>
          </valueSet>
        </item>
        <item>
          <key>domain-name-servers</key>
          <valueSet>
            <item>
              <value>10.2.5.1</value>
            </item>
          </valueSet>
        </item>
        <item>
          <key>domain-name-servers</key>
          <valueSet>
            <item>
              <value>10.2.5.2</value>
            </item>
          </valueSet>
        </item>
      </dhcpConfigurationSet>
    </item>
  </dhcpOptionsSet>
</tagSet/>
```

```
</item>  
</dhcpOptionsSet>  
</DescribeDhcpOptionsResponse>
```

Example Request

This example uses filters to give a description of any DHCP options set that includes a domain-name option whose value includes the string `example`.

```
https://ec2.amazonaws.com/?Action=DescribeDhcpOptions  
&Filter.1.Name=key  
&Filter.1.Value.1=domain-name  
&Filter.2.Name=value  
&Filter.2.Value.1=*example*  
&AUTHPARAMS
```

Related Operations

- [CreateDhcpOptions](#) (p. 55)
- [AssociateDhcpOptions](#) (p. 21)
- [DeleteDhcpOptions](#) (p. 107)

DescribeExportTasks

Description

Describes your export tasks. If no export task IDs are specified, all export tasks initiated by you are returned.

Request Parameters

| Name | Description | Required |
|-----------------------|---|----------|
| <i>ExportTaskId.n</i> | One or more export task IDs. If no task IDs are provided, all active export tasks are described. Type: String Default: None | No |

Response Elements

The elements in the following table are wrapped in a `DescribeExportTasks` structure.

| Name | Description |
|----------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>exportTaskSet</code> | A list of export tasks, each one wrapped in an item element. Type: ExportTaskResponseType (p. 426) |

Examples

Example Request

This example describes a single export task.

```
https://ec2.amazonaws.com/?Action=DescribeExportTasks
&exportTaskId.1=export-i-1234wxyz
&AUTHPARAMS
```

Example Response

```
<DescribeExportTasksResponse xmlns="http://ec2.amazonaws.com/doc/2020-02-02/">
<requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
<exportTaskSet>
  <item>
    <exportTaskId>export-i-1234wxyz</exportTaskId>
    <description>Example for docs</description>
    <state>active</state>
```

```
<statusMessage>Running</statusMessage>
<instanceExport>
<instanceId>i-12345678</instanceId>
<targetEnvironment>VMWare</targetEnvironment>
</instanceExport>
<exportToS3>
<diskImageFormat>VMDK</diskImageFormat>
<containerFormat>OVA</containerFormat>
<s3Bucket>my-bucket-for-exported-vm</s3Bucket>
<s3Key>my-exports/ export-i-1234wxyz .ova</s3Key>
</exportToS3>
</item>
</exportTaskSet>
</ DescribeExportTasksResponse>
```

Related Operations

- [CancelExportTask](#) (p. 47)
- [CreateInstanceExportTask](#) (p. 60)

DescribeImageAttribute

Description

Gets information about an attribute of an AMI. You can get information about only one attribute per call. These are the available attributes:

- **description**—Description of the AMI provided at image creation
- **kernel**—ID of the kernel associated with the AMI
- **ramdisk**—ID of the RAM disk associated with the AMI
- **launchPermission**—Launch permissions for the AMI
- **productCodes**—Product codes associated with the AMI (if any). Each product code contains a product code and a type.
- **blockDeviceMapping**—Block device mapping of the AMI

Request Parameters

| Name | Description | Required |
|------------------|---|----------|
| <i>ImageId</i> | The ID of the AMI. Type: String Default: None | Yes |
| <i>Attribute</i> | The AMI attribute. Type: String Default: None Valid values: <code>description kernel ramdisk launchPermission productCodes blockDeviceMapping</code> | Yes |

Response Elements

The elements in the following table are wrapped in a `DescribeImageAttributeResponse` structure.

| Name | Description |
|-------------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>imageId</code> | The ID of the AMI. Type: <code>xsd:string</code> |
| <code>launchPermission</code> | A list of launch permissions, each one wrapped in an <code>item</code> element. Type: LaunchPermissionItemType (p. 446) |
| <code>productCodes</code> | A list of product codes, each one wrapped in an <code>item</code> element that contains a product code and a product code type. Type: ProductCodeItemType (p. 460) |

| Name | Description |
|--------------------|--|
| kernel | The kernel ID, wrapped in a <code>value</code> element. Type: <code>xsd:string</code> |
| ramdisk | The RAM disk ID, wrapped in a <code>value</code> element. Type: <code>xsd:string</code> |
| description | A user-created description of the AMI, wrapped in a <code>value</code> element. Type: <code>xsd:string</code> |
| blockDeviceMapping | One or more block device mapping entries, each one wrapped in an <code>item</code> element. Type: BlockDeviceMappingItemType (p. 406) |

Examples

Example Request

This example lists the launch permissions for the ami-61a54008 AMI

```
https://ec2.amazonaws.com/?Action=DescribeImageAttribute
&ImageId=ami-61a54008
&Attribute=launchPermission
&AUTHPARAMS
```

Example Response

```
<DescribeImageAttributeResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <imageId>ami-61a54008</imageId>
  <launchPermission>
    <item>
      <group>all</group>
    </item>
    <item>
      <userId>495219933132</userId>
    </item>
  </launchPermission>
</DescribeImageAttributeResponse>
```

Example Request

This example lists the product code for the ami-2bb65342 AMI.

```
https://ec2.amazonaws.com/?Action=DescribeImageAttribute
&ImageId=ami-2bb65342
&Attribute=productCodes
&AUTHPARAMS
```

Example Response

```
<DescribeImageAttributeResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <imageId>ami-2bb65342</imageId>
  <productCodes>
    <item>
      <productCode>a1b2c3d4e5f6g7h8i9j10k11</productCode>
      <type>marketplace</type>
    </item>
  </productCodes>
</DescribeImageAttributeResponse>
```

Related Operations

- [DescribeImages](#) (p. 170)
- [ModifyImageAttribute](#) (p. 321)
- [ResetImageAttribute](#) (p. 365)

DescribelImages

Description

Returns information about AMIs, AKIs, and ARIs. Images available to you include public images, private images that you own, and private images owned by other AWS accounts but for which you have explicit launch permissions.

Launch permissions fall into three categories:

| Launch Permission | Description |
|-------------------|---|
| public | The owner of the AMI granted launch permissions for the AMI to the <code>all</code> group. All AWS accounts have launch permissions for these AMIs. |
| explicit | The owner of the AMI granted launch permissions to a specific AWS account. |
| implicit | An AWS account has implicit launch permissions for all the AMIs it owns. |

The list of AMIs returned can be modified by specifying AMI IDs, AMI owners, or AWS accounts with launch permissions. If no options are specified, Amazon EC2 returns all AMIs for which you have launch permissions.

If you specify one or more AMI IDs, only AMIs that have the specified IDs are returned. If you specify an invalid AMI ID, an error is returned. If you specify an AMI ID for which you do not have access, it will not be included in the returned results.

If you specify one or more AMI owners, only AMIs from the specified owners and for which you have access are returned. The results can include the account IDs of the specified owners—`amazon` for AMIs owned by Amazon or `self`, for AMIs that you own, or `marketplace` for AMIs from the AWS Marketplace.

Note

For an overview of the AWS Marketplace, go to <https://aws.amazon.com/marketplace/help/200900000>. For details on how to use the AWS Marketplace, see [AWS Marketplace](#).

If you specify a list users with launch permissions, only AMIs with launch permissions for those users are returned. You can specify account IDs (if you own the AMI(s)), `self` for AMIs for which you own or have explicit permissions, or `all` for public AMIs.

Note

Deregistered images are included in the returned results for an unspecified interval after deregistration.

You can filter the results to return information only about images that match criteria you specify. For example, you could get information only about images that use a certain kernel. You can specify multiple values for a filter (e.g., the image uses either kernel `aki-1a2b3c4d` or kernel `aki-9b8c7d6f`). An image must match at least one of the specified values for it to be included in the results.

You can specify multiple filters (e.g., the image uses a certain kernel, and uses an Amazon EBS volume as the root device). The result includes information for a particular image only if it matches *all* your filters. If there's no match, no special message is returned; the response is simply empty.

Amazon Elastic Compute Cloud API Reference Description

You can use wildcards with the filter values: * matches zero or more characters, and ? matches exactly one character. You can escape special characters using a backslash before the character. For example, a value of `*amazon\?\` searches for the literal string `*amazon?\`.

The following table shows the available filters.

| Filter Name | Description |
|---|--|
| <code>architecture</code> | The image architecture. Type: String Valid Values: <code>i386</code> <code>x86_64</code> |
| <code>block-device-mapping.delete-on-termination</code> | Whether the Amazon EBS volume is deleted on instance termination. Type: Boolean |
| <code>block-device-mapping.device-name</code> | The device name (e.g., <code>/dev/sdh</code>) for an Amazon EBS volume mapped to the image. Type: String |
| <code>block-device-mapping.snapshot-id</code> | The snapshot ID for an Amazon EBS volume mapped to the image. Type: String |
| <code>block-device-mapping.volume-size</code> | The volume size for an Amazon EBS volume mapped to the image. Type: Integer |
| <code>description</code> | The description of the AMI (provided during image creation). Type: String |
| <code>image-id</code> | The ID of the image. Type: String |
| <code>image-type</code> | The image type. Type: String Valid Values: <code>machine</code> <code>kernel</code> <code>ramdisk</code> |
| <code>is-public</code> | Indicates whether the image is public. Type: Boolean |
| <code>kernel-id</code> | The kernel ID. Type: String |
| <code>manifest-location</code> | The location of the image manifest. Type: String |
| <code>name</code> | The name of the AMI (provided during image creation). Type: String |
| <code>owner-alias</code> | The AWS account alias (e.g., <code>amazon</code>) Type: String |

Amazon Elastic Compute Cloud API Reference
Description

| Filter Name | Description |
|----------------------|--|
| owner-id | The AWS account ID of the image owner. Type: String |
| platform | The platform. To only list Windows-based AMIs, use <code>windows</code> . Otherwise, leave blank. Type: String Valid value: <code>windows</code> |
| product-code | The product code associated with the AMI. Type: String |
| product-code.type | The type of AMI product code. Type: String Valid values: <code>devpay</code> <code>marketplace</code> |
| ramdisk-id | The RAM disk ID. Type: String |
| root-device-name | The root device name of the AMI (e.g., <code>/dev/sda1</code>). Type: String |
| root-device-type | The root device type that the AMI uses. Type: String Valid values: <code>ebs</code> <code>instance-store</code> |
| state | The state of the image. Type: String Valid values: <code>available</code> <code>pending</code> <code>failed</code> |
| state-reason-code | The reason code for the state change. Type: String |
| state-reason-message | The message for the state change. Type: String |
| tag-key | The key of a tag assigned to the resource. This filter is independent of the <code>tag-value</code> filter. For example, if you use both the filter <code>tag-key=Purpose</code> and the filter <code>tag-value=X</code> , you get any resources assigned both the tag key <code>Purpose</code> (regardless of what the tag's value is), and the tag value <code>X</code> (regardless of what the tag's key is). If you want to list only resources where <code>Purpose=X</code> , see the <code>tag:key</code> filter later in this table. For more information about tags, see Using Tags in the <i>Amazon Elastic Compute Cloud User Guide</i> . Type: String |
| tag-value | The value of a tag assigned to the resource. This filter is independent of the <code>tag-key</code> filter. Type: String |

| Filter Name | Description |
|----------------------------------|--|
| <code>tag:<i>key</i></code> | Filters the results based on a specific tag/value combination. Example: To list just the resources assigned tag Purpose=X, then specify: <code>Filter.1.Name=tag:Purpose</code> <code>Filter.1.Value.1=X</code> Example: To list just resources assigned tag Purpose=X OR Purpose=Y, then specify: <code>Filter.1.Name=tag:Purpose</code> <code>Filter.1.Value.1=X</code> <code>Filter.1.Value.2=Y</code> |
| <code>virtualization-type</code> | The virtualization type of the image. Type: String Valid values: <code>paravirtual</code> <code>hvm</code> |
| <code>hypervisor</code> | The hypervisor type of the image. Type: String Valid values: <code>ovm</code> <code>xen</code> |

Request Parameters

| Name | Description | Required |
|-----------------------------|--|----------|
| <code>ExecutableBy.n</code> | The AMIs for which the specified user ID has explicit launch permissions. The user ID can be an AWS account ID, <code>self</code> to return AMIs for which the sender of the request has explicit launch permissions, or <code>all</code> to return AMIs with public launch permissions. Type: String Default: None | No |
| <code>ImageId.n</code> | One or more AMI IDs. Type: String Default: Returns all AMIs, or only those otherwise specified. | No |
| <code>Owner.n</code> | The AMIs owned by the specified owner. Multiple owner values can be specified. The IDs <code>amazon</code> , <code>aws-marketplace</code> , and <code>self</code> can be used to include AMIs owned by Amazon, AWS Marketplace, or AMIs owned by you, respectively. Type: String Default: None Valid values: <code>amazon</code> <code>aws-marketplace</code> <code>self</code> AWS account ID <code>all</code> | No |

| Name | Description | Required |
|-------------------------|--|----------|
| <i>Filter.n.Name</i> | The name of a filter. See the preceding table for a list of allowed filter names. Type: String Default: None | No |
| <i>Filter.n.Value.m</i> | A value for the filter. See the preceding table for a list of allowed values for each filter. Type: String Default: None | No |

Response Elements

The elements in the following table are wrapped in a `DescribeImagesResponse` structure.

| Name | Description |
|------------------------|--|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>imagesSet</code> | A list of images, each one wrapped in an <code>item</code> element. Type: DescribeImagesResponseItemType (p. 414) |

Examples

Example Request

This example describes the `ami-be3adfd7` AMI.

```
https://ec2.amazonaws.com/?Action=DescribeImages
&ImageId.1=ami-be3adfd7
&AUTHPARAMS
```

Example Response

```
<DescribeImagesResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <imagesSet>
    <item>
      <imageId>ami-be3adfd7</imageId>
      <imageLocation>amazon/getting-started</imageLocation>
      <imageState>available</imageState>
      <imageOwnerId>206029621532</imageOwnerId>
      <isPublic>true</isPublic>
      <architecture>i386</architecture>
      <imageType>machine</imageType>
      <kernelId>aki-d3376696</kernelId>
      <ramdiskId>ari-e73766a2</ramdiskId>
      <imageOwnerAlias>amazon</imageOwnerAlias>
    </item>
  </imagesSet>
</DescribeImagesResponse>
```

```
<name>getting-started</name>
<description>Fedora 8 v1.11 i386 lvm-rootVG-rootFS ext3 ec2pnp enabled</de
scription>
<rootDeviceType>ebs</rootDeviceType>
<rootDeviceName>/dev/sda</rootDeviceName>
<blockDeviceMapping>
  <item>
    <deviceName>/dev/sda</deviceName>
    <ebs>
      <snapshotId>snap-32885f5a</snapshotId>
      <volumeSize>15</volumeSize>
      <deleteOnTermination>>false</deleteOnTermination>
    </ebs>
  </item>
</blockDeviceMapping>
<virtualizationType>paravirtual</virtualizationType>
<tagSet/>
<hypervisor>xen</hypervisor>
</item>
</imagesSet>
</DescribeImagesResponse>
```

Example Request

This example filters the results to display only the public Windows images with an x86_64 architecture.

```
https://ec2.amazonaws.com/?Action=DescribeImages
&Filter.1.Name=is-public
&Filter.1.Value.1=true
&Filter.2.Name=architecture
&Filter.2.Value.1=x86_64
&Filter.3.Name=platform
&Filter.3.Value.1=windows
&AUTHPARAMS
```

Example Response

```
<DescribeImagesResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <imagesSet>
    <item>
      <imageId>ami-dd20c3b4</imageId>
      <imageLocation>ec2-public-windows-images/Server2003r2-x86_64-Win-
v1.07.manifest.xml</imageLocation>
      <imageState>available</imageState>
      <imageOwnerId>206029621532</imageOwnerId>
      <isPublic>>true</isPublic>
      <architecture>x86_64</architecture>
      <imageType>machine</imageType>
      <platform>windows</platform>
      <imageOwnerAlias>amazon</imageOwnerAlias>
      <rootDeviceType>instance-store</rootDeviceType>
      <blockDeviceMapping/>
      <virtualizationType>hvm</virtualizationType>
      <tagSet/>
    </item>
  </imagesSet>
</DescribeImagesResponse>
```

```
        <hypervisor>xen</hypervisor>
    </item>
    ...
</imagesSet>
</DescribeImagesResponse>
```

Example Request

This example retruns the results to display images where the owner is aws-marketplace.

```
https://ec2.amazonaws.com/?Action=DescribeImages
&Owner.0=aws-marketplace
&AUTHPARAMS
```

Example Response

```
<DescribeImagesResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>4a4a27a2-2e7c-475d-b35b-ca822EXAMPLE</requestId>
  <imagesSet>
    <item>
      <imageId>ami-a2469acf</imageId>
      <imageLocation>aws-marketplace/example-marketplace-amzn-ami.1</imageLocation>
      <imageState>available</imageState>
      <imageOwnerId>123456789999</imageOwnerId>
      <isPublic>true</isPublic>
      <productCodes>
        <item>
          <productCode>alb2c3d4e5f6g7h8i9j10k11</productCode>
          <type>marketplace</type>
        </item>
      </productCodes>
      <architecture>i386</architecture>
      <imageType>machine</imageType>
      <kernelId>aki-805ea7e9</kernelId>
      <imageOwnerAlias>aws-marketplace</imageOwnerAlias>
      <name>example-marketplace-amzn-ami.1</name>
      <description>Amazon Linux AMI i386 EBS</description>
      <rootDeviceType>ebs</rootDeviceType>
      <rootDeviceName>/dev/sda1</rootDeviceName>
      <blockDeviceMapping>
        <item>
          <deviceName>/dev/sda1</deviceName>
          <ebs>
            <snapshotId>snap-787e9403</snapshotId>
            <volumeSize>8</volumeSize>
            <deleteOnTermination>true</deleteOnTermination>
          </ebs>
        </item>
      </blockDeviceMapping>
      <virtualizationType>paravirtual</virtualizationType>
      <hypervisor>xen</hypervisor>
    </item>
    ...
  </imagesSet>
</DescribeImagesResponse>
```

```
</imagesSet>  
</DescribeImagesResponse>
```

Related Operations

- [DescribeInstances](#) (p. 181)
- [DescribeImageAttribute](#) (p. 167)

DescribeInstanceAttribute

Description

Returns information about an attribute of an instance. You can get information about only one attribute per call. These are the available attributes:

- **instanceType**—Instance type (e.g., m1.small)
- **kernel**—ID of the kernel associated with the instance
- **ramdisk**—ID of the RAM disk associated with the instance
- **userData**—MIME, Base64-encoded user data provided to the instance
- **disableApiTermination**—Whether the instance can be terminated using the Amazon EC2 API (`false` means the instance can be terminated with the API)
- **instanceInitiatedShutdownBehavior**—Whether the instance stops or terminates when an instance shutdown is initiated (default is stop)
- **productCodes**—Product codes associated with the instance. Each product code contains a product code and a type.
- **blockDeviceMapping**—Block device mapping of the instance
- **sourceDestCheck**—This attribute exists to enable a Network Address Translation (NAT) instance in a VPC to perform NAT. The attribute controls whether source/destination checking is enabled on the instance. A value of `true` means checking is enabled. The value must be `false` for the instance to perform NAT.
- **groupSet**—Security groups the instance belongs to

Request Parameters

| Name | Description | Required |
|-------------------|---|----------|
| <i>InstanceId</i> | The instance ID. Type: String Default: None | Yes |
| <i>Attribute</i> | The instance attribute. Type: String Default: None Valid values: <code>instanceType</code> <code>kernel</code> <code>ramdisk</code> <code>userData</code> <code>disableApiTermination</code> <code>instanceInitiatedShutdownBehavior</code> <code>rootDeviceName</code> <code>blockDeviceMapping</code> <code>productCodes</code> <code>sourceDestCheck</code> <code>groupSet</code> | Yes |

Response Elements

The elements in the following table are wrapped in a `DescribeInstanceAttributeResponse` structure.

Amazon Elastic Compute Cloud API Reference
Response Elements

| Name | Description |
|--|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>instanceId</code> | The ID of the instance. Type: <code>xsd:string</code> |
| <code>instanceType</code> | The instance type (for example, <code>m1.small</code>), wrapped in a <code>value</code> element. Type: <code>xsd:string</code> |
| <code>kernel</code> | The kernel ID, wrapped in a <code>value</code> element. Type: <code>xsd:string</code> |
| <code>ramdisk</code> | The RAM disk ID, wrapped in a <code>value</code> element. Type: <code>xsd:string</code> |
| <code>userData</code> | MIME, Base64-encoded user data, wrapped in a <code>value</code> element. Type: <code>xsd:string</code> |
| <code>disableApiTermination</code> | Indicates whether the instance can be terminated through the Amazon EC2 API. The value is wrapped in a <code>value</code> element. A value of <code>true</code> means you can't terminate the instance using the API (i.e., the instance is "locked"); a value of <code>false</code> means you can. You must modify this attribute before you can terminate any "locked" instances using the API. Type: <code>xsd:boolean</code> |
| <code>instanceInitiatedShutdownBehavior</code> | If an instance shutdown is initiated, this determines whether the instance stops or terminates. The value is wrapped in a <code>value</code> element. Type: <code>xsd:string</code> Valid values: <code>stop</code> <code>terminate</code> |
| <code>rootDeviceName</code> | The name of the root device (for example, <code>/dev/sda1</code>), wrapped in a <code>value</code> element. Type: <code>xsd:string</code> |
| <code>blockDeviceMapping</code> | Any block device mapping entries for the instance, each one wrapped in an <code>item</code> element. Type: InstanceBlockDeviceMappingResponseItemType (p. 434) |
| <code>sourceDestCheck</code> | This attribute exists to enable a Network Address Translation (NAT) instance in a VPC to perform NAT. The attribute controls whether source/destination checking is enabled on the instance. A value of <code>true</code> means checking is enabled, and <code>false</code> means checking is disabled. The value must be <code>false</code> for the instance to perform NAT. For more information, see NAT Instances in the <i>Amazon Virtual Private Cloud User Guide</i> . Type: <code>xsd:boolean</code> |
| <code>groupSet</code> | The security groups the instance belongs to. Each group's information is wrapped in an <code>item</code> element. Type: GroupItemType (p. 428) |

| Name | Description |
|--------------|--|
| productCodes | A list of product codes, each one wrapped in an item element that contains a product code and a product code type. Type: ProductCodesSetItemType (p. 461) |

Examples

Example Request

This example lists the kernel ID of the i-10a64379 instance.

```
https://ec2.amazonaws.com/?Action=DescribeInstanceAttribute
&InstanceId=i-10a64379
&Attribute=kernel
&AUTHPARAMS
```

Example Response

```
<DescribeInstanceAttributeResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <instanceId>i-10a64379</instanceId>
  <kernel>
    <value>aki-f70657b2</value>
  </kernel>
</DescribeInstanceAttributeResponse>
```

Related Operations

- [DescribeInstances](#) (p. 181)
- [ModifyInstanceAttribute](#) (p. 324)
- [ResetInstanceAttribute](#) (p. 367)

DescribeInstances

Description

Returns information about instances that you own.

If you specify one or more instance IDs, Amazon EC2 returns information for those instances. If you do not specify instance IDs, Amazon EC2 returns information for all relevant instances. If you specify an invalid instance ID, an error is returned. If you specify an instance that you do not own, it is not included in the returned results.

Recently terminated instances might appear in the returned results. This interval is usually less than one hour.

You can filter the results to return information only about instances that match criteria you specify. For example, you could get information about only instances launched with a certain key pair. You can specify multiple values for a filter (e.g., the instance was launched with either key pair A or key pair B). An instance must match at least one of the specified values for it to be included in the results.

You can specify multiple filters (e.g., the instance was launched with a certain key pair and uses an Amazon EBS volume as the root device). An instance must match *all* the filters for it to be included in the results. If there's no match, no special message is returned; the response is simply empty.

You can use wildcards with the filter values: * matches zero or more characters, and ? matches exactly one character. You can escape special characters using a backslash before the character. For example, a value of `*amazon\?\` searches for the literal string `*amazon?\`.

The following table shows the available filters.

| Filter Name | Description |
|---|---|
| <code>architecture</code> | The instance architecture. Type: String Valid values: <code>i386</code> <code>x86_64</code> |
| <code>availability-zone</code> | The Availability Zone of the instance. Type: String |
| <code>block-device-mapping.attach-time</code> | The attach time for an Amazon EBS volume mapped to the instance, e.g., <code>2010-09-15T17:15:20.000Z</code> Type: <code>xsd:dateTime</code> |
| <code>block-device-mapping.delete-on-termination</code> | Indicates whether the Amazon EBS volume is deleted on instance termination. Type: Boolean |
| <code>block-device-mapping.device-name</code> | The device name (for example, <code>/dev/sdh</code>) for an Amazon EBS volume mapped to the instance. Type: String |

**Amazon Elastic Compute Cloud API Reference
Description**

| Filter Name | Description |
|---|---|
| <code>block-device-mapping.status</code> | The status for an Amazon EBS volume mapped to the instance. Type: String Valid values: <code>attaching</code> <code>attached</code> <code>detaching</code> <code>detached</code> |
| <code>block-device-mapping.volume-id</code> | The ID of an Amazon EBS volume mapped to the instance. Type: String |
| <code>client-token</code> | The idempotency token you provided when you launched the instance. Type: String |
| <code>dns-name</code> | The public DNS name of the instance. Type: String |
| <code>group-id</code> | The ID of a EC2 security group the instance is in. This filter does not work for VPC security groups (instead, use <code>instance.group-id</code>). Type: String |
| <code>group-name</code> | The name of a EC2 security group the instance is in. This filter does not work for VPC security groups (instead, use <code>instance.group-name</code>). Type: String |
| <code>image-id</code> | The ID of the image used to launch the instance. Type: String |
| <code>instance-id</code> | The ID of the instance. Type: String |
| <code>instance-lifecycle</code> | Indicates whether this is a Spot Instance. Type: String Valid values: <code>spot</code> |
| <code>instance-state-code</code> | A code representing the state of the instance. The high byte is an opaque internal value and should be ignored. The low byte is set based on the state represented Type: Integer (16-bit unsigned integer) Valid values: 0 (pending) 16 (running) 32 (shutting-down) 48 (terminated) 64 (stopping) 80 (stopped) |
| <code>instance-state-name</code> | The state of the instance. Type: String Valid values: <code>pending</code> <code>running</code> <code>shutting-down</code> <code>terminated</code> <code>stopping</code> <code>stopped</code> |

**Amazon Elastic Compute Cloud API Reference
Description**

| Filter Name | Description |
|-----------------------------------|---|
| <code>instance-type</code> | The type of instance (for example, m1.small). Type: String |
| <code>instance.group-id</code> | The ID of a VPC security group the instance is in. This filter does not work for EC2 security groups (instead, use <code>group-id</code>). Type: String |
| <code>instance.group-name</code> | The name of a VPC security group the instance is in. This filter does not work for EC2 security groups (instead, use <code>group-name</code>). Type: String |
| <code>ip-address</code> | The public IP address of the instance. Type: String |
| <code>kernel-id</code> | The kernel ID. Type: String |
| <code>key-name</code> | The name of the key pair used when the instance was launched. Type: String |
| <code>launch-index</code> | When launching multiple instances, this is the index for the instance in the launch group (e.g., 0, 1, 2, etc.). Type: String |
| <code>launch-time</code> | The time the instance was launched, e.g., 2010-08-07T11:54:42.000Z. Type: xsd:dateTime |
| <code>monitoring-state</code> | Indicates whether monitoring is enabled for the instance. Type: String Valid values: <code>disabled</code> <code>enabled</code> |
| <code>owner-id</code> | The AWS account ID of the instance owner. Type: String |
| <code>placement-group-name</code> | The name of the placement group the instance is in. Type: String |
| <code>platform</code> | The platform. Use <code>windows</code> if you have Windows based instances; otherwise, leave blank. Type: String Valid value: <code>windows</code> |
| <code>private-dns-name</code> | The private DNS name of the instance. Type: String |

Amazon Elastic Compute Cloud API Reference
Description

| Filter Name | Description |
|---------------------------------|---|
| <code>private-ip-address</code> | The private IP address of the instance. Type: String |
| <code>product-code</code> | The product code associated with the AMI used to launch the instance. Type: String |
| <code>product-code.type</code> | The type of product code. Type: String Valid values: <code>devpay</code> <code>marketplace</code> |
| <code>ramdisk-id</code> | The RAM disk ID. Type: String |
| <code>reason</code> | The reason for the current state of the instance (e.g., shows "User Initiated [date]" when you stop or terminate the instance). Similar to the <code>state-reason-code</code> filter. Type: String |
| <code>requester-id</code> | The ID of the entity that launched the instance on your behalf (e.g., AWS Management Console, Auto Scaling, etc.) Type: String |
| <code>reservation-id</code> | The ID of the instance's reservation. A reservation ID is created any time you launch an instance. A reservation ID has a one-to-one relationship with an instance launch request, but can be associated with more than one instance if you launch multiple instances using the same launch request. For example, if you launch one instance, you'll get one reservation ID. If you launch ten instances using the same launch request, you'll also get one reservation ID. Type: String |
| <code>root-device-name</code> | The name of the root device for the instance (e.g., <code>/dev/sda1</code>). Type: String |
| <code>root-device-type</code> | The type of root device the instance uses. Type: String Valid values: <code>ebs</code> <code>instance-store</code> |
| <code>source-dest-check</code> | Indicates whether the instance performs source/destination checking. A value of <code>true</code> means checking is enabled, and <code>false</code> means checking is disabled. The value must be <code>false</code> for the instance to perform Network Address Translation (NAT) in your VPC. Type: Boolean |

**Amazon Elastic Compute Cloud API Reference
Description**

| Filter Name | Description |
|--------------------------|--|
| spot-instance-request-id | The ID of the Spot Instance request. Type: String |
| state-reason-code | The reason code for the state change. Type: String |
| state-reason-message | A message that describes the state change. Type: String |
| subnet-id | The ID of the subnet the instance is in (if using Amazon Virtual Private Cloud). Type: String |
| tag-key | The key of a tag assigned to the resource. This filter is independent of the <code>tag-value</code> filter. For example, if you use both the filter <code>tag-key=Purpose</code> and the filter <code>tag-value=X</code> , you get any resources assigned both the tag key <code>Purpose</code> (regardless of what the tag's value is), and the tag value <code>X</code> (regardless of what the tag's key is). If you want to list only resources where <code>Purpose=X</code> , see the <code>tag:key</code> filter later in this table. For more information about tags, see Using Tags in the <i>Amazon Elastic Compute Cloud User Guide</i> . Type: String |
| tag-value | The value of a tag assigned to the resource. This filter is independent of the <code>tag-key</code> filter. Type: String |
| tag: <i>key</i> | Filters the results based on a specific tag/value combination. Example: To list just the resources assigned tag <code>Purpose=X</code> , then specify: <code>Filter.1.Name=tag:Purpose</code> <code>Filter.1.Value.1=X</code> Example: To list just resources assigned tag <code>Purpose=X</code> OR <code>Purpose=Y</code> , then specify: <code>Filter.1.Name=tag:Purpose</code> <code>Filter.1.Value.1=X</code> <code>Filter.1.Value.2=Y</code> |
| virtualization-type | The virtualization type of the instance. Type: String Valid values: <code>paravirtual</code> <code>hvm</code> |
| vpc-id | The ID of the VPC the instance is in (if using Amazon Virtual Private Cloud). Type: String |

Amazon Elastic Compute Cloud API Reference
Description

| Filter Name | Description |
|--|--|
| hypervisor | The hypervisor type of the instance. Type: String Valid values: ovm xen |
| network-interface.description | The description of the network interface (available only in Amazon Virtual Private Cloud). Type: String |
| network-interface.subnet-id | The ID of the subnet of the network interface (available only in Amazon Virtual Private Cloud). Type: String |
| network-interface.vpc-id | The ID of the Amazon VPC of the network interface. (available only in Amazon Virtual Private Cloud). Type: String |
| network-interface.network-interface-id | The ID of the network interface (available only in Amazon Virtual Private Cloud). Type: String |
| network-interface.owner-id | The ID of the owner of the network interface (available only in Amazon Virtual Private Cloud). Type: String |
| network-interface.availability-zone | The availability zone of the network interface (available only in Amazon Virtual Private Cloud). Type: String |
| network-interface.requester-id | The requester ID of the network interface (available only in Amazon Virtual Private Cloud). Type: String |
| network-interface.requester-managed | Indicates whether the network interface is being managed by an AWS service (e.g., AWSManagement Console, Auto Scaling, etc). This filter is available only in Amazon Virtual Private Cloud. Type: Boolean |
| network-interface.status | The status of the network interface (available only in Amazon Virtual Private Cloud). Type: String Valid Values: available in-use |
| network-interface.mac-address | The MAC address of the network interface (available only in Amazon Virtual Private Cloud). Type: String Valid Values: available in-use |
| network-interface-private-dns-name | The private DNS name of the network interface (available only in Amazon Virtual Private Cloud). Type: String |

**Amazon Elastic Compute Cloud API Reference
Description**

| Filter Name | Description |
|---|--|
| <code>network-interface.source-destination-check</code> | Whether the network interface performs source/destination checking. A value of true means checking is enabled, and false means checking is disabled. The value must be false for the network interface to perform Network Address Translation (NAT) in your VPC (available only in Amazon Virtual Private Cloud). Type: Boolean |
| <code>network-interface.group-id</code> | The ID of a VPC security group associated with the network interface (available only in Amazon Virtual Private Cloud). Type: String |
| <code>network-interface.group-name</code> | The name of a VPC security group associated with the network interface (available only in Amazon Virtual Private Cloud). Type: String |
| <code>network-interface.attachment.attachment-id</code> | The ID of the interface attachment (available only in Amazon Virtual Private Cloud). Type: String |
| <code>network-interface.attachment.instance-id</code> | The ID of the instance to which the network interface is attached (available only in Amazon Virtual Private Cloud). Type: String |
| <code>network-interface.attachment.instance-owner-id</code> | The owner ID of the instance to which the network interface is attached (available only in Amazon Virtual Private Cloud). Type: String |
| <code>network-interface.addresses.private-ip-address</code> | The private IP address associated with the network interface (available only in Amazon Virtual Private Cloud). Type: String |
| <code>network-interface.attachment.device-index</code> | The device index to which the network interface is attached (available only in Amazon Virtual Private Cloud). Type: Integer |
| <code>network-interface.attachment.status</code> | The status of the attachment. (available only in Amazon Virtual Private Cloud). Type: String Valid values: attaching attached detaching detached |
| <code>network-interface.attachment.attach-time</code> | The time that the network interface was attached to an instance (available only in Amazon Virtual Private Cloud). Type: Date |

| Filter Name | Description |
|--|--|
| <code>network-interface.attachment.delete-on-termination</code> | Specifies whether the attachment is deleted when an instance is terminated (available only in Amazon Virtual Private Cloud). Type: Boolean |
| <code>network-interface.addresses.primary</code> | Specifies whether the IP address of the network interface is the primary private IP address (available only in Amazon Virtual Private Cloud). Type: Boolean |
| <code>network-interface.addresses.association.public-ip</code> | The ID representing the association of a VPC Elastic IP address with a network interface in a VPC (available only in Amazon Virtual Private Cloud). Type: String |
| <code>network-interface.addresses.association.ip-owner-id</code> | The owner ID of the private IP address associated with the network interface (available only in Amazon Virtual Private Cloud). Type: String |
| <code>association.public-ip</code> | The address of the Elastic IP address bound to the network interface (available only in Amazon Virtual Private Cloud). Type: String |
| <code>association.ip-owner-id</code> | The owner of the Elastic IP address associated with the network interface (available only in Amazon Virtual Private Cloud). Type: String |
| <code>association.allocation-id</code> | The allocation ID that AWS returned when you allocated the Elastic IP address for your network interface (available only in Amazon Virtual Private Cloud). Type: String |
| <code>association.association-id</code> | The association ID returned when the network interface was associated with an IP address (available only in Amazon Virtual Private Cloud). Type: String |

Request Parameters

| Name | Description | Required |
|---------------------------|---|----------|
| <code>InstanceId.n</code> | One or more instance IDs. Type: String Default: Returns all instances, or only those otherwise specified. | No |

| Name | Description | Required |
|-------------------------|--|----------|
| <i>Filter.n.Name</i> | The name of a filter. See the preceding table for a list of allowed filter names. Type: String Default: None | No |
| <i>Filter.n.Value.m</i> | A value for the filter. See the preceding table for a list of allowed values for each filter. Type: String Default: None | No |

Response Elements

The elements in the following table are wrapped in a `DescribeInstancesResponse` structure.

| Name | Description |
|-----------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>reservationSet</code> | A list of reservations, each one wrapped in an <code>item</code> element. Type: ReservationInfoType (p. 463) |

Examples

Example Request

This example describes the current state of the instances owned by your AWS account.

```
https://ec2.amazonaws.com/?Action=DescribeInstances
&AUTHPARAMS
```

Example Response

```
<DescribeInstancesResponse xmlns='http://ec2.amazonaws.com/doc/2012-06-15/' >
  <requestId>fdcdcab1-ae5c-489e-9c33-4637c5dda355</requestId>
  <reservationSet>
    <item>
      <reservationId>r-0ece705a</reservationId>
      <ownerId>053230519467</ownerId>
      <groupSet/>
      <instancesSet>
        <item>
          <instanceId>i-7a00642e</instanceId>
          <imageId>ami-1cd4924e</imageId>
          <instanceState>
            <code>16</code>
            <name>running</name>
          </instanceState>
        </item>
      </instancesSet>
    </item>
  </reservationSet>
</DescribeInstancesResponse>
```

```
<privateDnsName/>
<dnsName/>
<reason/>
<keyName>VPCKey</keyName>
<amiLaunchIndex>0</amiLaunchIndex>
<productCodes/>
<instanceType>c1.medium</instanceType>
<launchTime>2012-06-28T17:41:48.000Z</launchTime>
<placement>
  <availabilityZone>ap-southeast-1b</availabilityZone>
  <groupName/>
  <tenancy>default</tenancy>
</placement>
<platform>windows</platform>
<monitoring>
  <state>disabled</state>
</monitoring>
<subnetId>subnet-c53c87ac</subnetId>
<vpcId>vpc-cc3c87a5</vpcId>
<privateIpAddress>10.0.0.12</privateIpAddress>
<ipAddress>46.51.219.63</ipAddress>
<sourceDestCheck>>true</sourceDestCheck>
<groupSet>
  <item>
    <groupId>sg-374b565b</groupId>
    <groupName>quick-start-3</groupName>
  </item>
</groupSet>
<architecture>x86_64</architecture>
<rootDeviceType>ebs</rootDeviceType>
<rootDeviceName>/dev/sda1</rootDeviceName>
<blockDeviceMapping>
  <item>
    <deviceName>/dev/sda1</deviceName>
    <ebs>
      <volumeId>vol-9e151bfc</volumeId>
      <status>attached</status>
      <attachTime>2012-06-28T17:42:05.000Z</attachTime>
      <deleteOnTermination>>true</deleteOnTermination>
    </ebs>
  </item>
</blockDeviceMapping>
<virtualizationType>hvm</virtualizationType>
<clientToken>JNlxa1340905307390</clientToken>
<tagSet>
  <item>
    <key>Name</key>
    <value>SingleENI</value>
  </item>
</tagSet>
<hypervisor>xen</hypervisor>
<networkInterfaceSet>
  <item>
    <networkInterfaceId>eni-d83388b1</networkInterfaceId>
    <subnetId>subnet-c53c87ac</subnetId>
    <vpcId>vpc-cc3c87a5</vpcId>
    <description>Primary network interface</description>
    <ownerId>053230519467</ownerId>
```

```
<status>in-use</status>
<privateIpAddress>10.0.0.12</privateIpAddress>
<sourceDestCheck>true</sourceDestCheck>
<groupSet>
  <item>
    <groupId>sg-374b565b</groupId>
    <groupName>quick-start-3</groupName>
  </item>
</groupSet>
<attachment>
  <attachmentId>eni-attach-31b87358</attachmentId>
  <deviceIndex>0</deviceIndex>
  <status>attached</status>
  <attachTime>2012-06-28T17:41:48.000Z</attachTime>
  <deleteOnTermination>true</deleteOnTermination>
</attachment>
<association>
  <publicIp>46.51.219.63</publicIp>
  <ipOwnerId>053230519467</ipOwnerId>
</association>
<privateIpAddressesSet>
  <item>
    <privateIpAddress>10.0.0.12</privateIpAddress>
    <primary>true</primary>
    <association>
      <publicIp>46.51.219.63</publicIp>
      <ipOwnerId>053230519467</ipOwnerId>
    </association>
  </item>
  <item>
    <privateIpAddress>10.0.0.14</privateIpAddress>
    <primary>false</primary>
    <association>
      <publicIp>46.51.221.177</publicIp>
      <ipOwnerId>053230519467</ipOwnerId>
    </association>
  </item>
</privateIpAddressesSet>
</item>
</networkInterfaceSet>
</item>
</instancesSet>
</item>
<item>
  <reservationId>r-58b30a0c</reservationId>
  <ownerId>053230519467</ownerId>
  <groupSet>
    <item>
      <groupId>sg-aa4170f8</groupId>
      <groupName>quick-start-5</groupName>
    </item>
  </groupSet>
  <instancesSet>
    <item>
      <instanceId>i-507f1804</instanceId>
      <imageId>ami-70d49222</imageId>
      <instanceState>
        <code>16</code>
      </instanceState>
    </item>
  </instancesSet>
</item>
</reservationSet>
</item>
</instancesSet>
</item>
</instancesSet>
```

```
        <name>running</name>
      </instanceState>
      <privateDnsName>ip-10-139-34-251.ap-southeast-1.compute.intern
al.privateDnsName>
      <dnsName>ec2-122-248-233-255.ap-southeast-1.compute.amazon
aws.com/dnsName>
      <reason/>
      <keyName>EC2Key</keyName>
      <amiLaunchIndex>0</amiLaunchIndex>
      <productCodes/>
      <instanceType>t1.micro</instanceType>
      <launchTime>2012-06-29T22:53:42.000Z</launchTime>
      <placement>
        <availabilityZone>ap-southeast-1a</availabilityZone>
        <groupName/>
        <tenancy>default</tenancy>
      </placement>
      <platform>windows</platform>
      <monitoring>
        <state>disabled</state>
      </monitoring>
      <privateIpAddress>10.139.34.251</privateIpAddress>
      <ipAddress>122.248.233.255</ipAddress>
      <groupSet>
        <item>
          <groupId>sg-aa4170f8</groupId>
          <groupName>quick-start-5</groupName>
        </item>
      </groupSet>
      <architecture>x86_64</architecture>
      <rootDeviceType>ebs</rootDeviceType>
      <rootDeviceName>/dev/sda1</rootDeviceName>
      <blockDeviceMapping>
        <item>
          <deviceName>/dev/sda1</deviceName>
          <ebs>
            <volumeId>vol-a22b3ac0</volumeId>
            <status>attached</status>
            <attachTime>2012-06-29T22:54:02.000Z</attachTime>
            <deleteOnTermination>true</deleteOnTermination>
          </ebs>
        </item>
      </blockDeviceMapping>
      <virtualizationType>hvm</virtualizationType>
      <clientToken>clNwH1341010421443</clientToken>
      <tagSet>
        <item>
          <key>Name</key>
          <value>EC2 Instance</value>
        </item>
      </tagSet>
      <hypervisor>xen</hypervisor>
      <networkInterfaceSet/>
    </item>
  </instancesSet>
</item>
</reservationSet>
</DescribeInstancesResponse>
```

Example Request

This example filters the results to display only the m1.small or m1.large instances that have an Amazon EBS volume that is both attached and set to delete on termination.

```
https://ec2.amazonaws.com/?Action=DescribeInstances
&Filter.1.Name=instance-type
&Filter.1.Value.1=m1.small
&Filter.1.Value.2=m1.large
&Filter.2.Name=block-device-mapping.status
&Filter.2.Value.1=attached
&Filter.3.Name=block-device-mapping.delete-on-termination
&Filter.3.Value.1=true
&AUTHPARAMS
```

Example Response

```
<DescribeInstancesResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <reservationSet>
    <item>
      <reservationId>r-bc7e30d7</reservationId>
      <ownerId>111122223333</ownerId>
      <groupSet>
        <item>
          <groupId>sg-2eac845a</groupId>
          <groupName>default</groupName>
        </item>
      </groupSet>
      <instancesSet>
        <item>
          <instanceId>i-c7cd56ad</instanceId>
          <imageId>ami-b232d0db</imageId>
          <instanceState>
            <code>l6</code>
            <name>running</name>
          </instanceState>
          <privateDnsName>domU-12-31-39-01-76-06.compute-1.intern
al</privateDnsName>
          <dnsName>ec2-72-44-52-124.compute-1.amazonaws.com</dnsName>
          <keyName>GSG_Keypair</keyName>
          <amiLaunchIndex>0</amiLaunchIndex>
          <productCodes/>
          <instanceType>m1.small</instanceType>
          <launchTime>2010-08-17T01:15:16.000Z</launchTime>
          <placement>
            <availabilityZone>us-east-1b</availabilityZone>
          </placement>
          <kernelId>aki-94c527fd</kernelId>
          <ramdiskId>ari-96c527ff</ramdiskId>
          <monitoring>
            <state>disabled</state>
          </monitoring>
          <privateIpAddress>10.255.121.240</privateIpAddress>
          <ipAddress>72.44.52.124</ipAddress>
          <sourceDestCheck>true</sourceDestCheck>
        </item>
      </instancesSet>
    </item>
  </reservationSet>
</DescribeInstancesResponse>
```



```
<groupSet>
  <item>
    <groupId>sg-2eac845a</groupId>
    <groupName>default</groupName>
  </item>
</groupSet>
<architecture>i386</architecture>
<rootDeviceType>ebs</rootDeviceType>
<rootDeviceName>/dev/sda1</rootDeviceName>
<blockDeviceMapping>
  <item>
    <deviceName>/dev/sda1</deviceName>
    <ebs>
      <volumeId>vol-a482c1cd</volumeId>
      <status>attached</status>
      <attachTime>2010-08-17T01:15:26.000Z</attachTime>
      <deleteOnTermination>true</deleteOnTermination>
    </ebs>
  </item>
</blockDeviceMapping/>
<virtualizationType>paravirtual</virtualizationType>
<clientToken/>
<tagSet/>
<hypervisor>xen</hypervisor>
</item>
</instancesSet>
</item>
</reservationSet>
</DescribeInstancesResponse>
```

Example Request

The following example describes an instance running in Amazon VPC with instance ID i-7a00642e.

```
https://ec2.amazonaws.com/?Action=DescribeInstances
&Filter.1.Name=instance-id
&Filter.1.Value.1=i-7a00642e
&AUTHPARAMS
```

Example Response

```
<DescribeInstancesResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>7f5f05d5-1a11-4ca9-9608-07dd351487a5</requestId>
  <reservationSet>
    <item>
      <reservationId>r-0ece705a</reservationId>
      <ownerId>053230519467</ownerId>
      <groupSet/>
      <instancesSet>
        <item>
          <instanceId>i-7a00642e</instanceId>
          <imageId>ami-1cd4924e</imageId>
          <instanceState>
            <code>16</code>
            <name>running</name>
          </instanceState>
        </item>
      </instancesSet>
    </item>
  </reservationSet>
</DescribeInstancesResponse>
```

```
</instanceState>
<privateDnsName/>
<dnsName/>
<reason/>
<keyName>VPCKey</keyName>
<amiLaunchIndex>0</amiLaunchIndex>
<productCodes/>
<instanceType>c1.medium</instanceType>
<launchTime>2012-06-28T17:41:48.000Z</launchTime>
<placement>
  <availabilityZone>ap-southeast-1b</availabilityZone>
  <groupName/>
  <tenancy>default</tenancy>
</placement>
<platform>windows</platform>
<monitoring>
  <state>disabled</state>
</monitoring>
<subnetId>subnet-c53c87ac</subnetId>
<vpcId>vpc-cc3c87a5</vpcId>
<privateIpAddress>10.0.0.12</privateIpAddress>
<ipAddress>46.51.219.63</ipAddress>
<sourceDestCheck>true</sourceDestCheck>
<groupSet>
  <item>
    <groupId>sg-374b565b</groupId>
    <groupName>quick-start-3</groupName>
  </item>
</groupSet>
<architecture>x86_64</architecture>
<rootDeviceType>ebs</rootDeviceType>
<rootDeviceName>/dev/sda1</rootDeviceName>
<blockDeviceMapping>
  <item>
    <deviceName>/dev/sda1</deviceName>
    <ebs>
      <volumeId>vol-9e151bfc</volumeId>
      <status>attached</status>
      <attachTime>2012-06-28T17:42:05.000Z</attachTime>
      <deleteOnTermination>true</deleteOnTermination>
    </ebs>
  </item>
</blockDeviceMapping>
<virtualizationType>hvm</virtualizationType>
<clientToken>JNlxa1340905307390</clientToken>
<tagSet>
  <item>
    <key>Name</key>
    <value>SingleENI</value>
  </item>
</tagSet>
<hypervisor>xen</hypervisor>
<networkInterfaceSet>
  <item>
    <networkInterfaceId>eni-d83388b1</networkInterfaceId>
    <subnetId>subnet-c53c87ac</subnetId>
    <vpcId>vpc-cc3c87a5</vpcId>
    <description>Primary network interface</description>
```

```
<ownerId>053230519467</ownerId>
<status>in-use</status>
<privateIpAddress>10.0.0.12</privateIpAddress>
<sourceDestCheck>true</sourceDestCheck>
<groupSet>
  <item>
    <groupId>sg-374b565b</groupId>
    <groupName>quick-start-3</groupName>
  </item>
</groupSet>
<attachment>
  <attachmentId>eni-attach-31b87358</attachmentId>
  <deviceIndex>0</deviceIndex>
  <status>attached</status>
  <attachTime>2012-06-28T17:41:48.000Z</attachTime>
  <deleteOnTermination>true</deleteOnTermination>
</attachment>
<association>
  <publicIp>46.51.219.63</publicIp>
  <ipOwnerId>053230519467</ipOwnerId>
</association>
<privateIpAddressesSet>
  <item>
    <privateIpAddress>10.0.0.12</privateIpAddress>
    <primary>true</primary>
    <association>
      <publicIp>46.51.219.63</publicIp>
      <ipOwnerId>053230519467</ipOwnerId>
    </association>
  </item>
  <item>
    <privateIpAddress>10.0.0.14</privateIpAddress>
    <primary>false</primary>
    <association>
      <publicIp>46.51.221.177</publicIp>
      <ipOwnerId>053230519467</ipOwnerId>
    </association>
  </item>
</privateIpAddressesSet>
</item>
</networkInterfaceSet>
</item>
</instancesSet>
</item>
</reservationSet>
</DescribeInstancesResponse>
```

Related Operations

- [RunInstances](#) (p. 379)
- [StopInstances](#) (p. 392)
- [StartInstances](#) (p. 390)
- [TerminateInstances](#) (p. 394)

DescribeInstanceStatus

Description

Describes the status of an Amazon EC2 instance including any scheduled events for an instance. Instance status has two main components:

- System Status reports impaired functionality that stems from issues related to the systems that support an instance, such as hardware failures and network connectivity problems. The `DescribeInstanceStatus` response elements report such problems as impaired reachability.
- Instance Status reports impaired functionality that arises from problems internal to the instance. The `DescribeInstanceStatus` response elements report such problems as impaired reachability.

Instance status provides information about three types of scheduled events for an instance that may require your attention:

- Scheduled Reboot: When Amazon EC2 determines that an instance must be rebooted, the instance's status will return one of two event codes: `system-reboot` or `instance-reboot`. System reboot commonly occurs if certain maintenance or upgrade operations require a reboot of the underlying host that supports an instance. Instance reboot commonly occurs if the instance must be rebooted, rather than the underlying host. Rebooting events include a scheduled start and end time.
- System Maintenance: When Amazon EC2 determines that an instance requires maintenance that requires power or network impact, the instance's status will return an event code called `system-maintenance`. System maintenance is either power maintenance or network maintenance. For power maintenance, your instance will be unavailable for a brief period of time and then rebooted. For network maintenance, your instance will experience a brief loss of network connectivity. System maintenance events include a scheduled start and end time. You will also be notified by email if one of your instances is set for system maintenance. The email message indicates when your instance is scheduled for maintenance.
- Scheduled Retirement: When Amazon EC2 determines that an instance must be shut down, the instance's status will return an event code called `instance-retirement`. Retirement commonly occurs when the underlying host is degraded and must be replaced. Retirement events include a scheduled start and end time. You will also be notified by email if one of your instances is set to retiring. The email message indicates when your instance will be permanently retired.

When your instance is retired, it will either be terminated (if its root device type is the instance-store) or stopped (if its root device type is an EBS volume). Instances stopped due to retirement will not be restarted, but you can do so manually. You can also avoid retirement of EBS-backed instances by manually restarting your instance when its event code is `instance-retirement`. This ensures that your instance is started on a different underlying host.

`DescribeInstanceStatus` returns information only for instances in the `running` state.

You can filter the results to return information only about instances that match criteria you specify. For example, you could get information about instances in a specific Availability Zone. You can specify multiple values for a filter (e.g., more than one Availability Zone). An instance must match at least one of the specified values for it to be included in the results.

You can specify multiple filters (e.g., the instance is in a specific Availability Zone and its status is set to `retiring`). An instance must match *all* the filters for it to be included in the results. If there's no match, no special message is returned; the response is simply empty.

Amazon Elastic Compute Cloud API Reference Description

You can use wildcards with the filter values: * matches zero or more characters, and ? matches exactly one character. You can escape special characters using a backslash before the character. For example, a value of `*amazon\?\` searches for the literal string `*amazon?\`.

The following table shows the available filters.

| Filter Name | Description |
|---|--|
| <code>availability-zone</code> | The Availability Zone of the instance. Type: String |
| <code>event.code</code> | The code identifying the type of event. Type: String Valid values: <code>instance-reboot</code> <code>system-reboot</code> <code>system-maintenance</code> <code>instance-retirement</code> |
| <code>event.description</code> | A description of the event. Type: String |
| <code>event.not-after</code> | The latest end time for the scheduled event. Type: <code>dateType</code> |
| <code>event.not-before</code> | The earliest start time for the scheduled event. Type: <code>dateType</code> |
| <code>instance-state-name</code> | The intended state of the instance, e.g., <code>running</code> Type: String |
| <code>instance-state-code</code> | The code for intended state of the instance, e.g., <code>16</code> . Type: Integer |
| <code>system-status.status</code> | The system status of the instance. Type: String Valid values: <code>ok</code> <code>impaired</code> <code>initializing</code> <code>insufficient-data</code> <code>not-applicable</code> |
| <code>system-status.reachability</code> | Filters on system status where the name is <code>reachability</code> . Type: String Valid values: <code>passed</code> <code>failed</code> <code>initializing</code> <code>insufficient-data</code> |
| <code>instance-status.status</code> | The status of the instance. Type: String Valid values: <code>ok</code> <code>impaired</code> <code>initializing</code> <code>insufficient-data</code> <code>not-applicable</code> |
| <code>instance-status.reachability</code> | Filters on instance status where the name is <code>reachability</code> . Type: String Valid values: <code>passed</code> <code>failed</code> <code>initializing</code> <code>insufficient-data</code> |

Request Parameters

| Name | Description | Required |
|----------------------------|---|----------|
| <i>InstanceId</i> | The list of instance IDs. If not specified, all instances are described. Type: String Default: None | No |
| <i>IncludeAllInstances</i> | When <code>true</code> , returns the health status for all instances (for example, running, stopped, pending, shutting down). When <code>false</code> , returns only the health status for running instances. Type: Boolean Default: <code>false</code> | No |
| <i>MaxResults</i> | The maximum number of paginated instance items per response. Type: Integer Default: None | No |
| <i>NextToken</i> | The next paginated set of results to return. Type: String Default: None | No |

Response Elements

The elements in the following table are wrapped in a `DescribeInstanceStatusResponse` structure.

| Name | Description |
|--------------------------------|--|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>InstanceStatusSet</code> | A set of InstanceStatusItemType (p. 436) elements that describe the status of each instance. |
| <i>NextToken</i> | A string specifying the next paginated set of results to return. Type: <code>xsd:string</code> |

Examples

Example Request

This example returns instance status descriptions for all instances.

```
https://ec2.amazonaws.com/?
Action=DescribeInstanceStatus
&Version=2011-10-01
&AuthParams
```

Example Request

This example returns instance status descriptions for the specified instances.

```
https://ec2.amazonaws.com/?
Action=DescribeInstanceStatus
&InstanceId.0=i-0cf27c63
&InstanceId.1=i-283f9f47
&Version=2011-10-01
&AuthParams
```

Example Request

This example returns instance status descriptions for all instances specified by supported DescribeInstanceStatus filters.

```
https://ec2.amazonaws.com/?
Action=DescribeInstanceStatus
&Filter.0.Name=system-status.reachability
&Filter.0.Value.failed
&Version=2011-10-01
&AuthParams
```

Example Response

```
<DescribeInstanceStatusResponse xmlns='http://ec2.amazonaws.com/doc/2012-04-01/'>
  <requestId>3be1508e-c444-4fef-89cc-0b1223c4f02f</requestId>
  <instanceStatusSet>
    <item>
      <instanceId>i-283f9f47</instanceId>
      <availabilityZone>us-east-1d</availabilityZone>
      <instanceState>
        <code>16</code>
        <name>running</name>
      </instanceState>
      <systemStatus>
        <status>impaired</status>
        <details>
          <item>
            <name>reachability</name>
            <status>failed</status>
            <impairedSince>2012-03-27T16:10:46.000Z</impairedSince>
          </item>
        </details>
      </systemStatus>
    </instanceStatus>
  </instanceStatusSet>
  <status>impaired</status>
  <details>
    <item>
      <name>reachability</name>
      <status>failed</status>
    </item>
  </details>
</DescribeInstanceStatusResponse>
```

```
        <impairedSince>2012-03-27T16:10:46.000Z</impairedSince>
      </item>
    </details>
  </instanceStatus>
  <eventsSet>
    <code>instance-retirement</code>
    <notBefore>2011-12-05T13:00:00+0000</notBefore>
    <notAfter>2011-12-06T13:00:00+000</notAfter>
    <description>
      The instance is running on degraded hardware
    </description>
  </eventsSet>
</item>
<item>
  <instanceId>i-d2e36dbd</instanceId>
  <availabilityZone>us-east-1d</availabilityZone>
  <instanceState>
    <code>l6</code>
    <name>running</name>
  </instanceState>
  <systemStatus>
    <status>ok</status>
    <details>
      <item>
        <name>reachability</name>
        <status>passed</status>
      </item>
    </details>
  </systemStatus>
  <instanceStatus>
    <status>ok</status>
    <details>
      <item>
        <name>reachability</name>
        <status>passed</status>
      </item>
    </details>
  </instanceStatus>
  <eventsSet>
    <code>instance-reboot</code>
    <notBefore>2011-12-05T13:00:00+0000</notBefore>
    <notAfter>2011-12-06T13:00:00+000</notAfter>
    <description>
      The instance is scheduled for a reboot
    </description>
  </eventsSet>
</item>
<item>
  <instanceId>i-9fa454f1</instanceId>
  <availabilityZone>us-east-1c</availabilityZone>
  <instanceState>
    <code>l6</code>
    <name>running</name>
  </instanceState>
  <systemStatus>
    <status>ok</status>
    <details>
```



```
        <item>
          <name>reachability</name>
          <status>passed</status>
        </item>
      </details>
    </systemStatus>
  <instanceStatus>
    <status>ok</status>
    <details>
      <item>
        <name>reachability</name>
        <status>passed</status>
      </item>
    </details>
  </instanceStatus>
</item>
<item>
  <instanceId>i-0ed2936e</instanceId>
  <availabilityZone>us-east-1c</availabilityZone>
  <instanceState>
    <code>16</code>
    <name>running</name>
  </instanceState>
  <systemStatus>
    <status>ok</status>
    <details>
      <item>
        <name>reachability</name>
        <status>passed</status>
      </item>
    </details>
  </systemStatus>
  <instanceStatus>
    <status>insufficient-data</status>
    <details>
      <item>
        <name>reachability</name>
        <status>insufficient-data</status>
      </item>
    </details>
  </instanceStatus>
</item>
</instanceStatusSet>
</DescribeInstanceStatusResponse>
```

DescribeInternetGateways

Description

Gives you information about your Internet gateways. You can filter the results to return information only about Internet gateways that match criteria you specify. For example, you could get information only about gateways with particular tags. The Internet gateway must match at least one of the specified values for it to be included in the results.

You can specify multiple filters (e.g., the Internet gateway is attached to a particular VPC and is tagged with a particular value). The result includes information for a particular Internet gateway only if the gateway matches *all* your filters. If there's no match, no special message is returned; the response is simply empty.

You can use wildcards with the filter values: `*` matches zero or more characters, and `?` matches exactly one character. You can escape special characters using a backslash before the character. For example, a value of `*amazon\?\` searches for the literal string `*amazon?\`.

The following table shows the available filters.

| Filter Name | Description |
|----------------------------------|--|
| <code>attachment.state</code> | The current state of the attachment between the gateway and the VPC. Returned only if a VPC is attached. Type: String Valid value: <code>available</code> |
| <code>attachment.vpc-id</code> | The ID of an attached VPC. Type: String |
| <code>internet-gateway-id</code> | The ID of the Internet gateway. Type: String |
| <code>tag-key</code> | The key of a tag assigned to the resource. This filter is independent of the <code>tag-value</code> filter. For example, if you use both the filter <code>tag-key=Purpose</code> and the filter <code>tag-value=X</code> , you get any resources assigned both the tag key <code>Purpose</code> (regardless of what the tag's value is), and the tag value <code>X</code> (regardless of what the tag's key is). If you want to list only resources where <code>Purpose=X</code> , see the <code>tag:key</code> filter later in this table. For more information about tags, see Using Tags in the <i>Amazon Elastic Compute Cloud User Guide</i> . Type: String |
| <code>tag-value</code> | The value of a tag assigned to the resource. This filter is independent of the <code>tag-key</code> filter. Type: String |

| Filter Name | Description |
|------------------------------|---|
| <code>tag: <i>key</i></code> | <p>Filters the results based on a specific tag/value combination.</p> <p>Example: To list just the resources assigned tag Purpose=X, then specify:</p> <pre>Filter.1.Name=tag:Purpose Filter.1.Value.1=X</pre> <p>Example: To list just resources assigned tag Purpose=X OR Purpose=Y, then specify:</p> <pre>Filter.1.Name=tag:Purpose Filter.1.Value.1=X Filter.1.Value.2=Y</pre> |

For more information about Amazon Virtual Private Cloud and Internet gateways, see the [Amazon Virtual Private Cloud User Guide](#).

Request Parameters

| Name | Description | Required |
|----------------------------------|---|----------|
| <code>InternetGatewayId.n</code> | One or more Internet gateway IDs. Type: String Default: None | No |
| <code>Filter.n.Name</code> | The name of a filter. See the preceding table for a list of allowed filter names. Type: String Default: None | No |
| <code>Filter.n.Value.m</code> | A value for the filter. See the preceding table for a list of allowed filter values for each filter. Type: String Default: None | No |

Response Elements

The elements in the following table are wrapped in a `DescribeInternetGatewaysResponse` structure.

| Name | Description |
|----------------------------------|--|
| <code>requestId</code> | The ID of the request. Type: xsd:string |
| <code>internetGatewaysSet</code> | A list of Internet gateways, each one wrapped in an <code>item</code> element. Type: InternetGatewayType (p. 444) |

Examples

Example Request

This example describes your Internet gateways.

```
https://ec2.amazonaws.com/?Action=DescribeInternetGateways
```

Example Response

```
<DescribeInternetGatewaysResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <internetGatewaySet>
    <item>
      <internetGatewayId>igw-eaad4883EXAMPLE</internetGatewayId>
      <attachmentSet>
        <item>
          <vpcId>vpc-11ad4878</vpcId>
          <state>available</state>
        </item>
      </attachmentSet>
      <tagSet/>
    </item>
  </internetGatewaySet>
</DescribeInternetGatewaysResponse>
```

Related Operations

- [CreateInternetGateway](#) (p. 63)
- [DeleteInternetGateway](#) (p. 109)
- [DetachInternetGateway](#) (p. 25)
- [DetachInternetGateway](#) (p. 294)

DescribeKeyPairs

Description

Returns information about key pairs available to you. If you specify key pairs, information about those key pairs is returned. Otherwise, information for all your key pairs is returned.

You can filter the results to return information only about key pairs that match criteria you specify. For example, you could filter the results to return only the key pairs whose names include the string `Dave`. You can specify multiple values for a filter. A key pair must match at least one of the specified values for it to be included in the results.

You can specify multiple filters (e.g., the key pair name includes the string `Dave`, and the fingerprint equals a certain value). The result includes information for a particular key pair only if it matches *all* your filters. If there's no match, no special message is returned; the response is simply empty.

You can use wildcards with the filter values: `*` matches zero or more characters, and `?` matches exactly one character. You can escape special characters using a backslash before the character. For example, a value of `*amazon\?\` searches for the literal string `*amazon?\`.

The following table shows the available filters.

| Filter Name | Description |
|--------------------------|--|
| <code>fingerprint</code> | The fingerprint of the key pair. Type: String |
| <code>key-name</code> | The name of the key pair. Type: String |

Request Parameters

| Name | Description | Required |
|-------------------------------|--|----------|
| <code>KeyName.n</code> | One or more key pair names. Type: String Default: Describes all key pairs you own, or only those otherwise specified. | No |
| <code>Filter.n.Name</code> | The name of a filter. See the preceding table for a list of allowed filter names. Type: String Default: None | No |
| <code>Filter.n.Value.m</code> | A value for the filter. See the preceding table for a list of allowed values for each filter. Type: String Default: None | No |

Response Elements

The elements in the following table are wrapped in a `DescribeKeyPairsResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>keySet</code> | A list of key pairs, each one wrapped in an <code>item</code> element. Type: DescribeKeyPairsResponseItem (p. 416) |

Examples

Example Request

This example describes the keypair with name `gsg-keypair`.

```
https://ec2.amazonaws.com/?Action=DescribeKeyPairs
&KeyName.1=gsg-keypair
&AUTHPARAMS
```

Example Response

```
<DescribeKeyPairsResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <keySet>
    <item>
      <keyName>gsg-keypair</keyName>
      <keyFingerprint>
        00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00
      </keyFingerprint>
    </item>
  </keySet>
</DescribeKeyPairsResponse>
```

Example Request

This example filters the results to display only key pairs whose names include the string `Dave`.

```
https://ec2.amazonaws.com/?Action=DescribeKeyPairs
&Filter.1.Name=key-name
&Filter.1.Value.1=*Dave*
&AUTHPARAMS
```

Related Operations

- [CreateKeyPair](#) (p. 65)
- [ImportKeyPair](#) (p. 316)

- [DeleteKeyPair](#) (p. 111)

DescribeNetworkAcls

Description

Gives you information about the network ACLs in your VPC.

You can filter the results to return information only about ACLs that match criteria you specify. For example, you could get information only about the ACL associated with a particular subnet. The ACL must match at least one of the specified values for it to be included in the results.

You can specify multiple filters (e.g., the ACL is associated with a particular subnet and has an egress entry that denies traffic to a particular port). The result includes information for a particular ACL only if it matches *all* your filters. If there's no match, no special message is returned; the response is simply empty.

You can use wildcards with the filter values: * matches zero or more characters, and ? matches exactly one character. You can escape special characters using a backslash before the character. For example, a value of `*amazon\?\` searches for the literal string `*amazon?.`

The following table shows the available filters.

| Filter Name | Description |
|---|---|
| <code>association.association-id</code> | The ID of an association ID for the ACL. Type: String |
| <code>association.network-acl-id</code> | The ID of the network ACL involved in the association. Type: String |
| <code>association.subnet-id</code> | The ID of the subnet involved in the association. Type: String |
| <code>default</code> | Indicates whether the ACL is the default network ACL in the VPC. Type: Boolean |
| <code>entry.cidr</code> | The CIDR range specified in the entry. Type: String |
| <code>entry.egress</code> | Indicates whether the entry applies to egress traffic. Type: Boolean |
| <code>entry.icmp.code</code> | The ICMP code specified in the entry, if any. Type: Integer |
| <code>entry.icmp.type</code> | The ICMP type specified in the entry, if any. Type: Integer |
| <code>entry.port-range.from</code> | The start of the port range specified in the entry. Type: Integer |
| <code>entry.port-range.to</code> | The end of the port range specified in the entry. Type: Integer |

Amazon Elastic Compute Cloud API Reference
Description

| Filter Name | Description |
|--------------------------------|--|
| <code>entry.protocol</code> | The protocol specified in the entry. Type: String Valid values: <code>tcp</code> <code>udp</code> <code>icmp</code> or a protocol number |
| <code>entry.rule-action</code> | Indicates whether the entry allows or denies the matching traffic. Type: String Valid Values: <code>allow</code> <code>deny</code> |
| <code>entry.rule-number</code> | The number of an entry (i.e., rule) in the ACL's set of entries. Type: Integer |
| <code>network-acl-id</code> | The ID of the network ACL. Type: String |
| <code>tag-key</code> | The key of a tag assigned to the resource. This filter is independent of the <code>tag-value</code> filter. For example, if you use both the filter <code>tag-key=Purpose</code> and the filter <code>tag-value=X</code> , you get any resources assigned both the tag key <code>Purpose</code> (regardless of what the tag's value is), and the tag value <code>X</code> (regardless of what the tag's key is). If you want to list only resources where <code>Purpose=X</code> , see the <code>tag:key</code> filter later in this table. For more information about tags, see Using Tags in the <i>Amazon Elastic Compute Cloud User Guide</i> . Type: String |
| <code>tag-value</code> | The value of a tag assigned to the resource. This filter is independent of the <code>tag-key</code> filter. Type: String |
| <code>tag:key</code> | Filters the results based on a specific tag/value combination. Example: To list just the resources assigned tag <code>Purpose=X</code> , then specify: <code>Filter.1.Name=tag:Purpose</code> <code>Filter.1.Value.1=X</code> Example: To list just resources assigned tag <code>Purpose=X</code> OR <code>Purpose=Y</code> , then specify: <code>Filter.1.Name=tag:Purpose</code> <code>Filter.1.Value.1=X</code> <code>Filter.1.Value.2=Y</code> |
| <code>vpc-id</code> | The ID of the VPC the network ACL is in. Type: String |

For more information about Amazon Virtual Private Cloud and network ACLs, see [Network ACLs](#) in the *Amazon Virtual Private Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|-------------------------|---|----------|
| <i>NetworkAclId.n</i> | One or more network ACL IDs. Type: string Default: None | No |
| <i>Filter.n.Name</i> | The name of a filter. See the preceding table for a list of allowed filter names. Type: String Default: None | No |
| <i>Filter.n.Value.m</i> | A value for the filter. See the preceding table for a list of allowed filter values for each filter. Type: String Default: None | No |

Response Elements

The elements in the following table are wrapped in a `DescribeNetworkAclsResponse` structure.

| Name | Description |
|----------------------------|--|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>networkAclSet</code> | A list of network ACLs, each one wrapped in an <code>item</code> element. Type: NetworkAclType (p. 452) |

Examples

Example Request

This example describes all the network ACLs in your VPC.

```
https://ec2.amazonaws.com/?Action=DescribeNetworkAcls
```

Example Response

The first ACL in the returned list is the VPC's default ACL.

```
<DescribeNetworkAclsResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <networkAclSet>
    <item>
      <networkAclId>acl-5566953c</networkAclId>
```

```
<vpcId>vpc-5266953b</vpcId>
<default>true</default>
<entrySet>
  <item>
    <ruleNumber>100</ruleNumber>
    <protocol>all</protocol>
    <ruleAction>allow</ruleAction>
    <egress>true</egress>
    <cidrBlock>0.0.0.0/0</cidrBlock>
  </item>
  <item>
    <ruleNumber>32767</ruleNumber>
    <protocol>all</protocol>
    <ruleAction>deny</ruleAction>
    <egress>true</egress>
    <cidrBlock>0.0.0.0/0</cidrBlock>
  </item>
  <item>
    <ruleNumber>100</ruleNumber>
    <protocol>all</protocol>
    <ruleAction>allow</ruleAction>
    <egress>false</egress>
    <cidrBlock>0.0.0.0/0</cidrBlock>
  </item>
  <item>
    <ruleNumber>32767</ruleNumber>
    <protocol>all</protocol>
    <ruleAction>deny</ruleAction>
    <egress>false</egress>
    <cidrBlock>0.0.0.0/0</cidrBlock>
  </item>
</entrySet>
<associationSet/>
<tagSet/>
</item>
<item>
  <networkAclId>acl-5d659634</networkAclId>
  <vpcId>vpc-5266953b</vpcId>
  <default>false</default>
  <entrySet>
    <item>
      <ruleNumber>110</ruleNumber>
      <protocol>6</protocol>
      <ruleAction>allow</ruleAction>
      <egress>true</egress>
      <cidrBlock>0.0.0.0/0</cidrBlock>
      <portRange>
        <from>49152</from>
        <to>65535</to>
      </portRange>
    </item>
    <item>
      <ruleNumber>32767</ruleNumber>
      <protocol>all</protocol>
      <ruleAction>deny</ruleAction>
      <egress>true</egress>
      <cidrBlock>0.0.0.0/0</cidrBlock>
    </item>
  </entrySet>
</item>
```

```
<item>
  <ruleNumber>110</ruleNumber>
  <protocol>6</protocol>
  <ruleAction>allow</ruleAction>
  <egress>>false</egress>
  <cidrBlock>0.0.0.0/0</cidrBlock>
  <portRange>
    <from>80</from>
    <to>80</to>
  </portRange>
</item>
<item>
  <ruleNumber>120</ruleNumber>
  <protocol>6</protocol>
  <ruleAction>allow</ruleAction>
  <egress>>false</egress>
  <cidrBlock>0.0.0.0/0</cidrBlock>
  <portRange>
    <from>443</from>
    <to>443</to>
  </portRange>
</item>
<item>
  <ruleNumber>32767</ruleNumber>
  <protocol>all</protocol>
  <ruleAction>deny</ruleAction>
  <egress>>false</egress>
  <cidrBlock>0.0.0.0/0</cidrBlock>
</item>
</entrySet>
<associationSet>
  <item>
    <networkAclAssociationId>aclassoc-5c659635</networkAclAssociationId>
    <networkAclId>acl-5d659634</networkAclId>
    <subnetId>subnet-ff669596</subnetId>
  </item>
  <item>
    <networkAclAssociationId>aclassoc-c26596ab</networkAclAssociationId>
    <networkAclId>acl-5d659634</networkAclId>
    <subnetId>subnet-f0669599</subnetId>
  </item>
</associationSet>
<tagSet/>
</item>
</networkAclSet>
</DescribeNetworkAclsResponse>
```

Related Operations

- [CreateNetworkAcl](#) (p. 67)
- [DeleteNetworkAcl](#) (p. 113)
- [ReplaceNetworkAclAssociation](#) (p. 345)
- [CreateNetworkAclEntry](#) (p. 69)
- [DeleteNetworkAclEntry](#) (p. 115)
- [ReplaceNetworkAclEntry](#) (p. 347)

DescribeNetworkInterfaceAttribute

Description

Describes a network interface attribute. Only one attribute can be specified per call.

Request Parameters

| Name | Description | Required |
|---------------------------|---|----------|
| <i>NetworkInterfaceId</i> | The ID of the network interface. Type: String Default: None | Yes |
| <i>Attribute</i> | The attribute of the network interface. Type: String Default: None Valid values: description groupSet sourceDestCheck attachment | Yes |

Response Elements

The elements in the following table are wrapped in a `DescribeNetworkInterfaceAttribute` structure.

| Name | Description |
|---------------------------------|--|
| <code>requestId</code> | The ID of the request. Type: xsd:string |
| <code>networkInterfaceId</code> | The ID of the network interface. Type: xsd:string |

Examples

Example Request

This example describes the attributes of a network interface.

```
http://ec2.us-east-1.amazonaws.com/?Action=DescribeNetworkInterfaceAttribute&NetworkInterfaceId=eni-686ea200&Attribute=sourceDestCheck&AUTH_PARAMS
```

Example Response

```
<DescribeNetworkInterfaceAttributeResponse
  xmlns="http://ec2.amazonaws.com/doc/2011-12-15/">
  <requestId>7a20c6b2-d71c-45fb-bba7-37306850544b</requestId>
  <networkInterfaceId>eni-686ea200</networkInterfaceId>
```

```
<sourceDestCheck>  
  <value>true</value>  
</sourceDestCheck>  
</DescribeNetworkInterfaceAttributeResponse>
```

Related Operations

- [AttachNetworkInterface](#) (p. 27)
- [DetachNetworkInterface](#) (p. 296)
- [CreateNetworkInterface](#) (p. 72)
- [DeleteNetworkInterface](#) (p. 117)
- [DescribeNetworkInterfaces](#) (p. 216)
- [ModifyNetworkInterfaceAttribute](#) (p. 327)
- [ResetNetworkInterfaceAttribute](#) (p. 369)

DescribeNetworkInterfaces

Description

Provides information about one or more network interfaces.

You can filter the results to return information only about network interfaces that match criteria you specify. For example, you could get information about only network interfaces launched in a specific Availability Zone. You can specify multiple values for a filter (e.g., more than one Availability Zone). A network interface must match at least one of the specified values for it to be included in the results.

You can specify multiple filters (e.g., the network interface is in a specific Availability Zone, and its owner ID matches a specific owner ID). A network interface must match all the filters for it to be included in the results. If there's no match, no special message is returned; the response is simply empty.

You can use wildcards with the filter values: * matches zero or more characters, and ? matches exactly one character. You can escape special characters using a backslash before the character. For example, a value of `*amazon\?\` searches for the literal string `*amazon?\`.

The following table shows the available filters.

| Filter Name | Description |
|--|--|
| <code>addresses.private-ip-address</code> | The private IP addresses associated with the network interface. Type: String |
| <code>addresses.primary</code> | Whether the private IP address is the primary IP address associated with the network interface. Type: Boolean Valid Values: true false |
| <code>addresses.association.public-ip</code> | The association ID returned when the network interface was associated with the Elastic IP address. Type: String |
| <code>addresses.association.owner-id</code> | The owner ID of the addresses associated with the network interface. Type: String |
| <code>association.association-id</code> | The association ID returned when the network interface was associated with an IP address. Type: String |
| <code>association.allocation-id</code> | The allocation ID that AWS returned when you allocated the Elastic IP address for your network interface. Type: String |
| <code>association.ip-owner-id</code> | The owner of the Elastic IP address associated with the network interface. Type: String |

**Amazon Elastic Compute Cloud API Reference
Description**

| Filter Name | Description |
|---|--|
| <code>association.public-ip</code> | The address of the Elastic IP address bound to the network interface. Type: String |
| <code>attachment.attachment-id</code> | The ID of the interface attachment. Type: String |
| <code>attachment.instance-id</code> | The ID of the instance to which the network interface is attached. Type: String |
| <code>attachment.instance-owner-id</code> | The owner ID of the instance to which the network interface is attached. Type: String |
| <code>attachment.device-index</code> | The device index to which the network interface is attached. Type: Integer |
| <code>attachment.status</code> | The status of the attachment. Type: String Valid values: <code>attaching</code> <code>attached</code> <code>detaching</code> <code>detached</code> |
| <code>attachment.attach.time</code> | The time that the network interface was attached to an instance. Type: Date |
| <code>attachment.delete-on-termination</code> | Indicates whether the attachment is deleted when an instance is terminated. Type: Boolean |
| <code>availability-zone</code> | The Availability Zone of the network interface. Type: String |
| <code>description</code> | The description of the network interface. Type: String |
| <code>group-id</code> | The ID of a VPC security group associated with the network interface. Type: String |
| <code>group-name</code> | The name of a VPC security group associated with the network interface. Type: String |
| <code>mac-address</code> | The MAC address of the network interface. Type: String |
| <code>network-interface-id</code> | The ID of the network interface. Type: String |

Amazon Elastic Compute Cloud API Reference
Description

| Filter Name | Description |
|---------------------------------|--|
| <code>owner-id</code> | The AWS account ID of the network interface owner. Type: String |
| <code>private-ip-address</code> | The private IP address or addresses of the network interface. Type: String |
| <code>private-dns-name</code> | The private DNS name of the network interface. Type: String |
| <code>requester-id</code> | The ID of the entity that launched the instance on your behalf (e.g., AWS Management Console, Auto Scaling, etc.). Type: String |
| <code>requester-managed</code> | Indicates whether the network interface is being managed by an AWS service (e.g., AWS Management Console, Auto Scaling, etc). Type: Boolean |
| <code>source-dest-check</code> | Indicates whether the network interface performs source/destination checking. A value of <code>true</code> means checking is enabled, and <code>false</code> means checking is disabled. The value must be <code>false</code> for the network interface to perform Network Address Translation (NAT) in your VPC. Type: Boolean |
| <code>status</code> | The status of the network interface. If the network interface is not attached to an instance, the status shows <code>available</code> ; if a network interface is attached to an instance the status shows <code>in-use</code> . Type: String Valid values: <code>available</code> <code>in-use</code> |
| <code>subnet-id</code> | The ID of the subnet that the network interface is in. Type: String |
| <code>tag-key</code> | The key of a tag assigned to the resource. This filter is independent of the <code>tag-value</code> filter. For example, if you use both the filter <code>tag-key=Purpose</code> and the filter <code>tag-value=X</code> , you get any resources assigned both the tag key <code>Purpose</code> (regardless of what the tag's value is), and the tag value <code>X</code> (regardless of what the tag's key is). If you want to list only resources where <code>Purpose=X</code> , see the <code>tag:key</code> filter later in this table. For more information about tags, see Using Tags in the <i>Amazon Elastic Compute Cloud User Guide</i> . Type: String |

| Filter Name | Description |
|-----------------|---|
| tag-value | The value of a tag assigned to the resource. This filter is independent of the tag-key filter. Type: String |
| tag: <i>key</i> | Filters the results based on a specific tag/value combination. Example: To list just the resources assigned tag Purpose=X, then specify: Filter.1.Name=tag:Purpose Filter.1.Value.1=X Example: To list just resources assigned tag Purpose=X OR Purpose=Y, then specify: Filter.1.Name=tag:Purpose Filter.1.Value.1=X Filter.1.Value.2=Y |
| vpc-id | The ID of the VPC that the network interface is in. Type: String |

Request Parameters

| Name | Description | Required |
|----------------------|---|----------|
| NetworkInterfaceId.n | One or more network interface IDs. Type: String Default: None | No |
| Filter.n.Name | The filter name. Type: String Default: None | No |
| Filter.n.Value.n | The filter value. Type: String Default: None | No |

Response Elements

| Name | Description |
|---------------------|--|
| requestId | The ID of the request. Type: xsd:string |
| networkInterfaceSet | Returns information about the network interfaces. Type: InstanceNetworkInterfaceSetItemRequestType (p. 440) |

Examples

Example Request

This example describes network interfaces.

```
https://ec2.amazonaws.com/?Action=DescribeNetworkInterfaces
&AUTHPARAMS
```

Example Response

```
<DescribeNetworkInterfacesResponse xmlns='http://ec2.amazonaws.com/doc/2012-06-15/'>
  <requestId>fc45294c-006b-457b-bab9-012f5b3b0e40</requestId>
  <networkInterfaceSet>
    <item>
      <networkInterfaceId>eni-0f62d866</networkInterfaceId>
      <subnetId>subnet-c53c87ac</subnetId>
      <vpcId>vpc-cc3c87a5</vpcId>
      <availabilityZone>ap-southeast-1b</availabilityZone>
      <description/>
      <ownerId>053230519467</ownerId>
      <requesterManaged>>false</requesterManaged>
      <status>in-use</status>
      <macAddress>02:81:60:cb:27:37</macAddress>
      <privateIpAddress>10.0.0.146</privateIpAddress>
      <sourceDestCheck>>true</sourceDestCheck>
      <groupSet>
        <item>
          <groupId>sg-3f4b5653</groupId>
          <groupName>default</groupName>
        </item>
      </groupSet>
      <attachment>
        <attachmentId>eni-attach-6537fc0c</attachmentId>
        <instanceId>i-22197876</instanceId>
        <instanceOwnerId>053230519467</instanceOwnerId>
        <deviceIndex>0</deviceIndex>
        <status>attached</status>
        <attachTime>2012-07-01T21:45:27.000Z</attachTime>
        <deleteOnTermination>>true</deleteOnTermination>
      </attachment>
      <tagSet/>
      <privateIpAddressesSet>
        <item>
          <privateIpAddress>10.0.0.146</privateIpAddress>
          <primary>>true</primary>
        </item>
        <item>
          <privateIpAddress>10.0.0.148</privateIpAddress>
          <primary>>false</primary>
        </item>
        <item>
          <privateIpAddress>10.0.0.150</privateIpAddress>
          <primary>>false</primary>
        </item>
      </privateIpAddressesSet>
    </item>
  </networkInterfaceSet>
</DescribeNetworkInterfacesResponse>
```

```
    </item>
  </privateIpAddressesSet>
</item>
<item>
  <networkInterfaceId>eni-a66ed5cf</networkInterfaceId>
  <subnetId>subnet-cd8a35a4</subnetId>
  <vpcId>vpc-f28a359b</vpcId>
  <availabilityZone>ap-southeast-1b</availabilityZone>
  <description>Primary network interface</description>
  <ownerId>053230519467</ownerId>
  <requesterManaged>>false</requesterManaged>
  <status>in-use</status>
  <macAddress>02:78:d7:00:8a:1e</macAddress>
  <privateIpAddress>10.0.1.233</privateIpAddress>
  <sourceDestCheck>>true</sourceDestCheck>
  <groupSet>
    <item>
      <groupId>sg-a2a0b2ce</groupId>
      <groupName>quick-start-1</groupName>
    </item>
  </groupSet>
  <attachment>
    <attachmentId>eni-attach-a99c57c0</attachmentId>
    <instanceId>i-886401dc</instanceId>
    <instanceOwnerId>053230519467</instanceOwnerId>
    <deviceIndex>0</deviceIndex>
    <status>attached</status>
    <attachTime>2012-06-27T20:08:44.000Z</attachTime>
    <deleteOnTermination>>true</deleteOnTermination>
  </attachment>
  <tagSet/>
  <privateIpAddressesSet>
    <item>
      <privateIpAddress>10.0.1.233</privateIpAddress>
      <primary>>true</primary>
    </item>
    <item>
      <privateIpAddress>10.0.1.20</privateIpAddress>
      <primary>>false</primary>
    </item>
  </privateIpAddressesSet>
</item>
</networkInterfaceSet>
</DescribeNetworkInterfacesResponse>
```

Related Operations

- [AttachNetworkInterface](#) (p. 27)
- [DetachNetworkInterface](#) (p. 296)
- [CreateNetworkInterface](#) (p. 72)
- [DeleteNetworkInterface](#) (p. 117)
- [DescribeNetworkInterfaceAttribute](#) (p. 214)
- [ModifyNetworkInterfaceAttribute](#) (p. 327)
- [ResetNetworkInterfaceAttribute](#) (p. 369)

DescribePlacementGroups

Description

Returns information about one or more placement groups in your account. For more information about placement groups and cluster instances, see [Using Cluster Instances](#) in the *Amazon Elastic Compute Cloud User Guide*.

You can filter the results to return information only about placement groups that match criteria you specify. For example, you could filter the results to return only the groups whose state is `deleted`. You can specify multiple values for a filter. A placement group must match at least one of the specified values for it to be included in the results.

You can specify multiple filters (e.g., the group's state is `deleted` and the name includes the string `Project`). The result includes information for a particular group only if it matches *all* your filters. If there's no match, no special message is returned; the response is simply empty.

You can use wildcards with the filter values: `*` matches zero or more characters, and `?` matches exactly one character. You can escape special characters using a backslash before the character. For example, a value of `*amazon\?\` searches for the literal string `*amazon?\`.

The following table shows the available filters.

| Filter Name | Description |
|-------------------------|---|
| <code>group-name</code> | The name of the placement group. Type: String |
| <code>state</code> | The state of the placement group. Type: String Valid values: <code>pending</code> <code>available</code> <code>deleting</code> <code>deleted</code> |
| <code>strategy</code> | The strategy of the placement group. Type: String Valid value: <code>cluster</code> |

Request Parameters

| Name | Description | Required |
|----------------------------|--|----------|
| <code>GroupName.n</code> | One or more placement group names. Type: string Default: Describes all your placement groups, or only those otherwise specified. | No |
| <code>Filter.n.Name</code> | The name of a filter. See the preceding table for a list of allowed filter names. Type: String Default: None | No |

| Name | Description | Required |
|-------------------------|--|----------|
| <i>Filter.n.Value.m</i> | A value for the filter. See the preceding table for a list of allowed values for each filter. Type: String Default: None | No |

Response Elements

The elements in the following table are wrapped in a `DescribePlacementGroupsResponse` structure.

| Name | Description |
|--------------------------------|--|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>placementGroupSet</code> | A list of placement groups, each one wrapped in an <code>item</code> element. Type: PlacementGroupInfoType (p. 457) |

Examples

Example Request

This example describes the placement group named XYZ-cluster.

```
https://ec2.amazonaws.com/?Action=DescribePlacementGroups
&GroupName.1=XYZ-cluster
&AUTHPARAMS
```

Example Response

```
<DescribePlacementGroupsResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestID>d4904fd9-82c2-4ea5-adfe-a9cc3EXAMPLE</requestID>
  <placementGroupSet>
    <item>
      <groupName>XYZ-cluster</groupName>
      <strategy>cluster</strategy>
      <state>available</state>
    </item>
  </placementGroupSet>
</DescribePlacementGroupsResponse>
```

Example Request

This example filters the results to display only placement groups that include the string `Project` in the name.

```
https://ec2.amazonaws.com/?Action=DescribePlacementGroups  
&Filter.1.Name=group-name  
&Filter.1.Value=*Project*  
&AUTHPARAMS
```

Related Operations

- [CreatePlacementGroup](#) (p. 77)
- [DeletePlacementGroup](#) (p. 119)

DescribeRegions

Description

Describes Regions that are currently available to the account.

You can use filters with this call just as you can with other "describe" calls.

You can use wildcards with the filter values: * matches zero or more characters, and ? matches exactly one character. You can escape special characters using a backslash before the character. For example, a value of `*amazon\?\` searches for the literal string `*amazon?\`.

The following table shows the available filters.

| Filter Name | Description |
|-------------|---|
| endpoint | The endpoint of the Region (e.g., ec2.us-east-1.amazonaws.com). Type: String |
| region-name | The name of the Region. Type: String |

Request Parameters

| Name | Description | Required |
|-------------------------|--|----------|
| <i>RegionName.n</i> | One or more Region names. Type: String Default: Describes all Regions available to the account. | No |
| <i>Filter.n.Name</i> | The name of a filter. See the preceding table for a list of allowed filter names. Type: String Default: None | No |
| <i>Filter.n.Value.m</i> | A value for the filter. See the preceding table for a list of allowed values for each filter. Type: String Default: None | No |

Response Elements

The elements in the following table are wrapped in a `DescribeRegionsResponse` structure.

| Name | Description |
|-----------|--|
| requestId | The ID of the request. Type: xsd:string |

| Name | Description |
|------------|---|
| regionInfo | A list of Regions, each one wrapped in an <code>item</code> element. Type: RegionItemType (p. 463) |

Examples

Example Request

This example displays information about all Regions.

```
https://ec2.amazonaws.com/?Action=DescribeRegions
&AUTHPARAMS
```

Example Request

This example displays information about just the specified Regions.

```
https://ec2.amazonaws.com/?Action=DescribeRegions
&RegionName.1=us-east-1
&RegionName.2=eu-west-1
&AUTHPARAMS
```

Example Response

```
<DescribeRegionsResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <regionInfo>
    <item>
      <regionName>us-east-1</regionName>
      <regionEndpoint>ec2.us-east-1.amazonaws.com</regionEndpoint>
    </item>
    <item>
      <regionName>eu-west-1</regionName>
      <regionEndpoint>ec2.eu-west-1.amazonaws.com</regionEndpoint>
    </item>
  </regionInfo>
</DescribeRegionsResponse>
```

Example Request

This example displays information about all Regions that have the string `ap` in the endpoint.

```
https://ec2.amazonaws.com/?Action=DescribeRegions
&Filter.1.Name=endpoint
&Filter.1.Value.1=*ap*
&AUTHPARAMS
```

Example Response

```
<DescribeRegionsResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <regionInfo>
    <item>
      <regionName>ap-southeast-1</regionName>
      <regionEndpoint>ec2.ap-southeast-1.amazonaws.com</regionEndpoint>
    </item>
  </regionInfo>
</DescribeRegionsResponse>
```

Related Operations

- [DescribeAvailabilityZones](#) (p. 150)
- [RunInstances](#) (p. 379)

DescribeReservedInstances

Description

Describes Reserved Instances that you purchased.

Starting with the 2011-11-01 API version, AWS expanded its offering of Amazon EC2 Reserved Instances to address a range of projected instance use. There are three types of Reserved Instances based on customer utilization levels: *Heavy Utilization*, *Medium Utilization*, and *Light Utilization*. You determine the type of the Reserved Instances offerings by including the optional *offeringType* parameter. The Medium Utilization offering type is equivalent to the Reserved Instance offering available before API version 2011-11-01. If you are using tools that predate the 2011-11-01 API version, you only have access to the `Medium Utilization` Reserved Instance offering type.

For more information about Reserved Instances, see [Reserved Instances](#) in the *Amazon Elastic Compute Cloud User Guide*.

You can filter the results to return information about Reserved Instances that matches criteria you specify. For example, you could get information about Reserved Instances in a particular Availability Zone. Or you can specify multiple values for a filter. A Reserved Instance must match at least one of the specified values for it to be included in the results.

You can specify multiple filters as well. For example, you could specify that your Reserved Instance must be in a particular Availability Zone and must be tagged with a particular value. The result includes information for a particular instance only if it matches *all* of your filters. If there's no match, no special message is returned; the response is simply empty.

You can use wildcards with the filter values: `*` matches zero or more characters, and `?` matches exactly one character. You can escape special characters using a backslash before the character. For example, a value of `*amazon\?\` searches for the literal string `*amazon?\`.

The following table shows the available filters.

| Filter Name | Description |
|----------------------------------|---|
| <code>availability-zone</code> | The Availability Zone where the Reserved Instance can be used. Type: String |
| <code>duration</code> | The duration of the Reserved Instance (one year or three years), in seconds. Type: <code>xs:long</code> Valid values: <code>31536000 94608000</code> |
| <code>fixed-price</code> | The purchase price of the Reserved Instance (e.g., <code>9800.0</code>) Type: <code>xs:double</code> |
| <code>instance-type</code> | The instance type on which the Reserved Instance can be used. Type: String |
| <code>product-description</code> | The product description of the Reserved Instance. Type: String Valid values: <code>Linux/UNIX Linux/UNIX (Amazon VPC) Windows Windows (Amazon VPC)</code> |

| Filter Name | Description |
|-----------------------|---|
| reserved-instances-id | The ID of the Reserved Instance. Type: String |
| start | The time at which the Reserved Instance purchase request was placed, e.g., 2010-08-07T11:54:42.000Z. Type: xsd:dateTime |
| state | The state of the Reserved Instance. Type: String Valid values: pending-payment active payment-failed retired |
| tag-key | The key of a tag assigned to the resource. This filter is independent of the tag-value filter. For example, if you use both the filter tag-key=Purpose and the filter tag-value=X, you get any resources assigned both the tag key Purpose (regardless of what the tag's value is), and the tag value X (regardless of what the tag's key is). If you want to list only resources where Purpose=X, see the tag:key filter later in this table. For more information about tags, see Using Tags in the <i>Amazon Elastic Compute Cloud User Guide</i> . Type: String |
| tag-value | The value of a tag assigned to the resource. This filter is independent of the tag-key filter. Type: String |
| tag:key | Filters the results based on a specific tag/value combination. Example: To list just the resources assigned tag Purpose=X, then specify: Filter.1.Name=tag:Purpose Filter.1.Value.1=X Example: To list just resources assigned tag Purpose=X OR Purpose=Y, then specify: Filter.1.Name=tag:Purpose Filter.1.Value.1=X Filter.1.Value.2=Y |
| usage-price | The usage price of the Reserved Instance, per hour (e.g., 0.84) Type: xs:double |

Request Parameters

| Name | Description | Required |
|--|--|----------|
| <i>ReservedInstancesId</i> . <i>n</i> | One or more Reserved Instance IDs. Type: String Default: Describes all your Reserved Instances, or only those otherwise specified. | No |

| Name | Description | Required |
|-------------------------|--|----------|
| <i>Filter.n.Name</i> | The name of a filter. See the preceding table for a list of allowed filter names. Type: String Default: None | No |
| <i>Filter.n.Value.m</i> | A value for the filter. See the preceding table for a list of allowed values for each filter. Type: String Default: None | No |
| <i>offeringType</i> | The Reserved Instance offering type. Type: String Valid values: Heavy Utilization Medium Utilization Light Utilization | No |

Response Elements

The elements in the following table are wrapped in a `DescribeReservedInstancesResponse` structure.

| Name | Description |
|-----------------------------------|--|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>reservedInstancesSet</code> | A list of Reserved Instances, each one wrapped in an <code>item</code> element. Type: DescribeReservedInstancesResponseSetItemType (p. 418) |

Examples

Example Request

This example describes Reserved Instances owned by your account.

```
https://ec2.amazonaws.com/?Action=DescribeReservedInstances
&AUTHPARAMS
```

Example Response

```
<DescribeReservedInstancesResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <reservedInstancesSet>
    <item>
      <reservedInstancesId>4b2293b4-5813-4cc8-9ce3-1957fc1dcfc8EXAMPLE</re
servedInstancesId>
      <instanceType>m1.xlarge</instanceType>
      <availabilityZone>us-east-1a</availabilityZone>
```

```
<duration>31536000</duration>
<fixedPrice>1820.0</fixedPrice>
<usagePrice>0.24</usagePrice>
<instanceCount>3</instanceCount>
<productDescription>Linux/UNIX</productDescription>
<state>active</state>
<tagSet/>
</item>
</reservedInstancesSet>
</DescribeReservedInstancesResponse>
```

Example Request

This example filters the results to display only one-year, m1.small Linux/UNIX Reserved Instances. If you want Linux/UNIX Reserved Instances specifically for use with Amazon VPC, set the product description to Linux/UNIX (Amazon VPC).

```
https://ec2.amazonaws.com/?Action=DescribeReservedInstances
&Filter.1.Name=duration
&Filter.1.Value.1=31536000
&Filter.2.Name=instance-type
&Filter.2.Value.1=m1.small
&Filter.3.Name=product-description
&Filter.3.Value.1=Linux/UNIX
&AUTHPARAMS
```

Related Operations

- [PurchaseReservedInstancesOffering](#) (p. 335)
- [DescribeReservedInstancesOfferings](#) (p. 232)

DescribeReservedInstancesOfferings

Description

Describes Reserved Instance offerings that are available for purchase. With Amazon EC2 Reserved Instances, you purchase the right to launch Amazon EC2 instances for a period of time (without getting insufficient capacity errors) and pay a lower usage rate for the actual time used.

Starting with the 2011-11-01 API version, AWS expanded its offering of Amazon EC2 Reserved Instances to address a range of projected instance use. There are three types of Reserved Instances based on customer utilization levels: *Heavy Utilization*, *Medium Utilization*, and *Light Utilization*. You determine the type of the Reserved Instances offerings by including the optional *offeringType* parameter when calling `DescribeReservedInstancesOfferings`. The Medium Utilization offering type is equivalent to the Reserved Instance offering available before API version 2011-11-01. If you are using tools that predate the 2011-11-01 API version, `DescribeReservedInstancesOfferings` will only list information about the `Medium Utilization` Reserved Instance offering type.

For more information about Reserved Instances, see [Reserved Instances](#) in the *Amazon Elastic Compute Cloud User Guide*.

Our policy is to provide filters for all *describe* calls so that you can limit the results to your specified criteria. Therefore, you can use filters to limit the results when describing Reserved Instances offerings, even though you can use the regular request parameters to do something similar.

For example, you could use the regular request parameters or a filter to get the offerings for a particular instance type. You can specify multiple request parameters or multiple filters (e.g., limit the results to the `m2.xlarge` instance type, and only for `Windows` instances). The result includes information for a particular offering only if it matches *all* of your request parameters or filters. If there's no match, no special message is returned; the response is simply empty.

You can use wildcards with the filter values: `*` matches zero or more characters, and `?` matches exactly one character. You can escape special characters using a backslash before the character. For example, a value of `*amazon?\\` searches for the literal string `*amazon?\\`.

The following table shows the available filters.

| Filter Name | Description |
|--------------------------------|---|
| <code>availability-zone</code> | The Availability Zone where the Reserved Instance can be used. Type: String |
| <code>duration</code> | The duration of the Reserved Instance (e.g., one year or three years), in seconds. Type: Long Valid values: 31536000 94608000 |
| <code>fixed-price</code> | The purchase price of the Reserved Instance (e.g., 9800.0) Type: Double |
| <code>instance-type</code> | The Amazon EC2 instance type on which the Reserved Instance can be used. Type: String |

| Filter Name | Description |
|--------------------------------|--|
| product-description | The description of the Reserved Instance. Type: String Valid values: Linux/UNIX Linux/UNIX (Amazon VPC) Windows Windows (Amazon VPC) |
| reserved-instances-offering-id | The Reserved Instances offering ID. Type: String |
| usage-price | The usage price of the Reserved Instance, per hour (e.g., 0.84) Type: Double |

Request Parameters

| Name | Description | Required |
|--------------------------------------|--|----------|
| <i>ReservedInstancesOfferingId.n</i> | One or more Reserved Instances offering IDs. Type: String Default: None | No |
| <i>InstanceType</i> | The instance type on which the Reserved Instance can be used. Type: String Default: None | No |
| <i>AvailabilityZone</i> | The Availability Zone in which the Reserved Instance can be used. Type: String Default: None | No |
| <i>ProductDescription</i> | The Reserved Instance description. Instances that include (Amazon VPC) in the description are for use with Amazon VPC. Type: String Valid values: Linux/UNIX Linux/UNIX (Amazon VPC) Windows Windows (Amazon VPC) Default: None | No |
| <i>Filter.n.Name</i> | The name of a filter. See the preceding table for a list of allowed filter names. Type: String Default: None | No |
| <i>Filter.n.Value.m</i> | A value for the filter. See the preceding table for a list of allowed values for each filter. Type: String Default: None | No |

| Name | Description | Required |
|------------------------|---|----------|
| <i>instanceTenancy</i> | The tenancy of the Reserved Instance offering. A Reserved Instance with tenancy of dedicated will run on single-tenant hardware and can only be launched within a VPC. Type: String Valid values: default dedicated Default: default | No |
| <i>offeringType</i> | The Reserved Instance offering type. Type: String Valid values: Heavy Utilization Medium Utilization Light Utilization Default: none | No |

Response Elements

The elements in the following table are wrapped in a `DescribeReservedInstancesOfferingsResponse` structure.

| Name | Description |
|--|--|
| <code>requestId</code> | The ID of the request. Type: xsd:string |
| <code>reservedInstancesOfferingsSet</code> | A list of Reserved Instances offerings, each one wrapped in an <code>item</code> element. Type: DescribeReservedInstancesOfferingsResponseSetItemType (p. 417) |

Examples

Example Request

This example describes available Reserved Instance offerings.

```
https://ec2.amazonaws.com/?Action=DescribeReservedInstancesOfferings
&AUTHPARAMS
```

Example Response

```
<DescribeReservedInstancesOfferingsResponse xmlns="http://ec2.amazon
aws.com/doc/2012-06-15/">
  <requestId>48692a1d-3036-48fd-8c0e-d34681b97efdEXAMPLE</requestId>
  <reservedInstancesOfferingsSet>
    <item>
      <reservedInstancesOfferingId>248e7b75-c83a-48c1-bcf7-
b7f03e9c43feEXAMPLE</reservedInstancesOfferingId>
      <instanceType>c1.medium</instanceType>
```

```
<availabilityZone>us-east-1b</availabilityZone>
<duration>94608000</duration>
<fixedPrice>700.0</fixedPrice>
<usagePrice>0.06</usagePrice>
<productDescription>Linux/UNIX (Amazon VPC)</productDescription>
<instanceTenancy>default</instanceTenancy>
<currencyCode>USD</currencyCode>
<offeringType>Medium Utilization</offeringType>
<recurringCharges/>
</item>
...
</reservedInstancesOfferingsSet>
</DescribeReservedInstancesOfferingsResponse>
```

Example Request

This example filters the results to display only one-year, m1.small or m1.large Linux/UNIX Reserved Instances. If you want Linux/UNIX Reserved Instances specifically for use with Amazon VPC, set the product description to Linux/UNIX (Amazon VPC).

```
https://ec2.amazonaws.com/?Action=DescribeReservedInstancesOfferings
&Filter.1.Name=duration
&Filter.1.Value.1=31536000
&Filter.2.Name=instance-type
&Filter.2.Value.1=m1.small
&Filter.2.Value.2=m1.large
&Filter.3.Name=product-description
&Filter.3.Value.1=Linux/UNIX
&AUTHPARAMS
```

Related Operations

- [PurchaseReservedInstancesOffering](#) (p. 335)
- [DescribeReservedInstances](#) (p. 228)

DescribeRouteTables

Description

Gives you information about your route tables. You can filter the results to return information only about tables that match criteria you specify. For example, you could get information only about a table associated with a particular subnet. You can specify multiple values for the filter. The table must match at least one of the specified values for it to be included in the results.

You can specify multiple filters (e.g., the table has a particular route, and is associated with a particular subnet). The result includes information for a particular table only if it matches *all* your filters. If there's no match, no special message is returned; the response is simply empty.

You can use wildcards with the filter values: `*` matches zero or more characters, and `?` matches exactly one character. You can escape special characters using a backslash before the character. For example, a value of `*amazon\?\` searches for the literal string `*amazon?\`.

The following table shows the available filters.

| Filter Name | Description |
|---|--|
| <code>association.route-table-association-id</code> | The ID of an association ID for the route table. Type: String |
| <code>association.route-table-id</code> | The ID of the route table involved in the association. Type: String |
| <code>association.subnet-id</code> | The ID of the subnet involved in the association. Type: String |
| <code>association.main</code> | Indicates whether the route table is the main route table in the VPC. Type: Boolean |
| <code>route-table-id</code> | The ID of the route table. Type: String |
| <code>route.destination-cidr-block</code> | The CIDR range specified in a route in the table. Type: String |
| <code>route.gateway-id</code> | The ID of a gateway specified in a route in the table. Type: String |
| <code>route.instance-id</code> | The ID of an instance specified in a route in the table. Type: String |

Amazon Elastic Compute Cloud API Reference
Description

| Filter Name | Description |
|--------------------------|--|
| <code>route.state</code> | <p>The state of a route in the route table. The <code>blackhole</code> state indicates that the route's target isn't available (e.g., the specified gateway isn't attached to the VPC, the specified NAT instance has been terminated, etc.).</p> <p>Type: String Valid values: <code>active</code> <code>blackhole</code></p> |
| <code>tag-key</code> | <p>The key of a tag assigned to the resource. This filter is independent of the <code>tag-value</code> filter. For example, if you use both the filter <code>tag-key=Purpose</code> and the filter <code>tag-value=X</code>, you get any resources assigned both the tag key <code>Purpose</code> (regardless of what the tag's value is), and the tag value <code>X</code> (regardless of what the tag's key is). If you want to list only resources where <code>Purpose=X</code>, see the <code>tag:key</code> filter later in this table.</p> <p>For more information about tags, see Using Tags in the <i>Amazon Elastic Compute Cloud User Guide</i>.</p> <p>Type: String</p> |
| <code>tag-value</code> | <p>The value of a tag assigned to the resource. This filter is independent of the <code>tag-key</code> filter.</p> <p>Type: String</p> |
| <code>tag:key</code> | <p>Filters the results based on a specific tag/value combination.</p> <p>Example: To list just the resources assigned tag <code>Purpose=X</code>, then specify:</p> <pre>Filter.1.Name=tag:Purpose Filter.1.Value.1=X</pre> <p>Example: To list just resources assigned tag <code>Purpose=X</code> OR <code>Purpose=Y</code>, then specify:</p> <pre>Filter.1.Name=tag:Purpose Filter.1.Value.1=X Filter.1.Value.2=Y</pre> |
| <code>vpc-id</code> | <p>The ID of the VPC the route table is in.</p> <p>Type: String</p> |

For more information about Amazon Virtual Private Cloud and route tables, see [Route Tables](#) in the *Amazon Virtual Private Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|-------------------------|---|----------|
| <i>RouteTableId.n</i> | One or more route table IDs. Type: string Default: Returns all route tables, or only those otherwise specified. | No |
| <i>Filter.n.Name</i> | The name of a filter. See the preceding table for a list of allowed filter names. Type: String Default: None | No |
| <i>Filter.n.Value.m</i> | A value for the filter. See the preceding table for a list of allowed filter values for each filter. Type: String Default: None | No |

Response Elements

The elements in the following table are wrapped in a `DescribeRouteTablesResponse` structure.

| Name | Description |
|----------------------------|--|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>routeTableSet</code> | A list of route tables, each one wrapped in an <code>item</code> element. Type: RouteTableType (p. 465) |

Examples

Example Request

This example describes all route tables in the VPC.

```
https://ec2.amazonaws.com/?Action=DescribeRouteTables
```

Example Response

The first route table in the returned list is the VPC's main route table. Its association ID represents the association between the table and the VPC

```
DescribeRouteTablesResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>6f570b0b-9c18-4b07-bdec-73740dcf861a</requestId>
  <routeTableSet>
    <item>
```

```
<routeTableId>rtb-13ad487a</routeTableId>
<vpcId>vpc-11ad4878</vpcId>
<routeSet>
  <item>
    <destinationCidrBlock>10.0.0.0/22</destinationCidrBlock>
    <gatewayId>local</gatewayId>
    <state>active</state>
  </item>
</routeSet>
<associationSet>
  <item>
    <routeTableAssociationId>rtbassoc-12ad487b</routeTableAssoci
ationId>
    <routeTableId>rtb-13ad487a</routeTableId>
    <main>true</main>
  </item>
</associationSet>
<tagSet/>
</item>
<item>
  <routeTableId>rtb-f9ad4890</routeTableId>
  <vpcId>vpc-11ad4878</vpcId>
  <routeSet>
    <item>
      <destinationCidrBlock>10.0.0.0/22</destinationCidrBlock>
      <gatewayId>local</gatewayId>
      <state>active</state>
    </item>
    <item>
      <destinationCidrBlock>0.0.0.0/0</destinationCidrBlock>
      <gatewayId>igw-eaad4883</gatewayId>
      <state>active</state>
    </item>
  </routeSet>
  <associationSet>
    <item>
      <routeTableAssociationId>rtbassoc-faad4893</routeTableAssoci
ationId>
      <routeTableId>rtb-f9ad4890</routeTableId>
      <subnetId>subnet-15ad487c</subnetId>
    </item>
  </associationSet>
  <tagSet/>
</item>
</routeTableSet>
</DescribeRouteTablesResponse>
```

Related Operations

- [AssociateRouteTable](#) (p. 23)
- [DisassociateRouteTable](#) (p. 304)
- [DeleteRouteTable](#) (p. 123)
- [CreateRouteTable](#) (p. 82)
- [ReplaceRouteTableAssociation](#) (p. 352)

DescribeSecurityGroups

Description

Returns information about security groups in your account. This includes both EC2 security groups and VPC security groups. For information about how the two types of groups differ, see [Security Groups](#) in the *Amazon Virtual Private Cloud User Guide*.

You can filter the results to return information only about security groups that match criteria you specify. For example, you could get information about groups whose name contains a particular string. You can specify multiple values for a filter. A security group must match at least one of the specified values for it to be included in the results.

You can specify multiple filters (e.g., the group's name contains a particular string, and the group gives permission to another security group with a different string in its name). The result includes information for a particular group only if it matches *all* your filters. If there's no match, no special message is returned; the response is simply empty.

Important

Filters are based on literal strings only. This is important to remember when you want to use filters to return only security groups with access allowed on a specific port number or numbers. For example, let's say you want to get all groups that have access on port 22. And let's say GroupA gives access on a range of ports using `fromPort=20` and `toPort=30`. If you filter with `ip-permission.from-port=22` or `ip-permission.to-port=22` (or both), GroupA is not returned in the results. It is only returned in the results if you specify `ip-permission.from-port=20` or `ip-permission.to-port=30` (or both).

You can use wildcards with the filter values: `*` matches zero or more characters, and `?` matches exactly one character. You can escape special characters using a backslash before the character. For example, a value of `*amazon\?\` searches for the literal string `*amazon?\`.

The following table shows the available filters.

| Filter Name | Description |
|--------------------------------------|--|
| <code>description</code> | The description of the security group. Type: String |
| <code>group-id</code> | The ID of the security group. Type: String |
| <code>group-name</code> | The name of the security group. Type: String |
| <code>ip-permission.cidr</code> | The CIDR range that has been granted the permission. Type: String |
| <code>ip-permission.from-port</code> | The start of port range for the TCP and UDP protocols, or an ICMP type number. Type: String |

| Filter Name | Description |
|---------------------------------------|---|
| <code>ip-permission.group-name</code> | The name of security group that has been granted the permission. Type: String |
| <code>ip-permission.protocol</code> | The IP protocol for the permission. Type: String Valid values: <code>tcp</code> <code>udp</code> <code>icmp</code> or a protocol number |
| <code>ip-permission.to-port</code> | The end of port range for the TCP and UDP protocols, or an ICMP code. Type: String |
| <code>ip-permission.user-id</code> | The ID of an AWS account that has been granted the permission. Type: String |
| <code>owner-id</code> | The AWS account ID of the owner of the security group. Type: String |
| <code>tag-key</code> | The key of a tag assigned to the security group. Type: String |
| <code>tag-value</code> | The value of a tag assigned to the security group. Type: String |

Request Parameters

| Name | Description | Required |
|-------------------------|--|----------|
| <i>GroupName.n</i> | One or more security group names. Type: String Default: Describes all groups you own, or only those otherwise specified. | No |
| <i>GroupId.n</i> | One or more security group IDs. Type: String Default: Describes all groups you own, or only those otherwise specified. | No |
| <i>Filter.n.Name</i> | The name of a filter. See the preceding table for a list of allowed filter names. Type: String Default: None | No |
| <i>Filter.n.Value.m</i> | A value for the filter. See the preceding table for a list of allowed values for each filter. Type: String Default: None | No |

Response Elements

The elements in the following table are wrapped in a `DescribeSecurityGroupsResponse` structure.

| Name | Description |
|--------------------------------|--|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>securityGroupInfo</code> | A list of security groups, each one wrapped in an <code>item</code> element. Type: SecurityGroupItemType (p. 470) |

Examples

Example Request

This example returns information about two security groups that are configured for the account.

```
https://ec2.amazonaws.com/?Action=DescribeSecurityGroups
&GroupName.1=WebServers
&GroupName.2=RangedPortsBySource
&AUTHPARAMS
```

Example Response

```
<DescribeSecurityGroupsResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <securityGroupInfo>
    <item>
      <ownerId>111122223333</ownerId>
      <groupId>sg-443d0a12</groupId>
      <groupName>WebServers</groupName>
      <groupDescription>Web Servers</groupDescription>
      <vpcId/>
      <ipPermissions>
        <item>
          <ipProtocol>tcp</ipProtocol>
          <fromPort>80</fromPort>
          <toPort>80</toPort>
          <groups/>
          <ipRanges>
            <item>
              <cidrIp>0.0.0.0/0</cidrIp>
            </item>
          </ipRanges>
        </item>
      </ipPermissions>
      <ipPermissionsEgress/>
      <tagSet/>
    </item>
    <item>
```

```
<ownerId>111122223333</ownerId>
<groupId>sg-5ff8a023</groupId>
<groupName>RangedPortsBySource</groupName>
<groupDescription>Group A</groupDescription>
<ipPermissions>
  <item>
    <ipProtocol>tcp</ipProtocol>
    <fromPort>6000</fromPort>
    <toPort>7000</toPort>
    <groups>
      <item>
        <userId>111122223333</userId>
        <groupId>sg-99gh4012</groupId>
        <groupName>Group B</groupName>
      </item>
    </groups>
    <ipRanges/>
  </item>
</ipPermissions>
<ipPermissionsEgress/>
<tagSet/>
</item>
</securityGroupInfo>
</DescribeSecurityGroupsResponse>
```

Example Request

This example returns information about all security groups that grant access over TCP specifically on port 22 from instances in either the `app_server_group` or `database_group`.

```
https://ec2.amazonaws.com/?Action=DescribeSecurityGroups
&Filter.1.Name=ip-permission.protocol
&Filter.1.Value.1=tcp
&Filter.2.Name=ip-permission.from-port
&Filter.2.Value.1=22
&Filter.3.Name=ip-permission.to-port
&Filter.3.Value.1=22
&Filter.4.Name=ip-permission.group-name
&Filter.4.Value.1=app_server_group
&Filter.4.Value.2=database_group
&AUTHPARAMS
```

Related Operations

- [CreateSecurityGroup](#) (p. 84)
- [AuthorizeSecurityGroupIngress](#) (p. 36)
- [RevokeSecurityGroupIngress](#) (p. 376)
- [DeleteSecurityGroup](#) (p. 125)

DescribeSnapshotAttribute

Description

Returns information about an attribute of a snapshot. You can get information about only one attribute per call.

Request Parameters

| Name | Description | Required |
|-------------------|---|----------|
| <i>SnapshotId</i> | The ID of the Amazon EBS snapshot. Type: String Default: None | Yes |
| <i>Attribute</i> | The snapshot attribute. Type: String Default: None Valid values: <code>createVolumePermission</code> <code>productCodes</code> | Yes |

Response Elements

The elements in the following table are wrapped in a `DescribeSnapshotAttributeResponse` structure.

| Name | Description |
|-------------------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>snapshotId</code> | The ID of the Amazon EBS snapshot. Type: <code>xsd:string</code> |
| <code>createVolumePermission</code> | A list of permissions for creating volumes from the snapshot. Each permission is wrapped in an <code>item</code> element. Type: CreateVolumePermissionItemType (p. 411) |
| <code>productCodes</code> | A list of product codes. Each product code is wrapped in an <code>item</code> element type that contains a product code and a type. Type: ProductCodesSetItemType (p. 461) |

Examples

Example Request

This example describes permissions for the `snap-78a54011` snapshot.

```
https://ec2.amazonaws.com/?Action=DescribeSnapshotAttribute
&SnapshotId=snap-78a54011
&Attribute=createVolumePermission
&AUTHPARAMS
```

Example Response

```
<DescribeSnapshotAttributeResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <snapshotId>snap-78a54011</snapshotId>
  <createVolumePermission>
    <item>
      <group>all</group>
    </item>
  </createVolumePermission>
</DescribeSnapshotAttributeResponse>
```

Example Request

This example describes product codes associated with the snap-78a12345 snapshot.

```
https://ec2.amazonaws.com/?Action=DescribeSnapshotAttribute
&SnapshotId=snap-78a12345
&Attribute=productCodes
&AUTHPARAMS
```

Example Response

```
<DescribeSnapshotAttributeResponse xmlns="http://ec2.amazonaws.com/doc/2012-04-01/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <snapshotId>snap-78a12345</snapshotId>
  <productCodes>
    <item>
      <productCode>a1b2c3d4e5f6g7h8i9j10k11</productCode>
      <type>marketplace</type>
    </item>
  </productCodes>
</DescribeSnapshotAttributeResponse>
```

Related Operations

- [ModifySnapshotAttribute](#) (p. 329)
- [DescribeSnapshots](#) (p. 246)
- [ResetSnapshotAttribute](#) (p. 371)
- [CreateSnapshot](#) (p. 86)

DescribeSnapshots

Description

Returns information about Amazon EBS snapshots available to you. Snapshots available to you include public snapshots available for any AWS account to launch, private snapshots you own, and private snapshots owned by another AWS account but for which you've been given explicit create volume permissions.

The create volume permissions fall into 3 categories:

| Permission | Description |
|------------|--|
| public | The owner of the snapshot granted create volume permissions for the snapshot to the <code>all</code> group. All AWS accounts have create volume permissions for these snapshots. |
| explicit | The owner of the snapshot granted create volume permissions to a specific AWS account. |
| implicit | An AWS account has implicit create volume permissions for all snapshots it owns. |

The list of snapshots returned can be modified by specifying snapshot IDs, snapshot owners, or AWS accounts with create volume permissions. If no options are specified, Amazon EC2 returns all snapshots for which you have create volume permissions.

If you specify one or more snapshot IDs, only snapshots that have the specified IDs are returned. If you specify an invalid snapshot ID, an error is returned. If you specify a snapshot ID for which you do not have access, it will not be included in the returned results.

If you specify one or more snapshot owners, only snapshots from the specified owners and for which you have access are returned. The results can include the AWS account IDs of the specified owners, `amazon` for snapshots owned by Amazon, or `self` for snapshots that you own.

If you specify a list of restorable users, only snapshots with create snapshot permissions for those users are returned. You can specify AWS account IDs (if you own the snapshot(s)), `self` for snapshots for which you own or have explicit permissions, or `all` for public snapshots.

You can filter the results to return information only about snapshots that match criteria you specify. For example, you could get information about snapshots whose status is `pending`. You can specify multiple values for a filter (e.g., the snapshot's status is either `pending` or `completed`). A snapshot must match at least one of the specified values for it to be included in the results.

You can specify multiple filters (e.g., the snapshot's status is `pending`, and it is tagged with a particular value). The result includes information for a particular snapshot only if it matches *all* your filters. If there's no match, no special message is returned; the response is simply empty.

You can use wildcards with the filter values: `*` matches zero or more characters, and `?` matches exactly one character. You can escape special characters using a backslash before the character. For example, a value of `*amazon\?\` searches for the literal string `*amazon?\`.

The following table shows the available filters.

**Amazon Elastic Compute Cloud API Reference
Description**

| Filter Name | Description |
|-------------|---|
| description | A description of the snapshot. Type: String |
| owner-alias | The AWS account alias (e.g., amazon) that owns the snapshot. Type: String |
| owner-id | The ID of the AWS account that owns the snapshot. Type: String |
| progress | The progress of the snapshot, as a percentage (e.g., 80%). Type: String |
| snapshot-id | The snapshot ID. Type: String |
| start-time | The time stamp when the snapshot was initiated. Type: xsd:dateTime |
| status | The status of the snapshot. Type: String Valid values: pending completed error |
| tag-key | The key of a tag assigned to the resource. This filter is independent of the tag-value filter. For example, if you use both the filter tag-key=Purpose and the filter tag-value=X, you get any resources assigned both the tag key Purpose (regardless of what the tag's value is), and the tag value X (regardless of what the tag's key is). If you want to list only resources where Purpose=X, see the tag:key filter later in this table. For more information about tags, see Using Tags in the <i>Amazon Elastic Compute Cloud User Guide</i> . Type: String |
| tag-value | The value of a tag assigned to the resource. This filter is independent of the tag-key filter. Type: String |
| tag:key | Filters the results based on a specific tag/value combination. Example: To list just the resources assigned tag Purpose=X, then specify: Filter.1.Name=tag:Purpose Filter.1.Value.1=X Example: To list just resources assigned tag Purpose=X OR Purpose=Y, then specify: Filter.1.Name=tag:Purpose Filter.1.Value.1=X Filter.1.Value.2=Y |
| volume-id | The ID of the volume the snapshot is for. Type: String |
| volume-size | The size of the volume, in GiB (e.g., 20). Type: String |

Request Parameters

| Name | Description | Required |
|-------------------------|--|----------|
| <i>SnapshotId.n</i> | One or more snapshot IDs. Type: String Default: Describes snapshots for which you have launch permissions. | No |
| <i>Owner.n</i> | Returns the snapshots owned by the specified owner. Multiple owners can be specified. Type: String Valid values: <code>self</code> <code>amazon</code> AWS Account ID Default: None | No |
| <i>RestorableBy.n</i> | One or more AWS accounts IDs that can create volumes from the snapshot. Type: String Default: None | No |
| <i>Filter.n.Name</i> | The name of a filter. See the preceding table for a list of allowed filter names. Type: String Default: None | No |
| <i>Filter.n.Value.m</i> | A value for the filter. See the preceding table for a list of allowed values for each filter. Type: String Default: None | No |

Response Elements

The elements in the following table are wrapped in a `DescribeSnapshotsResponse` structure.

| Name | Description |
|--------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>snapshotSet</code> | A list of snapshots. Each snapshot is wrapped in an <code>item</code> element. Type: DescribeSnapshotsSetItemResponseType (p. 419) |

Examples

Example Request

This example describes snapshot `snap-78a54011`.

```
https://ec2.amazonaws.com/?Action=DescribeSnapshots
&SnapshotId=snap-78a54011
&AUTHPARAMS
```

Example Response

```
<DescribeSnapshotsResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <snapshotSet>
    <item>
      <snapshotId>snap-78a54011</snapshotId>
      <volumeId>vol-4d826724</volumeId>
      <status>pending</status>
      <startTime>2008-05-07T12:51:50.000Z</startTime>
      <progress>80&#x0025;</progress>
      <ownerId>111122223333</ownerId>
      <volumeSize>10</volumeSize>
      <description>Daily Backup</description>
      <tagSet/>
    </item>
  </snapshotSet>
</DescribeSnapshotsResponse>
```

Example Request

This example filters the results to display only snapshots with the `pending` status, and that are also tagged with a value that includes the string `db_`.

```
https://ec2.amazonaws.com/?Action=DescribeSnapshots
&Filter.1.Name=status
&Filter.1.Value.1=pending
&Filter.2.Name=tag-value
&Filter.2.Value.1=*db_*
&AUTHPARAMS
```

Example Response

```
<DescribeSnapshotsResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <snapshotSet>
    <item>
      <snapshotId>snap-1a2b3c4d</snapshotId>
      <volumeId>vol-8875daef</volumeId>
      <status>pending</status>
      <startTime>2010-07-29T04:12:01.000Z</startTime>
      <progress>30%</progress>
      <ownerId>111122223333</ownerId>
      <volumeSize>15</volumeSize>
      <description>Daily Backup</description>
      <tagSet>
        <item>
          <key>Purpose</key>
          <value>demo_db_14_backup</value>
        </item>
      </tagSet>
    </item>
  </snapshotSet>
</DescribeSnapshotsResponse>
```



```
        </item>  
      </tagSet>  
    </item>  
  </snapshotSet>  
</DescribeSnapshotsResponse>
```

Related Operations

- [CreateSnapshot](#) (p. 86)
- [DeleteSnapshot](#) (p. 127)

DescribeSpotDatafeedSubscription

Description

Describes the datafeed for Spot Instances. For more information about Spot Instances, see [Spot Instances](#) in the *Amazon Elastic Compute Cloud User Guide*.

Request Parameters

The `DescribeSpotDatafeedSubscription` operation does not have any request parameters.

Response Elements

The elements in the following table are wrapped in a `DescribeSpotDatafeedSubscriptionResponse` structure.

| Name | Description |
|---------------------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>spotDatafeedSubscription</code> | The Spot Instance datafeed subscription. Type: SpotDatafeedSubscriptionType (p. 471) |

Examples

Example Request

This example describes the datafeed for the account.

```
https://ec2.amazonaws.com/?Action=DescribeSpotDatafeedSubscription
&AUTHPARAMS
```

Example Response

```
<DescribeSpotDatafeedSubscriptionResponse xmlns="http://ec2.amazon
aws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <spotDatafeedSubscription>
    <ownerId>111122223333</ownerId>
    <bucket>myawsbucket</bucket>
    <prefix>spotdata</prefix>
    <state>Active</state>
  </spotDatafeedSubscription>
</DescribeSpotDatafeedSubscriptionResponse>
```

Related Operations

- [CreateSpotDatafeedSubscription](#) (p. 89)

- [DeleteSpotDatafeedSubscription](#) (p. 129)

DescribeSpotInstanceRequests

Description

Describes the Spot Instance requests that belong to your account. Spot Instances are instances that Amazon EC2 starts on your behalf when the maximum price that you specify exceeds the current Spot Price. Amazon EC2 periodically sets the Spot Price based on available Spot Instance capacity and current Spot Instance requests. For more information about Spot Instances, see [Spot Instances](#) in the *Amazon Elastic Compute Cloud User Guide*.

You can filter the results to return information only about Spot Instance requests that match criteria you specify. For example, you could get information about requests where the Spot Price you specified is a certain value (however, you can't use greater than or less than comparison, but you can use * and ? wildcards). You can specify multiple values for a filter. A Spot Instance request must match at least one of the specified values for it to be included in the results.

You can specify multiple filters (e.g., the Spot Price is equal to a particular value, and the instance type is m1.small). The result includes information for a particular request only if it matches *all* your filters. If there's no match, no special message is returned; the response is simply empty.

You can use wildcards with the filter values: * matches zero or more characters, and ? matches exactly one character. You can escape special characters using a backslash before the character. For example, a value of `*amazon\?\` searches for the literal string `*amazon?\`.

The following table shows the available filters.

| Filter Name | Description |
|--|---|
| <code>availability-zone-group</code> | The Availability Zone group. If you specify the same Availability Zone group for all Spot Instance requests, all Spot Instances are launched in the same Availability Zone. Type: String |
| <code>create-time</code> | The time stamp when the Spot Instance request was created. Type: String |
| <code>fault-code</code> | The fault code related to the request. Type: String |
| <code>fault-message</code> | The fault message related to the request. Type: String |
| <code>instance-id</code> | The ID of the instance that fulfilled the request. Type: String |
| <code>launch-group</code> | The Spot Instance launch group. Launch groups are Spot Instances that launch together and terminate together. Type: String |
| <code>launch.block-device-mapping.delete-on-termination</code> | Indicates whether an Amazon EBS volume mapped to the instance is deleted on instance termination. Type: Boolean |

Amazon Elastic Compute Cloud API Reference
Description

| Filter Name | Description |
|--|---|
| <code>launch.block-device-mapping.device-name</code> | The device name (e.g., <code>/dev/sdh</code>) for an Amazon EBS volume mapped to the instance. Type: String |
| <code>launch.block-device-mapping.snapshot-id</code> | The ID of a snapshot mapped to the instance. Type: String |
| <code>launch.block-device-mapping.volume-size</code> | The size of an Amazon EBS volume mapped to the instance (in GiB). Type: String |
| <code>launch.group-id</code> | A security group the instance is in. Type: String |
| <code>launch.image-id</code> | The AMI ID. Type: String |
| <code>launch.instance-type</code> | The type of instance (e.g., <code>m1.small</code>). Type: String |
| <code>launch.kernel-id</code> | The kernel ID. Type: String |
| <code>launch.key-name</code> | The name of the key pair the instance launched with. Type: String |
| <code>launch.monitoring-enabled</code> | Indicates whether monitoring is enabled for the Spot Instance. Type: Boolean |
| <code>launch.ramdisk-id</code> | The RAM disk ID. Type: String |
| <code>launch.network-interface.network-interface-id</code> | The ID of the network interface (available only in Amazon Virtual Private Cloud). Type: String |
| <code>launch.network-interface.device-index</code> | The index of the device for the network interface attachment on the instance (available only in Amazon Virtual Private Cloud). Type: Integer |
| <code>launch.network-interface.subnet-id</code> | The ID of the subnet that the instance is in (available only in Amazon Virtual Private Cloud). Type: String |
| <code>launch.network-interface.description</code> | A description of the network interface (available only in Amazon Virtual Private Cloud). Type: String |

**Amazon Elastic Compute Cloud API Reference
Description**

| Filter Name | Description |
|---|---|
| <code>launch.network-interface.private-ip-address</code> | The primary private IP address of the network interface (available only in Amazon Virtual Private Cloud). Type: String |
| <code>launch.network-interface.delete-on-termination</code> | Indicates whether the network interface is deleted when the instance is terminated (available only in Amazon Virtual Private Cloud). Type: Boolean |
| <code>launch.network-interface.group-id</code> | The ID of the security group associated with the network interface (available only in Amazon Virtual Private Cloud). Type: String |
| <code>launch.network-interface.group-name</code> | The name of the security group associated with the network interface (available only in Amazon Virtual Private Cloud). Type: String |
| <code>launch.network-interface.addresses.primary</code> | Specifies whether or not the IP address is the primary private IP address (available only in Amazon Virtual Private Cloud). Type: String |
| <code>product-description</code> | The product description associated with the instance. Type: String Valid values: Linux/UNIX Windows |
| <code>spot-instance-request-id</code> | The Spot Instance request ID. Type: String |
| <code>spot-price</code> | The maximum hourly price for any Spot Instance launched to fulfill the request. Type: String |
| <code>state</code> | The state of the Spot Instance request. Type: String Valid values: active cancelled open closed failed |

**Amazon Elastic Compute Cloud API Reference
Description**

| Filter Name | Description |
|----------------------------|--|
| tag-key | <p>The key of a tag assigned to the resource. This filter is independent of the <code>tag-value</code> filter. For example, if you use both the filter <code>tag-key=Purpose</code> and the filter <code>tag-value=X</code>, you get any resources assigned both the tag key <code>Purpose</code> (regardless of what the tag's value is), and the tag value <code>X</code> (regardless of what the tag's key is). If you want to list only resources where <code>Purpose=X</code>, see the <code>tag:key</code> filter later in this table.</p> <p>For more information about tags, see Using Tags in the <i>Amazon Elastic Compute Cloud User Guide</i>.</p> <p>Type: String</p> |
| tag-value | <p>The value of a tag assigned to the resource. This filter is independent of the <code>tag-key</code> filter.</p> <p>Type: String</p> |
| tag: <i>key</i> | <p>Filters the results based on a specific tag/value combination.</p> <p>Example: To list just the resources assigned tag <code>Purpose=X</code>, then specify:</p> <pre>Filter.1.Name=tag:Purpose Filter.1.Value.1=X</pre> <p>Example: To list just resources assigned tag <code>Purpose=X OR Purpose=Y</code>, then specify:</p> <pre>Filter.1.Name=tag:Purpose Filter.1.Value.1=X Filter.1.Value.2=Y</pre> |
| type | <p>The type of Spot Instance request.</p> <p>Type: String</p> <p>Valid values: <code>one-time</code> <code>persistent</code></p> |
| launched-availability-zone | <p>The Availability Zone in which the bid is launched.</p> <p>Type: String</p> <p>Valid values: <code>us-east-1a</code>, etc.</p> |
| valid-from | <p>The start date of the request.</p> <p>Type: <code>xsd:dateTime</code></p> |
| valid-until | <p>The end date of the request.</p> <p>Type: <code>xsd:dateTime</code></p> |

Request Parameters

| Name | Description | Required |
|---------------------------------|--|----------|
| <i>SpotInstanceRequestIds.n</i> | One or more Spot Instance request IDs. Type: String Default: None | No |
| <i>Filter.n.Name</i> | The name of a filter. See the preceding table for a list of allowed filter names. Type: String Default: None | No |
| <i>Filter.n.Value.m</i> | A value for the filter. See the preceding table for a list of allowed values for each filter. Type: String Default: None | No |

Response Elements

The elements in the following table are wrapped in a `DescribeSpotInstanceRequestsResponse` structure.

| Name | Description |
|-------------------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>spotInstanceRequestSet</code> | A list of Spot Instance requests. Each request is wrapped in an <code>item</code> element. Type: SpotInstanceRequestSetItemType (p. 472) |
| <code>networkInterfaceSet</code> | Information about the network interface. Type: InstanceNetworkInterfaceSetItemRequestType (p. 440) |

Examples

Example Request

This example returns information about current Spot Instance requests.

```
https://ec2.amazonaws.com/?Action=DescribeSpotInstanceRequests
&AUTHPARAMS
```

Example Response

```
<DescribeSpotInstanceRequestsResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/"
```



```
<requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
<spotInstanceRequestSet>
  <item>
    <spotInstanceRequestId>sir-e1471206</spotInstanceRequestId>
    <spotPrice>0.09</spotPrice>
    <type>one-time</type>
    <state>active</state>
    <launchSpecification>
      <imageId>ami-813968c4</imageId>
      <keyName>MyKey</keyName>
      <groupSet>
        <item>
          <groupId>default</groupId>
        </item>
      </groupSet>
      <instanceType>m1.small</instanceType>
      <blockDeviceMapping/>
      <monitoring>
        <enabled>>false</enabled>
      </monitoring>
    </launchSpecification>
    <instanceId>i-992cf7dd</instanceId>
    <createTime>2010-09-13T23:50:44.000Z</createTime>
    <productDescription>Linux/UNIX</productDescription>
    <launchedAvailabilityZone>us-east-1c</launchedAvailabilityZone>
  </item>
</spotInstanceRequestSet/>
<DescribeSpotInstanceRequestsResponse>
```

Example Request

This example describes all persistent Spot Instance requests that have resulted in the launch of at least one m1.small instance, that has been fulfilled in the us-east-1a Availability Zone, and that also has monitoring enabled.

```
https://ec2.amazonaws.com/?Action=DescribeSpotInstanceRequests
&Filter.1.Name=type
&Filter.1.Value.1=persistent
&Filter.2.Name=instance-type
&Filter.2.Value.1=m1.small
&Filter.3.Name=monitoring-enabled
&Filter.3.Value.1=true
&Filter.4.Name=launched-availability-zone
&Filter.4.Value.1=us-east-1a
&AUTHPARAMS
```

Related Operations

- [RequestSpotInstances](#) (p. 357)
- [CancelSpotInstanceRequests](#) (p. 49)
- [DescribeSpotPriceHistory](#) (p. 259)

DescribeSpotPriceHistory

Description

Describes the Spot Price history. Spot Instances are instances that Amazon EC2 starts on your behalf when the maximum price that you specify exceeds the current Spot Price. Amazon EC2 periodically sets the Spot Price based on available Spot Instance capacity and current Spot Instance requests. For more information about Spot Instances, see [Spot Instances](#) in the *Amazon Elastic Compute Cloud User Guide*.

When you use the `availability-zone` option, this command describes the price history for the specified Availability Zone with the most recent set of prices listed first. If you don't specify an Availability Zone, the command returns the prices across all Availability Zones, starting with the most recent set. However, if you use this command with versions of the API earlier than the 2011-05-15 version, this command returns the lowest price across the Region for the given time period. The prices returned are listed in chronological order — from the oldest to the most recent.

Note

Our policy is to provide filters for all "describe" calls so you can limit the results to your specified criteria. Therefore, you can use filters to limit the results when describing Spot Price histories, even though you can use the regular request parameters to do something similar.

For example, you could use the regular request parameters or a filter to get the history for a particular instance type. You can specify multiple request parameters or multiple filters (e.g., limit the results to the `m2.xlarge` instance type, and only for Windows instances). The result includes information for a particular price history only if it matches *all* your request parameters or filters. If there's no match, no special message is returned; the response is simply empty.

You can use wildcards with the filter values: `*` matches zero or more characters, and `?` matches exactly one character. You can escape special characters using a backslash before the character. For example, a value of `*amazon\?\` searches for the literal string `*amazon?\`.

The following table shows the available filters.

| Filter Name | Description |
|----------------------------------|---|
| <code>instance-type</code> | The type of instance (e.g., <code>m1.small</code>). Type: String |
| <code>product-description</code> | The product description for the Spot Price. Type: String Valid values: <code>Linux/UNIX SUSE Linux Windows Linux/UNIX (Amazon VPC) SUSE Linux (Amazon VPC) Windows (Amazon VPC)</code> |
| <code>spot-price</code> | The Spot Price. The value must match exactly (or use wildcards; greater than or less than comparison is not supported). Type: String |
| <code>timestamp</code> | The timestamp of the Spot Price history, e.g., <code>2010-08-16T05:06:11.000Z</code> . You can use wildcards (<code>*</code> and <code>?</code>). Greater than or less than comparison is not supported. Type: <code>xsd:dateTime</code> |
| <code>availability-zone</code> | The Availability Zone for which prices should be returned. Type: String |

Request Parameters

| Name | Description | Required |
|-----------------------------|---|----------|
| <i>StartTime</i> | The start date and time of the Spot Instance price history data. Type: DateTime Default: None | No |
| <i>EndTime</i> | The end date and time of the Spot Instance price history data. Type: DateTime Default: None | No |
| <i>InstanceType.n</i> | The instance type to return. Type: String Valid values: <code>m1.small</code> <code>m1.large</code> <code>m1.xlarge</code> <code>c1.medium</code> <code>c1.xlarge</code> <code>m2.xlarge</code> <code>m2.2xlarge</code> <code>m2.4xlarge</code> <code>t1.micro</code> Default: None | No |
| <i>ProductDescription.n</i> | Filters the results by basic product description. Type: String Valid values: <code>Linux/UNIX</code> <code>SUSE Linux</code> <code>Windows</code> <code>Linux/UNIX (Amazon VPC)</code> <code>SUSE Linux (Amazon VPC)</code> <code>Windows (Amazon VPC)</code> Default: Returns all information | No |
| <i>Filter.n.Name</i> | The name of a filter. See the preceding table for a list of allowed filter names. Type: String Default: None | No |
| <i>Filter.n.Value.m</i> | A value for the filter. See the preceding table for a list of allowed values for each filter. Type: String Default: None | No |
| <i>AvailabilityZone</i> | Filters the results by availability zone. Type: String Valid values: <code>us-east-1a</code> , etc. Default: None | No |
| <i>MaxResults</i> | Specifies the number of rows to return. Type: int Valid values: 0 Default: None | No |

| Name | Description | Required |
|------------------|---|----------|
| <i>NextToken</i> | Specifies the next set of rows to return. Type: String Valid values: A NextToken value returned by a previous call of the API. Default: None | No |

Response Elements

The elements in the following table are wrapped in a `DescribeSpotPriceHistoryResponse` structure.

| Name | Description |
|---------------------|--|
| requestId | The ID of the request. Type: xsd:string |
| spotPriceHistorySet | A list of historical Spot Prices. Each price is wrapped in an <code>item</code> element. Type: SpotPriceHistorySetItemType (p. 474) |
| nextToken | The string marking the next set of results returned. Displays empty if there are no more results to be returned. Type: xsd:string |

Examples

Example Request

This example returns Spot Price history for a particular day in December 2009 for Availability Zone us-east-1a.

```
https://ec2.amazonaws.com/?Action=DescribeSpotPriceHistory
&StartTime=2009-12-04T00:00:00.000Z
&EndTime=2009-12-04T23:59:59.000Z
&AvailabilityZone=us-east-1a
&AUTHPARAMS
```

This request uses filters instead of regular request parameters to achieve the same results.

```
https://ec2.amazonaws.com/?Action=DescribeSpotPriceHistory
&Filter.1.Name=timestamp
&Filter.1.Value.1=2009-12-04*
&Filter.2.Name=availability-zone
&Filter.2.Value.1=us-east-1a
&AUTHPARAMS
```

Example Response

```
<DescribeSpotPriceHistoryResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <spotPriceHistorySet>
    <item>
      <instanceType>m1.small</instanceType>
      <productDescription>Linux/UNIX</productDescription>
      <spotPrice>0.287</spotPrice>
      <timestamp>2009-12-04T20:56:05.000Z</timestamp>
      <availabilityZone>us-east-1a</availabilityZone>
    </item>
    <item>
      <instanceType>m1.small</instanceType>
      <productDescription>Windows</productDescription>
      <spotPrice>0.033</spotPrice>
      <timestamp>2009-12-04T22:33:47.000Z</timestamp>
      <availabilityZone>us-east-1a</availabilityZone>
    </item>
  </spotPriceHistorySet>
  <nextToken/>
</DescribeSpotPriceHistoryResponse>
```

Related Operations

- [DescribeSpotInstanceRequests](#) (p. 253)
- [RequestSpotInstances](#) (p. 357)
- [CancelSpotInstanceRequests](#) (p. 49)

DescribeSubnets

Description

Gives you information about your subnets. You can filter the results to return information only about subnets that match criteria you specify. For example, you could get information only about subnets whose state is `available`. You can specify multiple values for the filter. The subnet must match at least one of the specified values for it to be included in the results.

You can specify multiple filters (e.g., the subnet is in a particular VPC, and the subnet's state is `available`). The result includes information for a particular subnet only if it matches *all* your filters. If there's no match, no special message is returned; the response is simply empty.

You can use wildcards with the filter values: `*` matches zero or more characters, and `?` matches exactly one character. You can escape special characters using a backslash before the character. For example, a value of `*amazon\?\` searches for the literal string `*amazon?\`.

The following table shows the available filters.

| Filter Name | Description |
|---|--|
| <code>availability-zone</code> | The Availability Zone the subnet is in. Type: String |
| <code>available-ip-address-count</code> | The number of IP addresses in the subnet that are available. Type: String |
| <code>cidr</code> | The CIDR block of the subnet. The CIDR block you specify must exactly match the subnet's CIDR block for information to be returned for the subnet. Type: String Constraints: Must contain the slash followed by one or two digits (e.g., <code>/28</code>) |
| <code>state</code> | The state of the subnet. Type: String Valid values: <code>pending</code> <code>available</code> |
| <code>subnet-id</code> | The ID of the subnet. Type: String |
| <code>tag-key</code> | The key of a tag assigned to the resource. This filter is independent of the <code>tag-value</code> filter. For example, if you use both the filter <code>tag-key=Purpose</code> and the filter <code>tag-value=X</code> , you get any resources assigned both the tag key <code>Purpose</code> (regardless of what the tag's value is), and the tag value <code>X</code> (regardless of what the tag's key is). If you want to list only resources where <code>Purpose=X</code> , see the <code>tag:key</code> filter later in this table. For more information about tags, see Using Tags in the <i>Amazon Elastic Compute Cloud User Guide</i> . Type: String |
| <code>tag-value</code> | The value of a tag assigned to the resource. This filter is independent of the <code>tag-key</code> filter. Type: String |

| Filter Name | Description |
|----------------------|--|
| <code>tag:key</code> | Filters the results based on a specific tag/value combination. Example: To list just the resources assigned tag Purpose=X, then specify: <code>Filter.1.Name=tag:Purpose</code> <code>Filter.1.Value.1=X</code> Example: To list just resources assigned tag Purpose=X OR Purpose=Y, then specify: <code>Filter.1.Name=tag:Purpose</code> <code>Filter.1.Value.1=X</code> <code>Filter.1.Value.2=Y</code> |
| <code>vpc-id</code> | The ID of the VPC the subnet is in. Type: String |

For more information about Amazon Virtual Private Cloud and subnets, see the [Amazon Virtual Private Cloud User Guide](#).

Request Parameters

| Name | Description | Required |
|-------------------------------|--|----------|
| <code>SubnetId.n</code> | A subnet ID. You can specify more than one in the request. Type: String Default: Returns information about all your subnets | No |
| <code>Filter.n.Name</code> | The name of a filter. See the preceding table for a list of allowed filter names. Type: String Default: Returns information about all your subnets or those you specify by ID. | No |
| <code>Filter.n.Value.m</code> | A value for the filter. See the preceding table for a list of allowed values for each filter. Type: String Default: None | No |

Response Elements

The elements in the following table are wrapped in an `DescribeSubnetsResponsestructure`.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>subnetSet</code> | A list of subnets. Each subnet is wrapped in an <code>item</code> element. Type: SubnetType (p. 476) |

Examples

Example Request

This example gives a description of two subnets with IDs subnet-9d4a7b6c and subnet-6e7f829e.

```
https://ec2.amazonaws.com/?Action=DescribeSubnets
&SubnetId.1=subnet-9d4a7b6c
&SubnetId.2=subnet-6e7f829e
&AUTHPARAMS
```

Example Response

```
<DescribeSubnetsResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</requestId>
  <subnetSet>
    <item>
      <subnetId>subnet-9d4a7b6c</subnetId>
      <state>available</state>
      <vpcId>vpc-1a2b3c4d</vpcId>
      <cidrBlock>10.0.1.0/24</cidrBlock>
      <availableIpAddressCount>250</availableIpAddressCount>
      <availabilityZone>us-east-1a</availabilityZone>
      <tagSet/>
    </item>
    <item>
      <subnetId>subnet-6e7f829e</subnetId>
      <state>available</state>
      <vpcId>vpc-1a2b3c4d</vpcId>
      <cidrBlock>10.0.0.0/24</cidrBlock>
      <availableIpAddressCount>250</availableIpAddressCount>
      <availabilityZone>us-east-1a</availabilityZone>
      <tagSet/>
    </item>
  </subnetSet>
</DescribeSubnetsResponse>
```

Example Request

This example uses filters to give a description of any subnet you own that is in the VPC with ID vpc-1a2b3c4d or vpc-6e7f8a92, and whose state is available.

```
https://ec2.amazonaws.com/?Action=DescribeSubnets
&Filter.1.Name=vpc-id
&Filter.1.Value.1=vpc-1a2b3c4d
&Filter.1.Value.2=vpc-6e7f8a92
&Filter.2.Name=state
&Filter.2.Value.1=available
&AUTHPARAMS
```

Related Operations

- [CreateSubnet](#) (p. 91)

- [DeleteSubnet \(p. 130\)](#)

DescribeTags

Description

Lists your tags. For more information about tags, see [Using Tags](#) in the *Amazon Elastic Compute Cloud User Guide*.

You can use filters to limit the results when describing tags. For example, you could get only the tags for a particular resource type. You can specify multiple values for a filter. A tag must match at least one of the specified values for it to be included in the results.

You can specify multiple filters (e.g., limit the results to a specific resource type, and get only tags with values that contain the string `database`). The result includes information for a particular tag only if it matches *all* your filters. If there's no match, no special message is returned; the response is simply empty.

You can use wildcards with the filter values: `*` matches zero or more characters, and `?` matches exactly one character. You can escape special characters using a backslash before the character. For example, a value of `*amazon\?\` searches for the literal string `*amazon?`.

The following table shows the available filters.

| Filter Name | Description |
|----------------------------|---|
| <code>key</code> | The tag key. Type: String |
| <code>resource-id</code> | The resource ID. Type: String |
| <code>resource-type</code> | The resource type. Type: String Valid values: <code>customer-gateway dhcp-options image instance internet-gateway network-acl reserved-instances route-table security-group snapshot spot-instances-request subnet volume vpc vpn-connection vpn-gateway</code> |
| <code>value</code> | The tag value. Type: String |

Request Parameters

| Name | Description | Required |
|-------------------------------|--|----------|
| <code>Filter.n.Name</code> | The name of a filter. See the preceding table for a list of allowed filter names. Type: String Default: None | No |
| <code>Filter.n.Value.m</code> | A value for the filter. See the preceding table for a list of allowed values for each filter. Type: String Default: None | No |

Response Elements

The elements in the following table are wrapped in a `DescribeTagsResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>tagSet</code> | A list of tags. Each tag is wrapped in an <code>item</code> element. Type: TagSetItemType (p. 477) |

Examples

Example Request

This example describes all the tags in your account.

```
https://ec2.amazonaws.com/?Action=DescribeTags
&AUTHPARAMS
```

Sample response:

```
<DescribeTagsResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</requestId>
  <tagSet>
    <item>
      <resourceId>ami-1a2b3c4d</resourceId>
      <resourceType>image</resourceType>
      <key>webserver</key>
      <value/>
    </item>
    <item>
      <resourceId>ami-1a2b3c4d</resourceId>
      <resourceType>image</resourceType>
      <key>stack</key>
      <value>Production</value>
    </item>
    <item>
      <resourceId>i-5f4e3d2a</resourceId>
      <resourceType>instance</resourceType>
      <key>webserver</key>
      <value/>
    </item>
    <item>
      <resourceId>i-5f4e3d2a</resourceId>
      <resourceType>instance</resourceType>
      <key>stack</key>
      <value>Production</value>
    </item>
    <item>
      <resourceId>i-12345678</resourceId>
      <resourceType>instance</resourceType>
```

```
    <key>database_server</key>
    <value/>
  </item>
  <item>
    <resourceId>i-12345678</resourceId>
    <resourceType>instance</resourceType>
    <key>stack</key>
    <value>Test</value>
  </item>
</tagSet>
</DescribeTagsResponse>
```

Example Request

This example describes only the tags for the AMI with ID ami-1a2b3c4d.

```
https://ec2.amazonaws.com/?Action=DescribeTags
&Filter.1.Name=resource-id
&Filter.1.Value.1=ami-1a2b3c4d
&AUTHPARAMS
```

Sample response:

```
<DescribeTagsResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</requestId>
  <tagSet>
    <item>
      <resourceId>ami-1a2b3c4d</resourceId>
      <resourceType>image</resourceType>
      <key>webserver</key>
      <value/>
    </item>
    <item>
      <resourceId>ami-1a2b3c4d</resourceId>
      <resourceType>image</resourceType>
      <key>stack</key>
      <value>Production</value>
    </item>
  </tagSet>
</DescribeTagsResponse>
```

Example Request

This example describes the tags for all your instances.

```
https://ec2.amazonaws.com/?Action=DescribeTags
&Filter.1.Name=resource-type
&Filter.1.Value.1=instance
&AUTHPARAMS
```

Sample response:

```
<DescribeTagsResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</requestId>
  <tagSet>
    <item>
      <resourceId>i-5f4e3d2a</resourceId>
      <resourceType>instance</resourceType>
      <key>webserver</key>
      <value/>
    </item>
    <item>
      <resourceId>i-5f4e3d2a</resourceId>
      <resourceType>instance</resourceType>
      <key>stack</key>
      <value>Production</value>
    </item>
    <item>
      <resourceId>i-12345678</resourceId>
      <resourceType>instance</resourceType>
      <key>database_server</key>
      <value/>
    </item>
    <item>
      <resourceId>i-12345678</resourceId>
      <resourceType>instance</resourceType>
      <key>stack</key>
      <value>Test</value>
    </item>
  </tagSet>
</DescribeTagsResponse>
```

Example Request

This example describes the tags for all your instances tagged with the key *webserver*. Note that you can use wildcards with filters. So you could specify the value as *?ebserver* to find tags with the key *webserver* or *Webserver*.

```
https://ec2.amazonaws.com/?Action=DescribeTags
&Filter.1.Name=key
&Filter.1.Value.1=webserver
&AUTHPARAMS
```

Sample response:

```
<DescribeTagsResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</requestId>
  <tagSet>
    <item>
      <resourceId>i-5f4e3d2a</resourceId>
      <resourceType>instance</resourceType>
      <key>webserver</key>
      <value/>
    </item>
  </tagSet>
</DescribeTagsResponse>
```

Example Request

This example describes the tags for all your instances tagged with either `stack=Test` or `stack=Production`.

```
https://ec2.amazonaws.com/?Action=DescribeTags
&Filter.1.Name=resource-type
&Filter.1.Value.1=instance
&Filter.2.Name=key
&Filter.2.Value.1=stack
&Filter.3.Name=value
&Filter.3.Value.1=Test
&Filter.3.Value.2=Production
&AUTHPARAMS
```

Sample response:

```
<DescribeTagsResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</requestId>
  <tagSet>
    <item>
      <resourceId>i-5f4e3d2a</resourceId>
      <resourceType>instance</resourceType>
      <key>stack</key>
      <value>Production</value>
    </item>
    <item>
      <resourceId>i-12345678</resourceId>
      <resourceType>instance</resourceType>
      <key>stack</key>
      <value>Test</value>
    </item>
  </tagSet>
</DescribeTagsResponse>
```

Example Request

This example describes the tags for all your instances tagged with `Purpose=[empty string]`.

```
https://ec2.amazonaws.com/?Action=DescribeTags
&Filter.1.Name=resource-type
&Filter.1.Value.1=instance
&Filter.2.Name=key
&Filter.2.Value.1=Purpose
&Filter.3.Name=value
&Filter.3.Value.1=
&AUTHPARAMS
```

Related Operations

- [CreateTags](#) (p. 93)
- [DeleteTags](#) (p. 132)

DescribeVolumes

Description

Describes your Amazon EBS volumes. For more information about Amazon EBS, see [Using Amazon Elastic Block Store](#) in the *Amazon Elastic Compute Cloud User Guide*.

You can filter the results to return information only about volumes that match criteria you specify. For example, you could get information about volumes whose status is `available`. You can specify multiple values for a filter (e.g., the volume's status is either `available` or `in-use`). A volume must match at least one of the specified values for it to be included in the results.

You can specify multiple filters (e.g., the volume's status is `available`, and it is tagged with a particular value). The result includes information for a particular volume only if it matches *all* your filters. If there's no match, no special message is returned; the response is simply empty.

You can use wildcards with the filter values: `*` matches zero or more characters, and `?` matches exactly one character. You can escape special characters using a backslash before the character. For example, a value of `*amazon\?\` searches for the literal string `*amazon?\`.

The following table shows the available filters.

| Filter Name | Description |
|---|---|
| <code>attachment.attach-time</code> | The time stamp when the attachment initiated. Type: <code>xsd:dateTime</code> |
| <code>attachment.delete-on-termination</code> | Indicates whether the volume is deleted on instance termination. Type: <code>Boolean</code> |
| <code>attachment.device</code> | The device name that is exposed to the instance (e.g., <code>/dev/sda1</code>). Type: <code>String</code> |
| <code>attachment.instance-id</code> | The ID of the instance the volume is attached to. Type: <code>String</code> |
| <code>attachment.status</code> | The attachment state. Type: <code>String</code> Valid values: <code>attaching</code> <code>attached</code> <code>detaching</code> <code>detached</code> |
| <code>availability-zone</code> | The Availability Zone in which the volume was created. Type: <code>String</code> |
| <code>create-time</code> | The time stamp when the volume was created. Type: <code>xsd:dateTime</code> |
| <code>size</code> | The size of the volume, in GiB (e.g., 20). Type: <code>String</code> |

| Filter Name | Description |
|-----------------|--|
| snapshot-id | The snapshot from which the volume was created. Type: String |
| status | The status of the volume. Type: String Valid values: <code>creating</code> <code>available</code> <code>in-use</code> <code>deleting</code> <code>deleted</code> <code>error</code> |
| tag-key | The key of a tag assigned to the resource. This filter is independent of the <code>tag-value</code> filter. For example, if you use both the filter <code>tag-key=Purpose</code> and the filter <code>tag-value=X</code> , you get any resources assigned both the tag key <code>Purpose</code> (regardless of what the tag's value is), and the tag value <code>X</code> (regardless of what the tag's key is). If you want to list only resources where <code>Purpose=X</code> , see the <code>tag:key</code> filter later in this table. For more information about tags, see Using Tags in the <i>Amazon Elastic Compute Cloud User Guide</i> . Type: String |
| tag-value | The value of a tag assigned to the resource. This filter is independent of the <code>tag-key</code> filter. Type: String |
| tag: <i>key</i> | Filters the results based on a specific tag/value combination. Example: To list just the resources assigned tag <code>Purpose=X</code> , then specify: <code>Filter.1.Name=tag:Purpose</code> <code>Filter.1.Value.1=X</code> Example: To list just resources assigned tag <code>Purpose=X</code> OR <code>Purpose=Y</code> , then specify: <code>Filter.1.Name=tag:Purpose</code> <code>Filter.1.Value.1=X</code> <code>Filter.1.Value.2=Y</code> |
| volume-id | The volume ID. Type: String |

Request Parameters

| Name | Description | Required |
|-------------------|--|----------|
| <i>VolumeId.n</i> | One or more volume IDs. Type: String Default: Describes all volumes that you own, or only those otherwise specified. | No |

| Name | Description | Required |
|-------------------------|--|----------|
| <i>Filter.n.Name</i> | The name of a filter. See the preceding table for a list of allowed filter names. Type: String Default: None | No |
| <i>Filter.n.Value.m</i> | A value for the filter. See the preceding table for a list of allowed values for each filter. Type: String Default: None | No |

Response Elements

The elements in the following table are wrapped in a `DescribeVolumesResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>volumeSet</code> | A list of volumes. Each volume is wrapped in an <code>item</code> element. Type: DescribeVolumesSetItemResponseType (p. 420) |

Examples

Example Request

This example describes all volumes associated with your account.

```
https://ec2.amazonaws.com/?Action=DescribeVolumes
&AUTHPARAMS
```

Example Response

```
<DescribeVolumesResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <volumeSet>
    <item>
      <volumeId>vol-4282672b</volumeId>
      <size>80</size>
      <snapshotId/>
      <availabilityZone>us-east-1a</availabilityZone>
      <status>in-use</status>
      <createTime>2008-05-07T11:51:50.000Z</createTime>
      <attachmentSet>
        <item>
          <volumeId>vol-4282672b</volumeId>
          <instanceId>i-6058a509</instanceId>
          <device>/dev/sdh</device>
        </item>
      </attachmentSet>
    </item>
  </volumeSet>
</DescribeVolumesResponse>
```

```
        <status>attached</status>
        <attachTime>2008-05-07T12:51:50.000Z</attachTime>
        <deleteOnTermination>>false</deleteOnTermination>
      </item>
    </attachmentSet>
    <tagSet/>
  </item>
</volumeSet>
</DescribeVolumesResponse>
```

Example Request

This example describes all volumes that are both attached to instance i-1a2b3c4d and also set to delete when the instance terminates.

```
https://ec2.amazonaws.com/?Action=DescribeVolumes
&Filter.1.Name=attachment.instance-id
&Filter.1.Value.1=i-1a2b3c4d
&Filter.2.Name=attachment.delete-on-termination
&Filter.2.Value.1=true
&AUTHPARAMS
```

Related Operations

- [CreateVolume](#) (p. 95)
- [DeleteVolume](#) (p. 135)
- [AttachVolume](#) (p. 29)
- [DetachVolume](#) (p. 298)

DescribeVolumeAttribute

Description

Describes an attribute of the volume.

Currently, volumes have two attributes, `autoEnableIO` and `productCodes`. You can only specify the description of a single attribute.

Request Parameters

| Name | Description | Required |
|------------------|---|----------|
| <i>VolumeId</i> | The ID of the volume. Type: String Default: None | Yes |
| <i>Attribute</i> | The instance attribute. Type: String Default: None Valid values: <code>autoEnableIO</code> <code>productCodes</code> | Yes |

Response Elements

The elements in the following table are wrapped in a `DescribeVolumeAttributeResponse` structure. Only one attribute (either `autoEnableIO` or `productCodes` is returned, depending on what attribute you specified.

| Name | Description |
|---------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>volumeId</code> | The ID of the volume. Type: <code>xsd:string</code> |
| <code>autoEnableIO</code> | The state of <code>autoEnableIO</code> attribute. Type: <code>NullableAttributeBooleanValueType</code> |
| <code>productCodes</code> | A list of product codes. Each product code is wrapped in an <code>item</code> element that contains a product code and a type. Type: <code>ProductCodesSetItemType</code> (p. 461) |

Example

Example Request

This example describes the `autoEnableIO` attribute of the volume `vol-12345678`.

```
https://ec2.amazonaws.com/?Action=DescribeVolumeAttribute
&Attribute=autoEnableIO
&VolumeId=vol-12345678
&AUTHPARAMS
```

Example Response

```
<DescribeVolumeAttributeResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>5jkd074-37ed-4004-8671-a78ee82bf1cbEXAMPLE</requestId>
  <volumeId>vol-12345678</volumeId>
  <autoEnableIO>
    <value>>false</value>
  </autoEnableIO>
</DescribeVolumeAttributeResponse>
```

Example Request

This example describes the `productCodes` attribute of the volume `vol-12345678`.

```
https://ec2.amazonaws.com/?Action=DescribeVolumeAttribute
&Attribute=productCodes
&VolumeId=vol-12345678
&AUTHPARAMS
```

Example Response

```
<DescribeVolumeAttributeResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>5jkd074-37ed-4004-8671-a78ee82bf1cbEXAMPLE</requestId>
  <volumeId>vol-12345678</volumeId>
  <productCodes>
    <item>
      <productCode>alb2c3d4e5f6g7h8i9j10k11</productCode>
      <type>marketplace</type>
    </item>
  </productCodes>
</DescribeVolumeAttributeResponse>
```

Related Operations

- [DescribeVolumeStatus](#) (p. 278)
- [ModifyVolumeAttribute](#) (p. 331)

DescribeVolumeStatus

Description

Returns the status of one or more volumes. Volume status provides the result of the checks performed on your volumes to determine events that can impair the performance of your volumes. The performance of a volume can be affected if an issue occurs on the volume's underlying host. If the volume's underlying host experiences a power outage or system issue, once the system is restored there could be data inconsistencies on the volume. Volume events notify you if this occurs. Volume actions notify you if any action needs to be taken in response to the event.

The `DescribeVolumeStatus` operation provides the following information about the specified volumes:

Status: Reflects the current status of the volume. The possible values are `ok`, `impaired`, or `insufficient-data`. If all checks pass, the overall status of the volume is `ok`. If the check fails, the overall status is `impaired`. If the status is `insufficient-data`, then the checks may still be taking place on your volume at the time. We recommend you retry the request. For more information on volume status, see [Monitoring the Status of Your Volumes](#).

Events: Reflect the cause of a volume status and may require you to take an action. For example, if your volume returns an `impaired` status, then the volume event might be `potential-data-inconsistency`. This means that your volume has been affected by an issue with the underlying host, has all I/O operations disabled, and may have inconsistent data.

Actions: Reflect the actions you may have to take in response to an event. For example, if the status of the volume is `impaired` and the volume event shows `potential-data-inconsistency`, then the action will show `enable-volume-io`. This means that you may want to enable the I/O operations for the volume by calling the [EnableVolumeIO](#) (p. 306) action and then check the volume for data consistency.

Note

Volume status only has one status check. It does not check volume state as reported by `DescribeVolumes`. Therefore, it does not detect volumes in the `ERROR` state (i.e., when a volume is incapable of accepting I/Os because it is in an error state.)

You can filter the results to return information only about volumes that match criteria you specify. For example, you could get information about volumes that have `impaired` status. You can specify multiple values for a filter (e.g., more than one Availability Zone). A volume must match at least one of the specified values for it to be included in the results.

You can specify multiple filters (e.g., the volume is in a specific Availability Zone and its status is set to `impaired`). A volume must match *all* the filters for it to be included in the results. If there's no match, no special message is returned; the response is simply empty.

You can use wildcards with the filter values: `*` matches zero or more characters, and `?` matches exactly one character. You can escape special characters using a backslash before the character. For example, a value of `*amazon\?\` searches for the literal string `*amazon?\`.

The following table shows the available filters.

| Filter Name | Description |
|--------------------------------|--|
| <code>availability-zone</code> | The Availability Zone of the instance. Type: String |

| Filter Name | Description |
|---|--|
| <code>volume-status.status</code> | The status of the volume. Type: String Valid values: <code>ok</code> <code>impaired</code> <code>insufficient-data</code> |
| <code>volume-status.details-name</code> | The cause for the <code>volume-status.status</code> . Type: String Valid values: <code>io-enabled</code> |
| <code>volume-status.details-status</code> | The status of the <code>volume-status.details-name</code> . Type: String Valid values: <code>passed</code> <code>failed</code> |
| <code>event.description</code> | A description of the event. Type: String |
| <code>event.not-after</code> | The latest end time for the event. Type: <code>dateType</code> |
| <code>event.not-before</code> | The earliest start time for the event. Type: <code>dateType</code> |
| <code>event.event-id</code> | The event ID. Type: String |
| <code>event.event-type</code> | The event type, e.g., <code>potential-data-inconsistency</code> Type: String |
| <code>action.code</code> | The action code for the event, e.g., <code>enable-volume-io</code> Type: String |
| <code>action.event-id</code> | The event ID associated with the action. Type: String |
| <code>action.description</code> | A description of the action. Type: String |

Request Parameters

| Name | Description | Required |
|-------------------------|--|----------|
| <code>VolumeId.n</code> | One or more volume IDs. Type: String Default: Describes all volumes that you own, or only those otherwise specified. | No |

| Name | Description | Required |
|-------------------------|--|----------|
| <i>Filter.n.Name</i> | The name of a filter. See the preceding table for a list of allowed filter names. Type: String Default: None | No |
| <i>Filter.n.Value.m</i> | The value for the filter. See the preceding table for a list of allowed values for each filter. Type: String Default: None | No |
| <i>MaxResults</i> | The maximum number of paginated volume items per response. Type: Integer Default: None | No |
| <i>NextToken</i> | A string specifying the next paginated set of results to return using the pagination token returned by a previous call to this API. Type: String Default: None | No |

Response Elements

The elements in the following table are wrapped in a `DescribeVolumeStatusResponse` structure.

| Name | Description |
|------------------------------|--|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>volumeStatusSet</code> | A list of volumes. Each volume is wrapped in an <code>item</code> element. Type: VolumeStatusItemType |
| <code>nextToken</code> | A string specifying the next paginated set of results to return. Type: <code>xsd:string</code> |

Examples

Example Request

This example describes the status of all the volumes associated with your account.

```
https://ec2.amazonaws.com/?Action=DescribeVolumeStatus
&AUTHPARAMS
```

Example Response

```
<DescribeVolumeStatus xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>5jdkf074-37ed-4004-8671-a78ee82bf1cbEXAMPLE</requestId>
  <volumeStatusSet>
    <item>
      <VolumeId>vol-11111111</volumeId>
      <availabilityZone>us-east-1d</availabilityZone>
      <volumeStatus>
        <status>ok</status>
        <details>
          <item>
            <name>io-enabled</name>
            <status>passed</status>
          </item>
        </details>
      </volumeStatus>
    </item>
    <item>
      <volumeId>vol-22222222</volumeId>
      <availabilityZone>us-east-1d</availabilityZone>
      <volumeStatus>
        <status>impaired</status>
        <details>
          <item>
            <name>io-enabled</name>
            <status>failed</status>
          </item>
        </details>
      </volumeStatus>
      <eventsSet>
        <item>
          <eventId>evol-61a54008</eventId>
          <eventType>potential-data-inconsistency</eventType>
          <description>THIS IS AN EXAMPLE</description>
          <notBefore>2011-12-01T14:00:00.000Z</notBefore>
          <notAfter>2011-12-01T15:00:00.000Z</notAfter>
        </item>
      </eventsSet>
      <actionsSet>
        <item>
          <code>enable-volume-io</code>
          <eventId> evol-61a54008</eventId>
          <eventType>potential-data-inconsistency</eventType>
          <description>THIS IS AN EXAMPLE</description>
        </item>
      </actionsSet>
    </item>
  </volumeStatusSet>
</DescribeVolumesStatusResponse>
```

Example Request

This example describes all the volumes in the `us-east-1d` Availability Zone with failed `io-enabled` status.


```
https://ec2.amazonaws.com/?Action=DescribeVolumeStatus
&Filter.1.Name=availability-zone
&Filter.1.Value.1=us-east-1d
&Filter.2.Name=volume-status.details-name
&Filter.2.Value.1=io-enabled
&Filter.3.Name=volume-status.details-status
&Filter.3.Value.1=failed
&AUTHPARAMS
```

Related Operations

- [ModifyVolumeAttribute](#) (p. 331)
- [DescribeVolumeAttribute](#) (p. 276)
- [EnableVolumeIO](#) (p. 306)

DescribeVpcs

Description

Gives you information about your VPCs. You can filter the results to return information only about VPCs that match criteria you specify. For example, you could get information only about VPCs whose state is `available`. You can specify multiple values for the filter. A VPC must match at least one of the specified values for it to be included in the results.

You can specify multiple filters (e.g., the VPC uses one of several sets of DHCP options, and the VPC's state is `available`). The result includes information for a particular VPC only if it matches *all* your filters. If there's no match, no special message is returned; the response is simply empty.

You can use wildcards with the filter values: `*` matches zero or more characters, and `?` matches exactly one character. You can escape special characters using a backslash before the character. For example, a value of `*amazon\?\` searches for the literal string `*amazon?\`.

The following table shows the available filters.

| Filter Name | Description |
|------------------------------|--|
| <code>cidr</code> | The CIDR block of the VPC. The CIDR block you specify must exactly match the VPC's CIDR block for information to be returned for the VPC. Type: String Constraints: Must contain the slash followed by one or two digits (e.g., <code>/28</code>) |
| <code>dchp-options-id</code> | The ID of a set of DHCP options. Type: String |
| <code>state</code> | The state of the VPC. Type: String Valid Values: <code>pending</code> <code>available</code> |
| <code>tag-key</code> | The key of a tag assigned to the resource. This filter is independent of the <code>tag-value</code> filter. For example, if you use both the filter <code>tag-key=Purpose</code> and the filter <code>tag-value=X</code> , you get any resources assigned both the tag key <code>Purpose</code> (regardless of what the tag's value is), and the tag value <code>X</code> (regardless of what the tag's key is). If you want to list only resources where <code>Purpose=X</code> , see the <code>tag:key</code> filter later in this table. For more information about tags, see Using Tags in the <i>Amazon Elastic Compute Cloud User Guide</i> . Type: String |
| <code>tag-value</code> | The value of a tag assigned to the resource. This filter is independent of the <code>tag-key</code> filter. Type: String |

| Filter Name | Description |
|-----------------------------|--|
| <code>tag:<i>key</i></code> | Filters the results based on a specific tag/value combination. Example: To list just the resources assigned tag Purpose=X, then specify: <code>Filter.1.Name=tag:Purpose</code> <code>Filter.1.Value.1=X</code> Example: To list just resources assigned tag Purpose=X OR Purpose=Y, then specify: <code>Filter.1.Name=tag:Purpose</code> <code>Filter.1.Value.1=X</code> <code>Filter.1.Value.2=Y</code> |
| <code>vpc-id</code> | The ID of the VPC. Type: String |

For more information about Amazon Virtual Private Cloud and VPCs, see the [Amazon Virtual Private Cloud User Guide](#).

Request Parameters

| Name | Description | Required |
|-------------------------------|---|----------|
| <code>VpcId.n</code> | The ID of the VPC. Type: String Default: Returns information about all your VPCs, or only those otherwise specified | No |
| <code>Filter.n.Name</code> | The name of a filter. See the preceding table for a list of allowed filter names. Type: String Default: Returns information about all your VPCs, or only those otherwise specified. | No |
| <code>Filter.n.Value.m</code> | A value for the filter. See the preceding table for a list of allowed values for each filter. Type: String Default: None | No |

Response Elements

The elements in the following table are wrapped in an `DescribeVpcsResponse` structure.

| Name | Description |
|------------------------|--|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>vpcSet</code> | A list of VPCs. Each VPC is wrapped in an <code>item</code> element. Type: VpcType (p. 483) |

Examples

Example Request

This example gives a description of the VPC with ID vpc-1a2b3c4d.

```
https://ec2.amazonaws.com/?Action=DescribeVpcs
&VpcId.1=vpc-1a2b3c4d
&AUTHPARAMS
```

Example Response

```
<DescribeVpcsResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</requestId>
  <vpcSet>
    <item>
      <vpcId>vpc-1a2b3c4d</vpcId>
      <state>available</state>
      <cidrBlock>10.0.0.0/23</cidrBlock>
      <dhcpOptionsId>dopt-7a8b9c2d</dhcpOptionsId>
      <tagSet/>
    </item>
  </vpcSet>
</DescribeVpcsResponse>
```

Example Request

This example uses filters to give a description of any VPC you own that uses the set of DHCP options with ID dopt-7a8b9c2d or dopt-2b2a3d3c and whose state is available.

```
https://ec2.amazonaws.com/?Action=DescribeVpcs
&Filter.1.Name=dhcp-options-id
&Filter.1.Value.1=dopt-7a8b9c2d
&Filter.1.Value.2=dopt-2b2a3d3c
&Filter.2.Name=state
&Filter.2.Value.1=available
&AUTHPARAMS
```

Related Operations

- [CreateVpc](#) (p. 97)
- [DeleteVpc](#) (p. 137)
- [CreateDhcpOptions](#) (p. 55)
- [AssociateDhcpOptions](#) (p. 21)

DescribeVpnConnections

Description

Gives you information about your VPN connections.

Important

We strongly recommend you use HTTPS when calling this operation because the response contains sensitive cryptographic information for configuring your customer gateway.

You can filter the results to return information only about VPN connections that match criteria you specify. For example, you could get information only about VPN connections whose state is `pending` or `available`. You can specify multiple values for the filter. A VPN connection must match at least one of the specified values for it to be included in the results.

You can specify multiple filters (e.g., the VPN connection is associated with a particular virtual private gateway, and the gateway's state is `pending` or `available`). The result includes information for a particular VPN connection only if it matches *all* your filters. If there's no match, no special message is returned; the response is simply empty.

You can use wildcards with the filter values: `*` matches zero or more characters, and `?` matches exactly one character. You can escape special characters using a backslash before the character. For example, a value of `*amazon?\` searches for the literal string `*amazon?\`.

The following table shows the available filters.

| Filter Name | Description |
|---|--|
| <code>customer-gateway-configuration</code> | The configuration information for the customer gateway. Type: String |
| <code>customer-gateway-id</code> | The ID of a customer gateway associated with the VPN connection. Type: String |
| <code>state</code> | The state of the VPN connection. Type: String Valid values: <code>pending</code> <code>available</code> <code>deleting</code> <code>deleted</code> |
| <code>tag-key</code> | The key of a tag assigned to the resource. This filter is independent of the <code>tag-value</code> filter. For example, if you use both the filter <code>tag-key=Purpose</code> and the filter <code>tag-value=X</code> , you get any resources assigned both the tag key <code>Purpose</code> (regardless of what the tag's value is), and the tag value <code>X</code> (regardless of what the tag's key is). If you want to list only resources where <code>Purpose=X</code> , see the <code>tag:key</code> filter later in this table. For more information about tags, see Using Tags in the <i>Amazon Elastic Compute Cloud User Guide</i> . Type: String |
| <code>tag-value</code> | The value of a tag assigned to the resource. This filter is independent of the <code>tag-key</code> filter. Type: String |

| Filter Name | Description |
|--------------------------------|--|
| <code>tag: <i>key</i></code> | Filters the results based on a specific tag/value combination. Example: To list just the resources assigned tag Purpose=X, then specify: <code>Filter.1.Name=tag:Purpose</code> <code>Filter.1.Value.1=X</code> Example: To list just resources assigned tag Purpose=X OR Purpose=Y, then specify: <code>Filter.1.Name=tag:Purpose</code> <code>Filter.1.Value.1=X</code> <code>Filter.1.Value.2=Y</code> |
| <code>type</code> | The type of VPN connection. Currently the only supported type is <code>ipsec.1</code> . Type: String Valid values: <code>ipsec.1</code> |
| <code>vpn-connection-id</code> | The ID of the VPN connection. Type: String |
| <code>vpn-gateway-id</code> | The ID of a virtual private gateway associated with the VPN connection. Type: String |

For more information about Amazon Virtual Private Cloud and VPN connections, see [Adding an IPsec Hardware Virtual Private Gateway to Your VPC](#) in the *Amazon Virtual Private Cloud User Guide*.

Note

You can get the customer gateway configuration information in a friendly format by using the **ec2-describe-vpn-connections** command instead. For more information, see [ec2-describe-vpn-connections](#) in the *Amazon Virtual Private Cloud Command Line Reference*.

Request Parameters

| Name | Description | Required |
|--------------------------------|--|----------|
| <code>VpnConnectionId.n</code> | A VPN connection ID. You can specify more than one in the request. Type: String Default: Returns information about all your VPN connections | No |
| <code>Filter.n.Name</code> | The name of a filter. See the preceding table for a list of allowed filter names. Type: String Default: Returns information about all your VPN connections or those you specify by ID. | No |
| <code>Filter.n.Value.m</code> | A value for the filter. See the preceding table for a list of allowed values for each filter. Type: String Default: None | No |

Response Elements

The elements in the following table are wrapped in an `DescribeVpnConnectionsResponse` structure.

| Name | Description |
|-------------------------------|--|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>vpnConnectionSet</code> | A list of VPN connections. Each VPN connection is wrapped in an <code>item</code> element. Type: VpnConnectionType (p. 484) |

Examples

Example Request

This example gives a description of the VPN connection with ID `vpn-44a8938f`. The response includes the customer gateway configuration information. Because it's a long set of information, we haven't displayed it here. You can see an example in the topic for `CreateVpnConnection`.

```
https://ec2.amazonaws.com/?Action=DescribeVpnConnections
&VpnConnectionId.1=vpn-44a8938f
&AUTHPARAMS
```

Example Response

```
<DescribeVpnConnectionsResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</requestId>
  <vpnConnectionSet>
    <item>
      <vpnConnectionId>vpn-44a8938f</vpnConnectionId>
      <state>available</state>
      <CustomerGatewayConfiguration>
        Customer gateway configuration data in escaped XML format...
        ...
      </CustomerGatewayConfiguration>
      <type>ipsec.1</type>
      <customerGatewayId>cgw-b4dc3961</customerGatewayId>
      <vpnGatewayId>vgw-8db04f81</vpnGatewayId>
      <tagSet/>
    </item>
  </vpnConnectionSet>
</DescribeVpnConnectionsResponse>
```

Example Request

This example gives a description of any VPN connection you own associated with the customer gateway with ID `cgw-b4dc3961`, and whose state is either `pending` or `available`.

```
https://ec2.amazonaws.com/?Action=DescribeVpnConnections
&Filter.1.Name=customer-gateway-id
&Filter.1.Value.1=cgw-b4dc3961
&Filter.2.Name=state
&Filter.2.Value.1=pending
&Filter.2.Value.2=available
&AUTHPARAMS
```

Related Operations

- [CreateVpnConnection](#) (p. 99)
- [DeleteVpnConnection](#) (p. 139)

DescribeVpnGateways

Description

Gives you information about your virtual private gateways. You can filter the results to return information only about virtual private gateways that match criteria you specify. For example, you could get information only about virtual private gateways whose state is `pending` or `available`. You can specify multiple values for the filter. A virtual private gateway must match at least one of the specified values for it to be included in the results.

You can specify multiple filters (e.g., the virtual private gateway is in a particular Availability Zone and the gateway's state is `pending` or `available`). The result includes information for a particular virtual private gateway only if it matches *all* your filters. If there's no match, no special message is returned; the response is simply empty.

You can use wildcards with the filter values: `*` matches zero or more characters, and `?` matches exactly one character. You can escape special characters using a backslash before the character. For example, a value of `*amazon\?\` searches for the literal string `*amazon?`.

The following table shows the available filters.

| Filter Name | Description |
|--------------------------------|--|
| <code>attachment.state</code> | The current state of the attachment between the gateway and the VPC. Type: String Valid values: <code>attaching</code> <code>attached</code> <code>detaching</code> <code>detached</code> |
| <code>attachment.vpc-id</code> | The ID of an attached VPC. Type: String |
| <code>availability-zone</code> | The Availability Zone the virtual private gateway is in. Type: String |
| <code>state</code> | The state of the virtual private gateway. Type: String Valid values: <code>pending</code> <code>available</code> <code>deleting</code> <code>deleted</code> |
| <code>tag-key</code> | The key of a tag assigned to the resource. This filter is independent of the <code>tag-value</code> filter. For example, if you use both the filter <code>tag-key=Purpose</code> and the filter <code>tag-value=X</code> , you get any resources assigned both the tag key <code>Purpose</code> (regardless of what the tag's value is), and the tag value <code>X</code> (regardless of what the tag's key is). If you want to list only resources where <code>Purpose=X</code> , see the <code>tag:key</code> filter later in this table. For more information about tags, see Using Tags in the <i>Amazon Elastic Compute Cloud User Guide</i> . Type: String |
| <code>tag-value</code> | The value of a tag assigned to the resource. This filter is independent of the <code>tag-key</code> filter. Type: String |

| Filter Name | Description |
|------------------------------|--|
| <code>tag: <i>key</i></code> | Filters the results based on a specific tag/value combination. Example: To list just the resources assigned tag Purpose=X, then specify: <code>Filter.1.Name=tag:Purpose</code> <code>Filter.1.Value.1=X</code> Example: To list just resources assigned tag Purpose=X OR Purpose=Y, then specify: <code>Filter.1.Name=tag:Purpose</code> <code>Filter.1.Value.1=X</code> <code>Filter.1.Value.2=Y</code> |
| <code>type</code> | The type of virtual private gateway. Currently the only supported type is <code>ipsec.1</code> . Type: String Valid values: <code>ipsec.1</code> |
| <code>vpn-gateway-id</code> | The ID of the virtual private gateway. Type: String |

For more information about Amazon Virtual Private Cloud and virtual private gateways, see [Adding an IPsec Hardware Virtual Private Gateway to Your VPC](#) in the *Amazon Virtual Private Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|-------------------------------|---|----------|
| <code>VpnGatewayId.n</code> | A virtual private gateway ID. You can specify more than one in the request. Type: String Default: Returns information about all your virtual private gateways. | No |
| <code>Filter.n.Name</code> | The name of a filter. See the preceding table for a list of allowed filter names. Type: String Default: Returns information about all your virtual private gateways or those you specify by ID. | No |
| <code>Filter.n.Value.m</code> | A value for the filter. See the preceding table for a list of allowed values for each filter. Type: String Default: None | No |

Response Elements

The elements in the following table are wrapped in an `DescribeVpnGatewaysResponsestructure`.

| Name | Description |
|---------------|---|
| requestId | The ID of the request. Type: xsd:string |
| vpnGatewaySet | A list of virtual private gateways. Each virtual private gateway is wrapped in an <code>item</code> element. Type: VpnGatewayType (p. 485) |

Examples

Example Request

This example gives a description of the virtual private gateway with ID `vgw-8db04f81`.

```
https://ec2.amazonaws.com/?Action=DescribeVpnGateways
&VpnGatewayId.1=vgw-8db04f81
&AUTHPARAMS
```

Example Response

```
<DescribeVpnGatewaysResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</requestId>
  <vpnGatewaySet>
    <item>
      <vpnGatewayId>vgw-8db04f81</vpnGatewayId>
      <state>available</state>
      <type>ipsec.1</type>
      <availabilityZone>us-east-1a</availabilityZone>
      <attachments>
        <item>
          <vpcId>vpc-1a2b3c4d</vpcId>
          <state>attached</state>
        </item>
      </attachments>
      <tagSet/>
    </item>
  </vpnGatewaySet>
</DescribeVpnGatewaysResponse>
```

Example Request

This example uses filters to give a description of any virtual private gateway you own that is in the `us-east-1a` Availability Zone, and whose state is either `pending` or `available`.

```
https://ec2.amazonaws.com/?Action=DescribeVpnGateways
&Filter.1.Name=availability-zone
&Filter.1.Value.1=us-east-1a
&Filter.2.Name=state
&Filter.2.Value.1=pending
```

```
&Filter.2.Value.2=available  
&AUTHPARAMS
```

Related Operations

- [CreateVpnGateway](#) (p. 103)
- [DeleteVpnGateway](#) (p. 141)

DetachInternetGateway

Description

Detaches an Internet gateway from a VPC, disabling connectivity between the Internet and the VPC. The VPC must not contain any running instances with Elastic IP addresses.

For more information about Amazon Virtual Private Cloud and Internet gateways, see the [Amazon Virtual Private Cloud User Guide](#).

Request Parameters

| Name | Description | Required |
|--------------------------|--|----------|
| <i>InternetGatewayId</i> | The ID of the Internet gateway. Type: String Default: None | Yes |
| <i>VpcId</i> | The ID of the VPC. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in a `DetachInternetGatewayResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

The example detaches the Internet gateway with ID `igw-eaad4883` from the VPC with ID `vpc-11ad4878`.

```
https://ec2.amazonaws.com/?Action=DetachInternetGateway
&InternetGatewayId=igw-eaad4883
&VpcId=vpc-11ad4878
&AUTHPARAMS
```

Example Response

```
<DetachInternetGatewayResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <return>true</return>
</DetachInternetGatewayResponse>
```

Related Operations

- [CreateInternetGateway](#) (p. 63)
- [DeleteInternetGateway](#) (p. 109)
- [DetachInternetGateway](#) (p. 25)
- [DescribeInternetGateways](#) (p. 203)

DetachNetworkInterface

Description

Detaches a network interface from an instance.

Request Parameters

| Name | Description | Required |
|--------------|---|----------|
| AttachmentId | The ID of the attachment. Type: String Default: None | Yes |
| Force | Set to <code>true</code> to force a detachment. Type: Boolean Default: None | No |

Response Elements

The elements in the following table are wrapped in a `DetachNetworkInterface` structure.

| Name | Description |
|-----------|---|
| requestId | The ID of the request. Type: <code>xsd:string</code> |
| return | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example detaches an elastic network interface (ENI) `eni-attach-d94b09b0`.

```
https://ec2.amazonaws.com/?Action=DetachNetworkInterface
&AttachmentId=eni-attach-d94b09b0
&AUTHPARAMS
```

Example Response

```
<DetachNetworkInterfaceResponse xmlns='http://ec2.amazonaws.com/doc/2011-11-15/'>
  <requestId>ce540707-0635-46bc-97da-33a8a362a0e8</requestId>
  <return>true</return>
</DetachNetworkInterfaceResponse>
```

Related Operations

- [AttachNetworkInterface](#) (p. 27)
- [CreateNetworkInterface](#) (p. 72)
- [DeleteNetworkInterface](#) (p. 117)
- [DescribeNetworkInterfaceAttribute](#) (p. 214)
- [DescribeNetworkInterfaces](#) (p. 216)
- [ModifyNetworkInterfaceAttribute](#) (p. 327)
- [ResetNetworkInterfaceAttribute](#) (p. 369)

DetachVolume

Description

Detaches an Amazon EBS volume from an instance. Make sure to unmount any file systems on the device within your operating system before detaching the volume. Failure to do so will result in volume being stuck in "busy" state while detaching. For more information about Amazon EBS, see [Using Amazon Elastic Block Store](#) in the *Amazon Elastic Compute Cloud User Guide*.

Note

If an Amazon EBS volume is the root device of an instance, it cannot be detached while the instance is in the "running" state. To detach the root volume, stop the instance first.

If the root volume is detached from an instance with an AWS Marketplace product code, then the AWS Marketplace product codes from that volume are no longer associated with the instance.

Request Parameters

| Name | Description | Required |
|-------------------|--|----------|
| <i>VolumeId</i> | The ID of the volume. Type: String Default: None | Yes |
| <i>InstanceId</i> | The ID of the instance. Type: String Default: None | No |
| <i>Device</i> | The device name. Type: String Default: None | No |
| <i>Force</i> | Forces detachment if the previous detachment attempt did not occur cleanly (logging into an instance, unmounting the volume, and detaching normally). This option can lead to data loss or a corrupted file system. Use this option only as a last resort to detach a volume from a failed instance. The instance won't have an opportunity to flush file system caches or file system metadata. If you use this option, you must perform file system check and repair procedures. Type: Boolean Default: None | No |

Response Elements

The elements in the following table are wrapped in a `DetachVolumeResponse` structure.

| Name | Description |
|------------|--|
| requestId | The ID of the request. Type: xsd:string |
| volumeId | The ID of the volume. Type: xsd:string |
| instanceId | The ID of the instance. Type: xsd:string |
| device | The device name exposed to the instance. Type: xsd:string |
| status | The attachment state. Type: xsd:string Valid values: attaching attached detaching detached |
| attachTime | The time stamp when the attachment initiated. Type: xsd:dateTime |

Examples

Example Request

This example detaches volume `vol-4d826724`.

```
https://ec2.amazonaws.com/?Action=DetachVolume
&VolumeId=vol-4d826724
&InstanceId=i-6058a509
&AUTHPARAMS
```

Example Response

```
<DetachVolumeResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <volumeId>vol-4d826724</volumeId>
  <instanceId>i-6058a509</instanceId>
  <device>/dev/sdh</device>
  <status>detaching</status>
  <attachTime>2008-05-08T11:51:50.000Z</attachTime>
</DetachVolumeResponse>
```

Related Operations

- [CreateVolume](#) (p. 95)
- [DeleteVolume](#) (p. 135)
- [DescribeVolumes](#) (p. 272)
- [AttachVolume](#) (p. 29)

DetachVpnGateway

Description

Detaches a virtual private gateway from a VPC. You do this if you're planning to turn off the VPC and not use it anymore. You can confirm a virtual private gateway has been completely detached from a VPC by describing the virtual private gateway (any attachments to the virtual private gateway are also described).

You must wait for the attachment's state to switch to `detached` before you can delete the VPC or attach a different VPC to the virtual private gateway.

For more information about Amazon Virtual Private Cloud and virtual private gateways, see [Adding an IPsec Hardware Virtual Private Gateway to Your VPC](#) in the *Amazon Virtual Private Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|---------------------|---|----------|
| <i>VpnGatewayId</i> | The ID of the virtual private gateway. Type: String Default: None | Yes |
| <i>VpcId</i> | The ID of the VPC. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in an `DetachVpnGatewayResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example detaches the virtual private gateway with ID `vgw-8db04f81` from the VPC with VPC ID `vpc-1a2b3c4d`.

```
https://ec2.amazonaws.com/?Action=DetachVpnGateway
&VpnGatewayId=vgw-8db04f81
```

```
&VpcId=vpc-1a2b3c4d  
&AUTHPARAMS
```

Example Response

```
<DetachVpnGatewayResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">  
  <requestId>7a62c49f-347e-4fc4-9331-6e8eEXAMPLE</requestId>  
  <return>true</return>  
</DetachVpnGatewayResponse>
```

Related Operations

- [AttachVpnGateway](#) (p. 31)
- [DescribeVpnGateways](#) (p. 290)

DisassociateAddress

Description

Disassociates an Elastic IP address from the instance it's assigned to.

This action applies to both EC2 Elastic IP addresses and VPC Elastic IP addresses. For information about VPC addresses and how they differ from EC2 addresses, see [Elastic IP Addresses](#) in the *Amazon Virtual Private Cloud User Guide*.

This is an idempotent action. If you enter it more than once, Amazon EC2 does not return an error.

Request Parameters

| Name | Description | Required |
|----------------------|--|-------------|
| <i>PublicIp</i> | The EC2 Elastic IP address. Type: String Default: None Condition: Required for EC2 Elastic IP addresses | Conditional |
| <i>AssociationId</i> | The association ID corresponding to the VPC Elastic IP address. Type: String Default: None Condition: Required for VPC Elastic IP addresses | Conditional |

Response Elements

The elements in the following table are wrapped in a `DisassociateAddressResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example disassociates the EC2 Elastic IP address 67.202.55.255 from the instance to which it is assigned.

```
https://ec2.amazonaws.com/?Action=DisassociateAddress
&PublicIp=192.0.2.1
&AUTHPARAMS
```

Example Request

This example disassociates the VPC Elastic IP address with association ID eipassoc-aa7486c3 from the VPC instance to which it is assigned.

```
https://ec2.amazonaws.com/?Action=DisassociateAddress
&AssociationID=eipassoc-aa7486c3
&AUTHPARAMS
```

Example Response

```
<DisassociateAddressResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <return>true</return>
</DisassociateAddressResponse>
```

Related Operations

- [AllocateAddress](#) (p. 13)
- [DescribeAddresses](#) (p. 145)
- [ReleaseAddress](#) (p. 343)
- [AssociateAddress](#) (p. 18)

DisassociateRouteTable

Description

Disassociates a subnet from a route table.

After you perform this action, the subnet no longer uses the routes in the route table. Instead, it uses the routes in the VPC's main route table. For more information about route tables, see [Route Tables](#) in the *Amazon Virtual Private Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|----------------------|--|----------|
| <i>AssociationId</i> | The association ID representing the current association between the route table and subnet. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in a `DisassociateRouteTableResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example disassociates the route table with association ID `rtbassoc-fdad4894` from the subnet it's associated to.

```
https://ec2.amazonaws.com/?Action=DisassociateRouteTable
&AssociationId=rtbassoc-fdad4894
&AUTHPARAMS
```

Example Response

```
<DisassociateRouteTableResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
```

```
<requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>  
<return>>true</return>  
</DisassociateRouteTableResponse>
```

Related Operations

- [CreateRouteTable](#) (p. 82)
- [AssociateRouteTable](#) (p. 23)
- [DeleteRouteTable](#) (p. 123)
- [DescribeRouteTables](#) (p. 236)
- [ReplaceRouteTableAssociation](#) (p. 352)

EnableVolumeIO

Description

Enables I/O operations for a volume that had I/O operations disabled because the data on the volume was potentially inconsistent.

Request Parameters

| Name | Description | Required |
|-----------------|---|----------|
| <i>VolumeId</i> | The volume ID. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in a `EnableVolumeIOResponse` structure.

| Name | Description |
|------------------------|--|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the I/O operations of the volume are enabled. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example enables the I/O operations of the volume `vol-88888888`.

```
https://ec2.amazonaws.com/?Action=EnableVolumeIO
&VolumeId= vol-88888888
&AUTHPARAMS
```

Example Response

```
<EnableVolumeIOResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <return>true</return>
</EnableVolumeIOResponse>
```

Related Operations

- [DescribeVolumeStatus](#) (p. 278)

- [ModifyVolumeAttribute](#) (p. 331)
- [DescribeVolumeAttribute](#) (p. 276)

GetConsoleOutput

Description

Retrieves console output for the specified instance.

Instance console output is buffered and posted shortly after instance boot, reboot, and termination. Amazon EC2 preserves the most recent 64 KB output which will be available for at least one hour after the most recent post.

Request Parameters

| Name | Description | Required |
|-------------------|--|----------|
| <i>InstanceId</i> | The ID of the instance. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in a `GetConsoleOutputResponse` structure.

| Name | Description |
|-------------------------|---|
| <code>requestId</code> | The ID of the request. Type: xsd:string |
| <code>instanceId</code> | The instance ID. Type: xsd:string |
| <code>timestamp</code> | The time the output was last updated. Type: xsd:dateTime |
| <code>output</code> | The console output, Base64 encoded. Type: xsd:string |

Examples

Example Request

This example retrieves the console output for the `i-10a64379` Linux and UNIX instance.

```
https://ec2.amazonaws.com/?Action=GetConsoleOutput
&InstanceId=i-10a64379
&AUTHPARAMS
```

Example Response

```
<GetConsoleOutputResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <instanceId>i-28a64341</instanceId>
  <timestamp>2010-10-14T01:12:41.000Z</timestamp>
  <output>TGludXggdmVyc2lubiAyLjYuMTYteGVuVSAoYnVpbGRlckBwYXRjaGJhdC5hb
WF6b25zYSkgKGdj
YyB2ZXJzaW9uIDQuMC4xIDIwMDUwNzI3IChSZWQgSGF0IDQuMC4xLTUpKSAjMSBTTVAgVGh1IE9j
dCAyNiAwODo0MToyNiBTQVNUIDlwMDYKQklPUy1wcm92aWRlZCBwaHlzaWNhbcBSQU0gbWFWOgpY
ZW46IDAwMDAwMDAwMDAwMDAwMDAgLSAwMDAwMDAwMDZhNDAwMDAwIChlc2FibGUpcjk4ME1CIEhJ
R0hNRU0gYXZhaWxhYmxlLGo3MjdNQiBMTldNRU0gYXZhaWxhYmxlLgpoWCAoRXhlY3V0ZSBEaXNh
YmxlKSBwcm90ZWNoaW9uOiBhY3RpdmUKSVJRIGxvY2t1cCBkZXRLY3Rpb24gZGlzYWJsZWQKQnVp
bHQgMSB6b25lbG1zdHMKS2VybVVsIGNvbW1hbmQgbGluZTogcm9vdD0vZGV2L3NkYTEgcm8gNApF
bmFibGluZyBmYXN0IEZQVSBzYXZlIGFuZCByZXN0b3JlLi4uIGRvbmUuCG==</output>
</GetConsoleOutputResponse>
```

Related Operations

- [RunInstances](#) (p. 379)

GetPasswordData

Description

Retrieves the encrypted administrator password for an instance running Windows.

Note

The Windows password is only generated the first time an AMI is launched. It is not generated for rebundled AMIs or after the password is changed on an instance.

The password is encrypted using the key pair that you provided.

Request Parameters

| Name | Description | Required |
|-------------------|---|----------|
| <i>InstanceId</i> | A Windows instance ID. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in a `GetPasswordDataResponse` structure.

| Name | Description |
|---------------------------|--|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>instanceId</code> | The ID of the instance. Type: <code>xsd:string</code> |
| <code>timestamp</code> | The time the data was last updated. Type: <code>xsd:dateTime</code> |
| <code>passwordData</code> | The password of the instance. Type: <code>xsd:string</code> |

Examples

Example Request

This example returns the encrypted version of the administrator password for the `i-2574e22a` instance.

```
https://ec2.amazonaws.com/?Action=GetPasswordData
&InstanceId=i-10a64379
&AUTHPARAMS
```

Example Response

```
<GetPasswordDataResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <instanceId>i-2574e22a</instanceId>
  <timestamp>2009-10-24 15:00:00</timestamp>
  <passwordData>TGludXggdmVyc2lvbiAyLjYuMTYteGVuVSAoYnVpbGRlckBwYXRjaGJhdC5hb
WF6b25zYSkgKGdj</passwordData>
</GetPasswordDataResponse>
```

Related Operations

- [RunInstances](#) (p. 379)

ImportInstance

Description

Creates a new import instance task using metadata from the specified disk image. After importing the image, you then upload it using the `ec2-upload-disk-image` command in the EC2 command line tools. For more information, see [Using the Command Line Tools to Import Your Virtual Machine to Amazon EC2](#) in the *Amazon Elastic Compute Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|-----------------------------------|---|----------|
| <i>Description</i> | A description of the instance being imported. Type: String Default: None | No |
| <i>Architecture</i> | The architecture of the instance. Type: String Default: None Valid values: i386 x86_64 | Yes |
| <i>SecurityGroup.n</i> | One or more security group names. Type: String Default: None | No |
| <i>UserData</i> | User data to be made available to the instance. Type: String Default: None | No |
| <i>InstanceType</i> | The instance type. Type: String Valid values: m1.small m1.large m1.xlarge c1.medium c1.xlarge m2.xlarge m2.2xlarge m2.4xlarge t1.micro Default: m1.small | Yes |
| <i>Placement.AvailabilityZone</i> | The Availability Zone to launch the instance into. Type: String Default: EC2 chooses a zone for you | No |
| <i>Monitoring.Enabled</i> | Specifies whether to enable detailed monitoring for the instance. Type: Boolean Default: false | No |
| <i>SubnetId</i> | If you're using Amazon Virtual Private Cloud, this specifies the ID of the subnet you want to launch the instance into. Type: String Default: None | No |

**Amazon Elastic Compute Cloud API Reference
Response Elements**

| Name | Description | Required |
|--|---|----------|
| <i>InstanceInitiatedShutdownBehavior</i> | Specifies whether the instance stops or terminates on instance-initiated shutdown. Type: String Valid values: stop terminate Default: stop | No |
| <i>PrivateIpAddress</i> | If you're using Amazon Virtual Private Cloud, you can optionally use this parameter to assign the instance a specific available IP address from the subnet (e.g., 10.0.0.25). Type: String Default: Amazon VPC selects an IP address from the subnet for the instance | No |
| <i>DiskImage.n.Image.Format</i> | The file format of the disk image. Type: String Default: None Valid values: VMDC RAW VHD | Yes |
| <i>DiskImage.n.Image.Bytes</i> | The number of bytes in the disk image. Type: Long Default: None | Yes |
| <i>DiskImage.n.Image.ImportManifestUrl</i> | The manifest for the disk image, stored in Amazon S3 and presented here as an Amazon S3 presigned URL. For information about creating a presigned URL for an Amazon S3 object, read the "Signing and Authenticating REST Requests" section of the Signing and Authenticating REST Requests topic in the <i>Amazon Simple Storage Service Developer Guide</i> . Type: String Default: None | Yes |
| <i>DiskImage.n.Image.Description</i> | An optional description of the disk image. Type: String Default: None | No |
| <i>DiskImage.n.Volume.Size</i> | The size, in GB (2 ³⁰ bytes), of the Amazon EBS volume that will hold the converted image. Type: Integer Default: None | Yes |
| <i>Platform</i> | The EC2 instance operating system. Type: String Default: None Valid value: Windows | Yes |

Response Elements

The elements in the following table are wrapped in an `ImportInstanceResponse` structure.

| Name | Description |
|----------------|--|
| conversionTask | Information about the import instance task. Type: ConversionTaskType (p. 411) |

Examples

Example Request

This example creates an import instance task that migrates a Windows Server 2008 SP2 (32-bit) VM into the AWS us-east-1 Region.

```
https://ec2.amazonaws.com/?Action=ImportInstance
&Architecture=x86_64
&InstanceType=m1.xlarge
&DiskImage.1.Image.Format=VMDK
&DiskImage.1.Image.Bytes=1179593728
&DiskImage.1.Image.ImportManifestUrl=https://s3.amazonaws.com/myawsbucket/
a3a5e1b6-590d-43cc-97c1-15c7325d3f41/Win_2008_Server_Data_Center_SP2_32-bit.
vmdkmanifest.xml?AWSAccessKeyId=AKIAIOSFODNN7EXAMPLE&Expires=1294855591&Signa
ture=5snej01TtL0uR7KExtEXAMPLE%3D
&DiskImage.1.Volume.Size=12
&Platform=Windows
&AUTHPARAMS
```

Example Response

```
<ImportInstanceResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <conversionTask>
    <conversionTaskId>import-i-ffvko9js</conversionTaskId>
    <expirationTime>2010-12-22T12:01Z</expirationTime>
    <importInstance>
      <volumes>
        <item>
          <bytesConverted>0</bytesConverted>
          <availabilityZone>us-east-1a</availabilityZone>
          <image>
            <format>VMDK</format>
            <size>1179593728</size>
            <importManifestUrl>
              https://s3.amazonaws.com/myawsbucket/a3a5e1b6-590d-43cc-97c1-
15c7325d3f41/Win_2008_Server_Data_Center_SP2_32-bit.vmdkmanifest.xml?AWSAccess
KeyId=AKIAIOSFODNN7EXAMPLE&Expires=1294855591&Signature=5snej01TtL0uR7KEx
tEXAMPLE%3D
            </importManifestUrl>
          </image>
          <description/>
          <volume>
            <size>12</size>
            <id>vol-1a2b3c4d</id>
          </volume>
          <status>active</status>
          <statusMessage/>
        </item>
      </volumes>
    </importInstance>
  </conversionTask>
</ImportInstanceResponse>
```

```
        </item>
      </volumes>
      <instanceId>i-12655a7f</instanceId>
      <description/>
    </importInstance>
  </conversionTask>
</ImportInstanceResponse>
```

Related Operations

- [ImportVolume](#) (p. 318)
- [DescribeConversionTasks](#) (p. 156)
- [CancelConversionTask](#) (p. 45)

ImportKeyPair

Description

Imports the public key from an RSA key pair that you created with a third-party tool. Compare this with `CreateKeyPair`, in which AWS creates the key pair and gives the keys to you (AWS keeps a copy of the public key). With `ImportKeyPair`, you create the key pair and give AWS just the public key. The private key is never transferred between you and AWS.

You can easily create an RSA key pair on Windows and Linux using the `ssh-keygen` command line tool (provided with the standard OpenSSH installation). Standard library support for RSA key pair creation is also available in Java, Ruby, Python, and many other programming languages.

Supported formats:

- OpenSSH public key format (e.g., the format in `~/.ssh/authorized_keys`)
- Base64 encoded DER format
- SSH public key file format as specified in [RFC4716](#)

DSA keys are not supported. Make sure your key generator is set up to create RSA keys.

Supported lengths: 1024, 2048, and 4096.

Request Parameters

| Name | Description | Required |
|--------------------------|--|----------|
| <i>KeyName</i> | A unique name for the key pair. Type: String Default: None Constraints: Accepts alphanumeric characters, spaces, dashes, and underscores. | Yes |
| <i>PublicKeyMaterial</i> | The public key. You must base64 encode the public key material before sending it to AWS. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in an `ImportKeyPairResponse` structure.

| Name | Description |
|------------------------|--|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>keyName</code> | The key pair name you provided. Type: <code>xsd:string</code> |

ImportVolume

Description

Creates a new import volume task using metadata from the specified disk image. After importing the image, you then upload it using the `ec2-upload-disk-image` command in the EC2 command line tools. For more information, see [Using the Command Line Tools to Import Your Virtual Machine to Amazon EC2](#) in the *Amazon Elastic Compute Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|--------------------------------|---|----------|
| <i>AvailabilityZone</i> | The Availability Zone for the resulting Amazon EBS volume. Type: String Default: None | Yes |
| <i>Image.Format</i> | The file format of the disk image. Type: String Default: None Valid values: VMDK RAW VHD | Yes |
| <i>Image.Bytes</i> | The number of bytes in the disk image. Type: Long Default: None | Yes |
| <i>Image.ImportManifestUrl</i> | The manifest for the disk image, stored in Amazon S3 and presented here as an Amazon S3 presigned URL. For information about creating a presigned URL for an Amazon S3 object, read the "Signing and Authenticating REST Requests" section of the Signing and Authenticating REST Requests topic in the <i>Amazon Simple Storage Service Developer Guide</i> . Type: String Default: None | Yes |
| <i>Description</i> | An optional description of the volume being imported. Type: String Default: None | No |
| <i>Volume.Size</i> | The size, in GB (2 ³⁰ bytes), of an Amazon EBS volume to hold the converted image. Type: Integer Default: None | Yes |

Response Elements

The elements in the following table are wrapped in an `ImportVolumeResponse` structure.

| Name | Description |
|----------------|--|
| conversionTask | Information about the import volume task. Type: ConversionTaskType (p. 411) |

Examples

Example Request

This example creates an import volume task that migrates a Windows Server 2008 SP2 (32-bit) volume into the AWS us-east-1 Region.

```
https://ec2.amazonaws.com/?Action=ImportVolume
&AvailabilityZone=us-east-1c
&Image.Format=VMDK
&Image.Bytes=128696320
&Image.ImportManifestUrl=https://s3.amazonaws.com/myawsbucket/a3a5e1b6-590d-43cc-97c1-15c7325d3f41/Win_2008_Server_Data_Center_SP2_32-bit.vmdkmanifest.xml?AWSAccessKeyId=AKIAIOSFODNN7EXAMPLE&Expires=1294855591&Signature=5snej01TlTtL0uR7KExtEXAMPLE%3D
&VolumeSize=8
&AUTHPARAMS
```

Example Response

```
<ImportVolumeResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <conversionTask>
    <conversionTaskId>import-i-fh95npoc</conversionTaskId>
    <expirationTime>2010-12-22T12:01Z</expirationTime>
    <importVolume>
      <bytesConverted>0</bytesConverted>
      <availabilityZone>us-east-1c</availabilityZone>
      <description/>
      <image>
        <format>VMDK</format>
        <size>128696320</size>
        <importManifestUrl>
          https://s3.amazonaws.com/myawsbucket/a3a5e1b6-590d-43cc-97c1-15c7325d3f41/Win_2008_Server_Data_Center_SP2_32-bit.vmdkmanifest.xml?AWSAccessKeyId=AKIAIOSFODNN7EXAMPLE&Expires=1294855591&Signature=5snej01TlTtL0uR7KExtEXAMPLE%3D
        </importManifestUrl>
        <checksum>ccb1b0536a4a70e86016b85229b5c6b10b14a4eb</checksum>
      </image>
      <volume>
        <size>8</size>
        <id>vol-34d8a2ff</id>
      </volume>
    </importVolume>
    <state>active</state>
    <statusMessage/>
  </conversionTask>
</ImportVolumeResponse>
```

Related Operations

- [ImportInstance](#) (p. 312)
- [DescribeConversionTasks](#) (p. 156)
- [CancelConversionTask](#) (p. 45)

ModifyImageAttribute

Description

Modifies an attribute of an AMI.

Note

AWS Marketplace product codes cannot be modified. Images with an AWS Marketplace product code cannot be made public.

Request Parameters

| Name | Description | Required |
|---|---|----------|
| <i>ImageId</i> | The AMI ID. Type: String Default: None | Yes |
| <i>LaunchPermission.Add.n.UserId</i> | Adds the specified AWS account ID to the AMI's list of launch permissions. Type: String Default: None | No |
| <i>LaunchPermission.Remove.n.UserId</i> | Removes the specified AWS account ID from the AMI's list of launch permissions. Type: String Default: None | No |
| <i>LaunchPermission.Add.n.Group</i> | Adds the specified group to the image's list of launch permissions. The only valid value is <code>all</code> . Type: String Valid value: <code>all</code> (for all EC2 users) Default: None | No |
| <i>LaunchPermission.Remove.n.Group</i> | Removes the specified group from the image's list of launch permissions. The only valid value is <code>all</code> . Type: String Valid value: <code>all</code> (for all EC2 users) Default: None | No |
| <i>ProductCode.n</i> | Adds the specified product code to the specified Amazon S3-backed AMI. Once you add a product code to an AMI, it can't be removed. Type: String Default: None | No |
| <i>Description.Value</i> | Changes the AMI's description to the specified value. Type: String Default: None | No |

Response Elements

The elements in the following table are wrapped in a `ModifyImageAttributeResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if successful. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example makes the AMI public (i.e., so any AWS account can launch it).

```
https://ec2.amazonaws.com/?Action=ModifyImageAttribute
&ImageId=ami-61a54008
&LaunchPermission.Add.1.Group=all
&AUTHPARAMS
```

Example Request

This example makes the AMI private (i.e., so only you as the owner can launch it).

```
https://ec2.amazonaws.com/?Action=ModifyImageAttribute
&ImageId=ami-61a54008
&LaunchPermission.Remove.1.Group=all
&AUTHPARAMS
```

Example Request

This example grants launch permission to the AWS account with ID 111122223333.

```
https://ec2.amazonaws.com/?Action=ModifyImageAttribute
&ImageId=ami-61a54008
&LaunchPermission.Add.1.UserId=111122223333
&AUTHPARAMS
```

Example Request

This example removes launch permission from the AWS account with ID 111122223333.

```
https://ec2.amazonaws.com/?Action=ModifyImageAttribute
&ImageId=ami-61a54008
&LaunchPermission.Remove.1.UserId=111122223333
&AUTHPARAMS
```

Example Request

This example adds the 774F4FF8 product code to the ami-61a54008 AMI.

```
https://ec2.amazonaws.com/?Action=ModifyImageAttribute
&ImageId=ami-61a54008
&ProductCode.1=774F4FF8
&AUTHPARAMS
```

Example Request

This example changes the description of the AMI to New_Description

```
https://ec2.amazonaws.com/?Action=ModifyImageAttribute
&ImageId=ami-61a54008
&Description.Value=New_Description
&AUTHPARAMS
```

Example Response

```
<ModifyImageAttributeResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <return>true</return>
</ModifyImageAttributeResponse>
```

Related Operations

- [ResetImageAttribute](#) (p. 365)
- [DescribeImageAttribute](#) (p. 167)

ModifyInstanceAttribute

Description

Modifies an attribute of an instance.

Note

To modify some attributes, the instance must be stopped. For more information, see [Using Instance Metadata](#) in the *Amazon Elastic Compute Cloud User's Guide*.

Note

If you want to add instance store volumes to an Amazon EBS-backed instance, you must add them when you launch the instance. For more information, see [Overriding the AMI's Block Device Mapping](#) in the *Amazon Elastic Compute Cloud User Guide*, or to [Using Amazon EC2 Instance Storage](#) in the *Amazon Elastic Compute Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|------------------------------------|---|----------|
| <i>InstanceId</i> | The ID of the instance. Type: String Default: None | Yes |
| <i>InstanceType.Value</i> | Changes the instance type to the specified value. Type: String Default: None | No |
| <i>Kernel.Value</i> | Changes the instance's kernel to the specified value. Type: String Default: None | No |
| <i>Ramdisk.Value</i> | Changes the instance's RAM disk to the specified value. Type: String Default: None | No |
| <i>UserData.Value</i> | Changes the instance's user data to the specified value. Type: String Default: None | No |
| <i>DisableApiTermination.Value</i> | Changes the instance's <code>DisableApiTermination</code> flag to the specified value. A value of <code>true</code> means you can't terminate the instance using the API (i.e., the instance is "locked"); a value of <code>false</code> means you can. You must modify this attribute before you can terminate any "locked" instances using the API. Type: Boolean Default: None | No |

| Name | Description | Required |
|--|--|----------|
| <i>InstanceInitiatedShutdownBehavior.Value</i> | <p>Changes the instance's InstanceInitiatedShutdownBehavior flag to the specified value.</p> <p>Type: String Default: None Valid values: stop terminate</p> | No |
| <i>BlockMappingDevice.Value</i> | <p>Modifies the DeleteOnTermination attribute for volumes that are currently attached. The volume must be owned by the caller. If no value is specified for DeleteOnTermination, the value defaults to true and the volume will be deleted when the instance is terminated.</p> <p>Type: BlockDeviceMapping Default: None Example:</p> <pre>&BlockDeviceMapping1.DeviceName=/dev/sdh &BlockDeviceMapping.1.Ebs.DeleteOnTermination=true</pre> | No |
| <i>SourceDestCheck.Value</i> | <p>Enables a Network Address Translation (NAT) instance in a VPC to perform NAT. The attribute controls whether source/destination checking is enabled on the instance. A value of true means checking is enabled, and false means checking is disabled. The value must be false for the instance to perform NAT. For more information, see NAT Instances in the <i>Amazon Virtual Private Cloud User Guide</i>.</p> <p>Type: Boolean Default: None</p> | No |
| <i>GroupId.n</i> | <p>For instances running in a VPC: Changes the security groups that an instance is in. The new set of groups you specify replaces the current set. You must specify at least one group, even if it's just the default security group in the VPC. You must specify the group ID and not the group name.</p> <p>For example, if you want the instance to be in sg-1a1a1a1a and sg-9b9b9b9b, specify GroupId.1=sg-1a1a1a1a and GroupId.2=sg-9b9b9b9b.</p> <p>Type: String Default: None</p> | No |

Response Elements

The elements in the following table are wrapped in a `ModifyInstanceAttributeResponse` structure.

| Name | Description |
|-----------|--|
| requestId | The ID of the request. Type: xsd:string |
| return | Returns <code>true</code> if successful. Otherwise, returns an error. Type: xsd:boolean |

Examples

Example Request

This example changes the kernel for the instance.

```
https://ec2.amazonaws.com/?Action=ModifyInstanceAttribute
&InstanceId=i-10a64379
&Kernel.Value=aki-f70657b2
&AUTHPARAMS
```

Example Response

```
<ModifyInstanceAttributeResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <return>true</return>
</ModifyInstanceAttributeResponse>
```

Related Operations

- [ResetInstanceAttribute](#) (p. 367)
- [DescribeInstanceAttribute](#) (p. 178)

ModifyNetworkInterfaceAttribute

Description

Modifies a network interface attribute. Only one attribute can be specified per call.

Request Parameters

| Name | Description | Required |
|---------------------------------------|---|-------------|
| <i>NetworkInterfaceId</i> | The ID of the network interface. Type: String Default: None | Yes |
| <i>Description.Value</i> | The description of the network interface. Type: String Default: None | No |
| <i>SecurityGroupId.n</i> | Changes the security groups that a network interface is in. The new set of groups you specify replaces the current set. You must specify at least one group, even if it's just the default security group in the VPC. You must specify the group ID and not the group name. For example, if you want the instance to be in sg-1a1a1a1a and sg-9b9b9b9b, specify GroupId.1=sg-1a1a1a1a and GroupId.2=sg-9b9b9b9b. Type: String Default: None | No |
| <i>SourceDestCheck.Value</i> | Enables a Network Address Translation (NAT) instance in a VPC to perform NAT. The attribute controls whether source/destination checking is enabled on the instance. A value of <code>true</code> means checking is enabled, and <code>false</code> means checking is disabled. The value must be <code>false</code> for the instance to perform NAT. For more information, see NAT Instances in the <i>Amazon Virtual Private Cloud User Guide</i> . Type: Boolean Default: None | No |
| <i>Attachment.AttachmentId</i> | The ID of the interface attachment. This parameter is required if you are modifying the <code>DeleteOnTermination</code> attribute of an interface attachment. Type: String Default: None | Conditional |
| <i>Attachment.DeleteOnTermination</i> | Specifies whether to delete the attachment when terminating the instance. You must specify a specific attachment ID to change this attribute. Type: Boolean Default: None | Conditional |

Response Elements

The elements in the following table are wrapped in a `ModifyNetworkInterfaceAttribute` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example sets source/destination checking to `false` for the elastic network interface (ENI) `eni-ffda3197`.

```
https://ec2.amazonaws.com/?Action=ModifyNetworkInterfaceAttribute
&NetworkInterfaceId=eni-ffda3197
&SourceDestCheck.Value=false
&AUTHPARAMS
```

Example Response

```
<ModifyNetworkInterfaceAttributeResponse xmlns='http://ec2.amazon
aws.com/doc/2011-11-15/'>
  <requestId>657a4623-5620-4232-b03b-427e852d71cf</requestId>
  <return>true</return>
</ModifyNetworkInterfaceAttributeResponse>
```

Related Operations

- [AttachNetworkInterface](#) (p. 27)
- [DetachNetworkInterface](#) (p. 296)
- [CreateNetworkInterface](#) (p. 72)
- [DeleteNetworkInterface](#) (p. 117)
- [DescribeNetworkInterfaceAttribute](#) (p. 214)
- [DescribeNetworkInterfaces](#) (p. 216)
- [ResetNetworkInterfaceAttribute](#) (p. 369)

ModifySnapshotAttribute

Description

Adds or remove permission settings for the specified snapshot.

Note

Snapshots with AWS Marketplace product codes cannot be made public.

Request Parameters

| Name | Description | Required |
|---|---|----------|
| <i>SnapshotId</i> | The ID of the snapshot. Type: String Default: None | Yes |
| <i>CreateVolumePermission.Add.n.UserId</i> | Adds the specified AWS account ID to the volume's list of create volume permissions. Type: String Default: None | Yes |
| <i>CreateVolumePermission.Add.n.Group</i> | Adds the specified group to the volume's list of create volume permissions. The only valid value is <code>all</code> . Type: String Default: None | Yes |
| <i>CreateVolumePermission.Remove.n.UserId</i> | Removes the specified AWS account ID from the volume's list of create volume permissions. Type: String Default: None | No |
| <i>CreateVolumePermission.Remove.n.Group</i> | Removes the specified group from the volume's list of create volume permissions. Type: String Default: None | No |

Response Elements

The elements in the following table are wrapped in a `ModifySnapshotAttributeResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if successful. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example makes the snap-78a54011 snapshot public, and gives the account with ID 111122223333 permission to create volumes from the snapshot.

```
https://ec2.amazonaws.com/?Action=ModifySnapshotAttribute
&snapshotId=snap-78a54011
&CreateVolumePermission.Add.1.UserId=111122223333
&CreateVolumePermission.Add.1.Group=all
&AUTHPARAMS
```

This example makes the snap-78a54011 snapshot public, and removes the account with ID 111122223333 from the list of users with permission to create volumes from the snapshot.

```
https://ec2.amazonaws.com/?Action=ModifySnapshotAttribute
&snapshotId=snap-78a54011
&CreateVolumePermission.Remove.1.UserId=111122223333
&CreateVolumePermission.Add.1.Group=all
&AUTHPARAMS
```

Example Response

```
<ModifySnapshotAttributeResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <return>true</return>
</ModifySnapshotAttributeResponse>
```

Related Operations

- [DescribeSnapshotAttribute](#) (p. 244)
- [DescribeSnapshots](#) (p. 246)
- [ResetSnapshotAttribute](#) (p. 371)
- [CreateSnapshot](#) (p. 86)

ModifyVolumeAttribute

Description

Modifies a volume attribute.

By default, all I/O operations for the volume are suspended when the data on the volume is determined to be potentially inconsistent, to prevent undetectable, latent data corruption. The I/O access to the volume can be resumed by first calling [EnableVolumeIO \(p. 306\)](#) action to enable I/O access and then checking the data consistency on your volume.

You can change the default behavior to resume I/O operations without calling [EnableVolumeIO \(p. 306\)](#) action by setting the `AutoEnableIO` attribute of the volume to `true`. We recommend that you change this attribute only for volumes that are stateless, or disposable, or for boot volumes.

Request Parameters

| Name | Description | Required |
|---------------------------------|--|----------|
| <code>VolumeId</code> | The ID of the volume. Type: String Default: None | Yes |
| <code>AutoEnableIO.Value</code> | This attribute exists to auto-enable the I/O operations to the volume. Type: AttributeBooleanValueType Default: <code>false</code> | Yes |

Response Elements

The elements in the following table are wrapped in a `ModifyVolumeAttributeResponse` structure.

| Name | Description |
|------------------------|--|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the auto-enable of the specified volume is enabled. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example modifies the attribute of the volume `vol-12345678`

```
https://ec2.amazonaws.com/?Action=ModifyVolumeAttribute
&VolumeId=vol-12345678
```

```
&AutoEnableIO.Value=true  
&AUTHPARAMS
```

Example Response

```
<ModifyVolumeAttributeResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">  
  <requestId>5jkdf074-37ed-4004-8671-a78ee82bf1cbEXAMPLE</requestId>  
  <return>true</return>  
</ModifyVolumeAttributeResponse>
```

Related Operations

- [DescribeVolumeAttribute](#) (p. 276)
- [DescribeVolumeStatus](#) (p. 278)

MonitorInstances

Description

Enables monitoring for a running instance. For more information about monitoring instances, see [Monitoring Your Instances and Volumes](#) in the *Amazon Elastic Compute Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|---------------------|--|----------|
| <i>InstanceId.n</i> | One or more instance IDs. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in a `MonitorInstancesResponse` structure.

| Name | Description |
|---------------------------|--|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>instancesSet</code> | A list of instances. Each instance is wrapped in an <code>item</code> element. Type: MonitorInstancesResponseSetItemType (p. 450) |

Examples

Example Request

This example enables monitoring for i-43a4412a and i-23a3397d.

```
https://ec2.amazonaws.com/?Action=MonitorInstances
&InstanceId.1=i-43a4412a
&InstanceId.2=i-23a3397d
&AUTHPARAMS
```

Example Response

```
<MonitorInstancesResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <instancesSet>
    <item>
      <instanceId>i-43a4412a</instanceId>
      <monitoring>
        <state>pending</state>
```

```
    </monitoring>
  </item>
  <item>
    <instanceId>i-23a3397d</instanceId>
    <monitoring>
      <state>pending</state>
    </monitoring>
  </item>
</instancesSet>
</MonitorInstancesResponse>
```

Related Operations

- [UnmonitorInstances](#) (p. 398)
- [RunInstances](#) (p. 379)

PurchaseReservedInstancesOffering

Description

Purchases a Reserved Instance for use with your account. With Amazon EC2 Reserved Instances, you purchase the right to launch Amazon EC2 instances for a period of time (without getting insufficient capacity errors) and pay a lower usage rate for the actual time used.

Starting with the 2011-11-01 API version, AWS expanded its offering of Amazon EC2 Reserved Instances to address a range of projected instance use. There are three types of Reserved Instances based on customer utilization levels: *Heavy Utilization*, *Medium Utilization*, and *Light Utilization*. You determine the type of the Reserved Instances offerings by including the optional *offeringType* parameter when calling `DescribeReservedInstancesOfferings`. After you've identified the Reserved Instance with the offering type you want, specify its *ReservedInstancesOfferingId* when you call `PurchaseReservedInstancesOffering`.

The Medium Utilization offering type is equivalent to the Reserved Instance offering available before API version 2011-11-01. If you are using tools that predate the 2011-11-01 API version, `DescribeReservedInstancesOfferings` will only list information about the Medium Utilization Reserved Instance offering type.

For more information about Reserved Instances, see [Reserved Instances](#) in the *Amazon Elastic Compute Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|------------------------------------|--|----------|
| <i>ReservedInstancesOfferingId</i> | The ID of the Reserved Instance offering. Type: String Default: None | Yes |
| <i>InstanceCount</i> | The number of Reserved Instances to purchase. Type: Integer Default: 1 | No |

Response Elements

The elements in the following table are wrapped in a `PurchaseReservedInstancesOfferingResponse` structure.

| Name | Description |
|----------------------------------|--|
| <code>requestId</code> | The ID of the request. Type: xsd:string |
| <code>reservedInstancesId</code> | The IDs of the purchased Reserved Instances. Type: xsd:string |

Examples

Example Request

This example illustrates a purchase of a Reserved Instances offering.

```
https://ec2.amazonaws.com/?Action=PurchaseReservedInstancesOffering
&ReservedInstancesOfferingId=4b2293b4-5813-4cc8-9ce3-1957fc1dcfc8
&InstanceCount=2
&AUTHPARAMS
```

Example Response

```
<PurchaseReservedInstancesOfferingResponse xmlns="http://ec2.amazon
aws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <reservedInstancesId>af9f760e-c1c1-449b-8128-1342d3a6927a</reservedIn
stancesId>
</PurchaseReservedInstancesOfferingResponse>
```

Related Operations

- [DescribeReservedInstancesOfferings](#) (p. 232)
- [DescribeReservedInstances](#) (p. 228)

RebootInstances

Description

Requests a reboot of one or more instances. This operation is asynchronous; it only queues a request to reboot the specified instance(s). The operation will succeed if the instances are valid and belong to you. Requests to reboot terminated instances are ignored.

Note

If a Linux/UNIX instance does not cleanly shut down within four minutes, Amazon EC2 will perform a hard reboot.

Request Parameters

| Name | Description | Required |
|---------------------|--|----------|
| <i>InstanceId.n</i> | One or more instance IDs. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in a `RebootInstancesResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if successful. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example reboots two instances.

```
https://ec2.amazonaws.com/?Action=RebootInstances
&InstanceId.1=i-1a2b3c4d
&InstanceId.2=i-4d3acf62
&AUTHPARAMS
```


Example Response

```
<RebootInstancesResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">  
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>  
  <return>true</return>  
</RebootInstancesResponse>
```

Related Operations

- [RunInstances](#) (p. 379)

RegisterImage

Description

Registers a new AMI with Amazon EC2. When you're creating an AMI, this is the final step you must complete before you can launch an instance from the AMI. For more information about creating AMIs, see [Creating Your Own AMIs](#) in the *Amazon Elastic Compute Cloud User Guide*.

Note

For Amazon EBS-backed instances, the `CreateImage` operation creates and registers the AMI in a single request, so you don't have to register the AMI yourself.

You can also use the `RegisterImage` action to create an EBS-backed AMI from a snapshot of a root device volume. For more information, see [Launching an Instance from a Snapshot](#) in the *Amazon Elastic Compute Cloud User Guide*.

If needed, you can deregister an AMI at any time. Any modifications you make to an AMI backed by Amazon S3 invalidates its registration. If you make changes to an image, deregister the previous image and register the new image.

Note

You cannot register an image where a secondary (non-root) snapshot has AWS Marketplace product codes.

Request Parameters

| Name | Description | Required |
|----------------------|--|-------------|
| <i>ImageLocation</i> | The full path to your AMI manifest in Amazon S3 storage. Type: String Default: None Condition: Required if registering an Amazon-S3 backed AMI | Conditional |
| <i>Name</i> | A name for your AMI. Type: String Default: None Constraints: 3-128 alphanumeric characters, parenthesis (), commas (,), slashes (/), dashes (-), or underscores(_) | Yes |
| <i>Description</i> | A description of the AMI. Type: String Default: None Constraints: Up to 255 characters. | No |
| <i>Architecture</i> | The architecture of the image. Type: String Valid values: <code>i386</code> <code>x86_64</code> Default: <code>i386</code> for EBS backed AMIs. Instance store-backed AMIs will try to use the architecture specified in the manifest file. | No |

Amazon Elastic Compute Cloud API Reference
Request Parameters

| Name | Description | Required |
|--|--|-----------------|
| <i>KernelId</i> | The ID of the kernel. Type: String Default: None | No |
| <i>RamdiskId</i> | The ID of the RAM disk. Some kernels require additional drivers at launch. Check the kernel requirements for information on whether you need to specify a RAM disk. To find kernel requirements, refer to the Resource Center and search for the kernel ID. Type: String Default: None | No |
| <i>RootDeviceName</i> | The name of the root device (for example, /dev/sda1, or xvda). Type: String Default: None Condition: Required if registering an Amazon EBS-backed AMI | Conditional |
| <i>BlockDeviceMapping.n.DeviceName</i> | The device name exposed to the instance (for example, /dev/sdh, or xvdh). Type: String Default: None Condition: If registering an Amazon EBS-backed AMI from a snapshot, you must at least specify this field with the root device name (e.g., /dev/sda1, or xvda), and <i>BlockDeviceMapping.n.Ebs.SnapshotId</i> with the snapshot ID | Conditional |
| <i>BlockDeviceMapping.n.VirtualName</i> | The name of the virtual device. Type: String Default: None | No |
| <i>BlockDeviceMapping.n.Ebs.SnapshotId</i> | The ID of the snapshot. Type: String Default: None Condition: If registering an Amazon EBS-backed AMI from a snapshot, you must at least specify this field with the snapshot ID, and <i>BlockDeviceMapping.n.DeviceName</i> with the root device name | Conditional |
| <i>BlockDeviceMapping.n.Ebs.VolumeSize</i> | The size of the volume, in GiBs. Type: Integer Default: None Condition: Required if you are not creating a volume from a snapshot. | Conditional |
| <i>BlockDeviceMapping.n.Ebs.NoDevice</i> | Suppresses a device mapping. Type: Boolean Default: true | No |

| Name | Description | Required |
|---|---|----------|
| <i>BlockDeviceMapping.n.Ebs.DeleteOnTermination</i> | Specifies whether the Amazon EBS volume is deleted on instance termination. Type: Boolean Default: true | No |

Response Elements

The elements in the following table are wrapped in a `RegisterImageResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: xsd:string |
| <code>imageId</code> | The ID of the newly registered AMI. Type: xsd:string |

Examples

Example Request

This example registers the AMI specified in the `my-new-image.manifest.xml` manifest file, located in the bucket called `myawsbucket`.

```
https://ec2.amazonaws.com/?Action=RegisterImage
&ImageLocation=myawsbucket/my-new-image.manifest.xml
&AUTHPARAMS
```

Example Request

This example registers an Amazon EBS snapshot to create an AMI backed by Amazon EBS.

```
https://ec2.amazonaws.com/?Action=RegisterImage
&RootDeviceName=/dev/sda1
&BlockDeviceMapping.1.DeviceName=/dev/sda1
&BlockDeviceMapping.1.Ebs.SnapshotId=snap-6eba6e06
&Name=MyImage
&AUTHPARAMS
```

Example Request

This example registers the AMI with an Amazon EBS snapshot as the root device, a separate snapshot as a secondary device, and an empty 100 GiB Amazon EBS volume as a storage device.

```
https://ec2.amazonaws.com/?Action=RegisterImage
&RootDeviceName=/dev/sda1
&BlockDeviceMapping.1.DeviceName=/dev/sda1
```

```
&BlockDeviceMapping.1.Ebs.SnapshotId=snap-6eba6e06  
&BlockDeviceMapping.2.DeviceName=/dev/sdb  
&BlockDeviceMapping.2.Ebs.SnapshotId=snap-823ea6df  
&BlockDeviceMapping.3.DeviceName=/dev/sdc  
&BlockDeviceMapping.3.Ebs.VolumeSize=100  
&Name=MyImage  
&AUTHPARAMS
```

Example Response

```
<RegisterImageResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">  
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>  
  <imageId>ami-78a54043</imageId>  
</RegisterImageResponse>
```

Related Operations

- [DescribeImages](#) (p. 170)
- [DeregisterImage](#) (p. 143)

ReleaseAddress

Description

Releases an Elastic IP address allocated to your account.

This action applies to both EC2 Elastic IP addresses and VPC Elastic IP addresses. For information about VPC addresses and how they differ from EC2 addresses, see [Elastic IP Addresses](#) in the *Amazon Virtual Private Cloud User Guide*.

If you run this action on an Elastic IP address that is already released, the address might be assigned to another account, which will cause Amazon EC2 to return an error (`AuthFailure`).

Note

For EC2 addresses only: Releasing an IP address automatically disassociates it from any instance it's associated with. To disassociate an IP address without releasing it, use the `DisassociateAddress` action.

If you try to release a VPC address that's associated with an instance, Amazon EC2 returns an error (`InvalidIpAddress.InUse`).

Important

After releasing an Elastic IP address, it is released to the IP address pool and might be unavailable to your account. Make sure to update your DNS records and any servers or devices that communicate with the address.

Request Parameters

| Name | Description | Required |
|---------------------|--|-------------|
| <i>PublicIp</i> | The EC2 Elastic IP address. Type: String Default: None Condition: Required for EC2 Elastic IP addresses | Conditional |
| <i>AllocationId</i> | The allocation ID that AWS provided when you allocated the address for use with Amazon VPC. Type: String Default: None Condition: Required for VPC Elastic IP addresses | Conditional |

Response Elements

The elements in the following table are wrapped in a `ReleaseAddressResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |

| Name | Description |
|--------|---|
| return | Returns true if successful. Otherwise, returns an error. Type: xsd:boolean |

Examples

Example Request

This example releases an EC2 Elastic IP address (67.202.55.255).

```
https://ec2.amazonaws.com/?Action=ReleaseAddress
&PublicIp=192.0.2.1
&AUTHPARAMS
```

Example Request

This example releases a VPC Elastic IP address with allocation ID eipalloc-5723d13e.

```
https://ec2.amazonaws.com/?Action=ReleaseAddress
&AllocationId=eipalloc-5723d13e
&AUTHPARAMS
```

Example Response

```
<ReleaseAddressResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <return>true</return>
</ReleaseAddressResponse>
```

Related Operations

- [AllocateAddress](#) (p. 13)
- [DescribeAddresses](#) (p. 145)
- [AssociateAddress](#) (p. 18)
- [DisassociateAddress](#) (p. 302)

ReplaceNetworkAclAssociation

Description

Changes which network ACL a subnet is associated with. By default when you create a subnet, it's automatically associated with the default network ACL. For more information about network ACLs, see [Network ACLs](#) in the *Amazon Virtual Private Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|----------------------|---|----------|
| <i>AssociationId</i> | The ID representing the current association between the original network ACL and the subnet. Type: String Default: None | Yes |
| <i>NetworkAclId</i> | The ID of the new ACL to associate with the subnet. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in a `ReplaceNetworkAclAssociationResponse` structure.

| Name | Description |
|-------------------------------|--|
| <code>requestId</code> | The ID of the request. Type: xsd:string |
| <code>newAssociationId</code> | The ID representing the new association. Type: xsd:string |

Examples

Example Request

This example starts with a network ACL associated with a subnet, and a corresponding association ID `aassoc-e5b95c8c`. You want to associate a different network ACL (`acl-5fb85d36`) with the subnet. The result is a new association ID representing the new association.

```
https://ec2.amazonaws.com/?Action=ReplaceNetworkAclAssociation
&AssociationId=aassoc-e5b95c8c
&NetworkAclId=acl-5fb85d36
&AUTHPARAMS
```


Example Response

```
<ReplaceNetworkAclAssociationResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <newAssociationId>aassoc-17b85d7e</newAssociationId>
</ReplaceNetworkAclAssociationResponse>
```

Related Operations

- [CreateNetworkAcl](#) (p. 67)
- [DeleteNetworkAcl](#) (p. 113)
- [DescribeNetworkAcls](#) (p. 209)

ReplaceNetworkAclEntry

Description

Replaces an entry (i.e., rule) in a network ACL. For more information about network ACLs, see [Network ACLs](#) in the *Amazon Virtual Private Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|---------------------------|--|-------------|
| <code>NetworkAclId</code> | The ID of the ACL. Type: String Default: None | Yes |
| <code>RuleNumber</code> | The rule number of the entry to replace. Type: Integer Default: None | Yes |
| <code>Protocol</code> | The IP protocol the rule applies to. You can use -1 to mean all protocols. Type: Integer Valid values: -1 or a protocol number (go to Protocol Numbers). | Yes |
| <code>RuleAction</code> | Indicates whether to allow or deny traffic that matches the rule. Type: String Default: None Valid values: allow deny | Yes |
| <code>Egress</code> | Indicates whether this rule applies to egress traffic from the subnet (<code>true</code>) or ingress traffic to the subnet (<code>false</code>). Type: Boolean Default: <code>false</code> Valid values: <code>true</code> <code>false</code> | No |
| <code>CidrBlock</code> | The CIDR range to allow or deny, in CIDR notation (e.g., 172.16.0.0/24). Type: String Default: None | Yes |
| <code>Icmp.Code</code> | For the ICMP protocol, the ICMP code. You can use -1 to specify all ICMP codes for the given ICMP type. Type: Integer Default: None Condition: Required if specifying 1 (ICMP) for the protocol. | Conditional |

| Name | Description | Required |
|-----------------------------|---|-------------|
| <code>Icmp.Type</code> | For the ICMP protocol, the ICMP type. You can use -1 to specify all ICMP types. Type: Integer Default: None Condition: Required if specifying 1 (ICMP) for the protocol. | Conditional |
| <code>PortRange.From</code> | The first port in the range. Type: Integer Default: None Condition: Required if specifying 6 (TCP) or 17 (UDP) for the protocol. | Conditional |
| <code>PortRange.To</code> | The last port in the range. Type: Integer Default: None Condition: Required if specifying 6 (TCP) or 17 (UDP) for the protocol. | Conditional |

Response Elements

The elements in the following table are wrapped in a `ReplaceNetworkAclEntryResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example replaces the egress entry numbered 110 in the network ACL with ID `acl-2cb85d45`. The new rule denies egress traffic destined for anywhere (`0.0.0.0/0`) on TCP port 139.

```
https://ec2.amazonaws.com/?Action=ReplaceNetworkAclEntry
&NetworkAclId=acl-2cb85d45
&RuleNumber=110
&Protocol=tcp
&RuleAction=deny
&Egress=true
&CidrBlock=0.0.0.0/0
&PortRange.From=139
&PortRange.To=139
&AUTHPARAMS
```

Example Response

```
<ReplaceNetworkAclEntryResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <return>true</return>
</ReplaceNetworkAclEntryResponse>
```

Related Operations

- [CreateNetworkAclEntry](#) (p. 69)
- [DeleteNetworkAclEntry](#) (p. 115)
- [DescribeNetworkAcls](#) (p. 209)

ReplaceRoute

Description

Replaces an existing route within a route table in a VPC. For more information about route tables, see [Route Tables](#) in the *Amazon Virtual Private Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|-----------------------------|---|-------------|
| <i>RouteTableId</i> | The ID of the route table. Type: String Default: None | Yes |
| <i>DestinationCidrBlock</i> | The CIDR address block used for the destination match. For example: 0.0.0.0/0. The value you provide must match the CIDR of an existing route in the table. Type: String Default: None | Yes |
| <i>GatewayId</i> | The ID of a gateway attached to your VPC. Type: String Default: None Condition: You must provide only one of the following: a <code>GatewayId</code> , <code>InstanceId</code> , or <code>NetworkInterfaceId</code> . | Conditional |
| <i>InstanceId</i> | The ID of a NAT instance in your VPC. Type: String Default: None Condition: You must provide only one of the following: a <code>GatewayId</code> , <code>InstanceId</code> , or <code>NetworkInterfaceId</code> . | Conditional |
| <i>NetworkInterfaceId</i> | Allows routing to network interface attachments. Type: String Default: None Condition: You must provide only one of the following: <code>GatewayId</code> , <code>InstanceId</code> , or <code>NetworkInterfaceId</code> . | Conditional |

Response Elements

The elements in the following table are wrapped in a `ReplaceRouteResponse` structure.

| Name | Description |
|-----------|--|
| requestId | The ID of the request. Type: xsd:string |
| return | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: xsd:boolean |

Examples

Example Request

This example replaces a route in the route table with ID `rtb-e4ad488d`. The new route matches the CIDR `10.0.0/8` and sends the traffic to the virtual private gateway with ID `vgw-1d00376e`.

```
https://ec2.amazonaws.com/?Action=ReplaceRoute
&RouteTableId=rtb-e4ad488d
&DestinationCidrBlock=10.0.0/8
&GatewayId=vgw-1d00376e
&AUTHPARAMS
```

Example Response

```
<ReplaceRouteResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <return>true</return>
</ReplaceRouteResponse>
```

Related Operations

- [DeleteRoute](#) (p. 121)
- [CreateRoute](#) (p. 79)
- [DescribeRouteTables](#) (p. 236)

ReplaceRouteTableAssociation

Description

Changes the route table associated with a given subnet in a VPC. After you execute this action, the subnet uses the routes in the new route table it's associated with. For more information about route tables, see [Route Tables](#) in the *Amazon Virtual Private Cloud User Guide*.

You can also use this action to change which table is the main route table in the VPC. You just specify the main route table's association ID and the route table that you want to be the new main route table.

Request Parameters

| Name | Description | Required |
|----------------------|---|----------|
| <i>AssociationId</i> | The ID representing the current association between the original route table and the subnet. Type: String Default: None | Yes |
| <i>RouteTableId</i> | The ID of the new route table to associate with the subnet. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in a `ReplaceRouteTableAssociationResponse` structure.

| Name | Description |
|-------------------------------|--|
| <code>requestId</code> | The ID of the request. Type: xsd:string |
| <code>newAssociationId</code> | The ID representing the new association. Type: xsd:string |

Examples

Example Request

This example starts with a route table associated with a subnet, and a corresponding association ID `rtbassoc-f8ad4891`. You want to associate a different route table (table `rtb-f9ad4890`) to the subnet. The result is a new association ID representing the new association.

```
https://ec2.amazonaws.com/?Action=ReplaceRouteTableAssociation
&AssociationId=rtbassoc-f8ad4891
&RouteTableId=rtb-f9ad4890
&AUTHPARAMS
```

Example Response

```
<ReplaceRouteTableAssociationResponse xmlns="http://ec2.amazonaws.com/doc/2012-
06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <newAssociationId>rtbassoc-faad4893</newAssociationId>
</ReplaceRouteTableAssociationResponse>
```

Related Operations

- [CreateRouteTable](#) (p. 82)
- [DisassociateRouteTable](#) (p. 304)
- [DeleteRouteTable](#) (p. 123)
- [DescribeRouteTables](#) (p. 236)
- [AssociateRouteTable](#) (p. 23)

ReportInstanceStatus

Description

Use this action to submit feedback about an instance's status. This action works only for instances that are in the `running` state. If your experience with the instance differs from the instance status returned by the `DescribeInstanceStatus` action, use `ReportInstanceStatus` to report your experience with the instance. Amazon EC2 collects this information to improve the accuracy of status checks.

Note

Use of this action does not change the value returned by `DescribeInstanceStatus`.

To report an instance's status, specify an instance ID with the `InstanceID.n` parameter and a reason code with the `ReasonCodes.n` parameter that applies to that instance. The following table contains descriptions of all available reason codes.

| Reason Code | Description |
|----------------------------|--|
| instance-stuck-in-state | My instance is stuck in a state. |
| unresponsive | My instance is unresponsive. |
| not-accepting-credentials | My instance is not accepting my credentials. |
| password-not-available | A password is not available for my instance. |
| performance-network | My instance is experiencing performance problems which I believe are network related. |
| performance-instance-store | My instance is experiencing performance problems which I believe are related to the instance stores. |
| performance-ebs-volume | My instance is experiencing performance problems which I believe are related to an EBS volume. |
| performance-other | My instance is experiencing performance problems. |
| other | Other, explained in the submitted description parameter. |

Request Parameters

| Name | Description | Required |
|---------------------|---|----------|
| <i>InstanceID.n</i> | One or more instance IDs. Type: String | Yes |
| <i>Status</i> | The status of all instances listed in the <i>InstanceID.n</i> parameter. Type: String Valid values: <code>ok</code> <code>impaired</code> | Yes |
| <i>StartTime</i> | The time at which the reported instance health state began. Type: DateTime | No |

| Name | Description | Required |
|----------------------|---|----------|
| <i>EndTime</i> | The time at which the reported instance health state ended. Type: DateTime | No |
| <i>ReasonCodes.n</i> | A reason code that describes a specific instance's health state. Each code you supply corresponds to an instance ID that you supply with the <i>InstanceID.n</i> parameter. See the Description (p. 354) section for descriptions of each reason code. Type: String Valid values: instance-stuck-in-state unresponsive not-accepting-credentials password-not-available performance-network performance-instance-store performance-ebs-volume performance-other other | Yes |
| <i>Description</i> | Descriptive text about the instance health state. Type: String Default: None | No |

Response Elements

The elements in the following table are wrapped in a `ReportInstanceStatusResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>Return</code> | Indicates whether the values submitted were accepted by Amazon EC2. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example reports instance health state for two instances.

```
https://ec2.amazonaws.com/?Action=ReportInstanceStatus
&Status=impaired
&InstanceId.0=i-9440effb
&InstanceId.1=i-0cf27c63
&Version=2012-06-15
&AuthParams
```

Example Request

This example reports instance health state for two instances with reason codes.

```
https://ec2.amazonaws.com/?Action=ReportInstanceStatus
&Description=Description+of+my+issue.
&Status=impaired
&InstanceId.0=i-9440effb
&InstanceId.1=i-0cf27c63
&ReasonCode.0=instance-performance-network
&ReasonCode.1=instance-performance-disk
&Version=2012-06-15
&AuthParams
```

Example Response

```
<ReportInstanceStatusResponse xmlns='http://ec2.amazonaws.com/doc/2011-10-01/'>
  <requestId>b8131cff-dfbd-4277-bafe-be006fd0c4da</requestId>
  <return>>true</return>
</ReportInstanceStatusResponse>
```

RequestSpotInstances

Description

Creates a Spot Instance request. Spot Instances are instances that Amazon EC2 starts on your behalf when the maximum price that you specify exceeds the current Spot Price. Amazon EC2 periodically sets the Spot Price based on available Spot Instance capacity and current Spot Instance requests. For more information about Spot Instances, see [Using Spot Instances](#) in the *Amazon Elastic Compute Cloud User Guide*.

Note

Users must be subscribed to the required product to run an instance with AWS Marketplace product codes.

Request Parameters

| Name | Description | Required |
|----------------------|--|----------|
| <i>SpotPrice</i> | The maximum hourly price for any Spot Instance launched to fulfill the request. Type: String Default: None | Yes |
| <i>InstanceCount</i> | The maximum number of Spot Instances to launch. Type: xs:integer Default: 1 | No |
| <i>Type</i> | The Spot Instance request type. Type: String Valid values: one-time persistent Default: one-time | No |
| <i>ValidFrom</i> | The start date of the request. If this is a one-time request, the request becomes active at this date and time and remains active until all instances launch, the request expires, or the request is canceled. If the request is persistent, the request becomes active at this date and time and remains active until it expires or is canceled. Type: DateTime Default: Request is effective independently | No |
| <i>ValidUntil</i> | The end date of the request. If this is a one-time request, the request remains active until all instances launch, the request is canceled, or this date is reached. If the request is persistent, it remains active until it is canceled or this date and time is reached. Type: DateTime Default: Request is effective indefinitely | No |

**Amazon Elastic Compute Cloud API Reference
Request Parameters**

| Name | Description | Required |
|--|--|-----------------|
| <i>Subnet</i> | The ID of the Amazon VPC subnet in which to launch the Spot Instance. Type: String Default: None | No |
| <i>LaunchGroup</i> | The instance launch group. Launch groups are Spot Instances that launch together and terminate together. Type: String Default: Instances are launched and terminated individually | No |
| <i>AvailabilityZoneGroup</i> | The user-specified name for a logical grouping of bids. When you specify <i>AvailabilityZoneGroup</i> in a Spot Instance request, all Spot Instances in the request are launched in the same Availability Zone. Instance proximity is maintained with this parameter, but choice of Availability Zone is not. <i>AvailabilityZoneGroup</i> applies only to bids for Spot Instances of the same instance type. Any additional Spot Instance requests that are specified with the same <i>AvailabilityZoneGroup</i> name will be launched in that same Availability Zone, as long as at least one instance from the group is still active. If there is no active instance running in the Availability Zone group that you specify for a new Spot Instance request (i.e., all instances are terminated, the bid is expired, or the bid falls below current market), then Amazon EC2 will launch the instance in any Availability Zone where the constraint can be met. Consequently, the subsequent set of Spot Instances could be placed in a different zone from the original request, even if the same <i>AvailabilityZoneGroup</i> name was specified. To ensure that all Spot Instances across all bids are launched into a particular Availability Zone, specify <i>LaunchSpecification.Placement.AvailabilityZone</i> in the API or <i>-availability-zone</i> in the CLI. Type: String Default: Instances are launched in any available Availability Zone. | No |
| <i>Placement.GroupName</i> | The name of an existing placement group you want to launch the instance into (for cluster instances). Type: String Default: None. | No |
| <i>LaunchSpecification.AddressingType</i> | Deprecated. Type: String Default: None | No |
| <i>LaunchSpecification.BlockDeviceMapping.n.DeviceName</i> | The device named exposed to the instance. Type: String Default: None | No |

**Amazon Elastic Compute Cloud API Reference
Request Parameters**

| Name | Description | Required |
|---|---|-----------------|
| <i>LaunchSpecification. BlockDeviceMapping.n .VirtualName</i> | The name of the virtual device. Type: String Default: None | No |
| <i>LaunchSpecification. BlockDeviceMapping.n .Ebs.SnapshotId</i> | The ID of the snapshot. Type: String Default: None | No |
| <i>LaunchSpecification. BlockDeviceMapping.n .Ebs.VolumeSize</i> | The size of the volume, in GiBs. Required if you are not creating a volume from a snapshot. Type: Integer Default: None | No |
| <i>LaunchSpecification. BlockDeviceMapping.n .Ebs.NoDevice</i> | Suppresses the device mapping. Type: Boolean Default: true | No |
| <i>LaunchSpecification. BlockDeviceMapping.n .Ebs.DeleteOnTermination</i> | Specifies whether the Amazon EBS volume is deleted on instance termination. Type: Boolean Default: true | No |
| <i>LaunchSpecification. IamInstanceProfile.Arn</i> | The Amazon resource name (ARN) of the IAM Instance Profile (IIP) to associate with the instances. Type: String Default: None | No |
| <i>LaunchSpecification. IamInstanceProfile.Name</i> | The name of the IAM Instance Profile (IIP) to associate with the instances. Type: String Default: None | No |
| <i>LaunchSpecification. ImageId</i> | The ID of the AMI. Type: String Default: None | Yes |
| <i>LaunchSpecification. InstanceType</i> | The instance type. Type: String Valid values: m1.small m1.large m1.xlarge c1.medium c1.xlarge m2.xlarge m2.2xlarge m2.4xlarge t1.micro Default: m1.small | Yes |
| <i>LaunchSpecification. KernelId</i> | The ID of the kernel. Type: String Default: None | No |
| <i>LaunchSpecification. KeyName</i> | The name of the key pair. Type: String Default: None | No |

Amazon Elastic Compute Cloud API Reference
Request Parameters

| Name | Description | Required |
|---|--|----------|
| <i>LaunchSpecification.Monitoring.Enabled</i> | Enables monitoring for the instance. Type: String Default: Disabled | No |
| <i>LaunchSpecification.NetworkInterface.n.NetworkInterfaceId</i> | Attaches an existing interface to a single instance. Requires n=1 instances (available only in Amazon VPC). Type: String Default: | No |
| <i>LaunchSpecification.NetworkInterface.n.DeviceIndex</i> | Applies to both attaching existing network interfaces and when creating new network interfaces (available only in Amazon VPC). Type: Integer Default: | No |
| <i>LaunchSpecification.NetworkInterface.n.SubnetId</i> | Applies only when creating new network interfaces (available only in Amazon VPC). Type: String Default: | No |
| <i>LaunchSpecification.NetworkInterface.n.Description</i> | Applies only when creating new network interfaces (available only in Amazon VPC). Type: String Default: | No |
| <i>LaunchSpecification.NetworkInterface.n.PrivateIpAddress</i> | Specifies the primary private IP address of the network interface. Applies only when creating new network interfaces. Requires n=1 network interfaces in launch (available only in Amazon VPC). Only one private IP address can be designated as primary. Therefore, you cannot specify this parameter if you are also specifying <i>LaunchSpecification.NetworkInterface.n.PrivateIpAddresses.n.Primary</i> with a value of <code>true</code> with the <i>LaunchSpecification.NetworkInterface.n.PrivateIpAddresses.n.PrivateIpAddress</i> option. Type: String Default: | No |
| <i>LaunchSpecification.NetworkInterface.n.PrivateIpAddresses.n.PrivateIpAddress</i> | Specifies the primary private IP address of the network interface. Applies only when creating new network interfaces. Requires n=1 network interfaces in launch (available only in Amazon VPC). Only one private IP address can be designated as primary. Therefore, you cannot specify this parameter with <i>LaunchSpecification.NetworkInterface.n.PrivateIpAddresses.n.Primary</i> with a value of <code>true</code> if you are also specifying the <i>LaunchSpecification.NetworkInterface.n.PrivateIpAddress</i> option. Type: String Default: | No |

Amazon Elastic Compute Cloud API Reference
Request Parameters

| Name | Description | Required |
|---|---|----------|
| <i>LaunchSpecification.NetworkInterface.n.PrivateIpAddresses.n.PrivateIpAddress.Primary</i> | <p>Specifies whether the private IP address is the primary private IP address. Applies only when creating new network interfaces. Requires n=1 network interfaces in launch (available only in Amazon VPC).</p> <p>Only one private IP address can be designated as primary. Therefore, you cannot specify this parameter with a value of <code>true</code> with the <i>LaunchSpecification.NetworkInterface.n.PrivateIpAddresses.n.PrivateIpAddress</i> option if you specify the <i>LaunchSpecification.NetworkInterface.n.PrivateIpAddress</i> option.</p> <p>Type: String Default:</p> | No |
| <i>LaunchSpecification.NetworkInterface.n.SecondaryPrivateIpAddressCount</i> | <p>Specifies the number of secondary private IP addresses to assign to a network interface. When you specify a number of secondary IP addresses, AWS automatically assigns these IP addresses within the subnet's range (available only in Amazon VPC).</p> <p>The number of IP addresses you can assign to a network interface varies by instance type. For more information, go to Available Instance Types in the <i>Amazon Elastic Compute Cloud User Guide</i>.</p> <p>For a single network interface, you cannot specify this option and specify more than one private IP address using <i>LaunchSpecification.NetworkInterface.n.PrivateIpAddresses.n.PrivateIpAddress</i>.</p> <p>Type: Integer Default: None</p> | No |
| <i>LaunchSpecification.NetworkInterface.n.SecurityGroupId.n</i> | <p>The security group IDs to associate with the created instance. Applies only when creating new network interfaces.</p> <p>Type: String Default:</p> | No |
| <i>LaunchSpecification.NetworkInterface.n.DeleteOnTermination</i> | <p>Applies to all network interfaces.</p> <p>Type: Boolean Default:</p> | No |
| <i>LaunchSpecification.Placement.AvailabilityZone</i> | <p>The placement constraint (i.e., specific Availability Zone) for launching the instances.</p> <p>Specify if you want all of the Spot Instances in all of your bids to be launched in a particular Availability Zone. Specifying this option requires Amazon EC2 to find capacity in the specified Availability Zone instead of letting Amazon EC2 pick the best Availability Zone available; this can potentially delay the fulfillment of your bid, and/or require a higher bid price.</p> <p>Type: String Default: Amazon EC2 selects an Availability Zone.</p> | No |

| Name | Description | Required |
|--|---|-------------|
| <i>LaunchSpecification.RamdiskId</i> | The ID of the RAM disk. Some kernels require additional drivers at launch. Check the kernel requirements for information on whether you need to specify a RAM disk and search for the kernel ID. Type: String Default: None | No |
| <i>LaunchSpecification.SecurityGroup.n</i> | The name of the security group. You cannot use this parameter when launching an instance with Amazon VPC. Type: String Default: The instance uses the default security group Condition: If you want to specify one or more security groups, you can use either <i>LaunchSpecification.SecurityGroupId.n</i> or <i>LaunchSpecification.SecurityGroup.n</i> . | Conditional |
| <i>LaunchSpecification.SecurityGroupId.n</i> | The ID of the security group. You can use either this parameter or the next to specify a security group. You can use this parameter when launching instances with or without Amazon VPC. Type: String Default: The instance uses the default security group Condition: If you want to specify one or more security groups, you can use either <i>LaunchSpecification.SecurityGroupId.n</i> or <i>LaunchSpecification.SecurityGroup.n</i> . | Conditional |
| <i>LaunchSpecification UserData</i> | The MIME, Base64-encoded user data to make available to the instances. Type: String Default: None | No |

Response Elements

The elements in the following table are wrapped in a `RequestSpotInstancesResponse` structure.

| Name | Description |
|-------------------------------------|--|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>spotInstanceRequestSet</code> | Information about the Spot Instance request, wrapped in an <code>item</code> element. Type: SpotInstanceRequestSetItemType (p. 472) |

Examples

Example Request

This example creates a Spot Instances request for two m1.small instances and associates an IAM instance profile called "s3access" with them.

```
https://ec2.amazonaws.com/?Action=RequestSpotInstances
&SpotPrice=0.50
&InstanceCount=2
&Type=one-time
&AvailabilityZoneGroup=MyAzGroup
&LaunchSpecification.ImageId=ami-43a4412a
&LaunchSpecification.KeyName=MyKeypair
&LaunchSpecification.Group.1=webserv
&LaunchSpecification.InstanceType=m1.small
&LaunchSpecification.IamInstanceProfile.Name=s3access
&AUTHPARAMS
```

Example Response

```
<RequestSpotInstancesResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <spotInstanceRequestSet>
    <item>
      <spotInstanceRequestId>sir-83d64e02</spotInstanceRequestId>
      <spotPrice>0.5</spotPrice>
      <type>one-time</type>
      <state>open</state>
      <availabilityZoneGroup>MyAzGroup</availabilityZoneGroup>
      <launchSpecification>
        <imageId>ami-43a4412a</imageId>
        <keyName>MyKeypair</keyName>
        <groupSet>
          <item>
            <groupId>webserv</groupId>
          </item>
        </groupSet>
        <instanceType>m1.small</instanceType>
        <blockDeviceMapping/>
        <monitoring>
          <enabled>>false</enabled>
        </monitoring>
      </launchSpecification>
      <createTime>2010-10-20T18:23:41.000Z</createTime>
      <productDescription>Linux/UNIX</productDescription>
    </item>
    <item>
      ...
    </item>
  </spotInstanceRequestSet>
</RequestSpotInstancesResponse>
```

Related Operations

- [DescribeSpotInstanceRequests](#) (p. 253)
- [CancelSpotInstanceRequests](#) (p. 49)
- [DescribeSpotPriceHistory](#) (p. 259)

ResetImageAttribute

Description

Resets an attribute of an AMI to its default value.

Note

The `productCodes` attribute cannot be reset.

Request Parameters

| Name | Description | Required |
|------------------|---|----------|
| <i>ImageId</i> | The ID of the AMI. Type: String Default: None | Yes |
| <i>Attribute</i> | The attribute to reset (currently you can only reset the launch permission attribute). Type: String Default: None Valid value: <code>launchPermission</code> | Yes |

Response Elements

The elements in the following table are wrapped in a `ResetImageAttributeResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example resets the `launchPermission` attribute for the specified AMI.

```
https://ec2.amazonaws.com/?Action=ResetImageAttribute
&ImageId=ami-61a54008
&Attribute=launchPermission
&AUTHPARAMS
```

Example Response

```
<ResetImageAttributeResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">  
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>  
  <return>true</return>  
</ResetImageAttributeResponse>
```

Related Operations

- [ModifyImageAttribute](#) (p. 321)
- [DescribeImageAttribute](#) (p. 167)

ResetInstanceAttribute

Description

Resets an attribute of an instance to its default value. To reset the kernel or RAM disk, the instance must be in a stopped state. To reset the `SourceDestCheck`, the instance can be either running or stopped.

The `SourceDestCheck` attribute exists to enable a Network Address Translation (NAT) instance in a VPC to perform NAT. The attribute controls whether source/destination checking is enabled on the instance. The default value is `true`, which means checking is enabled. The value must be `false` for the instance to perform NAT. For more information, see [NAT Instances](#) in the *Amazon Virtual Private Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|-------------------------|---|----------|
| <code>InstanceId</code> | The ID of the instance. Type: String Default: None | Yes |
| <code>Attribute</code> | The attribute to reset. Type: String Default: None Valid values: <code>kernel</code> <code>ramdisk</code> <code>sourceDestCheck</code> | Yes |

Response Elements

The elements in the following table are wrapped in a `ResetInstanceAttributeResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example resets the `kernel` attribute.

```
https://ec2.amazonaws.com/?Action=ResetInstanceAttribute
&InstanceId=i-10a64379
&Attribute=kernel
&AUTHPARAMS
```

Example Response

```
<ResetInstanceAttributeResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <return>true</return>
</ResetInstanceAttributeResponse>
```

Related Operations

- [ModifyInstanceAttribute](#) (p. 324)
- [DescribeInstanceAttribute](#) (p. 178)

ResetNetworkInterfaceAttribute

Description

Resets a network interface attribute. Only one attribute can be specified per call.

Request Parameters

| Name | Description | Required |
|------------------------------------|---|----------|
| <i>NetworkInterfaceId</i> | The ID of the network interface. Type: String Default: None | Yes |
| <i>Attribute=[sourceDestCheck]</i> | The name of the attribute to reset; <i>sourceDestCheck</i> defaults to <i>true</i> . Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in a `ResetNetworkInterfaceAttribute` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example resets the `sourceDestCheck` attribute for the elastic network interface (ENI) `eni-ffda3197`.

```
https://ec2.amazonaws.com/?Action=ResetNetworkInterfaceAttribute&NetworkInterfaceId=eni-ffda3197&Attribute=sourceDestCheck&AUTHPARAMS
```

Example Response

```
<ResetNetworkInterfaceAttributeResponse xmlns='http://ec2.amazonaws.com/doc/2011-11-15/'>
  <requestId>5187642e-3f16-44a3-b05f-24c3848b5162</requestId>
  <return>true</return>
</ResetNetworkInterfaceAttributeResponse>
```


Related Operations

- [AttachNetworkInterface](#) (p. 27)
- [DetachNetworkInterface](#) (p. 296)
- [CreateNetworkInterface](#) (p. 72)
- [DeleteNetworkInterface](#) (p. 117)
- [DescribeNetworkInterfaceAttribute](#) (p. 214)
- [DescribeNetworkInterfaces](#) (p. 216)
- [ModifyNetworkInterfaceAttribute](#) (p. 327)

ResetSnapshotAttribute

Description

Resets permission settings for the specified snapshot.

Request Parameters

| Name | Description | Required |
|-------------------|--|----------|
| <i>SnapshotId</i> | The ID of the snapshot. Type: String Default: None | Yes |
| <i>Attribute</i> | The attribute to reset (currently only the attribute for permission to create volumes can be reset) Type: String Default: None Valid value: <code>createVolumePermission</code> | Yes |

Response Elements

The elements in the following table are wrapped in a `ResetSnapshotAttributeResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example resets the permissions for `snap-78a54011`, making it a private snapshot that can only be used by the account that created it.

```
https://ec2.amazonaws.com/?Action=ResetSnapshotAttribute
&SnapshotId=snap-78a54011
&Attribute=createVolumePermission
&AUTHPARAMS
```

Example Response

```
<ResetSnapshotAttributeResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <return>true</return>
</ResetSnapshotAttributeResponse>
```

Related Operations

- [ModifySnapshotAttribute](#) (p. 329)
- [DescribeSnapshotAttribute](#) (p. 244)
- [DescribeSnapshots](#) (p. 246)
- [CreateSnapshot](#) (p. 86)

RevokeSecurityGroupEgress

Description

This action applies only to security groups in a VPC. It doesn't work with EC2 security groups. For information about Amazon Virtual Private Cloud and VPC security groups, see [Security Groups](#) in the *Amazon Virtual Private Cloud User Guide*.

The action removes one or more egress rules from a VPC security group. The values that you specify in the revoke request (e.g., ports, etc.) must match the existing rule's values for the rule to be revoked.

Each rule consists of the protocol and the CIDR range or destination security group. For the TCP and UDP protocols, you must also specify the destination port or range of ports. For the ICMP protocol, you must also specify the ICMP type and code.

Rule changes are propagated to instances within the security group as quickly as possible. However, a small delay might occur.

Request Parameters

| Name | Description | Required |
|-----------------------------------|--|-------------|
| <i>GroupId</i> | The ID of the VPC security group to modify. Type: String Default: None | Yes |
| <i>IpPermissions.n.IpProtocol</i> | The IP protocol name or number (go to Protocol Numbers). When you call <code>DescribeSecurityGroups</code> , the protocol value returned is the number. Exception: For TCP, UDP, and ICMP, the value returned is the name (e.g., <code>tcp</code> , <code>udp</code> , or <code>icmp</code>). Type: String Valid values: <code>tcp</code> <code>udp</code> <code>icmp</code> or any protocol number (go to Protocol Numbers). Use <code>-1</code> to specify all. | Yes |
| <i>IpPermissions.n.FromPort</i> | The start of port range for the TCP and UDP protocols, or an ICMP type number. For the ICMP type number, you can use -1 to specify all ICMP types. Type: Integer Default: None Condition: Required for ICMP and any protocol that uses ports | Conditional |
| <i>IpPermissions.n.ToPort</i> | The end of port range for the TCP and UDP protocols, or an ICMP code number. For the ICMP code number, you can use -1 to specify all ICMP codes for the given ICMP type. Type: Integer Default: None Condition: Required for ICMP and any protocol that uses ports | Conditional |

| Name | Description | Required |
|--|--|-------------|
| <i>IpPermissions.n.Groups.m.GroupId</i> | The name of the destination security group. Cannot be used when specifying a CIDR IP address. Type: String Default: None Condition: Required if modifying access for one or more destination security groups. | Conditional |
| <i>IpPermissions.n.IpRanges.m.CidrIp</i> | The CIDR range. Cannot be used when specifying a destination security group. Type: String Default: None Constraints: Valid CIDR IP address range. Condition: Required if modifying access for one or more IP address ranges. | Conditional |

Response Elements

The elements in the following table are wrapped in a `RevokeSecurityGroupEgressResponse` structure.

| Name | Description |
|------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>return</code> | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: <code>xsd:boolean</code> |

Examples

Example Request

This example revokes the access that the `webserv` VPC security group (with ID `sg-1a2b3c4d`) has to the `205.192.0.0/16` and `205.159.0.0/16` address ranges on TCP port 80.

```
https://ec2.amazonaws.com/?Action=RevokeSecurityGroupEgress
&GroupName=webserv
&GroupName=sg-1a2b3c4d
&IpPermissions.1.IpProtocol=tcp
&IpPermissions.1.FromPort=80
&IpPermissions.1.ToPort=80
&IpPermissions.1.IpRanges.1.CidrIp=205.192.0.0/16
&IpPermissions.1.IpRanges.2.CidrIp=205.159.0.0/16
&AUTHPARAMS
```

Example Request

This example revokes the access that the VPC security group with ID `sg-1a2b3c4d` has to the VPC security group with ID `sg-9a8d7f5c` on TCP port 1433.

```
https://ec2.amazonaws.com/?Action=RevokeSecurityGroupEgress
&GroupId=sg-1a2b3c4d
&IpPermissions.1.IpProtocol=tcp
&IpPermissions.1.FromPort=1433
&IpPermissions.1.ToPort=1433
&IpPermissions.1.Groups.1.GroupId=sg-9a8d7f5c
&AUTHPARAMS
```

Example Response

```
<RevokeSecurityGroupEgressResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <return>true</return>
</RevokeSecurityGroupEgressResponse>
```

Related Operations

- [CreateSecurityGroup](#) (p. 84)
- [DescribeSecurityGroups](#) (p. 240)
- [AuthorizeSecurityGroupEgress](#) (p. 33)
- [AuthorizeSecurityGroupIngress](#) (p. 36)
- [AuthorizeSecurityGroupIngress](#) (p. 376)
- [DeleteSecurityGroup](#) (p. 125)

RevokeSecurityGroupIngress

Description

This action applies to both EC2 security groups and VPC security groups. For information about VPC security groups and how they differ from EC2 security groups, see [Security Groups](#) in the *Amazon Virtual Private Cloud User Guide*.

This action removes one or more ingress rules from a security group. The values that you specify in the revoke request (e.g., ports, etc.) must match the existing rule's values for the rule to be removed.

Each rule consists of the protocol and the CIDR range or source security group. For the TCP and UDP protocols, you must also specify the destination port or range of ports. For the ICMP protocol, you must also specify the ICMP type and code.

Rule changes are propagated to instances within the security group as quickly as possible. However, depending on the number of instances, a small delay might occur.

Request Parameters

| Name | Description | Required |
|-----------------------------------|---|-------------|
| <i>UserId</i> | Deprecated | No |
| <i>GroupId</i> | The ID of the EC2 or VPC security group to modify. The group must belong to your account. Type: String Default: None Condition: Required for VPC security groups; can be used instead of <i>GroupName</i> for EC2 security groups | Conditional |
| <i>GroupName</i> | The name of the EC2 security group to modify. Type: String Default: None Condition: Can be used instead of <i>GroupId</i> for EC2 security groups | Conditional |
| <i>IpPermissions.n.IpProtocol</i> | The IP protocol name or number (see Protocol Numbers). EC2 security groups can have rules only for TCP, UDP, and ICMP, whereas VPC security groups can have rules assigned to any protocol number. When you call <i>DescribeSecurityGroups</i> , the protocol value returned is the number. Exception: For TCP, UDP, and ICMP, the value returned is the name (e.g., <i>tcp</i> , <i>udp</i> , or <i>icmp</i>). Type: String Valid values for EC2 security groups: <i>tcp</i> <i>udp</i> <i>icmp</i> or the corresponding protocol number (6 17 1). Valid values for VPC groups: <i>tcp</i> <i>udp</i> <i>icmp</i> or any protocol number (see Protocol Numbers). Use -1 to specify all. | Required |

| Name | Description | Required |
|---|---|-------------|
| <i>IpPermissions.n.FromPort</i> | The start of port range for the TCP and UDP protocols, or an ICMP type number. For the ICMP type number, you can use -1 to specify all ICMP types. Type: Integer Default: None Default: Required for ICMP and any protocol that uses ports | Conditional |
| <i>IpPermissions.n.ToPort</i> | The end of port range for the TCP and UDP protocols, or an ICMP code number. For the ICMP code number, you can use -1 to specify all ICMP codes for the given ICMP type. Type: Integer Default: None Default: Required for ICMP and any protocol that uses ports | Conditional |
| <i>IpPermissions.n.Groups.m.UserId</i> | The AWS account ID that owns the source security group. Cannot be used when specifying a CIDR IP address. Type: String Default: None Condition: For EC2 security groups only. Required if modifying access for one or more source security groups. | Conditional |
| <i>IpPermissions.n.Groups.m.GroupName</i> | The name of the source security group. Cannot be used when specifying a CIDR IP address. Type: String Default: None Condition: Required if modifying access for one or more source security groups. | Conditional |
| <i>IpPermissions.n.Groups.m.GroupId</i> | The ID of the source security group. Cannot be used when specifying a CIDR IP address. Type: String Default: None Condition: For VPC security groups only. Required if modifying access for one or more source security groups. | Conditional |
| <i>IpPermissions.n.IpRanges.m.CidrIp</i> | The CIDR range. Cannot be used when specifying a source security group. Type: String Default: None Constraints: Valid CIDR IP address range. Condition: Required if modifying access for one or more IP address ranges. | Conditional |

Response Elements

The elements in the following table are wrapped in a `RevokeSecurityGroupIngressResponse` structure.

| Name | Description |
|-----------|--|
| requestId | The ID of the request. Type: xsd:string |
| return | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: xsd:boolean |

Examples

Example Request

This example revokes TCP port 80 access from the 205.192.0.0/16 address range for the webserv security group. Note that if the security group were a VPC security group, the ID of the security group would instead be required in the request.

```
https://ec2.amazonaws.com/?Action=RevokeSecurityGroupIngress
&GroupName=webserv
&IpProtocol=tcp
&FromPort=80
&ToPort=80
&CidrIp=205.192.0.0/16
&AUTHPARAMS
```

Example Response

```
<RevokeSecurityGroupIngressResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <return>true</return>
</RevokeSecurityGroupIngressResponse>
```

Related Operations

- [CreateSecurityGroup](#) (p. 84)
- [DescribeSecurityGroups](#) (p. 240)
- [AuthorizeSecurityGroupIngress](#) (p. 36)
- [DeleteSecurityGroup](#) (p. 125)

RunInstances

Description

Launches the specified number of instances of an AMI for which you have permissions.

If Amazon EC2 cannot launch the minimum number of instances you request, no instances will be launched. If there is insufficient capacity to launch the maximum number of instances you request, Amazon EC2 launches the minimum number specified and allocates the remaining available instances using round robin.

Note

Every instance is launched in a security group (created using the `CreateSecurityGroup` operation). If you don't specify a security group in the `RunInstances` request, the "default" security group is used.

For Linux instances, you can provide an optional key pair ID in the launch request (created using the `CreateKeyPair` or `ImportKeyPair` operation). The instances will have access to the public key at boot. You can use this key to provide secure access to an instance of an image on a per-instance basis. Amazon EC2 public images use this feature to provide secure access without passwords.

Important

Launching public images without a key pair ID will leave them inaccessible.

The public key material is made available to the instance at boot time by placing it in the `openssh_id.pub` file on a logical device that is exposed to the instance as `/dev/sda2` (the instance store). The format of this file is suitable for use as an entry within `~/.ssh/authorized_keys` (the OpenSSH format). This can be done at boot (e.g., as part of `rc.local`) allowing for secure access without passwords.

You can provide optional user data in the launch request. All instances that collectively comprise the launch request have access to this data. For more information, see [Instance Metadata](#) in the *Amazon Elastic Compute Cloud User Guide*.

Note

If any of the AMIs have a product code attached for which the user has not subscribed, the `RunInstances` call will fail.

Request Parameters

| Name | Description | Required |
|-----------------|--|----------|
| <i>ImageId</i> | The ID of the AMI. Type: String Default: None | Yes |
| <i>MinCount</i> | The minimum number of instances to launch. If the value is more than Amazon EC2 can launch, no instances are launched at all. Type: Integer Default: None Constraints: Between 1 and the maximum number allowed for your account (default: 20). | Yes |

Amazon Elastic Compute Cloud API Reference
Request Parameters

| Name | Description | Required |
|-----------------------------------|---|-----------------|
| <i>MaxCount</i> | The maximum number of instances to launch. If the value is more than Amazon EC2 can launch, the largest possible number above MinCount will be launched instead. Type: Integer Default: None Constraints: Between 1 and the maximum number allowed for your account (default: 20). | Yes |
| <i>KeyName</i> | The name of the key pair to use. Type: String Default: None | No |
| <i>SecurityGroupId.n</i> | One or more security group IDs. Type: String Default: None Condition: Required for VPC security groups; optional for EC2 security groups | Conditional |
| <i>SecurityGroup.n</i> | One or more security group names. Type: String Default: None Condition: Valid only for EC2 security groups; for EC2 groups either a group ID or a group name is accepted | Conditional |
| <i>UserData</i> | The Base64-encoded MIME user data to be made available to the instance(s) in this reservation. Type: String Default: None | No |
| <i>AddressingType</i> | This parameter is deprecated. Type: String Default: None | No |
| <i>InstanceType</i> | The instance type. Type: String Valid values: t1.micro m1.small m1.medium m1.large m1.xlarge c1.medium c1.xlarge m2.xlarge m2.2xlarge m2.4xlarge hi1.4xlarge cc1.4xlarge cg1.4xlarge cc2.8xlarge Default: m1.small | No |
| <i>Placement.AvailabilityZone</i> | The Availability Zone to launch the instance into. Type: String Default: EC2 chooses a zone for you | No |
| <i>Placement.GroupName</i> | The name of an existing placement group you want to launch the instance into (for cluster instances). Type: String Default: None | No |

Amazon Elastic Compute Cloud API Reference
Request Parameters

| Name | Description | Required |
|--|---|----------|
| <i>Placement.Tenancy</i> | The tenancy of the instance. An instance with a tenancy of <i>dedicated</i> runs on single-tenant hardware and can only be launched into a VPC. Type: String Default: default | No |
| <i>KernelId</i> | The ID of the kernel with which to launch the instance. Type: String Default: None | No |
| <i>RamdiskId</i> | The ID of the RAM disk. Some kernels require additional drivers at launch. Check the kernel requirements for information on whether you need to specify a RAM disk. To find kernel requirements, refer to the Resource Center and search for the kernel ID. Type: String Default: None | No |
| <i>BlockDeviceMapping.n.DeviceName</i> | The device name exposed to the instance (for example, <i>/dev/sdh</i> , or <i>xvdh</i>). The device can be mapped to an EBS volume, a virtual device, or to nothing. If you are using this device to map an EBS volume, follow this with the EBS volume specific parameters. For information about block device mapping, see Block Device Mapping in the <i>Amazon Elastic Compute Cloud User Guide</i> . Type: String Default: None | No |
| <i>BlockDeviceMapping.n.NoDevice</i> | Suppresses the device mapping. This parameter takes an empty string as input. Type: Empty String Default: None | No |
| <i>BlockDeviceMapping.n.VirtualName</i> | The virtual device name, <i>ephemeral[0..3]</i> . The number of instance store volumes depends on the instance type. For information about block device mapping, see Block Device Mapping in the <i>Amazon Elastic Compute Cloud User Guide</i> . Type: String Default: None | No |
| <i>BlockDeviceMapping.n.Ebs.SnapshotId</i> | The ID of the snapshot. Type: String Default: None | No |
| <i>BlockDeviceMapping.n.Ebs.VolumeSize</i> | The size of the volume, in GiBs. Required if you are not creating a volume from a snapshot. Type: Integer Default: None | No |

Amazon Elastic Compute Cloud API Reference
Request Parameters

| Name | Description | Required |
|---|--|----------|
| <i>BlockDeviceMapping.n.Ebs.DeleteOnTermination</i> | Specifies whether the Amazon EBS volume is deleted on instance termination. Type: Boolean Default: true | No |
| <i>Monitoring.Enabled</i> | Enables monitoring for the instance. Type: Boolean Default: false | No |
| <i>SubnetId</i> | If you're using Amazon Virtual Private Cloud, this specifies the ID of the subnet you want to launch the instance into. Type: String Default: None | No |
| <i>DisableApiTermination</i> | Specifies whether you can terminate the instance using the EC2 API. A value of <code>true</code> means you can't terminate the instance using the API (i.e., the instance is "locked"); a value of <code>false</code> means you can. If you set this to <code>true</code> , and you later want to terminate the instance, you must first change the <code>disableApiTermination</code> attribute's value to <code>false</code> using <code>ModifyInstanceAttribute</code> . Type: Boolean Default: false | No |
| <i>InstanceInitiatedShutdownBehavior</i> | Specifies whether the instance stops or terminates on instance-initiated shutdown. Type: String Valid values: <code>stop</code> <code>terminate</code> Default: <code>stop</code> | No |
| <i>PrivateIpAddress</i> | If you're using Amazon Virtual Private Cloud, you can optionally use this parameter to assign the instance a specific available IP address from the subnet (e.g., 10.0.0.25) as the primary IP address. Only one private IP address can be designated as primary. Therefore, you cannot specify this parameter if you are also specifying <code>PrivateIpAddresses.n.Primary</code> with a value of <code>true</code> with the <code>PrivateIpAddresses.n.PrivateIpAddress</code> option. Type: String Default: Amazon VPC selects an IP address from the subnet for the instance | No |
| <i>ClientToken</i> | Unique, case-sensitive identifier you provide to ensure idempotency of the request. For more information, go to How to Ensure Idempotency in the <i>Amazon Elastic Compute Cloud User Guide</i> . Type: String Default: None Constraints: Maximum 64 ASCII characters | No |

Amazon Elastic Compute Cloud API Reference
Request Parameters

| Name | Description | Required |
|---|--|----------|
| <i>NetworkInterface.n.NetworkInterfaceId</i> | Attaches an existing interface to a single instance. Requires n=1 instances. Type: String Default: None | No |
| <i>NetworkInterface.n.DeviceIndex</i> | Applies to both attaching existing network interfaces and when creating new network interfaces. Type: Integer Default: None | No |
| <i>NetworkInterface.n.SubnetId</i> | Applies only when creating new network interfaces. Type: String Default: None | No |
| <i>NetworkInterface.n.Description</i> | Applies only when creating new network interfaces. Type: String Default: None | No |
| <i>NetworkInterface.n.PrivateIpAddress</i> | The primary private IP address of the network interface. Applies only when creating new network interfaces. Requires n=1 network interfaces in launch. Type: String Default: None | No |
| <i>NetworkInterface.n.PrivateIpAddresses.n.PrivateIpAddress</i> | The private IP address of the specified network interface. This parameter can be used multiple times to specify explicit private IP addresses for a network interface, but only one private IP address can be designated as primary. Only one private IP address can be designated as primary. Therefore, you cannot specify this parameter with the <i>NetworkInterface.n.PrivateIpAddresses.n.Primary</i> value of <code>true</code> if you designate a primary private IP address using the <i>NetworkInterface.n.PrivateIpAddress</i> option. Type: String Default: None | No |
| <i>NetworkInterface.n.PrivateIpAddresses.n.Primary</i> | Specifies whether the private IP address is the primary private IP address. Only one private IP address can be designated as primary. Therefore, you cannot specify this parameter with the <i>NetworkInterface.n.PrivateIpAddresses.n.Primary</i> value of <code>true</code> and the <i>NetworkInterface.n.PrivateIpAddresses.n.PrivateIpAddress</i> option if you designate a primary private IP address using <i>NetworkInterface.n.PrivateIpAddress</i> . Type: Boolean Default: None | No |

| Name | Description | Required |
|--|--|----------|
| <i>NetworkInterface.n.SecondaryPrivateIpAddressCount</i> | The number of private IP addresses to assign to a network interface. For a single network interface, you cannot specify this option and specify more than one private IP address using <i>NetworkInterface.n.PrivateIpAddress</i> . | No |
| <i>NetworkInterface.n.SecurityGroupId.n</i> | Applies only when creating new network interfaces. Type: String Default: None | No |
| <i>NetworkInterface.n.DeleteOnTermination</i> | Applies to all network interfaces. Type: Boolean Default: None | No |
| <i>IamInstanceProfile.Arn</i> | Amazon resource name (ARN) of the IAM Instance Profile (IIP) to associate with the instances. Type: String Default: None | No |
| <i>IamInstanceProfile.Name</i> | The name of the IAM Instance Profile (IIP) to associate with the instances. Type: String Default: None | No |

Response Elements

The elements in the following table are wrapped in a `RunInstancesResponse` structure.

| Name | Description |
|----------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>reservationId</code> | The ID of the reservation. Type: <code>xsd:string</code> |
| <code>ownerId</code> | The ID of the AWS account that owns the reservation. Type: <code>xsd:string</code> |
| <code>groupSet</code> | A list of security groups the instance belongs to. Each group is wrapped in an <code>item</code> element. Type: GroupItemType (p. 428) |
| <code>instancesSet</code> | A list of instances. Each instance is wrapped in an <code>item</code> element. Type: RunningInstancesItemType (p. 467) |
| <code>requesterId</code> | The ID of the requester that launched the instances on your behalf (for example, AWS Management Console, Auto Scaling). Type: <code>xsd:string</code> |

Examples

Example Request

This example launches three instances of the ami-60a54009 AMI.

```
https://ec2.amazonaws.com/?Action=RunInstances
&ImageId=ami-60a54009
&MaxCount=3
&MinCount=1
&Placement.AvailabilityZone=us-east-1b
&Monitoring.Enabled=true
&AUTHPARAMS
```

Example Response

```
<RunInstancesResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <reservationId>r-47a5402e</reservationId>
  <ownerId>111122223333</ownerId>
  <groupSet>
    <item>
      <groupId>sg-245f6a01</groupId>
      <groupName>default</groupName>
    </item>
  </groupSet>
  <instancesSet>
    <item>
      <instanceId>i-2ba64342</instanceId>
      <imageId>ami-60a54009</imageId>
      <instanceState>
        <code>0</code>
        <name>pending</name>
      </instanceState>
      <privateDnsName></privateDnsName>
      <dnsName></dnsName>
      <keyName>example-key-name</keyName>
      <amiLaunchIndex>0</amiLaunchIndex>
      <instanceType>m1.small</instanceType>
      <launchTime>2007-08-07T11:51:50.000Z</launchTime>
      <placement>
        <availabilityZone>us-east-1b</availabilityZone>
      </placement>
      <monitoring>
        <enabled>true</enabled>
      </monitoring>
      <sourceDestCheck>true</sourceDestCheck>
      <groupSet>
        <item>
          <groupId>sg-245f6a01</groupId>
          <groupName>default</groupName>
        </item>
      </groupSet>
      <virtualizationType>paravirtual</virtualizationType>
      <clientToken/>
    </item>
  </instancesSet>
</RunInstancesResponse>
```



```
<tagSet/>
<hypervisor>xen</hypervisor>
</item>
<item>
  <instanceId>i-2bc64242</instanceId>
  <imageId>ami-60a54009</imageId>
  <instanceState>
    <code>0</code>
    <name>pending</name>
  </instanceState>
  <privateDnsName></privateDnsName>
  <dnsName></dnsName>
  <keyName>example-key-name</keyName>
  <amiLaunchIndex>1</amiLaunchIndex>
  <instanceType>m1.small</instanceType>
  <launchTime>2007-08-07T11:51:50.000Z</launchTime>
  <placement>
    <availabilityZone>us-east-1b</availabilityZone>
  </placement>
  <monitoring>
    <enabled>true</enabled>
  </monitoring>
  <sourceDestCheck>true</sourceDestCheck>
  <groupSet>
    <item>
      <groupId>sg-245f6a01</groupId>
      <groupName>default</groupName>
    </item>
  </groupSet>
  <virtualizationType>paravirtual</virtualizationType>
  <clientToken/>
  <tagSet/>
  <hypervisor>xen</hypervisor>
</item>
<item>
  <instanceId>i-2be64332</instanceId>
  <imageId>ami-60a54009</imageId>
  <instanceState>
    <code>0</code>
    <name>pending</name>
  </instanceState>
  <privateDnsName></privateDnsName>
  <dnsName></dnsName>
  <keyName>example-key-name</keyName>
  <amiLaunchIndex>2</amiLaunchIndex>
  <instanceType>m1.small</instanceType>
  <launchTime>2007-08-07T11:51:50.000Z</launchTime>
  <placement>
    <availabilityZone>us-east-1b</availabilityZone>
  </placement>
  <monitoring>
    <enabled>true</enabled>
  </monitoring>
  <sourceDestCheck>true</sourceDestCheck>
  <groupSet>
    <item>
      <groupId>sg-245f6a01</groupId>
      <groupName>default</groupName>
    </item>
  </groupSet>
  <tagSet/>
  <hypervisor>xen</hypervisor>
</item>
```

```
</groupSet>
<virtualizationType>paravirtual</virtualizationType>
<clientToken/>
<tagSet/>
<hypervisor>xen</hypervisor>
</item>
</instancesSet>
</RunInstancesResponse>
```

Example Request

This example launches an instance of the `ami-31814f58` AMI and attaches an elastic network interface to it.

```
https://ec2.amazonaws.com/?Action=RunInstances
ImageId=ami-31814f58
&InstanceType=m1.small
&MaxCount=1
&MinCount=1
&Monitoring.Enabled=false
&SubnetId=subnet-b2a249da
&AUTHPARAMS
```

Example Response

```
<RunInstancesResponse xmlns='http://ec2.amazonaws.com/doc/2011-11-15/'>
  <requestId>e86ff3c8-2400-45e3-a4e7-f158a69283d4</requestId>
  <reservationId>r-157ad274</reservationId>
  <ownerId>111122223333</ownerId>
  <groupSet/>
  <instancesSet>
    <item>
      <instanceId>i-0ee0356c</instanceId>
      <imageId>ami-31814f58</imageId>
      <instanceState>
        <code>0</code>
        <name>pending</name>
      </instanceState>
      <privateDnsName/>
      <dnsName/>
      <reason/>
      <amiLaunchIndex>0</amiLaunchIndex>
      <productCodes/>
      <instanceType>m1.small</instanceType>
      <launchTime>2011-12-20T08:29:31.000Z</launchTime>
      <placement>
        <availabilityZone>us-east-1b</availabilityZone>
        <groupName/>
        <tenancy>default</tenancy>
      </placement>
      <kernelId>aki-805ea7e9</kernelId>
      <monitoring>
        <state>disabled</state>
      </monitoring>
      <subnetId>subnet-b2a249da</subnetId>
```

```
<vpcId>vpc-1ea24976</vpcId>
<privateIpAddress>10.0.0.142</privateIpAddress>
<sourceDestCheck>>true</sourceDestCheck>
<groupSet>
  <item>
    <groupId>sg-050c1369</groupId>
    <groupName>default</groupName>
  </item>
</groupSet>
<stateReason>
  <code>pending</code>
  <message>pending</message>
</stateReason>
<architecture>i386</architecture>
<rootDeviceType>ebs</rootDeviceType>
<rootDeviceName>/dev/sdal</rootDeviceName>
<blockDeviceMapping/>
<virtualizationType>paravirtual</virtualizationType>
<clientToken/>
<hypervisor>xen</hypervisor>
<networkInterfaceSet>
  <item>
    <networkInterfaceId>eni-c6bb50ae</networkInterfaceId>
    <subnetId>subnet-b2a249da</subnetId>
    <vpcId>vpc-1ea24976</vpcId>
    <description/>
    <ownerId>111122223333</ownerId>
    <status>in-use</status>
    <privateIpAddress>10.0.0.142</privateIpAddress>
    <sourceDestCheck>>true</sourceDestCheck>
    <groupSet>
      <item>
        <groupId>sg-050c1369</groupId>
        <groupName>default</groupName>
      </item>
    </groupSet>
    <attachment>
      <attachmentId>eni-attach-0326646a</attachmentId>
      <deviceIndex>0</deviceIndex>
      <status>attaching</status>
      <attachTime>2011-12-20T08:29:31.000Z</attachTime>
      <deleteOnTermination>true</deleteOnTermination>
    </attachment>
  </item>
</networkInterfaceSet>
</item>
</instancesSet>
</RunInstancesResponse>
```

Example Request

The following example launches an m1.large instance into Amazon VPC in subnet subnet-a61dafcf with a single network interface, a primary private IP address of 10.0.2.106 and two secondary private IP addresses (10.0.2.107 and 10.0.2.108

```
https://ec2.amazonaws.com/?Action=RunInstances
&ImageId=ami-beb0caec
&InstanceType=m1.large
&MaxCount=1
&MinCount=1
&Monitoring.Enabled=false
&NetworkInterface.0.DeviceIndex=0
&NetworkInterface.0.PrivateIpAddresses.0.Primary=true
&NetworkInterface.0.PrivateIpAddresses.0.PrivateIpAddress=10.0.2.106
&NetworkInterface.0.PrivateIpAddresses.1.Primary=false
&NetworkInterface.0.PrivateIpAddresses.1.PrivateIpAddress=10.0.2.107
&NetworkInterface.0.PrivateIpAddresses.2.Primary=false
&NetworkInterface.0.PrivateIpAddresses.2.PrivateIpAddress=10.0.2.108
&NetworkInterface.0.SubnetId=subnet-a61dafcf
&AUTHPARAMS
```

Related Operations

- [DescribeInstances](#) (p. 181)
- [StopInstances](#) (p. 392)
- [StartInstances](#) (p. 390)
- [TerminateInstances](#) (p. 394)
- [AuthorizeSecurityGroupIngress](#) (p. 36)
- [RevokeSecurityGroupIngress](#) (p. 376)
- [DescribeSecurityGroups](#) (p. 240)
- [CreateSecurityGroup](#) (p. 84)
- [CreateKeyPair](#) (p. 65)
- [ImportKeyPair](#) (p. 316)

StartInstances

Description

Starts an Amazon EBS-backed AMI that you've previously stopped.

Instances that use Amazon EBS volumes as their root devices can be quickly stopped and started. When an instance is stopped, the compute resources are released and you are not billed for hourly instance usage. However, your root partition Amazon EBS volume remains, continues to persist your data, and you are charged for Amazon EBS volume usage. You can restart your instance at any time. Each time you transition an instance from stopped to started, we charge a full instance hour, even if transitions happen multiple times within a single hour.

Note

Before stopping an instance, make sure it is in a state from which it can be restarted. Stopping an instance does not preserve data stored in RAM.

Performing this operation on an instance that uses an instance store as its root device returns an error.

For more information, see [Using Amazon EBS-Backed AMIs and Instances](#).

Request Parameters

| Name | Description | Required |
|---------------------|--|----------|
| <i>InstanceId.n</i> | One or more instance IDs. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in a `StartInstancesResponse` structure.

| Name | Description |
|---------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>instancesSet</code> | A list of instance state changes. Each change is wrapped in an <code>item</code> element. Type: InstanceStateChangeType (p. 442) |

Examples

Example Request

This example starts the i-10a64379 instance.

```
https://ec2.amazonaws.com/?Action=StartInstances
&InstanceId.1=i-10a64379
&AUTHPARAMS
```

Example Response

```
<StartInstancesResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <instancesSet>
    <item>
      <instanceId>i-10a64379</instanceId>
      <currentState>
        <code>0</code>
        <name>pending</name>
      </currentState>
      <previousState>
        <code>80</code>
        <name>stopped</name>
      </previousState>
    </item>
  </instancesSet>
</StartInstancesResponse>
```

Related Operations

- [StopInstances](#) (p. 392)
- [RunInstances](#) (p. 379)
- [DescribeInstances](#) (p. 181)
- [TerminateInstances](#) (p. 394)

StopInstances

Description

Stops an Amazon EBS-backed instance. Each time you transition an instance from stopped to started, we charge a full instance hour, even if transitions happen multiple times within a single hour.

Important

Although Spot Instances can use Amazon EBS-backed AMIs, they don't support Stop/Start. In other words, you can't stop and start Spot Instances launched from an AMI with an Amazon EBS root device.

Instances that use Amazon EBS volumes as their root devices can be quickly stopped and started. When an instance is stopped, the compute resources are released and you are not billed for hourly instance usage. However, your root partition Amazon EBS volume remains, continues to persist your data, and you are charged for Amazon EBS volume usage. You can restart your instance at any time.

Note

Before stopping an instance, make sure it is in a state from which it can be restarted. Stopping an instance does not preserve data stored in RAM.

Performing this operation on an instance that uses an instance store as its root device returns an error.

You can stop, start, and terminate EBS-backed instances. You can only terminate S3-backed instances. What happens to an instance differs if you stop it or terminate it. For example, when you stop an instance, the root device and any other devices attached to the instance persist. When you terminate an instance, the root device and any other devices attached during the instance launch are automatically deleted. For more information about the differences between stopping and terminating instances, go to the "Stop/Start" and "Instance Termination" in [Basics of Amazon EBS-Backed AMIs and Instances](#) in the Amazon EC2 User Guide.

Request Parameters

| Name | Description | Required |
|--------------------|--|----------|
| <i>InstanceIds</i> | One or more instance IDs. Type: String Default: None | Yes |
| <i>Force</i> | Forces the instance to stop. The instance will not have an opportunity to flush file system caches or file system metadata. If you use this option, you must perform file system check and repair procedures. This option is not recommended for Windows instances. Type: Boolean Default: False | No |

Response Elements

The elements in the following table are wrapped in a `StopInstancesResponse` structure.

| Name | Description |
|--------------|---|
| requestId | The ID of the request. Type: xsd:string |
| instancesSet | A list of instance state changes. Each change is wrapped in an <code>item</code> element. Type: InstanceStateChangeType (p. 442) |

Examples

Example Request

This example stops the `i-10a64379` instance without using the "force" option.

```
https://ec2.amazonaws.com/?Action=StopInstances
&InstanceId.1=i-10a64379
&AUTHPARAMS
```

Example Response

```
<StopInstancesResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <instancesSet>
    <item>
      <instanceId>i-10a64379</instanceId>
      <currentState>
        <code>64</code>
        <name>stopping</name>
      </currentState>
      <previousState>
        <code>16</code>
        <name>running</name>
      </previousState>
    </item>
  </instancesSet>
</StopInstancesResponse>
```

Related Operations

- [StartInstances](#) (p. 390)
- [RunInstances](#) (p. 379)
- [DescribeInstances](#) (p. 181)
- [TerminateInstances](#) (p. 394)

TerminateInstances

Description

Shuts down one or more instances. This operation is idempotent; if you terminate an instance more than once, each call will succeed.

Terminated instances will remain visible after termination (approximately one hour).

Note

By default, Amazon EC2 deletes all Amazon EBS volumes that were attached when the instance launched. Amazon EBS volumes attached after instance launch continue running.

You can stop, start, and terminate EBS-backed instances. You can only terminate S3-backed instances. What happens to an instance differs if you stop it or terminate it. For example, when you stop an instance, the root device and any other devices attached to the instance persist. When you terminate an instance, the root device and any other devices attached during the instance launch are automatically deleted. For more information about the differences between stopping and terminating instances, go to the "Stop/Start" and "Instance Termination" in [Basics of Amazon EBS-Backed AMIS and Instances](#) in the Amazon EC2 User Guide.

Request Parameters

| Name | Description | Required |
|--------------------|--|----------|
| <i>InstanceIds</i> | One or more instance IDs. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in a `TerminateInstancesResponse` structure.

| Name | Description |
|---------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>instancesSet</code> | A list of instance state changes. Each change is wrapped in an <code>item</code> element. Type: InstanceStateChangeType (p. 442) |

Examples

Example Request

This example terminates the `i-3ea74257` instance.

```
https://ec2.amazonaws.com/?Action=TerminateInstances
&InstanceId.1=i-3ea74257
&AUTHPARAMS
```

Example Response

```
<TerminateInstancesResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <instancesSet>
    <item>
      <instanceId>i-3ea74257</instanceId>
      <currentState>
        <code>32</code>
        <name>shutting-down</name>
      </currentState>
      <previousState>
        <code>16</code>
        <name>running</name>
      </previousState>
    </item>
  </instancesSet>
</TerminateInstancesResponse>
```

Related Operations

- [DescribeInstances](#) (p. 181)
- [RunInstances](#) (p. 379)
- [StopInstances](#) (p. 392)
- [StartInstances](#) (p. 390)

UnassignPrivateIpAddresses

Description

Unassigns one or more secondary private IP addresses from a network interface in Amazon VPC.

This command is only available in Amazon VPC.

Request Parameters

| Name | Description | Required |
|---------------------------|--|----------|
| <i>NetworkInterfaceId</i> | The network interface from which the secondary private IP address will be unassigned. Type: String Default: None | Yes |
| <i>PrivateIpAddress.n</i> | The secondary private IP addresses that you want to unassign from the network interface. You can specify this option multiple times to unassign more than one IP address. Type: AssignPrivateIpAddressesSetItemRequestType Default: None | Yes |

Response Elements

The elements in the following table are wrapped in an `UnassignPrivateIpAddressesResponse` structure.

| Name | Description |
|------------------------|--|
| <code>requestId</code> | The ID of the request. Type: xsd:string |
| <code>return</code> | Returns <code>true</code> if the request succeeds. Otherwise, returns an error. Type: xsd:boolean |

Examples

Example Request

The following request unassigns two secondary private IP addresses from the specified network interface.

```
https://ec2.amazonaws.com/?Action=UnassignPrivateIpAddresses
&NetworkInterfaceId=eni-197d9972
&PrivateIpAddress.0=10.0.2.60
```

```
&PrivateIpAddress.1=10.0.2.65  
&AUTHPARAMS
```

Example Response

```
<UnassignPrivateIpAddresses xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">  
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>  
  <return>true</return>  
</UnassignPrivateIpAddresses>
```

Related Operations

- [AssignPrivateIpAddresses](#) (p. 15)

UnmonitorInstances

Description

Disables monitoring for a running instance. For more information about monitoring instances, see [Monitoring Your Instances and Volumes](#) in the *Amazon Elastic Compute Cloud User Guide*.

Request Parameters

| Name | Description | Required |
|---------------------|--|----------|
| <i>InstanceId.n</i> | One or more instance IDs. Type: String Default: None | Yes |

Response Elements

The elements in the following table are wrapped in an `UnmonitorInstancesResponse` structure.

| Name | Description |
|---------------------------|---|
| <code>requestId</code> | The ID of the request. Type: <code>xsd:string</code> |
| <code>instancesSet</code> | A list of monitoring information for one or more instances. Each set of information is wrapped in an <code>item</code> element. Type: MonitorInstancesResponseSetItemType (p. 450) |

Examples

Example Request

This example disables monitoring for i-43a4412a and i-23a3397d.

```
https://ec2.amazonaws.com/?Action=UnmonitorInstances
&InstanceId.1=i-43a4412a
&InstanceId.2=i-23a3397d
&AUTHPARAMS
```

Example Response

```
<UnmonitorInstancesResponse xmlns="http://ec2.amazonaws.com/doc/2012-06-15/">
  <requestId>59dbff89-35bd-4eac-99ed-be587EXAMPLE</requestId>
  <instancesSet>
    <item>
      <instanceId>i-43a4412a</instanceId>
      <monitoring>
```

```
        <state>disabled</state>
      </monitoring>
    </item>
    <item>
      <instanceId>i-23a3397d</instanceId>
      <monitoring>
        <state>disabled</state>
      </monitoring>
    </item>
  </instancesSet>
</UnmonitorInstancesResponse>
```

Related Operations

- [MonitorInstances](#) (p. 333)
- [RunInstances](#) (p. 379)

Data Types

Topics

- [AssignPrivateIpAddressesSetItemRequestType](#) (p. 402)
- [AssignPrivateIpAddressesType](#) (p. 403)
- [AttachmentSetItemResponseType](#) (p. 403)
- [AttachmentType](#) (p. 404)
- [AvailabilityZoneItemType](#) (p. 405)
- [AvailabilityZoneMessageType](#) (p. 406)
- [BlockDeviceMappingItemType](#) (p. 406)
- [BundleInstanceS3StorageType](#) (p. 407)
- [BundleInstanceTaskErrorType](#) (p. 408)
- [BundleInstanceTaskStorageType](#) (p. 408)
- [BundleInstanceTaskType](#) (p. 409)
- [CancelSpotInstanceRequestsResponseSetItemType](#) (p. 410)
- [ConversionTaskType](#) (p. 411)
- [CreateVolumePermissionItemType](#) (p. 411)
- [CustomerGatewayType](#) (p. 412)
- [DescribeAddressesResponseSetItemType](#) (p. 413)
- [DescribeImagesResponseSetItemType](#) (p. 414)
- [DescribeKeyPairsResponseSetItemType](#) (p. 416)
- [DescribeReservedInstancesOfferingsResponseSetItemType](#) (p. 417)
- [DescribeReservedInstancesResponseSetItemType](#) (p. 418)
- [DescribeSnapshotsSetItemResponseType](#) (p. 419)
- [DescribeVolumesSetItemResponseType](#) (p. 420)
- [DhcpConfigurationItemType](#) (p. 421)
- [DhcpOptionsType](#) (p. 422)
- [DhcpValueType](#) (p. 423)
- [DiskImageDescriptionType](#) (p. 423)
- [DiskImageVolumeDescriptionType](#) (p. 424)
- [EbsBlockDeviceType](#) (p. 425)
- [EbsInstanceBlockDeviceMappingResponseType](#) (p. 425)
- [ExportTaskResponseType](#) (p. 426)

- [ExportToS3TaskResponseType](#) (p. 427)
- [GroupItemType](#) (p. 428)
- [IamInstanceProfileRequestType](#) (p. 429)
- [IamInstanceProfileResponseType](#) (p. 429)
- [IcmpTypeCodeType](#) (p. 430)
- [ImportInstanceTaskDetailsType](#) (p. 430)
- [ImportInstanceVolumeDetailItemType](#) (p. 431)
- [ImportVolumeTaskDetailsType](#) (p. 432)
- [InstanceBlockDeviceMappingItemType](#) (p. 433)
- [InstanceBlockDeviceMappingResponseItemType](#) (p. 434)
- [InstanceEbsBlockDeviceType](#) (p. 434)
- [InstanceExportTaskResponseType](#) (p. 435)
- [InstanceStateEventsSetType](#) (p. 435)
- [InstanceStateEventType](#) (p. 436)
- [InstanceStateItemType](#) (p. 436)
- [InstanceStateSetType](#) (p. 437)
- [InstanceStateDetailsSetType](#) (p. 438)
- [InstanceStateType](#) (p. 438)
- [InstanceMonitoringStateType](#) (p. 439)
- [InstanceNetworkInterfaceSetItemRequestType](#) (p. 440)
- [InstanceNetworkInterfaceSetType](#) (p. 441)
- [InstanceStateChangeType](#) (p. 442)
- [InstanceStateType](#) (p. 442)
- [InternetGatewayAttachmentType](#) (p. 443)
- [InternetGatewayType](#) (p. 444)
- [IpPermissionType](#) (p. 445)
- [IpRangeItemType](#) (p. 446)
- [LaunchPermissionItemType](#) (p. 446)
- [LaunchSpecificationRequestType](#) (p. 447)
- [LaunchSpecificationResponseType](#) (p. 448)
- [MonitoringInstanceType](#) (p. 449)
- [MonitorInstancesResponseSetItemType](#) (p. 450)
- [NetworkAclEntryType](#) (p. 451)
- [NetworkAclType](#) (p. 452)
- [NetworkAclAssociationType](#) (p. 452)
- [NetworkInterfaceAssociationType](#) (p. 453)
- [NetworkInterfaceSet](#) (p. 454)
- [NetworkInterfaceAttachmentType](#) (p. 455)
- [NetworkInterfacePrivateIpAddressesSetItemType](#) (p. 456)
- [NetworkInterfaceType](#) (p. 456)
- [PlacementGroupInfoType](#) (p. 457)
- [PlacementRequestType](#) (p. 458)
- [PlacementResponseType](#) (p. 459)
- [PortRangeType](#) (p. 459)
- [PrivateIpAddressesSetItemRequestType](#) (p. 460)
- [ProductCodeItemType](#) (p. 460)

- [ProductCodesSetItemType](#) (p. 461)
- [ProductDescriptionSetItemType](#) (p. 462)
- [RecurringChargesSetItemType](#) (p. 462)
- [RegionItemType](#) (p. 463)
- [ReservationInfoType](#) (p. 463)
- [ResourceTagSetItemType](#) (p. 464)
- [RouteTableAssociationType](#) (p. 464)
- [RouteTableType](#) (p. 465)
- [RouteType](#) (p. 466)
- [RunningInstancesItemType](#) (p. 467)
- [SecurityGroupIdSetItemType](#) (p. 470)
- [SecurityGroupItemType](#) (p. 470)
- [SpotDatafeedSubscriptionType](#) (p. 471)
- [SpotInstanceRequestSetItemType](#) (p. 472)
- [SpotInstanceStateFaultType](#) (p. 474)
- [SpotPriceHistorySetItemType](#) (p. 474)
- [StateReasonType](#) (p. 475)
- [SubnetType](#) (p. 476)
- [TagSetItemType](#) (p. 477)
- [UserDataType](#) (p. 478)
- [UserIdGroupPairType](#) (p. 478)
- [ValueType](#) (p. 479)
- [VolumeStatusItemType](#) (p. 480)
- [VolumeStatusInfoType](#) (p. 481)
- [VolumeStatusDetailsItemType](#) (p. 481)
- [VolumeStatusEventItemType](#) (p. 482)
- [VolumeStatusActionItemType](#) (p. 482)
- [VpcType](#) (p. 483)
- [VpnConnectionType](#) (p. 484)
- [VpnGatewayType](#) (p. 485)
- [VpnTunnelTelemetryType](#) (p. 486)

AssignPrivateIpAddressesSetItemRequestType

The AssignPrivateIpAddressesSetItemRequestType data type.

Ancestors

- [AssignPrivateIpAddressesType](#)

Relevant Operations

- [AssignPrivateIpAddresses](#)
- [UnassignPrivateIpAddresses](#)

Contents

The following table describes the elements contained in `AssignPrivateIpAddressesSetItemRequest`.

| Name | Description |
|-------------------------------|---|
| <code>privateIpAddress</code> | The private IP address. Type: String |

AssignPrivateIpAddressesType

The `AssignPrivateIpAddressesType` data type.

Ancestors

- `AssignPrivateIpAddressesType`

Relevant Operations

- `AssignPrivateIpAddresses`

Contents

The following table describes the elements contained in the `AssignPrivateIpAddressesType`.

| Name | Description |
|---|---|
| <code>networkInterfaceId</code> | The ID of the network interface. Type: String |
| <code>privateIpAddressesSet</code> | The list of IP addresses to assign to the network interface. Type: AssignPrivateIpAddressesSetItemRequestType (p. 402) |
| <code>secondaryPrivateIpAddressCount</code> | The number of secondary private IP addresses. You cannot specify this option with the <code>privateIpAddressesSet</code> option. Type: Integer |
| <code>allowReassignment</code> | Specifies whether to allow a secondary private IP address to be reassigned if it is currently assigned to another instance or network interface. Type: Boolean |

AttachmentSetItemResponseType

The `AttachmentSetItemResponseType` data type.

Ancestors

- AttachmentSetResponseType

Relevant Operations

- DescribeVolumes

Contents

The following table describes the elements contained in AttachmentSetItemResponseType.

| Name | Description |
|---------------------|--|
| volumeId | The ID of the volume. Type: String |
| instanceId | The ID of the instance. Type: String |
| device | The device name exposed to the instance (e.g., /dev/sdh). Type: String |
| status | The attachment state. Type: String Valid values: <code>attaching</code> <code>attached</code> <code>detaching</code> <code>detached</code> |
| attachTime | The time stamp when the attachment initiated. Type: DateTime |
| deleteOnTermination | Specifies whether the Amazon EBS volume is deleted on instance termination. Type: Boolean |

AttachmentType

The AttachmentType data type.

Ancestors

- AttachmentSetType
- AttachVpnGatewayResponse

Relevant Operations

- CreateVpnGateway

- DescribeVpnGateways
- AttachVpnGateway

Contents

The following table describes the elements contained in AttachmentType.

| Name | Description |
|-------|---|
| vpcId | The ID of the VPC the virtual private gateway is attached to. Type: String |
| state | The current state of the attachment. Type: String Valid values: <code>attaching</code> <code>attached</code> <code>detaching</code> <code>detached</code> |

AvailabilityZoneItem

The AvailabilityZoneItem data type.

Ancestors

- AvailabilityZoneSetType

Relevant Operations

- DescribeAvailabilityZones

Contents

The following table describes the elements contained in AvailabilityZoneItem.

| Name | Description |
|------------|---|
| zoneName | The name of the Availability Zone. Type: String |
| zoneState | The state of the Availability Zone. Type: String |
| regionName | The name of the Region. Type: String |
| messageSet | Any messages about the Availability Zone, each one wrapped in an <code>item</code> element. Type: AvailabilityZoneMessageType (p. 406) |

AvailabilityZoneMessageType

The AvailabilityZoneMessageType data type.

Ancestors

- AvailabilityZoneMessageSetType

Relevant Operations

- DescribeAvailabilityZones

Contents

The following table describes the elements contained in AvailabilityZoneMessageType.

| Name | Description |
|---------|--|
| message | The message about the Availability Zone. Type: String |

BlockDeviceMappingItemType

The BlockDeviceMappingItemType data type.

Ancestors

- BlockDeviceMappingType

Relevant Operations

- DescribeImageAttribute
- DescribeImages
- RequestSpotInstances
- DescribeSpotInstanceRequests
- RequestSpotInstances
- RegisterImage
- RunInstances

Contents

The following table describes the elements contained in BlockDeviceMappingItemType.

| Name | Description |
|-------------|--|
| deviceName | The device name exposed to the instance (e.g., /dev/sdh). Type: String |
| virtualName | The virtual device name. Type: String |
| ebs | Parameters used to automatically set up Amazon EBS volumes when the instance is launched. Type: EbsBlockDeviceType (p. 425) |
| noDevice | Include this empty element to suppress the specified device included in the block device mapping of the AMI. |

BundleInstanceS3StorageType

The BundleInstanceS3StorageType data type.

Ancestors

- [BundleInstanceTaskStorageType](#) (p. 408)

Relevant Operations

- BundleInstance
- DescribeBundleTasks
- CancelBundleTask
- BundleInstance

Contents

The following table describes the elements contained in BundleInstanceS3StorageType.

| Name | Description |
|----------------|--|
| awsAccessKeyId | The Access Key ID of the owner of the Amazon S3 bucket. Type: String |
| bucket | The bucket in which to store the AMI. You can specify a bucket that you already own or a new bucket that Amazon EC2 creates on your behalf. If you specify a bucket that belongs to someone else, Amazon EC2 returns an error. Type: String |
| prefix | The beginning of the file name of the AMI. Type: String |

| Name | Description |
|-----------------------|--|
| uploadPolicy | A Base64-encoded Amazon S3 upload policy that gives Amazon EC2 permission to upload items into Amazon S3 on the user's behalf. Type: String |
| uploadPolicySignature | The signature of the Base64 encoded JSON document. Type: String |

BundleInstanceTaskErrorType

The BundleInstanceTaskErrorType data type.

Ancestors

- [BundleInstanceTaskType](#) (p. 409)

Relevant Operations

- BundleInstance
- DescribeBundleTasks
- CancelBundleTask

Contents

The following table describes the elements contained in BundleInstanceTaskErrorType.

| Name | Description |
|---------|------------------------------------|
| code | The error code. Type: String |
| message | The error message. Type: String |

BundleInstanceTaskStorageType

The BundleInstanceTaskStorageType data type.

Ancestors

- [BundleInstanceTaskType](#) (p. 409)
- BundleInstanceType

Relevant Operations

- BundleInstance
- DescribeBundleTasks
- CancelBundleTask
- BundleInstance

Contents

The following table describes the elements contained in BundleInstanceTaskStorageType.

| Name | Description |
|------|--|
| S3 | An Amazon S3 storage location. Type: BundleInstanceS3StorageType (p. 407) |

BundleInstanceTaskType

The BundleInstanceTaskType data type.

Ancestors

- BundleInstanceResponseType
- BundleInstanceTasksSetType
- CancelBundleTaskResponseType

Relevant Operations

- BundleInstance
- DescribeBundleTasks
- CancelBundleTask

Contents

The following table describes the elements contained in BundleInstanceTaskType.

| Name | Description |
|------------|--|
| instanceId | The ID of the instance associated with this bundle task. Type: String |
| bundleId | The ID for this bundle task. Type: String |

| Name | Description |
|------------|--|
| state | The state of the task. Type: String Valid values: pending waiting-for-shutdown bundling storing cancelling complete failed |
| startTime | The time this task started. Type: DateTime |
| updateTime | The time of the most recent update for the task. Type: DateTime |
| storage | The Amazon S3 storage locations. Type: BundleInstanceTaskStorageType (p. 408) |
| progress | The level of task completion, as a percent (for example, 20%). Type: String |
| error | If the task fails, a description of the error. Type: BundleInstanceTaskErrorType (p. 408) |

CancelSpotInstanceRequestsResponseSetItemType

The CancelSpotInstanceRequestsResponseSetItemType data type.

Ancestors

- [CancelSpotInstanceRequestsResponseSetType](#)

Relevant Operations

- [CancelSpotInstanceRequests](#)

Contents

The following table describes the elements contained in CancelSpotInstanceRequestsResponseSetItemType.

| Name | Description |
|-----------------------|--|
| spotInstanceRequestId | The ID of the Spot Instance request. Type: String |
| state | The state of the Spot Instance request. Type: String Valid values: active open closed cancelled failed |

ConversionTaskType

The ConversionTaskType data type.

Ancestors

- ConversionTaskSetType
- ImportInstanceResponse
- ImportVolumeResponse

Relevant Operations

- DescribeConversionTasks
- ImportInstance
- ImportVolume

Contents

The following table describes the elements contained in ConversionTaskType.

| Name | Description |
|------------------|---|
| conversionTaskId | The ID of the conversion task Type: String |
| expirationTime | The time when the task expires. If the upload isn't complete before the expiration time, we automatically cancel the task. Type: String |
| importVolume | If the task is for importing a volume, this contains information about the import volume task. Type: ImportVolumeTaskDetailsType (p. 432) |
| importInstance | If the task is for importing an instance, this contains information about the import instance task. Type: ImportInstanceTaskDetailsType (p. 430) |
| state | The state of the conversion task. Type: String Valid values: active cancelling cancelled completed |
| statusMessage | The status message related to the conversion task. Type: String |

CreateVolumePermissionItemType

The CreateVolumePermissionItemType data type.

Ancestors

- CreateVolumePermissionListType

Relevant Operations

- ModifySnapshotAttribute
- DescribeSnapshotAttribute

Contents

The following table describes the elements contained in CreateVolumePermissionItemType.

| Name | Description |
|--------|--|
| userId | The ID of an AWS account that can create volumes from the snapshot. Type: String |
| group | The group that is allowed to create volumes from the snapshot. Type: String Valid Value: all |

CustomerGatewayType

The CustomerGatewayType data type.

Ancestors

- CreateCustomerGatewayResponse
- CustomerGatewaySetType

Relevant Operations

- CreateCustomerGateway
- DescribeCustomerGateways

Contents

The following table describes the elements contained in CustomerGatewayType.

| Name | Description |
|-------------------|--|
| customerGatewayId | The ID of the customer gateway. Type: String |
| state | The current state of the customer gateway. Type: String Valid values: <code>pending</code> <code>available</code> <code>deleting</code> <code>deleted</code> |
| type | The type of VPN connection the customer gateway supports (ipsec.1). Type: String |
| ipAddress | The Internet-routable IP address of the customer gateway's outside interface. Type: String |
| bgpAsn | The customer gateway's Border Gateway Protocol (BGP) Autonomous System Number (ASN). Type: Integer |
| tagSet | Any tags assigned to the resource, each one wrapped in an <code>item</code> element. Type: ResourceTagSetItemType (p. 464) |

DescribeAddressesResponseItem

The DescribeAddressesResponseItem data type.

Ancestors

- DescribeAddressesResponseInfoType

Relevant Operations

- DescribeAddresses

Contents

The following table describes the elements contained in DescribeAddressesResponseItem.

| Name | Description |
|--------------|--|
| publicIp | The public IP address. Type: String |
| allocationId | The ID representing the allocation of the address for use with Amazon VPC. Type: String |

| Name | Description |
|-------------------------|---|
| domain | Specifies whether this Elastic IP address is for EC2 instances (i.e., standard) or VPC instances. Type: String Valid values: <code>standard</code> <code>vpc</code> |
| instanceId | The ID of the instance the address is associated with (if any). Type: String |
| associationId | The ID representing the association of a VPC Elastic IP address with an instance in a VPC. Type: String |
| networkInterfaceId | The ID of the network interface. Type: String |
| networkInterfaceOwnerId | The ID of the AWS account that owns the network interface. Type: String |

DescribeImagesResponseItem

The DescribeImagesResponseItem data type.

Ancestors

- DescribeImagesResponseInfo

Relevant Operations

- DescribeImages

Contents

The following table describes the elements contained in DescribeImagesResponseItem.

| Name | Description |
|---------------|--|
| imageId | The ID of the AMI. Type: String |
| imageLocation | The location of the AMI. Type: String |
| imageState | Current state of the AMI. If the operation returns <code>available</code> , the image is successfully registered and available for launching. Type: String Valid values: <code>available</code> <code>pending</code> <code>failed</code> |

**Amazon Elastic Compute Cloud API Reference
Contents**

| Name | Description |
|------------------------------|---|
| <code>imageOwnerId</code> | AWS account ID of the image owner. Type: String |
| <code>isPublic</code> | Specifies whether the image has public launch permissions. The value is <code>true</code> if this image has public launch permissions or <code>false</code> if it has only implicit and explicit launch permissions. Type: Boolean |
| <code>productCodes</code> | Any product codes associated with the AMI, each one wrapped in an <code>item</code> element. Type: ProductCodesSetItemType (p. 461) |
| <code>architecture</code> | The architecture of the image. Type: String |
| <code>imageType</code> | The type of image (machine, kernel, or RAM disk). Type: String |
| <code>kernelId</code> | The kernel associated with the image, if any. Only applicable for machine images. Type: String |
| <code>ramdiskId</code> | The RAM disk associated with the image, if any. Only applicable for machine images. Type: String |
| <code>platform</code> | The value is <code>Windows</code> for Windows AMIs; otherwise blank. Type: String |
| <code>stateReason</code> | The reason for the state change. Type: StateReasonType (p. 475) |
| <code>imageOwnerAlias</code> | The AWS account alias (e.g., <code>amazon</code> , <code>self</code> , etc.) or AWS account ID that owns the AMI. Type: String |
| <code>name</code> | The name of the AMI that was provided during image creation. Type: String |
| <code>description</code> | The description of the AMI that was provided during image creation. Type: String |
| <code>rootDeviceType</code> | The type of root device used by the AMI. The AMI can use an Amazon EBS volume or an instance store volume. Type: String Valid values: <code>ebs</code> <code>instance-store</code> |
| <code>rootDeviceName</code> | The device name of the root device (e.g., <code>/dev/sda1</code> , or <code>xvda</code>). Type: String |

| Name | Description |
|--------------------|--|
| blockDeviceMapping | Any block device mapping entries, each one wrapped in an <code>item</code> element. Type: BlockDeviceMappingItemType (p. 406) |
| virtualizationType | The type of virtualization of the AMI. Type: String Valid values: <code>paravirtual</code> <code>hvm</code> |
| tagSet | Any tags assigned to the resource, each one wrapped in an <code>item</code> element. Type: ResourceTagSetItemType (p. 464) |
| hypervisor | The image's hypervisor type. Type: String Valid values: <code>ovm</code> <code>xen</code> |

DescribeKeyPairsResponseItemType

The `DescribeKeyPairsResponseItem` data type.

Ancestors

- `DescribeKeyPairsResponseInfoType`

Relevant Operations

- `DescribeKeyPairs`

Contents

The following table describes the elements contained in `DescribeKeyPairsResponseItem`.

| Name | Description |
|----------------|---|
| keyName | The name of the key pair. Type: String |
| keyFingerprint | If you used <code>CreateKeyPair</code> to create the key pair, this is the SHA-1 digest of the DER encoded private key. If you used <code>ImportKeyPair</code> to provide AWS the public key, this is the MD5 public key fingerprint as specified in section 4 of RFC4716 . Type: String |

DescribeReservedInstancesOfferingsResponseSetItemType

The DescribeReservedInstancesOfferingsResponseSetItemType data type.

Ancestors

- DescribeReservedInstancesOfferingsResponseSetType

Relevant Operations

- DescribeReservedInstancesOfferings

Contents

The following table describes the elements contained in DescribeReservedInstancesOfferingsResponseSetItemType.

| Name | Description |
|-----------------------------|--|
| reservedInstancesOfferingId | The ID of the Reserved Instance offering. Type: String |
| instanceType | The instance type on which the Reserved Instance can be used. Type: String |
| availabilityZone | The Availability Zone in which the Reserved Instance can be used. Type: String |
| duration | The duration of the Reserved Instance, in seconds. Type: Long |
| fixedPrice | The purchase price of the Reserved Instance. Type: Double |
| usagePrice | The usage price of the Reserved Instance, per hour. Type: Double |
| productDescription | The Reserved Instance description. Type: String Valid values: Linux/UNIX Linux/UNIX (Amazon VPC) Windows Windows (Amazon VPC) |
| instanceTenancy | The tenancy of the reserved instance. Type: String |
| currencyCode | The currency of the Reserved Instance offering you are purchasing. It's specified using ISO 4217 standard currency codes (e.g., USD, JPY). At this time, the only supported currency is USD. Type: String |

| Name | Description |
|------------------|--|
| offeringType | The Reserved Instance offering type. Type: String |
| recurringCharges | The recurring charge tag assigned to the resource. Type: RecurringChargesSetItemType (p. 462) |

DescribeReservedInstancesResponseSetItemType

The DescribeReservedInstancesResponseSetItemType data type.

Ancestors

- DescribeReservedInstancesResponseSetType

Relevant Operations

- DescribeReservedInstances

Contents

The following table describes the elements contained in DescribeReservedInstancesResponseSetItemType.

| Name | Description |
|---------------------|---|
| reservedInstancesId | The ID of the Reserved Instance. Type: String |
| instanceType | The instance type on which the Reserved Instance can be used. Type: String |
| availabilityZone | The Availability Zone in which the Reserved Instance can be used. Type: String |
| start | The date and time the Reserved Instance started. Type: DateTime |
| duration | The duration of the Reserved Instance, in seconds. Type: Long |
| fixedPrice | The purchase price of the Reserved Instance. Type: Double |
| usagePrice | The usage price of the Reserved Instance, per hour. Type: Double |
| instanceCount | The number of Reserved Instances purchased. Type: Integer |

| Name | Description |
|--------------------|--|
| productDescription | The Reserved Instance description. Type: String Valid values: Linux/UNIX Linux/UNIX (Amazon VPC) Windows Windows (Amazon VPC) |
| state | The state of the Reserved Instance purchase. Type: String Valid values: payment-pending active payment-failed retired |
| tagSet | Any tags assigned to the resource, each one wrapped in an item element. Type: ResourceTagSetItemType (p. 464) |
| instanceTenancy | The tenancy of the reserved instance. Type: String Valid values: default dedicated |
| currencyCode | The currency of the Reserved Instance. It's specified using ISO 4217 standard currency codes. Type: String Valid values: As specified in ISO 4217 (e.g., USD, JPY) |
| offeringType | The Reserved Instance offering type. Type: String |
| recurringCharges | The recurring charge tag assigned to the resource. Type: RecurringChargesSetItemType (p. 462) |

DescribeSnapshotsSetItemResponseType

The DescribeSnapshotsSetItemResponseType data type.

Ancestors

- DescribeSnapshotsSetResponseType

Relevant Operations

- DescribeSnapshots

Contents

The following table describes the elements contained in DescribeSnapshotsSetItemResponseType.

| Name | Description |
|-------------|---|
| snapshotId | The ID of the snapshot. Type: String |
| volumeId | The ID of the volume. Type: String |
| status | The snapshot state. Type: String Valid values: <code>pending</code> <code>completed</code> <code>error</code> |
| startTime | The time stamp when the snapshot was initiated. Type: DateTime |
| progress | The progress of the snapshot, as a percentage. Type: String |
| ownerId | The ID of the AWS account that owns the snapshot. Type: String |
| volumeSize | The size of the volume, in GiB. Type: String |
| description | The description of the snapshot. Type: String |
| ownerAlias | The AWS account alias (<code>amazon</code> , <code>self</code> , etc.) or AWS account ID that owns the AML. Type: String |
| tagSet | Any tags assigned to the resource, each one wrapped in an <code>item</code> element. Type: ResourceTagSetItemType (p. 464) |

DescribeVolumesSetItemResponseType

The DescribeVolumesSetItemResponseType data type.

Ancestors

- `ItemType-DescribeVolumesSetResponseType`

Relevant Operations

- `DescribeVolumes`

Contents

The following table describes the elements contained in DescribeVolumesSetItemResponseType.

| Name | Description |
|------------------|--|
| volumeId | The ID of the volume. Type: String |
| size | The size of the volume, in GiBs. Type: String |
| snapshotId | The snapshot from which the volume was created (optional). Type: String |
| availabilityZone | The Availability Zone in which the volume was created. Type: String |
| status | The state of the volume. Type: String Valid values: <code>creating</code> <code>available</code> <code>in-use</code> <code>deleting</code> <code>deleted</code> <code>error</code> |
| createTime | The time stamp when volume creation was initiated. Type: DateTime |
| attachmentSet | Any volumes attached, each one wrapped in an <code>item</code> element. Type: AttachmentSetItemResponseType (p. 403) |
| tagSet | Any tags assigned to the resource, each one wrapped in an <code>item</code> element. Type: ResourceTagSetItemType (p. 464) |

DhcpConfigurationItemType

The DhcpConfigurationItemType data type.

Ancestors

- DhcpConfigurationItemSetType

Relevant Operations

- CreateDhcpOptions
- CreateDhcpOptions
- DescribeDhcpOptions

Contents

The following table describes the elements contained in `DhcpConfigurationItemType`.

| Name | Description |
|-----------------------|---|
| <code>key</code> | The name of a DHCP option. Type: String |
| <code>valueSet</code> | Any values for a DHCP option, each one wrapped in an <code>item</code> element. Type: DhcpValueType (p. 423) |

DhcpOptionsType

The `DhcpOptionsType` data type.

Ancestors

- `CreateDhcpOptionsResponse`
- `DhcpOptionsSetType`

Relevant Operations

- `CreateDhcpOptions`
- `DescribeDhcpOptions`

Contents

The following table describes the elements contained in `DhcpOptionsType`.

| Name | Description |
|-----------------------------------|--|
| <code>dhcpOptionsId</code> | The ID of the set of DHCP options. Type: String |
| <code>dhcpConfigurationSet</code> | The options in the set. Each option's key and set of values are wrapped in an <code>item</code> element. Type: DhcpConfigurationItemType (p. 421) |
| <code>tagSet</code> | Any tags assigned to the resource, each one wrapped in an <code>item</code> element. Type: ResourceTagSetItemType (p. 464) |

DhcpValueType

The DhcpValueType data type.

Ancestors

- DhcpValueSetType

Relevant Operations

- CreateDhcpOptions
- CreateDhcpOptions
- DescribeDhcpOptions

Contents

The following table describes the elements contained in DhcpValueType.

| Name | Description |
|-------|--|
| value | A value for the DHCP option. Type: String |

DiskImageDescriptionType

The DiskImageDescriptionType data type.

Ancestors

- [ImportInstanceVolumeDetailItemType](#) (p. 431)
- [ImportVolumeTaskDetailsType](#) (p. 432)

Relevant Operations

- DescribeConversionTasks
- ImportInstance
- ImportVolume

Contents

The following table describes the elements contained in DiskImageDescriptionType.

| Name | Description |
|-------------------|---|
| format | The disk image format. Type: String |
| size | The size of the disk image. Type: Long |
| importManifestUrl | A presigned URL for the import manifest stored in Amazon S3. For information about creating a presigned URL for an Amazon S3 object, read the "Query String Request Authentication Alternative" section of the Authenticating REST Requests topic in the <i>Amazon Simple Storage Service Developer Guide</i> . Type: String |
| checksum | The checksum computed for the disk image. Type: String |

DiskImageVolumeDescriptionType

The DiskImageVolumeDescriptionType data type.

Ancestors

- [ImportInstanceVolumeDetailItemType](#) (p. 431)
- [ImportVolumeTaskDetailsType](#) (p. 432)

Relevant Operations

- DescribeConversionTasks
- ImportInstance
- ImportVolume

Contents

The following table describes the elements contained in DiskImageVolumeDescriptionType.

| Name | Description |
|------|--|
| size | The size of the volume. Type: Integer |
| id | The volume identifier. Type: String |

EbsBlockDeviceType

The EbsBlockDeviceType data type.

Ancestors

- [BlockDeviceMappingItemType](#) (p. 406)

Relevant Operations

- DescribeImageAttribute
- DescribeImages
- RequestSpotInstances
- DescribeSpotInstanceRequests
- RequestSpotInstances
- RegisterImage
- RunInstances

Contents

The following table describes the elements contained in EbsBlockDeviceType.

| Name | Description |
|---------------------|---|
| snapshotId | The ID of the snapshot. Type: String |
| volumeSize | The size of the volume, in GiB. If you're specifying a block device mapping, this is required if you're not creating a volume from a snapshot. Type: integer |
| deleteOnTermination | Specifies whether the Amazon EBS volume is deleted on instance termination. Type: Boolean |

EbsInstanceBlockDeviceMappingResponseType

The EbsInstanceBlockDeviceMappingResponseType data type.

Ancestors

- [InstanceBlockDeviceMappingResponseItem](#) (p. 434)

Relevant Operations

- DescribeInstanceAttribute
- DescribeInstances
- RunInstances

Contents

The following table describes the elements contained in EbsInstanceBlockDeviceMappingResponseType.

| Name | Description |
|---------------------|--|
| volumeId | The ID of the Amazon EBS volume. Type: String |
| status | The attachment state. Type: String Valid values: <code>attaching</code> <code>attached</code> <code>detaching</code> <code>detached</code> |
| attachTime | The time stamp when the attachment initiated. Type: DateTime |
| deleteOnTermination | Specifies whether the Amazon EBS volume is deleted on instance termination. Type: Boolean |

ExportTaskResponseType

The ExportTaskResponseType data type.

Ancestors

- CreateInstanceExportTaskResponseType
- DescribeExportTasksResponseType
- ExportTaskSetResponseType

Relevant Operations

- CreateInstanceExportTask
- DescribeExportTasks

Contents

The following table describes the elements contained in DescribeExportTasksResponseType.

| Name | Description |
|----------------|--|
| exportTaskId | The ID of the export task. Type: String |
| description | A description of the resource being exported. Type: String |
| state | The state of the conversion task. Type: String Valid values: active cancelling cancelled completed |
| statusMessage | The status message related to the export task. Type: String |
| instanceExport | Information about the instance being exported. Type: InstanceExportTaskResponseType (p. 435) |
| exportToS3 | Information about the destination Amazon S3 bucket. Type: ExportToS3TaskResponseType (p. 427) |

ExportToS3TaskResponseType

The ExportToS3TaskResponseType data type.

Ancestors

- [CreateInstanceExportTaskResponseType](#)
- [DescribeExportTasksResponseType](#)
- [ExportTaskSetResponseType](#)
- [ExportTaskResponseType](#)

Relevant Operations

- [CreateInstanceExportTask](#)
- [DescribeExportTasks](#)

Contents

The following table describes the elements contained in ExportToS3TaskResponseType.

| Name | Description |
|-----------------|--|
| diskImageFormat | The format for the exported image. Type: String Valid values: vmdk vhd |

| Name | Description |
|-----------------|---|
| containerFormat | The container format used to combine disk images with metadata (such as OVF). Type: String Valid values: ova |
| s3Bucket | The Amazon S3 bucket for the destination image. Type: String |
| s3Key | The image written to a single object in s3bucket at the S3 key s3prefix + exportTaskId + '.' + diskImageFormat. Type: String |

GroupItem

The GroupItem data type.

Ancestors

- GroupSetType

Relevant Operations

- DescribeInstanceAttribute
- DescribeInstances
- RequestSpotInstances
- DescribeSpotInstanceRequests
- RequestSpotInstances
- RunInstances
- CreateNetworkInterface

Contents

The following table describes the elements contained in GroupItem.

| Name | Description |
|-----------|---|
| groupId | The ID of the security group. In API versions before 2011-01-01, this field returned the name of the security group. Type: String |
| groupName | The name of the security group. Type: String |

iamInstanceProfileRequestType

The iamInstanceProfileRequestType data type.

Ancestors

- RunInstancesType
- LaunchSpecificationRequestType
- LaunchSpecificationResponseType

Relevant Operations

- RunInstances
- RequestSpotInstances

Contents

The following table describes the elements contained in iamInstanceProfileRequestType.

| Name | Description |
|------|--|
| arn | The Amazon resource name (ARN) of the IAM Instance Profile (IIP) to associate with the instance. Type: String |
| name | The name of the IAM Instance Profile (IIP) to associate with the instance. Type: String |

iamInstanceProfileResponseType

The iamInstanceProfileResponseType data type.

Ancestors

- RunningInstancesItemType

Relevant Operations

- RunInstances
- RequestSpotInstances

Contents

The following table describes the elements contained in `IamInstanceProfileResponseType`.

| Name | Description |
|------------------|--|
| <code>arn</code> | The Amazon resource name (ARN) of the IAM Instance Profile (IIP) to associate with the instance. Type: String |
| <code>id</code> | The ID of the IAM Instance Profile ID (IIP) associated with the instance. Type: String |

IcmpTypeCodeType

The `IcmpTypeCodeType` data type.

Ancestors

- `NetworkAclEntryType`

Relevant Operations

- `CreateNetworkAcl`
- `DescribeNetworkAcls`

Contents

The following table describes the elements contained in `IcmpTypeCodeType`.

| Name | Description |
|-------------------|--|
| <code>code</code> | The ICMP code. A value of -1 means all codes for the specified ICMP type. Type: Integer |
| <code>type</code> | The ICMP type. A value of -1 means all types. Type: Integer |

ImportInstanceTaskDetailsType

The `ImportInstanceTaskDetailsType` data type.

Ancestors

- [ConversionTaskType](#) (p. 411)

Relevant Operations

- DescribeConversionTasks
- ImportInstance
- ImportVolume

Contents

The following table describes the elements contained in `ImportInstanceTaskDetailsType`.

| Name | Description |
|--------------------------|---|
| <code>volumes</code> | Any instance volumes for import, each one wrapped in an <code>item</code> element. Type: ImportInstanceVolumeDetailItemType (p. 431) |
| <code>instanceId</code> | The ID of the resulting instance in Amazon EC2. Type: String |
| <code>platform</code> | The instance operating system. Type: String Valid Value: windows |
| <code>description</code> | An optional description of the instance. Type: String |

ImportInstanceVolumeDetailItemType

The `ImportInstanceVolumeDetailItemType` data type.

Ancestors

- [ImportInstanceVolumeDetailSetType](#)

Relevant Operations

- DescribeConversionTasks
- ImportInstance
- ImportVolume

Contents

The following table describes the elements contained in `ImportInstanceVolumeDetailItemType`.

| Name | Description |
|-------------------------------|--|
| <code>bytesConverted</code> | The number of bytes converted so far. Type: Long |
| <code>availabilityZone</code> | The Availability Zone where the resulting instance will reside. Type: String |
| <code>image</code> | The information about the image. Type: DiskImageDescriptionType (p. 423) |
| <code>description</code> | The description you provided when starting the import instance task. Type: String |
| <code>volume</code> | The information about the volume. Type: DiskImageVolumeDescriptionType (p. 424) |
| <code>status</code> | The status of the import of this particular disk image. Type: String |
| <code>statusMessage</code> | The status information or errors related to the disk image. Type: String |

ImportVolumeTaskDetailsType

The `ImportVolumeTaskDetailsType` data type.

Ancestors

- [ConversionTaskType](#) (p. 411)

Relevant Operations

- `DescribeConversionTasks`
- `ImportInstance`
- `ImportVolume`

Contents

The following table describes the elements contained in `ImportVolumeTaskDetailsType`.

| Name | Description |
|------------------|--|
| bytesConverted | The number of bytes converted so far. Type: Long |
| availabilityZone | The Availability Zone where the resulting volume will reside. Type: String |
| description | The description you provided when starting the import volume task. Type: String |
| image | Information about the image. Type: DiskImageDescriptionType (p. 423) |
| volume | Information about the volume. Type: DiskImageVolumeDescriptionType (p. 424) |

InstanceBlockDeviceMappingItemType

The InstanceBlockDeviceMappingItemType data type.

Ancestors

- InstanceBlockDeviceMappingType

Relevant Operations

- ModifyInstanceAttribute

Contents

The following table describes the elements contained in InstanceBlockDeviceMappingItemType.

| Name | Description |
|-------------|--|
| deviceName | The device name exposed to the instance (e.g., /dev/sdh, or xvdh). Type: String |
| virtualName | The virtual device name. Type: String |
| ebs | Parameters used to automatically set up Amazon EBS volumes when the instance is launched. Type: InstanceEbsBlockDeviceType (p. 434) |
| noDevice | Include this empty element to suppress the specified device included in the block device mapping of the AMI. |

InstanceBlockDeviceMappingResponseItemType

The InstanceBlockDeviceMappingResponseItemType data type.

Ancestors

- InstanceBlockDeviceMappingResponseType

Relevant Operations

- DescribeInstanceAttribute
- DescribeInstances
- RunInstances

Contents

The following table describes the elements contained in InstanceBlockDeviceMappingResponseItemType.

| Name | Description |
|------------|---|
| deviceName | The device name exposed to the instance (e.g., /dev/sdh, or xvdh). Type: String |
| ebs | Parameters used to automatically set up Amazon EBS volumes when the instance is launched. Type: EbsInstanceBlockDeviceMappingResponseType (p. 425) |

InstanceEbsBlockDeviceType

The InstanceEbsBlockDeviceType data type.

Ancestors

- InstanceBlockDeviceMappingItemType (p. 433)

Relevant Operations

- ModifyInstanceAttribute

Contents

The following table describes the elements contained in InstanceEbsBlockDeviceType.

| Name | Description |
|----------------------------------|--|
| <code>deleteOnTermination</code> | Specifies whether the Amazon EBS volume is deleted on instance termination. Type: Boolean |
| <code>volumeId</code> | The ID of the Amazon EBS volume. Type: String |

InstanceExportTaskResponseType

The InstanceExportTaskResponseType data type.

Ancestors

- CreateInstanceExportTaskResponseType
- DescribeExportTasksResponseType
- ExportTaskSetResponseType
- ExportTaskResponseType

Relevant Operations

- CreateInstanceExportTask
- DescribeExportTasks

Contents

The following table describes the elements contained in InstanceExportTaskResponseType.

| Name | Description |
|--------------------------------|---|
| <code>instanceId</code> | The ID of the resource being exported. Type: String |
| <code>targetEnvironment</code> | The target virtualization environment. Type: String Valid values: vmware citrix |

InstanceStatusEventsSetType

The InstanceStatusEventsSetType data type.

Relevant Operations

- DescribeInstanceStatus (p. 197)

Contents

The following table describes the elements contained in InstanceStatusEventsSetType.

| Name | Description |
|------|---|
| item | Information about scheduled events for the instance. Type: InstanceStatusEventType |

InstanceStatusEventType

The InstanceStatusEventType data type.

Ancestors

- DescribeInstanceStatus
InstanceStatusEventsSetType

Relevant Operations

- [DescribeInstanceStatus](#) (p. 197)

Contents

The following table describes the elements contained in InstanceStatusEventType.

| Name | Description |
|-------------|---|
| code | The associated code of the event. Type: String Valid parameters: <code>instance-reboot</code> <code>system-reboot</code> <code>instance-retirement</code> |
| description | A description of the event. Type: String |
| notBefore | The earliest scheduled start time for the event. Type: DateTime |
| notAfter | The latest scheduled end time for the event. Type: DateTime |

InstanceStatusItemType

The InstanceStatusItemType data type.

Ancestors

- [DescribeInstanceStatus](#)
- [InstanceStatusSetType](#)

Relevant Operations

- [DescribeInstanceStatus](#) (p. 197)

Contents

The following table describes the elements contained in `InstanceStatusItemType`.

| Name | Description |
|-------------------------------|--|
| <code>instanceId</code> | The ID of the instance. Type: String |
| <code>availabilityZone</code> | The Availability Zone of the instance. Type: String |
| <code>eventsSet</code> | Extra information regarding events associated with the instance. Type: InstanceStatusEventsSetType (p. 435) |
| <code>instanceState</code> | The intended state of the instance. Calls to <code>DescribeInstanceStatus</code> require that an instance be in the <code>running</code> state. Type: InstanceStateType (p. 442) |
| <code>systemStatus</code> | Reports impaired functionality that stems from issues related to the systems that support an instance, such as hardware failures and network connectivity problems. Type: InstanceStatusType (p. 438) |
| <code>instanceStatus</code> | Reports impaired functionality that arises from problems internal to the instance. The DescribeInstanceStatus (p. 197) response elements report such problems as impaired reachability. Type: InstanceStatusType (p. 438) |

InstanceStatusSetType

The `InstanceStatusSetType` data type.

Relevant Operations

- [DescribeInstanceStatus](#) (p. 197)

Contents

The following table describes the elements contained in InstanceStatusSetType.

| Name | Description |
|------|---|
| item | Information about the status of the instance. Type: InstanceStatusItemType |

InstanceStatusDetailsSetType

The InstanceStateType data type.

Ancestors

- [InstanceStatusItemType](#) (p. 436)
- [InstanceStatusType](#) (p. 438)

Relevant Operations

- [DescribeInstanceStatus](#) (p. 197)

Contents

The following table describes the elements contained in InstanceStatusDetailsSetType.

| Name | Description |
|---------------|---|
| name | The type of instance status detail. Type: String Valid values: <code>reachability</code> |
| status | The status. Type: String Valid values: <code>passed</code> <code>failed</code> <code>insufficient-data</code> |
| impairedSince | The time when a status check failed. For an instance that was launched and impaired, this is the time when the instance was launched. Type: DateTime |

InstanceStatusType

The InstanceStateType data type.

Ancestors

- [InstanceStatusItemType](#) (p. 436)

Relevant Operations

- [DescribeInstanceStatus](#) (p. 197)

Contents

The following table describes the elements contained in InstanceStatusType.

| Name | Description |
|---------|---|
| status | The status. Type: String Valid values: ok impaired insufficient-data not-applicable |
| details | Information about system instance health or application instance health. Type: InstanceStatusDetailsSetType (p. 438) |

InstanceMonitoringStateType

The InstanceMonitoringStateType data type.

Ancestors

- [MonitorInstancesResponseSetItemType](#) (p. 450)
- [RunningInstancesItemType](#) (p. 467)

Relevant Operations

- MonitorInstances
- UnmonitorInstances
- DescribeInstances
- RunInstances

Contents

The following table describes the elements contained in InstanceMonitoringStateType.

| Name | Description |
|-------|---|
| state | The state of monitoring for the instance. The <code>disabled</code> state means that Detailed Monitoring is disabled for the instance. The <code>enabled</code> state means that Detailed Monitoring is enabled for the instance. The <code>pending</code> state means that the instance is launching or that you recently enabled Detailed Monitoring for the instance. Type: String Valid values: <code>disabled</code> <code>enabled</code> <code>pending</code> |

InstanceNetworkInterfaceSetItemRequestType

The InstanceNetworkInterfaceSetItemRequestType data type.

Contents

The following table describes the elements contained in InstanceNetworkInterfaceSetItemRequestType.

| Name | Description |
|--------------------------------|---|
| networkInterfaceId | The ID of the network interface. Type: String |
| deviceIndex | Required. The index of the device on the instance for the network interface attachment. Type: Integer |
| subnetId | The ID of the subnet associated with the network string. Type: String |
| description | The description of the network interface. Type: String |
| privateIpAddress | The private IP address of the network interface. Type: String |
| groupSet | The group IDs for use by the network interface. Type: SecurityGroupIdSetItemType (p. 470) |
| deleteOnTermination | If set to <code>true</code> , the interface is deleted when the instance is terminated. Type: Boolean |
| privateIpAddressesSet | The list of IP addresses to assign to the network interface. Type: PrivateIpAddressesSetItemRequestType (p. 460) |
| secondaryPrivateIpAddressCount | The number of secondary private IP addresses. You cannot specify this option with <code>privateIpAddressesSet</code> . Type: Integer |

InstanceNetworkInterfaceSetType

The InstanceNetworkInterfaceSetType data type.

Ancestors

- [InstanceNetworkInterfaceSetType](#) (p. 441)

Relevant Operations

- DescribeInstances
- RunInstances

Contents

The following table describes the elements contained in InstanceNetworkInterfaceSetType.

| Name | Description |
|--------------------|---|
| networkInterfaceId | The ID of the network interface. Type: String |
| subnetId | The ID of the subnet. Type: String |
| vpcId | The ID of the VPC. Type: String |
| description | The description. Type: String |
| ownerId | The ID of the customer who created the network interface. Type: String |
| status | The network interface's status (<code>available</code> or <code>in-use</code>). Type: String |
| privateIpAddress | The IP address of the network interface within the subnet. Type: String |
| privateDnsName | The private DNS name. Type: String |
| sourceDestCheck | Indicates whether to validate network traffic to or from this network interface. Type: Boolean |
| groupSet.item | A security group. Type: GroupItemType (p. 428) |

| Name | Description |
|-----------------------|--|
| attachment | The network interface attachment. Type: NetworkInterfaceAttachmentType (p. 455) |
| association | The association information for an Elastic IP associated with the network interface. Type: NetworkInterfaceAssociationType (p. 453) |
| privateIpAddressesSet | The private IP addresses associated with the network interface. Type: InstancePrivateIpAddressesSetType |

InstanceStateChangeType

The InstanceStateChangeType data type.

Ancestors

- [InstanceStateChangeSetType](#)

Relevant Operations

- [StartInstances](#)
- [StopInstances](#)
- [TerminateInstances](#)

Contents

The following table describes the elements contained in InstanceStateChangeType.

| Name | Description |
|---------------|---|
| instanceId | The instance ID. Type: String |
| currentState | The current state of the instance. Type: InstanceStateType (p. 442) |
| previousState | The previous state of the instance. Type: InstanceStateType (p. 442) |

InstanceStateType

The InstanceStateType data type.

Ancestors

- [InstanceStateChangeType](#) (p. 442)
- [InstanceStateChangeType](#) (p. 442)
- [RunningInstancesItemType](#) (p. 467)

Relevant Operations

- [StartInstances](#)
- [StopInstances](#)
- [TerminateInstances](#)
- [DescribeInstances](#)
- [DescribeInstanceStatus](#)
- [RunInstances](#)

Contents

The following table describes the elements contained in InstanceStateType.

| Name | Description |
|------|---|
| code | <p>The low byte represents the state. The high byte is an opaque internal value and should be ignored.</p> <p>Type: Integer (16-bit unsigned)</p> <p>Valid values: 0 (pending) 16 (running) 32 (shutting-down) 48 (terminated) 64 (stopping) 80 (stopped)</p> <p>Note</p> <p>A code of 272 typically indicates a problem with the host running the instance. A reboot might resolve the problem (be aware that for a Windows system, a reboot is a hard reboot that might result in data corruption). If a reboot doesn't work, post a message to the EC2 forums with the instance ID. Typically someone from the EC2 team can get your instance back to a normal state.</p> |
| name | <p>The current state of the instance.</p> <p>Type: String</p> <p>Valid values: pending running shutting-down terminated stopping stopped</p> |

InternetGatewayAttachmentType

The InternetGatewayAttachmentType data type.

Ancestors

- InternetGatewayAttachmentSetType
- AttachInternetGatewayResponse

Relevant Operations

- CreateInternetGateway
- DescribeInternetGateways
- AttachInternetGateway

Contents

The following table describes the elements contained in InternetGatewayAttachmentType.

| Name | Description |
|-------|---|
| vpcId | The ID of the VPC the Internet gateway is attached to. Type: String |
| state | The current state of the attachment. Type: String Valid values: <code>attaching</code> <code>attached</code> <code>detaching</code> <code>detached</code> |

InternetGatewayType

The VpnGatewayType data type.

Ancestors

- CreateInternetGatewayResponse
- InternetGatewaySetType

Relevant Operations

- CreateInternetGateway
- DescribeInternetGateways

Contents

The following table describes the elements contained in InternetGatewayType.

| Name | Description |
|-------------------|--|
| internetGatewayId | The ID of the Internet gateway. Type: String |
| attachmentSet | Any VPCs attached to the Internet gateway, each one wrapped in an <code>item</code> element. Type: InternetGatewayAttachmentType (p. 443) |
| tagSet | Any tags assigned to the resource, each one wrapped in an <code>item</code> element. Type: ResourceTagSetItemType (p. 464) |

IpPermissionType

The IpPermissionType data type.

Ancestors

- IpPermissionSetType

Relevant Operations

- AuthorizeSecurityGroupIngress
- RevokeSecurityGroupIngress
- DescribeSecurityGroups

Contents

The following table describes the elements contained in IpPermissionType.

| Name | Description |
|------------|---|
| ipProtocol | The protocol. When you call <code>DescribeSecurityGroups</code> , the protocol value returned is the number. Exception: For TCP, UDP, and ICMP, the value returned is the name (e.g., <code>tcp</code> , <code>udp</code> , or <code>icmp</code>). For a list of protocol numbers, see Protocol Numbers . Type: String |
| fromPort | The start of port range for the TCP and UDP protocols, or an ICMP type number. A value of -1 indicates all ICMP types. Type: Integer |
| toPort | The end of port range for the TCP and UDP protocols, or an ICMP code. A value of -1 indicates all ICMP codes for the given ICMP type. Type: Integer |

| Name | Description |
|----------|--|
| groups | A list of security group and AWS account ID pairs. Each pair is wrapped in an <code>item</code> element. Type: UserIdGroupPairType (p. 478) |
| ipRanges | A list of IP ranges. Each range is wrapped in an <code>item</code> element. Type: IpRangeItem (p. 446) |

IpRangeItem

The `IpRangeItem` data type.

Ancestors

- `IpRangeSetType`

Relevant Operations

- `AuthorizeSecurityGroupIngress`
- `RevokeSecurityGroupIngress`
- `DescribeSecurityGroups`

Contents

The following table describes the elements contained in `IpRangeItem`.

| Name | Description |
|---------------------|---|
| <code>cidrIp</code> | The CIDR range. Cannot be used when specifying a source security group. Type: String |

LaunchPermissionItem

The `LaunchPermissionItem` data type.

Ancestors

- `LaunchPermissionListType`

Relevant Operations

- `DescribeImageAttribute`

- [ModifyImageAttribute](#)

Contents

The following table describes the elements contained in `LaunchPermissionItemType`.

| Name | Description |
|---------------------|---|
| <code>group</code> | The name of the group. Type: String Valid Value: <code>all</code> |
| <code>userId</code> | The AWS account ID. Type: String |

LaunchSpecificationRequestType

The `LaunchSpecificationRequestType` data type.

Ancestors

- [RequestSpotInstancesType](#)

Relevant Operations

- [RequestSpotInstances](#)

Contents

The following table describes the elements contained in `LaunchSpecificationRequestType`.

| Name | Description |
|-----------------------------|---|
| <code>imageId</code> | The AMI ID. Type: String |
| <code>keyName</code> | The name of the key pair. Type: String |
| <code>groupSet</code> | A list of security groups. Each group is wrapped in an <code>item</code> element. Type: GroupItemType (p. 428) |
| <code>userData</code> | Base64-encoded MIME user data made available to the instance(s) in the reservation. Type: UserDataTypes (p. 478) |
| <code>addressingType</code> | Deprecated. Type: String |

| Name | Description |
|----------------------------------|--|
| <code>instanceType</code> | The instance type. Type: String |
| <code>placement</code> | The placement information for the instance. Type: PlacementRequestType (p. 458) |
| <code>kernelId</code> | The ID of the kernel to select. Type: String |
| <code>ramdiskId</code> | The ID of the RAM disk to select. Some kernels require additional drivers at launch. Check the kernel requirements for information on whether you need to specify a RAM disk and search for the kernel ID. Type: String |
| <code>blockDeviceMapping</code> | Any block device mapping entries for the instance. Each entry is wrapped in an <code>item</code> element. Type: BlockDeviceMappingItemType (p. 406) |
| <code>monitoring</code> | The monitoring information for the instance. Type: MonitoringInstanceType (p. 449) |
| <code>subnetId</code> | The Amazon VPC subnet ID within which to launch the instance(s) for Amazon Virtual Private Cloud. Type: String |
| <code>networkInterfaceSet</code> | The network interfaces associated with the instance. Type: InstanceNetworkInterfaceSetItemType (p. 440) |
| <code>iamInstanceProfile</code> | The IAM Instance Profile (IIP) associated with the instance. Type: IamInstanceProfileRequestType (p. 429) |

LaunchSpecificationResponseType

The LaunchSpecificationResponseType data type.

Ancestors

- [SpotInstanceRequestSetItemType](#) (p. 472)

Relevant Operations

- `DescribeSpotInstanceRequests`

Contents

The following table describes the elements contained in LaunchSpecificationResponseType.

| Name | Description |
|----------------------------------|--|
| <code>imageId</code> | The AMI ID. Type: String |
| <code>keyName</code> | The name of the key pair. Type: String |
| <code>groupSet</code> | A list of security groups. Each group is wrapped in an <code>item</code> element. Type: GroupItemType (p. 428) |
| <code>addressingType</code> | Deprecated. Type: String |
| <code>instanceType</code> | The instance type. Type: String |
| <code>placement</code> | The placement information for the instance. Type: PlacementRequestType (p. 458) |
| <code>kernelId</code> | The ID of the kernel to select. Type: String |
| <code>ramdiskId</code> | The ID of the RAM disk to select. Some kernels require additional drivers at launch. Check the kernel requirements for information on whether you need to specify a RAM disk and search for the kernel ID. Type: String |
| <code>blockDeviceMapping</code> | Any block device mapping entries for the instance. Each entry is wrapped in an <code>item</code> element. Type: BlockDeviceMappingItemType (p. 406) |
| <code>monitoring</code> | The monitoring information for the instance. Type: MonitoringInstanceType (p. 449) |
| <code>subnetId</code> | The Amazon VPC subnet ID within which to launch the instance(s) for Amazon Virtual Private Cloud. Type: String |
| <code>networkInterfaceSet</code> | The network interfaces for the instance. Type: InstanceNetworkInterfaceSetItemRequestType (p. 440) |
| <code>iamInstanceProfile</code> | The IAM Instance Profile (IIP) associated with the instance. Type: IamInstanceProfileRequestType (p. 429) |

MonitoringInstanceType

The MonitoringInstanceType data type.

Ancestors

- [LaunchSpecificationRequestType](#) (p. 447)
- [LaunchSpecificationResponseType](#) (p. 448)
- [RunInstancesType](#)

Relevant Operations

- [RequestSpotInstances](#)
- [DescribeSpotInstanceRequests](#)
- [RequestSpotInstances](#)
- [RunInstances](#)

Contents

The following table describes the elements contained in `MonitoringInstanceType`.

| Name | Description |
|---------|--|
| enabled | Specifies whether monitoring is enabled for the instance. Type: Boolean |

MonitorInstancesResponseSetItemType

The `MonitorInstancesResponseSetItemType` data type.

Ancestors

- [MonitorInstancesResponseType](#)

Relevant Operations

- [MonitorInstances](#)
- [UnmonitorInstances](#)

Contents

The following table describes the elements contained in `MonitorInstancesResponseSetItemType`.

| Name | Description |
|------------|----------------------------------|
| instanceId | The instance ID. Type: String |

| Name | Description |
|------------|---|
| monitoring | The monitoring information. Type: InstanceMonitoringStateType (p. 439) |

NetworkAclEntryType

The NetworkAclEntryType data type.

Ancestors

- NetworkAclEntrySetType

Relevant Operations

- CreateNetworkAcl
- DescribeNetworkAcls

Contents

The following table describes the elements contained in NetworkAclEntryType.

| Name | Description |
|--------------|---|
| ruleNumber | The rule number for the entry. ACL entries are processed in ascending order by rule number. Type: Integer |
| protocol | The protocol. A value of -1 means all protocols. Type: Integer Valid values: Any protocol number (see Protocol Numbers). |
| ruleAction | Specifies whether to allow or deny the traffic that matches the rule. Type: String |
| egress | Indicates an egress rule (rule is applied to traffic leaving the subnet). Value of <code>true</code> indicates egress. Type: Boolean |
| cidrBlock | The network range to allow or deny, in CIDR notation. Type: String |
| icmpTypeCode | ICMP protocol: The ICMP type and code. Type: IcmpTypeCodeType (p. 430) |
| portRange | TCP or UDP protocols: The range of ports the rule applies to. Type: PortRangeType (p. 459) |

NetworkACLType

The NetworkACLType data type.

Ancestors

- CreateNetworkAclResponse
- NetworkAclSetType

Relevant Operations

- CreateNetworkAcl
- DescribeNetworkAcls

Contents

The following table describes the elements contained in NetworkACLType.

| Name | Description |
|----------------|--|
| networkAclId | The ID of the network ACL. Type: String |
| vpcId | The ID of the VPC the network ACL is in. Type: String |
| default | Specifies whether this is the default network ACL in the VPC. Type: Boolean Valid values: <code>true</code> <code>false</code> |
| entrySet | A list of entries (rules) in the network ACL. Each entry is wrapped in an <code>item</code> element. Type: NetworkAclEntryType (p. 451) |
| associationSet | A list of associations between the network ACL and one or more subnets. Each association is wrapped in an <code>item</code> element. Type: NetworkAclAssociationType (p. 452) |
| tagSet | Any tags assigned to the resource, each one wrapped in an <code>item</code> element. Type: ResourceTagSetItemType (p. 464) |

NetworkAclAssociationType

The NetworkAclAssociationType data type.

Ancestors

- NetworkAclAssociationSetType

Relevant Operations

- CreateNetworkAcl
- DescribeNetworkAcls

Contents

The following table describes the elements contained in NetworkAclAssociationType.

| Name | Description |
|-------------------------|--|
| networkAclAssociationId | An identifier representing the association between a network ACL and a subnet. Type: String |
| networkAclId | The ID of the network ACL in the association. Type: String |
| subnetId | The ID of the subnet in the association. Type: String |

NetworkInterfaceAssociationType

The NetworkInterfaceAssociationType data type.

Ancestors

- InstanceNetworkInterfaceSetItemType

Relevant Operations

- RunInstances
- DescribeInstances

Contents

The following table describes the elements contained in NetworkInterfaceAssociationType.

| Name | Description |
|--------------|---|
| attachmentID | The ID of the network interface attachment. Type: String |
| instanceID | The ID of the instance attached to the network interface. Type: String |
| publicIp | The address of the Elastic IP address bound to the network interface. Type: String |
| ipOwnerId | The ID of the Elastic IP address owner. Type: String |

NetworkInterfaceSet

The NetworkInterfaceSet data type.

Ancestors

- InstanceNetworkInterfaceSetType

Relevant Operations

- DescribeInstances
- DescribeNetworkInterfaces
- RequestSpotInstances

Contents

The following table describes the elements contained in NetworkInterfaceSet.

| Name | Description |
|--------------------|---|
| networkInterfaceId | The ID of the network interface. Type: String |
| subnetId | The ID of the subnet. Type: String |
| vpcId | The ID of the VPC. Type: String |
| description | A description. Type: String |
| ownerId | The ID of the customer who created the interface. Type: String |

| Name | Description |
|-----------------------|--|
| status | The status (<code>available</code> or <code>in-use</code>). Type: String |
| privateIpAddress | The IP address of the interface within the subnet. Type: String |
| privateDnsName | The private DNS name. Type: String |
| sourceDestCheck | Specifies whether traffic to or from the instance is validated. Type: Boolean |
| groupSet | A security group. Type: GroupItemType (p. 428) |
| attachment | The network interface attachment. Type: NetworkInterfaceAttachmentType (p. 455) |
| association | The association information for an Elastic IP associated with the network interface. Type: NetworkInterfaceAssociationType (p. 453) |
| privateIpAddressesSet | The list of IP addresses assigned to the network interface. Type: NetworkInterfacePrivateIpAddressesSetItemType (p. 456) |

NetworkInterfaceAttachmentType

The `NetworkInterfaceType` data type.

Relevant Operations

- `DescribeNetworkInterfaces`

Contents

The following table describes the elements contained in `NetworkInterfaceAttachmentType`.

| Name | Description |
|--------------|---|
| attachmentID | The ID of the network interface attachment. Type: String |
| instanceID | The ID of the instance. Type: String |

NetworkInterfacePrivateAddressesSetItemType

The NetworkInterfacePrivateAddressesType data type.

Relevant Operations

- DescribeNetworkInterfaces

Contents

The following table describes the elements contained in NetworkInterfacePrivateAddressesSetItemType.

| Name | Description |
|------------------|--|
| privateIpAddress | The private IP address of the network interface Type: String |
| primary | Indicates whether this IP address is the primary private IP address of the network interface. Type: Boolean |
| association | The association information for an Elastic IP associated with the network interface. Type: NetworkInterfaceAssociationType (p. 453) |

NetworkInterfaceType

The NetworkInterfaceType data type.

Relevant Operations

- DescribeNetworkInterfaces

Contents

The following table describes the elements contained in NetworkInterfaceType.

| Name | Description |
|--------------------|--|
| networkInterfaceId | The ID of the network interface. Type: String |
| subnetId | The ID of the subnet. Type: String |
| vpcId | The ID of the VPC. Type: String |

| Name | Description |
|-----------------------|--|
| availabilityZone | The Availability Zone. Type: String |
| description | A description. Type: String |
| ownerId | The ID of the customer who created the interface. Type: String |
| requesterId | The ID of the entity that launched the instance on your behalf (for example, AWS Management Console or Auto Scaling) Type: String |
| requesterManaged | Type: String |
| status | The status (available or in-use). Type: String |
| macAddress | Type: String |
| privateIpAddress | The IP address of the interface within the subnet. Type: String |
| privateDnsName | The private DNS name. Type: String |
| sourceDestCheck | Specifies whether traffic to or from the instance is validated. Type: Boolean |
| groupSet | Type: GroupSetType |
| attachment | The network interface attachment. Type: NetworkInterfaceAttachmentType (p. 455) |
| association | The association information for an Elastic IP associated with the network interface. Type: NetworkInterfaceAssociationType (p. 453) |
| tagSet | Type: ResourceTagSetType |
| privateIpAddressesSet | The private IP addresses associated with the network interface. Items are returned in a set. Type: NetworkInterfacePrivateIpAddressesSetItemType |

PlacementGroupInfoType

Relevant Operations

- DescribePlacementGroups

Contents

The following table describes the elements contained in PlacementGroupInfoType.

| Name | Description |
|-----------|--|
| groupName | The name of the placement group. Type: String |
| strategy | The placement strategy. Type: String Valid values: <code>cluster</code> |
| state | The status of the placement group. Type: String Valid values: <code>pending</code> <code>available</code> <code>deleting</code> <code>deleted</code> |

PlacementRequestType

The PlacementRequestType data type.

Ancestors

- [LaunchSpecificationRequestType](#) (p. 447)
- [LaunchSpecificationResponseType](#) (p. 448)
- [RunInstancesType](#)

Relevant Operations

- [RequestSpotInstances](#)
- [DescribeSpotInstanceRequests](#)
- [RequestSpotInstances](#)
- [RunInstances](#)

Contents

The following table describes the elements contained in PlacementRequestType.

| Name | Description |
|------------------|---|
| availabilityZone | The Availability Zone for launching the instance. Type: String |
| groupName | The name of a placement group for the instance. Type: String |

PlacementResponseType

The PlacementResponseType data type.

Ancestors

- [RunningInstancesItemType](#) (p. 467)

Relevant Operations

- DescribeInstances
- RunInstances

Contents

The following table describes the elements contained in PlacementResponseType.

| Name | Description |
|------------------|--|
| availabilityZone | The Availability Zone of the instance. Type: String |
| groupName | The name of the placement group the instance is in (for cluster compute instances). Type: String |
| tenancy | The tenancy of the instance (if the instance is running within a VPC). An instance with a tenancy of dedicated runs on single-tenant hardware. Type: String |

PortRangeType

The PortRangeType data type.

Ancestors

- NetworkAclEntryType

Relevant Operations

- DescribeNetworkAcls

Contents

The following table describes the elements contained in PortRangeType.

| Name | Description |
|------|---|
| from | The first port in the range. Type: Integer |
| to | The last port in the range. Type: Integer |

PrivateIpAddressesSetItemRequestType

The PrivateIpAddressesSetItemRequest data type.

Relevant Operations

- AssignPrivateIpAddresses
- UnassignPrivateIpAddresses

Contents

The following table describes the elements contained in PrivateIpAddressesSetItemRequest.

| Name | Description |
|-----------------------|--|
| privateIpAddressesSet | The list of private IP addresses. Type: AssignPrivateIpAddressesSetItemRequestType (p. 402) |
| primary | Indicates whether the private IP address is the primary private IP address. Type: Boolean |

ProductCodeItemType

The ProductCodeItemType data type.

Ancestors

- ProductCodeListType

Relevant Operations

- DescribeImageAttribute

- `ModifyImageAttribute`

Contents

The following table describes the elements contained in `ProductCodeItemType`.

| Name | Description |
|--------------------------|-----------------------------------|
| <code>productCode</code> | The product code. Type: String |

ProductCodesSetItemType

The `ProductCodesSetItemType` data type.

Ancestors

- `ProductCodesSetType`

Relevant Operations

- `DescribeImages`
- `DescribeImageAttribute`
- `DescribeInstances`
- `DescribeInstanceAttribute`
- `DescribeSnapshotAttribute`
- `DescribeVolumeAttribute`
- `RunInstances`

Contents

The following table describes the elements contained in `ProductCodesSetItemType`.

| Name | Description |
|--------------------------|---|
| <code>productCode</code> | The product code. Type: String |
| <code>type</code> | The type of product code. Type: String Valid values: <code>devpay</code> <code>marketplace</code> |

ProductDescriptionSetItemType

The ProductDescriptionSetItemType data type.

Ancestors

- ProductDescriptionSetType

Relevant Operations

- DescribeSpotPriceHistory

Contents

The following table describes the elements contained in ProductDescriptionSetItemType.

| Name | Description |
|--------------------|--|
| productDescription | The description of the AMI. Type: String Valid values: Linux/UNIX SUSE Linux Windows |

RecurringChargesSetItemType

The RecurringChargesSetItemType data type.

Relevant Operations

- DescribeReservedInstances
- DescribeReservedInstanceOfferings

Contents

The following table describes the elements contained in RecurringChargesSetItemType.

| Name | Description |
|-----------|---|
| frequency | The frequency of the recurring charge. Type: String Valid value: Hourly |
| amount | The amount of the recurring charge. Type: Double |

RegionItemType

The RegionItemType data type.

Ancestors

- RegionSetType

Relevant Operations

- DescribeRegions

Contents

The following table describes the elements contained in RegionItemType.

| Name | Description |
|----------------|--|
| regionName | The name of the Region. Type: String |
| regionEndpoint | The Region service endpoint. Type: String |

ReservationInfoType

The ReservationInfoType data type.

Ancestors

- ReservationSetType

Relevant Operations

- DescribeInstances

Contents

The following table describes the elements contained in ReservationInfoType.

| Name | Description |
|---------------|--|
| reservationId | The ID of the reservation. Type: String |

| Name | Description |
|--------------|---|
| ownerId | The ID of the AWS account that owns the reservation. Type: String |
| groupSet | A list of security groups. Each group is wrapped in an <code>item</code> element. Type: GroupItemType (p. 428) |
| instancesSet | A list of instances. Each instance is wrapped in an <code>item</code> element. Type: RunningInstancesItemType (p. 467) |
| requesterId | The ID of the requester that launched the instances on your behalf (for example, AWS Management Console or Auto Scaling). Type: String |

ResourceTagSetItemType

The ResourceTagSetItemType data type.

Relevant Operations

- DescribeImages
- DescribeInstances
- DescribeVolumes
- DescribeSnapshots
- DescribeSpotInstanceRequests

Contents

The following table describes the elements contained in ResourceTagSetItemType.

| Name | Description |
|-------|--------------------------------|
| key | The tag key. Type: String |
| value | The tag value. Type: String |

RouteTableAssociationType

The RouteTableAssociationType data type.

Ancestors

- RouteTableAssociationSetType

Relevant Operations

- CreateRouteTable
- DescribeRouteTables

Contents

The following table describes the elements contained in NetworkAclAssociationType.

| Name | Description |
|-------------------------|--|
| routeTableAssociationId | An identifier representing the association between a route table and a subnet. Type: String |
| routeTableId | The ID of the route table in the association. Type: String |
| subnetId | The ID of the subnet in the association. Type: String |
| main | Whether this is the main route table. Type: Boolean |

RouteTableType

The RouteTableType data type.

Ancestors

- CreateRouteTableResponse
- RouteTableSetType

Relevant Operations

- CreateRouteTable
- DescribeRouteTables

Contents

The following table describes the elements contained in RouteTableType.

| Name | Description |
|--------------|---------------------------------------|
| routeTableId | The route table's ID. Type: String |

| Name | Description |
|-----------------------------|--|
| <code>vpcId</code> | The ID of the VPC the route table is in. Type: String |
| <code>routeSet</code> | A list of routes in the route table. Each route is wrapped in an <code>item</code> element. Type: RouteType (p. 466) |
| <code>associationSet</code> | A list of associations between the route table and one or more subnets. Each association is wrapped in an <code>item</code> element. Type: RouteTableAssociationType (p. 464) |
| <code>tagSet</code> | Any tags assigned to the resource, each one wrapped in an <code>item</code> element. Type: ResourceTagSetItemType (p. 464) |

RouteType

The RouteType data type.

Ancestors

- [RouteSetType](#)

Relevant Operations

- [CreateRouteTable](#)
- [DescribeRouteTables](#)

Contents

The following table describes the elements contained in RouteType.

| Name | Description |
|-----------------------------------|--|
| <code>destinationCidrBlock</code> | The CIDR address block used for the destination match. For example: 0.0.0.0/0. Type: String |
| <code>gatewayId</code> | The ID of a gateway attached to your VPC. Type: String |
| <code>instanceId</code> | The ID of a NAT instance in your VPC. Type: String |
| <code>instanceOwnerId</code> | The owner of the instance. Type: String |

| Name | Description |
|---------------------------|---|
| <i>networkInterfaceId</i> | The network interface ID. Type: String |
| <i>state</i> | The state of the route. The <code>blackhole</code> state indicates that the route's target isn't available (e.g., the specified gateway isn't attached to the VPC, the specified NAT instance has been terminated, etc.). Type: String Valid values: <code>active</code> <code>blackhole</code> |

RunningInstancesItemType

The RunningInstancesItemType data type.

Ancestors

- RunningInstancesSetType

Relevant Operations

- DescribeInstances
- RunInstances

Contents

The following table describes the elements contained in RunningInstancesItemType.

| Name | Description |
|-----------------------|---|
| <i>instanceId</i> | The ID of the instance launched. Type: String |
| <i>imageId</i> | The ID of the AMI used to launch the instance. Type: String |
| <i>instanceState</i> | The current state of the instance. Type: InstanceStateType (p. 442) |
| <i>privateDnsName</i> | The private DNS name assigned to the instance. This DNS name can only be used inside the Amazon EC2 network. This element remains empty until the instance enters a running state. Type: String |
| <i>dnsName</i> | The public DNS name assigned to the instance. This DNS name is contactable from outside the Amazon EC2 network. This element remains empty until the instance enters a running state. Type: String |

| Name | Description |
|------------------|--|
| reason | The reason for the most recent state transition. This might be an empty string. Type: String |
| keyName | The key pair name, if this instance was launched with an associated key pair. Type: String |
| amiLaunchIndex | The AMI launch index, which can be used to find this instance within the launch group. Type: String |
| productCodes | The product codes attached to this instance. Each product code is wrapped in an <code>item</code> element. Type: ProductCodesSetItemType (p. 461) |
| instanceType | The instance type (for example, m1.small). Type: String |
| launchTime | The time the instance was launched. Type: DateTime |
| placement | The location where the instance launched. Type: PlacementResponseType (p. 459) |
| kernelId | The kernel associated with this instance. Type: String |
| ramdiskId | The RAM disk associated with this instance. Type: String |
| platform | The platform of the instance (e.g., Windows). Type: String |
| monitoring | The monitoring information for the instance. Type: InstanceMonitoringStateType (p. 439) |
| subnetId | The Amazon VPC subnet ID in which the instance is running. Type: String |
| vpcId | The Amazon VPC in which the instance is running. Type: String |
| privateIpAddress | The private IP address assigned to the instance. Type: String |
| ipAddress | The IP address of the instance. Type: String |

**Amazon Elastic Compute Cloud API Reference
Contents**

| Name | Description |
|------------------------------------|---|
| <code>sourceDestCheck</code> | Specifies whether to enable a Network Address Translation (NAT) instance in a VPC to perform NAT. This controls whether source/destination checking is enabled on the instance. A value of <code>true</code> means checking is enabled, and <code>false</code> means checking is disabled. The value must be <code>false</code> for the instance to perform NAT. For more information, go to NAT Instances in the <i>Amazon Virtual Private Cloud User Guide</i> . Type: Boolean |
| <code>groupSet</code> | A list of VPC security groups the instance is in. Each group is wrapped in an <code>item</code> element. Type: GroupItemType (p. 428) |
| <code>stateReason</code> | The reason for the most recent state transition. See StateReasonType (p. 475) for a listing of supported state change codes. Type: StateReasonType (p. 475) |
| <code>architecture</code> | The architecture of the image. Type: String Valid values: <code>i386</code> <code>x86_64</code> |
| <code>rootDeviceType</code> | The root device type used by the AMI. The AMI can use an Amazon EBS or instance store root device. Type: String Valid values: <code>ebs</code> <code>instance-store</code> |
| <code>rootDeviceName</code> | The root device name (e.g., <code>/dev/sda1</code>). Type: String |
| <code>blockDeviceMapping</code> | Any block device mapping entries for the instance, each one wrapped in an <code>item</code> element. Type: InstanceBlockDeviceMappingResponseItemType (p. 434) |
| <code>instanceLifecycle</code> | Specifies whether this is a Spot Instance. Type: String Valid values: <code>spot</code> blank (no value) |
| <code>spotInstanceRequestId</code> | The ID of the Spot Instance request. Type: String |
| <code>virtualizationType</code> | The instance's virtualization type. Type: String Valid values: <code>paravirtual</code> <code>hvm</code> |
| <code>clientToken</code> | The idempotency token you provided when you launched the instance. Type: String |
| <code>tagSet</code> | Any tags assigned to the resource, each one wrapped in an <code>item</code> element. Type: ResourceTagSetItemType (p. 464) |

| Name | Description |
|---------------------|---|
| hypervisor | The instance's hypervisor type. Type: String Valid values: ovm xen |
| networkInterfaceSet | The network interfaces for the instance. Type: InstanceNetworkInterfaceSetType (p. 441) |
| iamInstanceProfile | The IAM Instance Profile (IIP) associated with the instance. Type: IamInstanceProfileResponseType (p. 429) |

SecurityGroupIdSetItemType

The SecurityGroupIdSetItemType data type.

Ancestors

- [LaunchSpecificationResponseType](#)
- [LaunchSpecificationRequestType](#)
- [InstanceNetworkInterfaceSetItemRequestType](#)

Relevant Operations

- [CreateNetworkInterface](#)
- [ModifyNetworkInterfaceAttribute](#)
- [ModifyInstanceAttribute](#)
- [RequestSpotInstances](#)
- [DescribeSpotInstanceRequests](#)
- [RunInstances](#)

Contents

The following table describes the elements contained in SecurityGroupItemtype.

| Name | Description |
|---------|---|
| groupId | The ID of the security group associated with the network interface. Type: String |

SecurityGroupItemtype

The SecurityGroupItemtype data type.

Ancestors

- SecurityGroupSetType

Relevant Operations

- DescribeSecurityGroups

Contents

The following table describes the elements contained in SecurityGroupItemType.

| Name | Description |
|---------------------|---|
| ownerId | The AWS account ID of the owner of the security group. Type: String |
| groupId | The ID of the security group. Type: String |
| groupName | The name of the security group. Type: String |
| groupDescription | A description of the security group. Type: String |
| vpcId | The ID of the VPC the security group is in (for VPC security groups). Type: String |
| ipPermissions | A list of inbound rules associated with the security group. Each permission is wrapped in an <code>item</code> element. Type: IpPermissionType (p. 445) |
| ipPermissionsEgress | A list of outbound rules associated with the security group (for VPC security groups). Each permission is wrapped in an <code>item</code> element. Type: IpPermissionType (p. 445) |
| tagSet | Any tags assigned to the resource, each one wrapped in an <code>item</code> element. Type: ResourceTagSetItemType (p. 464) |

SpotDatafeedSubscriptionType

The SpotDatafeedSubscriptionType data type.

Ancestors

- CreateSpotDatafeedSubscriptionResponseType

- DescribeSpotDatafeedSubscriptionResponseType

Relevant Operations

- CreateSpotDatafeedSubscription
- DescribeSpotDatafeedSubscription

Contents

The following table describes the elements contained in SpotDatafeedSubscriptionType.

| Name | Description |
|---------|--|
| ownerId | The AWS account ID of the account. Type: String |
| bucket | The Amazon S3 bucket where the Spot Instance datafeed is located. Type: String |
| prefix | The prefix that is prepended to datafeed files. Type: String |
| state | The state of the Spot Instance datafeed subscription. Type: String Valid values: <code>Active</code> <code>Inactive</code> |
| fault | The fault codes for the Spot Instance request, if any. Type: SpotInstanceStateFaultType (p. 474) |

SpotInstanceRequestSetItemType

The SpotInstanceRequestSetItemType data type.

Ancestors

- SpotInstanceRequestSetType

Relevant Operations

- DescribeSpotInstanceRequests
- RequestSpotInstances

Contents

The following table describes the elements contained in SpotInstanceRequestSetItemType.

**Amazon Elastic Compute Cloud API Reference
Contents**

| Name | Description |
|--------------------------|---|
| spotInstanceRequestId | The ID of the Spot Instance request. Type: String |
| spotPrice | The maximum hourly price for any Spot Instance launched to fulfill the request. Type: String |
| type | The Spot Instance request type. Type: String Valid values: <code>one-time</code> <code>persistent</code> |
| state | The state of the Spot Instance request. Type: String Valid values: <code>open</code> <code>closed</code> <code>cancelled</code> <code>failed</code> |
| fault | The fault codes for the Spot Instance request, if any. Type: SpotInstanceStateFaultType (p. 474) |
| validFrom | The start date of the request. If this is a one-time request, the request becomes active at this date and time and remains active until all instances launch, the request expires, or the request is canceled. If the request is persistent, the request becomes active at this date and time and remains active until it expires or is canceled. Type: DateTime |
| validUntil | The end date of the request. If this is a one-time request, the request remains active until all instances launch, the request is canceled, or this date is reached. If the request is persistent, it remains active until it is canceled or this date is reached. Type: DateTime |
| launchGroup | The instance launch group. Launch groups are Spot Instances that launch together and terminate together. Type: String |
| availabilityZoneGroup | The Availability Zone group. If you specify the same Availability Zone group for all Spot Instance requests, all Spot Instances are launched in the same Availability Zone. Type: String |
| launchedAvailabilityZone | The Availability Zone in which the bid is launched. Type: String |
| launchSpecification | Additional information for launching instances. Type: LaunchSpecificationResponseType (p. 448) |
| instanceId | The instance ID, if an instance has been launched to fulfill the Spot Instance request. Type: String |
| createTime | The time stamp when the Spot Instance request was created. Type: DateTime |

| Name | Description |
|--------------------|---|
| productDescription | The product description associated with the Spot Instance. Type: String |
| tagSet | Any tags assigned to the resource, each one wrapped in an <code>item</code> element. Type: ResourceTagSetItemType (p. 464) |

SpotInstanceStateFaultType

The SpotInstanceStateFaultType data type.

Ancestors

- [SpotDatafeedSubscriptionType](#) (p. 471)
- [SpotInstanceRequestSetItemType](#) (p. 472)

Relevant Operations

- [CreateSpotDatafeedSubscription](#)
- [DescribeSpotDatafeedSubscription](#)
- [DescribeSpotInstanceRequests](#)
- [RequestSpotInstances](#)

Contents

The following table describes the elements contained in SpotInstanceStateFaultType.

| Name | Description |
|---------|---|
| code | The reason code for the Spot Instance state change. Type: String |
| message | The message for the Spot Instance state change. Type: String |

SpotPriceHistorySetItemType

The SpotPriceHistorySetItemType data type.

Ancestors

- [SpotPriceHistorySetType](#)

Relevant Operations

- [DescribeSpotPriceHistory](#)

Contents

The following table describes the elements contained in `SpotPriceHistorySetItemType`.

| Name | Description |
|---------------------------------|---|
| <code>instanceType</code> | The instance type. Type: String |
| <code>productDescription</code> | A general description of the AMI. Type: String Valid values: <code>Linux/UNIX SUSE Linux Windows</code> |
| <code>spotPrice</code> | The maximum price you will pay to launch one or more Spot Instances. Type: String |
| <code>timestamp</code> | The date and time the request was created. Type: DateTime |
| <code>availabilityZone</code> | The Availability Zone. Type: String |

StateReasonType

The `StateReasonType` data type.

Ancestors

- [DescribeImagesResponseItemType](#) (p. 414)
- [RunningInstancesItemType](#) (p. 467)

Relevant Operations

- [DescribeImages](#)
- [DescribeInstances](#)
- [RunInstances](#)

Contents

The following table describes the elements contained in `StateReasonType`.

| Name | Description |
|---------|--|
| code | The reason code for the state change. See the following table for a list of codes. Type: String |
| message | The message for the state change. Type: String |

The following table lists the currently supported state reason codes.

| Code | Description |
|--|---|
| <code>Server.SpotInstanceTermination</code> | A Spot Instance was terminated due to an increase in the market price. |
| <code>Server.InternalError</code> | An internal error occurred during instance launch, resulting in termination. |
| <code>Server.InsufficientInstanceCapacity</code> | There was insufficient instance capacity to satisfy the launch request. |
| <code>Client.InternalError</code> | A client error caused the instance to terminate on launch. |
| <code>Client.InstanceInitiatedShutdown</code> | The instance initiated shutdown by a shutdown -h command issued from inside the instance. |
| <code>Client.UserInitiatedShutdown</code> | The instance was shutdown by a user via an API call. |
| <code>Client.VolumeLimitExceeded</code> | The volume limit was exceeded. |
| <code>Client.InvalidSnapshot.NotFound</code> | The specified snapshot was not found. |

SubnetType

The SubnetType data type.

Ancestors

- CreateSubnetResponse
- SubnetSetType

Relevant Operations

- CreateSubnet
- DescribeSubnets

Contents

The following table describes the elements contained in SubnetType.

| Name | Description |
|-------------------------|---|
| subnetId | The ID of the subnet. Type: String |
| state | The current state of the subnet. Type: String Valid values: <code>pending</code> <code>available</code> |
| vpcId | The ID of the VPC the subnet is in. Type: String |
| cidrBlock | The CIDR block assigned to the subnet. Type: String |
| availableIpAddressCount | The number of unused IP addresses in the subnet (the IP addresses for any stopped instances are considered unavailable). Type: Integer |
| availabilityZone | The Availability Zone of the subnet. Type: String |
| tagSet | Any tags assigned to the resource, each one wrapped in an <code>item</code> element. Type: ResourceTagSetItemType (p. 464) |

TagSetItemType

The TagSetItemType data type.

Relevant Operations

- `DescribeTags`

Contents

The following table describes the elements contained in TagSetItemType.

| Name | Description |
|------------|--|
| resourceId | The ID of the resource. For example, <code>ami-1a2b3c4d</code> . Type: String |

| Name | Description |
|--------------|---|
| resourceType | The type of resource. Type: String Valid values: customer-gateway dhcp-options image instance internet-gateway network-acl reserved-instances route-table security-group snapshot spot-instances-request subnet volume vpc vpn-connection vpn-gateway |
| key | The key of the tag. Type: String |
| value | The value of the tag. Type: String |

UserDataType

The UserData type data type.

Ancestors

- [LaunchSpecificationRequestType](#) (p. 447)
- [RunInstancesType](#)

Relevant Operations

- [RequestSpotInstances](#)
- [DescribeSpotInstanceRequests](#)
- [RequestSpotInstances](#)
- [RunInstances](#)

Contents

The following table describes the elements contained in UserData type.

| Name | Description |
|------|---|
| data | The Base64-encoded MIME user data made available to the instance(s) in the reservation. Type: String |

UserGroupIdPairType

The UserGroupIdPairType data type.

Ancestors

- UserIdGroupPairSetType

Relevant Operations

- AuthorizeSecurityGroupEgress
- AuthorizeSecurityGroupIngress
- RevokeSecurityGroupEgress
- RevokeSecurityGroupIngress
- DescribeSecurityGroups

Contents

The following table describes the elements contained in UserIdGroupPairType.

| Name | Description |
|-----------|--|
| userId | The ID of an AWS account. Cannot be used when specifying a CIDR IP address range. Type: String |
| groupId | The ID of the security group in the specified AWS account. Cannot be used when specifying a CIDR IP address range. Type: String |
| groupName | The name of the security group in the specified AWS account. Cannot be used when specifying a CIDR IP address range. Type: String |

ValueType

The ValueType data type.

Ancestors

- ValueSetType

Relevant Operations

- DescribeVpcs
- DescribeSubnets
- DescribeVpnGateways
- DescribeCustomerGateways

- DescribeVpnConnections

Contents

The following table describes the elements contained in `ValueType`.

| Name | Description |
|--------------------|--------------------------------------|
| <code>value</code> | An individual value. Type: String |

VolumeStatusItemType

The `VolumeStatusItemType` data type.

Ancestors

- VolumeStatusSetType

Relevant Operation

- DescribeVolumeStatus

Contents

The following table describes the elements contained in `VolumeStatusItemType`.

| Name | Description |
|-------------------------------|--|
| <code>volumeId</code> | The volume ID. Type: String |
| <code>availabilityZone</code> | The Availability Zone of the volume. Type: String |
| <code>volumeStatus</code> | The volume status. The status of each volume is wrapped in an <code>item</code> element. Type: VolumeStatusInfoType (p. 481). |
| <code>eventSet</code> | A list of events associated with the volume. Each event is wrapped in an <code>item</code> element. Type: VolumeStatusEventItemType (p. 482). |
| <code>actionSet</code> | The details of the action. Each action detail is wrapped in an <code>item</code> element. Type: VolumeStatusActionItemType (p. 482). |

VolumeStatusInfoType

The VolumeStatusInfoType data type.

Ancestors

- VolumeStatusItemType

Relevant Operation

- DescribeVolumeStatus

Contents

The following table describes the elements contained in VolumeStatusInfoType.

| Name | Description |
|---------|---|
| status | The status of the volume. Type: String Valid values : ok impaired insufficient-data |
| details | The details of the volume status. Each volume status detail is wrapped in an <code>item</code> type. Type: VolumeStatusDetailsItemType (p. 481). |

VolumeStatusDetailsItemType

The VolumeStatusDetailsItemType data type.

Ancestors

- VolumeStatusInfoType

Relevant Operation

- DescribeVolumeStatus

Contents

The following table describes the elements contained in VolumeStatusDetailsItemType.

| Name | Description |
|--------|---|
| name | The name of the volume's status. Type: String |
| status | The intended status of the volume status. Type: String |

VolumeStatusEventItemType

The VolumeStatusEventItemType data type.

Ancestors

- VolumeStatusItemType

Relevant Operation

- DescribeVolumeStatus

Contents

The following table describes the elements contained in VolumeStatusEventItemType.

| Name | Description |
|-------------|---|
| eventType | The type of this event. Type: String |
| eventId | The ID of this event. Type: String |
| description | A description of the event. Type: String |
| notBefore | The earliest start time of the event. Type: DateTime |
| notAfter | The latest end time of the event. Type: DateTime |

VolumeStatusActionItemType

The VolumeStatusActionItemType data type.

Ancestors

- VolumeStatusItemType

Relevant Operation

- DescribeVolumeStatus

Contents

The following table describes the elements contained in VolumeStatusActionItemType.

| Name | Description |
|-------------|--|
| code | The code identifying the action. Type: String |
| eventType | The event type associated with this action. Type: String |
| eventId | The ID of the event associated with this action. Type: String |
| description | A description of the action. Type: String |

VpcType

The VpcType data type.

Ancestors

- CreateVpcResponse
- VpcSetType

Relevant Operations

- CreateVpc
- DescribeVpcs

Contents

The following table describes the elements contained in VpcType.

| Name | Description |
|-----------------|---|
| vpcId | The ID of the VPC. Type: String |
| state | The current state of the VPC. Type: String Valid values: <code>pending</code> <code>available</code> |
| cidrBlock | The CIDR block the VPC covers. Type: String |
| dhcpOptionsId | The ID of the set of DHCP options you've associated with the VPC (or "default" if the default options are associated with the VPC). Type: String |
| tagSet | Any tags assigned to the resource, each one wrapped in an <code>item</code> element. Type: ResourceTagSetItemType (p. 464) |
| instanceTenancy | The allowed tenancy of instances launched into the VPC. Type: String |

VpnConnectionType

The VpnConnectionType data type.

Ancestors

- [CreateVpnConnectionResponse](#)
- [VpnConnectionSetType](#)

Relevant Operations

- [CreateVpnConnection](#)
- [DescribeVpnConnections](#)

Contents

The following table describes the elements contained in VpnConnectionType.

| Name | Description |
|-----------------|---|
| vpnConnectionId | The ID of the VPN connection. Type: String |

| Name | Description |
|------------------------------|---|
| state | The current state of the VPN connection. Type: String Valid values: <code>pending</code> <code>available</code> <code>deleting</code> <code>deleted</code> |
| customerGatewayConfiguration | The configuration information for the VPN connection's customer gateway (in the native XML format). This element is always present in the <code>CreateVpnConnection</code> response; however, it's present in the <code>DescribeVpnConnections</code> response only if the VPN connection is in the <code>pending</code> or <code>available</code> state. Type: String |
| type | The type of VPN connection (<code>ipsec.1</code>). Type: String |
| customerGatewayId | The ID of the customer gateway at your end of the VPN connection. Type: String |
| vpnGatewayId | The ID of the virtual private gateway at the VPC end of the VPN connection. Type: String |
| tagSet | Any tags assigned to the resource, each one wrapped in an <code>item</code> element. Type: ResourceTagSetItemType (p. 464) |
| vgwTelemetry | Information about the virtual private gateway. Each gateway is wrapped in an <code>item</code> element. Type: VpnTunnelTelemetryType (p. 486) |

VpnGatewayType

The `VpnGatewayType` data type contains information about a virtual private gateway.

Ancestors

- `CreateVpnGatewayResponse`
- `VpnGatewaySetType`

Relevant Operations

- `CreateVpnGateway`
- `DescribeVpnGateways`

Contents

The following table describes the elements contained in `VpnGatewayType`.

| Name | Description |
|-------------------------------|---|
| <code>vpnGatewayId</code> | The ID of the virtual private gateway. Type: String |
| <code>state</code> | The current state of the virtual private gateway. Type: String Valid values: <code>pending</code> <code>available</code> <code>deleting</code> <code>deleted</code> |
| <code>type</code> | The type of VPN connection the virtual private gateway supports (ipsec.1). Type: String |
| <code>availabilityZone</code> | The Availability Zone where the virtual private gateway was created. Type: String |
| <code>attachments</code> | Any VPCs attached to the virtual private gateway, each one wrapped in an <code>item</code> element. Type: AttachmentType (p. 404) |
| <code>tagSet</code> | Any tags assigned to the resource, each one wrapped in an <code>item</code> element. Type: ResourceTagSetItemType (p. 464) |

VpnTunnelTelemetryType

The `VpnTunnelTelemetryType` data type.

Ancestors

- `VgwTelemetryType`

Relevant Operations

- `CreateVpnConnection`
- `DescribeVpnConnections`

Contents

The following table describes the elements contained in `VpnTunnelTelemetryType`.

| Name | Description |
|-------------------------------|--|
| <code>outsideIpAddress</code> | The Internet-routable IP address of the virtual private gateway's outside interface. Type: String |

**Amazon Elastic Compute Cloud API Reference
Contents**

| Name | Description |
|--------------------|--|
| status | The status of the VPN tunnel. Type: String Valid values: UP DOWN |
| lastStatusChange | The date and time of the last change in status. Type: DateTime |
| statusMessage | If an error occurs, a description of the error. Type: String |
| acceptedRouteCount | The number of accepted routes. Type: Integer |

Common Query Parameters

All Query actions share a set of common parameters that must be present in each call.

| Name | Description | Required |
|-------------------------|--|----------|
| <i>Action</i> | Indicates the action to perform. Example: RunInstances | Yes |
| <i>Version</i> | The API version to use, as specified in the WSDL. Example: 2012-06-15 | Yes |
| <i>AWSSecurityToken</i> | The Access Key ID for the request sender. This identifies the account which will be charged for usage of the service. The account with which the Access Key ID is associated must be signed up for Amazon EC2, or requests will not be accepted. AKIAIOSFODNN7EXAMPLE | Yes |
| <i>Timestamp</i> | The date and time at which the request is signed, in the format YYYY-MM-DDThh:mm:ssZ. For more information, go to ISO 8601 . Example: 2006-07-07T15:04:56Z | Yes |
| <i>Expires</i> | The date and time at which the signature included in the request expires, in the format YYYY-MM-DDThh:mm:ssZ. Example: 2006-07-07T15:04:56Z | Yes |
| <i>SecurityToken</i> | The temporary security token obtained through a call to AWS Security Token Service. For more information, go to Using Temporary Security Credentials in the <i>Amazon Elastic Compute Cloud User Guide</i> . Default: None Type: String | No |
| <i>Signature</i> | The request signature. For more information, go to Making Query Requests in the <i>Amazon Elastic Compute Cloud User Guide</i> . Example: Qnp14Qk/7tINHzfXCiT7VEXAMPLE | Yes |

| Name | Description | Required |
|-------------------------|---|----------|
| <i>SignatureMethod</i> | The hash algorithm you use to create the request signature. Valid values: <code>HmacSHA256</code> <code>HmacSHA1</code> . For more information, go to Making Query Requests in the <i>Amazon Elastic Compute Cloud User Guide</i> . Example: <code>HmacSHA256</code> | Yes |
| <i>SignatureVersion</i> | The signature version you use to sign the request. Set this value to 2. For more information, go to Making Query Requests in the <i>Amazon Elastic Compute Cloud User Guide</i> . Example: 2 | Yes |

Note

The *Timestamp* parameter can be used instead of *Expires*. Requests must include either *Timestamp* or *Expires*, but cannot contain both.

Parameter values must be URL-encoded. This is true for any Query parameter passed to Amazon EC2 and is typically necessary in the *Signature* parameter. Some clients do this automatically, but this is not the norm.

Error Codes

Overview

There are two types of error codes: client and server.

Client error codes suggest that the error was caused by something the client did, such as an authentication failure or an invalid AMI identifier. In the SOAP API, these error codes are prefixed with `Client`. For example: `Client.AuthFailure`. In the Query API, these errors are accompanied by a 400-series HTTP response code.

Server error codes suggest a server-side issue caused the error and should be reported. In the SOAP API, these error codes are prefixed with `Server`. For example: `Server.Unavailable`. In the Query API, these errors are accompanied by a 500-series HTTP response code.

Summary of Client Error Codes

| Error Code | Description | Notes |
|-----------------------------------|---|--|
| <code>AddressLimitExceeded</code> | You've reached the limit on the number of elastic IP addresses your account can have. | Each AWS account has an EC2 elastic IP address limit. For new accounts, this limit is 5. If you need more than 5 EC2 elastic IP addresses, please complete the Amazon EC2 Elastic IP Address Request Form . We will ask you to think through your use case and help us understand your need for additional addresses. You have a separate limit for VPC elastic IP addresses (5). To request to increase the limit, complete the Amazon VPC Limits form . |

Amazon Elastic Compute Cloud API Reference
Summary of Client Error Codes

| Error Code | Description | Notes |
|------------------------------|---|---|
| AttachmentLimitExceeded | You've reached the limit on the number of Amazon EBS volumes that can be attached to a single instance. | |
| AuthFailure | User not authorized. | You might be trying to run an AMI for which you do not have permission. |
| Blocked | The account is currently blocked. | Contact aws-verification@amazon.com if you have questions. |
| CustomerGatewayLimitExceeded | You've reached the limit on the number of customer gateways you can create. | |
| DependencyViolation | The specified object has dependent resources. | |
| DiskImageSizeTooLarge | The disk image exceeds the allowed limit (for instance or volume import). | |
| FilterLimitExceeded | Request uses too many filters or too many total filter values. | |
| Gateway.NotAttached | Specified gateway isn't attached, so it can't be detached. | |
| IdempotentParameterMismatch | Request uses the same client token as a previous, but non-identical request. | Do not reuse a client token with different requests, unless the requests are identical. |
| IncorrectInstanceState | Instance is in an incorrect state so the attempted action cannot occur. | |
| IncorrectState | Volume is in an incorrect state. | To attach to an instance, it must be in the 'available' state. |
| InstanceLimitExceeded | Account has maximum allowed concurrent running instances. | Each AWS account has a concurrent running instance limit. For new accounts, this limit is 20. If you need more than 20 instances, please complete the Amazon EC2 Instance Request Form and your request will be considered. |
| InsufficientInstanceCapacity | There is insufficient capacity available for the requested instance type. | The returned message gives guidance on how to solve the problem. |

**Amazon Elastic Compute Cloud API Reference
Summary of Client Error Codes**

| Error Code | Description | Notes |
|--|---|--|
| <code>InsufficientReservedInstancesCapacity</code> | Insufficient Reserved Instances capacity. | |
| <code>InternetGatewayLimitExceeded</code> | You've reached the limit on the number of Internet gateways you can create. | |
| <code>InvalidAMIAttributeItemValue</code> | The value of an item added to, or removed from, an image attribute is invalid. | If you are specifying a <code>userId</code> , check that it is in the form of an AWS account ID. |
| <code>InvalidAMIID.Malformed</code> | Specified AMI ID is not valid. | |
| <code>InvalidAMIID.NotFound</code> | Specified AMI ID does not exist. | |
| <code>InvalidAMIID.Unavailable</code> | Specified AMI ID has been deregistered and is no longer available. | |
| <code>InvalidAssociationID.NotFound</code> | Specified association ID does not exist. | |
| <code>InvalidAttachment.NotFound</code> | The instance cannot detach from a volume to which it is not attached. | |
| <code>InvalidConversionTaskId</code> | Specified conversion task ID (for instance or volume import) is invalid. | |
| <code>InvalidCustomerGateway.DuplicateIpAddress</code> | Conflict among chosen gateway IP addresses. | |
| <code>InvalidCustomerGatewayID.NotFound</code> | The specified customer gateway ID does not exist. | |
| <code>InvalidDevice.InUse</code> | The device to which you are trying to attach (i.e. <code>/dev/sdh</code>) is already in use on the instance. | |
| <code>InvalidDhcpOptionsID.NotFound</code> | Specified DHCP options ID does not exist. | |
| <code>InvalidFormat</code> | Specified disk format (for instance or volume import) is invalid. | |
| <code>InvalidFilter</code> | Specified filter is invalid. | |
| <code>InvalidGatewayID.NotFound</code> | Specified gateway ID does not exist. | |
| <code>InvalidGroup.Duplicate</code> | Attempt to create a duplicate group. | |
| <code>InvalidGroupId.Malformed</code> | Specified group ID is invalid. | |

**Amazon Elastic Compute Cloud API Reference
Summary of Client Error Codes**

| Error Code | Description | Notes |
|--|--|--|
| <code>InvalidGroup.InUse</code> | Specified group cannot be deleted because it is in use. | |
| <code>InvalidGroup.NotFound</code> | Specified group name does not exist. | |
| <code>InvalidGroup.Reserved</code> | Specified group name is a reserved name. | |
| <code>InvalidInstanceID.Malformed</code> | Specified instance ID is not valid. | |
| <code>InvalidInstanceID.NotFound</code> | Specified instance ID does not exist. | |
| <code>InvalidInternetGatewayID.NotFound</code> | Specified Internet gateway ID does not exist. | |
| <code>InvalidIPAddress.InUse</code> | Specified IP address is currently in use. | |
| <code>InvalidKeyPair.Duplicate</code> | Attempt to create a duplicate key pair. | |
| <code>InvalidKeyPair.Format</code> | Format of the public key you've attempted to import is invalid. | |
| <code>InvalidKeyPair.NotFound</code> | Specified key pair name does not exist. | |
| <code>InvalidManifest</code> | Specified AMI has an unparsable manifest. | |
| <code>InvalidNetworkAclEntry.NotFound</code> | Specified network ACL entry does not exist. | |
| <code>InvalidNetworkAclID.NotFound</code> | Specified network ACL ID does not exist. | |
| <code>InvalidParameterCombination</code> | Example: <code>RunInstances</code> was called with both <code>minCount</code> and <code>maxCount</code> set to 0, or <code>minCount > maxCount</code> . | |
| <code>InvalidParameterValue</code> | The value supplied for a parameter was invalid. | Requests that could cause this error include (for example) supplying an invalid image attribute to the <code>DescribeImageAttribute</code> request or an invalid version or encoding value for the <code>userData</code> in a <code>RunInstances</code> request. |
| <code>InvalidPermission.Duplicate</code> | Attempt to authorize a permission that has already been authorized. | |

Amazon Elastic Compute Cloud API Reference
Summary of Client Error Codes

| Error Code | Description | Notes |
|---|---|--|
| <code>InvalidPermission.Malformed</code> | Specified permission is invalid. | |
| <code>InvalidReservationID.Malformed</code> | Specified reservation ID is invalid. | |
| <code>InvalidReservationID.NotFound</code> | Specified reservation ID does not exist. | |
| <code>InvalidRoute.NotFound</code> | Specified route does not exist in the route table. | |
| <code>InvalidRouteTableID.NotFound</code> | Specified route table ID does not exist. | |
| <code>InvalidSecurity.RequestHasExpired</code> | The difference between the request timestamp and the AWS server time is greater than 5 minutes. | Ensure that your system clock is accurate and configured to use the correct time zone. |
| <code>InvalidSnapshotID.Malformed</code> | The snapshot ID that was passed as an argument was malformed. | |
| <code>InvalidSnapshot.NotFound</code> | The specified snapshot does not exist. | |
| <code>InvalidUserID.Malformed</code> | The user ID is neither in the form of an AWS account ID or one of the special values accepted by the <code>owner</code> or <code>executableBy</code> flags in the <code>DescribeImages</code> call. | |
| <code>InvalidReservedInstancesId</code> | Reserved Instances ID not found. | |
| <code>InvalidReservedInstancesOfferingId</code> | Reserved Instances Offering ID not found. | |
| <code>InvalidSubnetID.NotFound</code> | Specified subnet ID does not exist. | |
| <code>InvalidVolumeID.Duplicate</code> | Volume already exists in the system. | |
| <code>InvalidVolumeID.Malformed</code> | Specified volume ID was malformed. | |
| <code>InvalidVolumeID.ZoneMismatch</code> | Specified volume ID and instance ID are in different Availability Zones. | |
| <code>InvalidVolume.NotFound</code> | Specified volume does not exist. | |
| <code>InvalidVpcID.NotFound</code> | Specified VPC ID does not exist. | |

Amazon Elastic Compute Cloud API Reference
Summary of Client Error Codes

| Error Code | Description | Notes |
|--|---|--|
| <code>InvalidVpnConnectionID.NotFound</code> | The specified VPN connection ID does not exist. | |
| <code>InvalidVpnGatewayID.NotFound</code> | Specified virtual private gateway ID does not exist. | |
| <code>InvalidZone.NotFound</code> | The specified zone does not exist. | |
| <code>LegacySecurityGroup</code> | You must delete the 2009-07-15-default security group before you can attach an Internet gateway. | |
| <code>MissingParameter</code> | The request is missing a required parameter. | |
| <code>NetworkAclEntryAlreadyExists</code> | Specified rule number already exists in this network ACL. | |
| <code>NetworkAclEntryLimitExceeded</code> | You've reached the limit on the number of network ACL entries you can add to the ACL. | |
| <code>NetworkAclLimitExceeded</code> | You've reached the limit on the number of network ACLs you can create. | |
| <code>NonEBSInstance</code> | The instance specified does not support EBS. | Please restart the instance and try again. This will ensure that the code is run on an instance with updated code. |
| <code>PendingSnapshotLimitExceeded</code> | You've reached the limit on the number of Amazon EBS snapshots you can have in the pending state. | |
| <code>PendingVerification</code> | The account is pending verification. | Contact aws-verification@amazon.com if you have questions. |
| <code>OptInRequired</code> | The user is not authorized to use the requested product. | This error message can apply to Amazon EC2 or individual AWS Marketplace product codes. |
| <code>RequestLimitExceeded</code> | The maximum request rate permitted by the Amazon EC2 APIs has been exceeded for your account. | Retry your request after a few seconds. |

**Amazon Elastic Compute Cloud API Reference
Summary of Client Error Codes**

| Error Code | Description | Notes |
|---|---|---|
| <code>ReservedInstancesLimitExceeded</code> | Your current quota does not allow you to purchase the required number of reserved instances. | |
| <code>Resource.AlreadyAssociated</code> | Specified gateway is already attached, or specified subnet is already associated with another object. | |
| <code>ResourceLimitExceeded</code> | Exceeded an EC2 resource limit. | Example: You reached the maximum number of import conversion tasks allowed. |
| <code>RouteAlreadyExists</code> | A route for the specified CIDR block already exists in this route table. | |
| <code>RouteLimitExceeded</code> | You've reached the limit on the number of routes you can add to a route table. | |
| <code>RouteTableLimitExceeded</code> | You've reached the limit on the number of route tables you can create. | |
| <code>RulesPerSecurityGroupLimitExceeded</code> | You've reached the limit on the number of rules you can add to a security group. | |
| <code>SecurityGroupLimitExceeded</code> | You've reached the limit on the number of security groups you can create. | |
| <code>SecurityGroupsPerInstanceLimitExceeded</code> | You've reached the limit on the number of security groups you can put an instance into. | |
| <code>SnapshotLimitExceeded</code> | You've reached the limit on the number of Amazon EBS snapshots you can create. | |
| <code>SubnetLimitExceeded</code> | You've reached the limit on the number of subnets you can create for the VPC. | |
| <code>UnknownParameter</code> | An unknown or unrecognized parameter was supplied. | Requests that could cause this error include supplying a misspelled parameter or a parameter that is not supported for the specified API version. |

**Amazon Elastic Compute Cloud API Reference
Summary of Server Error Codes**

| Error Code | Description | Notes |
|-----------------------------------|--|--|
| UnsupportedOperation | The instance type or feature is not supported in your requested Availability Zone or with the requested configuration. | The returned message gives guidance on how to solve the problem. |
| VolumeLimitExceeded | You've reached the limit on the number of Amazon EBS volumes you can create. | |
| VpcLimitExceeded | You've reached the limit on the number of VPCs you can create. | |
| VpnConnectionLimitExceeded | You've reached the limit on the number of VPN connections you can create. | |
| VpnGatewayAttachmentLimitExceeded | You've reached the limit on the number of VPCs that can be attached to the given virtual private gateway. | |
| VpnGatewayLimitExceeded | You've reached the limit on the number of virtual private gateways you can create. | |

Summary of Server Error Codes

| Error Code | Description | Notes |
|--------------------------------------|--|---|
| InsufficientAddressCapacity | Not enough available addresses to satisfy your minimum request. | Reduce the number of addresses you are requesting or wait for additional capacity to become available. |
| InsufficientInstanceCapacity | Not enough available instances to satisfy your minimum request. | Reduce the number of instances in your request or wait for additional capacity to become available. The returned message might also give specific guidance on how to solve the problem. |
| InsufficientReservedInstanceCapacity | Not enough available Reserved Instances to satisfy your minimum request. | Reduce the number of Reserved Instances in your request or wait for additional capacity to become available. |

| Error Code | Description | Notes |
|---------------------|---|--|
| InternalServerError | Internal Error. | This error should not occur. If this persists, please contact us with details by posting a message on the AWS forums . |
| Unavailable | The server is overloaded and cannot handle the request. | |

Request Error Response

The following shows the structure of a request error response.

```
<Response>
  <Errors>
    <Error>
      <Code>Error code text</Code>
      <Message>Error message</Message>
    </Error>
  </Errors>
  <RequestID>request ID</RequestID>
</Response>
```

Example Error Response Request

The following shows an example of an error response.

```
<Response>
  <Errors>
    <Error>
      <Code>InvalidInstanceID.NotFound</Code>
      <Message>The instance ID 'i-4cbc822a' does not exist</Message>
    </Error>
  </Errors>
  <RequestID>ea966190-f9aa-478e-9ede-cb5432daacc0</RequestID>
</Response>
```

Amazon EC2 Resources

The following table lists related resources that you'll find useful as you work with this service.

| Resource | Description |
|---|--|
| Amazon Elastic Compute Cloud Getting Started Guide | Provides a quick tutorial of the service based on a simple use case. Examples and instructions are included. |
| Amazon Elastic Compute Cloud User Guide | Provides conceptual information about Amazon EC2 and describes how to use Amazon EC2 features using the AWS Management Console, command line tools, and Query API. |
| Amazon Elastic Compute Cloud Command Line Reference | Contains a comprehensive description of all the command line tools and their options. |
| Amazon EC2 Technical FAQ | Covers the top questions developers have asked about this product. |
| Amazon EC2 Release Notes | Give a high-level overview of the current release. They specifically note any new features, corrections, and known issues. |
| AWS Developer Resource Center | A central starting point to find documentation, code samples, release notes, and other information to help you build innovative applications with AWS. |
| AWS Management Console | The console lets you perform most of the functions of Amazon EC2 and other AWS products without programming. |
| Discussion Forums | A community-based forum for developers to discuss technical questions related to Amazon Web Services. |
| AWS Support Center | The home page for AWS Technical Support, including access to our Developer Forums, Technical FAQs, Service Status page, and AWS Premium Support (if you are subscribed to this program). |
| AWS Premium Support Information | The primary web page for information about AWS Premium Support, a one-on-one, fast-response support channel to help you build and run applications on AWS Infrastructure Services. |

| Resource | Description |
|--|---|
| Amazon EC2 Product Information | The primary web page for information about Amazon EC2. |
| Form for questions related to your AWS account: Contact Us | This form is <i>only</i> for account questions. For technical questions, use the Discussion Forums. |
| Terms of Use | Detailed information about the copyright and trademark usage at Amazon.com and other topics. |

Document History

The following table describes the important changes since the last release of the Amazon EC2 documentation set.

API version: 2012-06-15.

Latest documentation update: April 19, 2012.

| Change | Description | Release Date |
|---|--|------------------|
| Support for AWS Marketplace and a New API Version | Added support for AWS Marketplace AMIs and a new API version: 2012-04-01. | 19 April 2012 |
| Support | | 18 April 2012 |
| Amazon EBS Volume Status Check | Starting with API version 2012-03-01, you can check the operational status of your Amazon EBS volume. The volume status check gives you information about the I/O, also known as read/write, capability of your EBS volumes. The volume status check lets you know when an EBS volume's data is potentially inconsistent. Amazon Web Services (AWS) gives you options to handle the potentially inconsistent volume. For information on the actions related to this release, see: <ul style="list-style-type: none"> • DescribeVolumeStatus (p. 278) • ModifyVolumeAttribute (p. 331) • DescribeVolumeAttribute (p. 276) • EnableVolumeIO (p. 306) | 12 March 2012 |
| Instance Status Checks | Starting with API version 2011-12-15, you can use the <code>DescribeInstanceStatus</code> action to retrieve results of automated checks performed by Amazon EC2. These status checks detect problems that may impair an instance's ability to run your applications. You can use <code>ReportInstanceStatus</code> to send us feedback or report an inaccurate instance status. | 30 December 2011 |

| Change | Description | Release Date |
|--|---|------------------|
| Elastic Network Interfaces (ENIs) for Amazon EC2 Instances in Amazon Virtual Private Cloud | Starting with API version 2011-12-01, you can attach an elastic network interface (ENI) to an EC2 instance in a VPC. For more information, see: <ul style="list-style-type: none"> • AttachNetworkInterface (p. 27) • DetachNetworkInterface (p. 296) • CreateNetworkInterface (p. 72) • DeleteNetworkInterface (p. 117) • DescribeNetworkInterfaces (p. 216) • DescribeNetworkInterfaceAttribute (p. 214) • ModifyNetworkInterfaceAttribute (p. 327) • ResetNetworkInterfaceAttribute (p. 369) | 21 December 2011 |
| New Offering Types for Amazon EC2 Reserved Instances | Starting with API version 2011-11-01, you can use the new <i>offering-type</i> parameter of <code>DescribeReservedInstancesOfferings</code> to identify the Reserved Instance offerings that address your projected use: <i>Heavy Utilization</i> , <i>Medium Utilization</i> , and <i>Light Utilization</i> . See DescribeReservedInstancesOfferings (p. 232). | 01 December 2011 |
| Support for Amazon EC2 Instance Status | The RequestParameters (p. 199) API action allows you to view the status of your instances and any upcoming scheduled events. | 14 November 2011 |
| Support for Amazon EC2 Spot Instances in Amazon VPC | The RequestSpotInstances (p. 357) action is updated with the <code>subnet</code> option, which enables you to specify an Amazon VPC subnet into which to launch your Spot Instances. | 11 October 2011 |
| Support for VHD file format added to the 2011-07-15 API version | We've added VHD as one of the VM file formats supported for import into Amazon EC2. See the API actions ImportInstance and ImportVolume , and the CLI commands <code>ec2-import-instance</code> and <code>ec2-import-volume</code> . | 24 August 2011 |
| Updates for the 2011-07-15 API version | We've added one new data type, VpnTunnelTelemetryType (p. 486), for the 2011-07-15 API release. | 03 August 2011 |
| Temporary Security Credentials | We've added one new common request parameter, <code>SecurityToken</code> , that supports temporary security credentials. For more information, see Common Query Parameters (p. 488) or go to Using Temporary Security Credentials in the <i>Amazon Elastic Compute Cloud User Guide</i> . | 03 August 2011 |
| Spot Instances Availability Zone pricing changes | We've updated several actions that explain API changes for the Spot Instances Availability Zone pricing feature. We've also added new Availability Zone pricing options as part of the information returned by Spot Instance Requests and Spot Price History API calls. | 26 May 2011 |
| Updates for the 2011-05-15 API Version | We've updated several existing actions for the 2011-05-15 API release. | 26 May 2011 |

| Change | Description | Release Date |
|---|--|-------------------|
| Dedicated Instances | As part of the Dedicated Instances feature release, we've added new options related to the tenancy attribute of instances, and the instance tenancy attribute of VPCs. | 27 March 2011 |
| Updates for the 2011-02-28 API version | We've updated several existing actions for the 2011-02-28 API release. | 27 March 2011 |
| Updates for the 2011-01-01 API version | We've added new actions and updated several existing actions for the 2011-01-01 API release. The new and updated actions are related to these Amazon VPC objects: Internet gateways, route tables, network ACLs, VPC security groups, and VPC Elastic IP addresses. | 11 March 2011 |
| Merged Amazon VPC Documentation | We've merged the Amazon VPC actions into this guide. | 11 March 2011 |
| VM Import | Added the following new actions, which allow you to import a virtual machine or volume into Amazon EC2: <ul style="list-style-type: none"> • ImportInstance (p. 312) • ImportVolume (p. 318) • DescribeConversionTasks (p. 156) • CancelConversionTask (p. 45) | 15 December 2010 |
| Consolidated Documentation | We've consolidated the Query and SOAP API topics. See Actions (p. 9). | 06 December 2010 |
| Parameters for ModifyImageAttribute and ModifyInstanceAttribute | Updated the list of Query parameters for ModifyImageAttribute (p. 321) and for ModifyInstanceAttribute (p. 324). | 20 November 2010 |
| Modifying Block Device Mapping | Removed information from ModifyInstanceAttribute (p. 324) about modifying an instance's block device mapping attribute. You currently can't modify an instance's block device mapping with this action. | 20 November 2010 |
| Filters and Tags | Added information about filters to many of the <i>describe</i> actions. Added information about creating, describing, and deleting tags. For more information about the API actions for tags, see CreateTags (p. 93), DeleteTags (p. 132), and DescribeTags (p. 267). | 19 September 2010 |
| Idempotent Instance Launch | Updated <code>RunInstances</code> to include a <code>ClientToken</code> parameter to ensure idempotency. For more information about the change to <code>RunInstances</code> , see RunInstances (p. 379). | 19 September 2010 |
| Import Key Pair | Added <code>ImportKeyPair</code> . For more information, see ImportKeyPair (p. 316). | 19 September 2010 |

| Change | Description | Release Date |
|--|--|------------------|
| Placement Groups for Cluster Compute Instances | Added information about placement groups, which you use with cluster compute instances. For more information about the API actions for placement groups, see CreatePlacementGroup (p. 77) , DescribePlacementGroups (p. 222) , and DeletePlacementGroup (p. 119) . | 12 July 2010 |
| Amazon VPC IP Address Designation | Amazon VPC users can now specify the IP address to assign an instance launched in a VPC. For information about using the <i>PrivateIpAddress</i> parameter with the <code>RunInstances</code> action, see RunInstances (p. 379) . | 12 July 2010 |
| Error List Update | Updated the list of errors to include <code>Client.Blocked</code> , <code>Client.InsufficientInstanceCapacity</code> , <code>Client.PendingVerification</code> , and <code>Client.Unsupported</code> . For more information, see Error Codes (p. 490) . | 21 May 2010 |
| Security Group Permissions | Clarified the information about authorizing security group permissions. For more information, see AuthorizeSecurityGroupIngress (p. 36) . | 28 April 2010 |
| New Region | Amazon EC2 now supports the Asia Pacific (Singapore) Region. The new endpoint for requests to this Region is <code>ec2.ap-southeast-1.amazonaws.com</code> . | 28 April 2010 |
| Clarification about Spot Instances | Clarified that you can't stop and start Spot Instances that use an Amazon EBS root device. For more information about stopping instances, see StopInstances (p. 392) . | 1 February 2010 |
| Spot Instances | To support customers that use Amazon EC2 instances, but have more flexible usage requirements (e.g., when instances run, how long they run, or whether usage completes within a specific timeframe), Amazon EC2 now provides Spot Instances. A Spot Instance is an instance that Amazon EC2 automatically runs for you when its maximum price is greater than the Spot Price. For conceptual information about Spot Instances, go to the Amazon Elastic Compute Cloud User Guide . | 14 December 2009 |